



SEE ISO
6820-R2-67337-01
E 1966'6.1/2"
S 2266'2.1/2"
EL +114'1.3/4"

F5 G7 B9

~~F24757~~

F4 G6 B8

F24758

S11

PS201-2

SEE ISO
6820-R2-67334-01
E 1962'1"
S 2266'2.1/2"
EL +114'2.5/8"

F24756

CLASS: ARWW-CS01
CLASS: ARWW-XX01

CLASS:
ARWW-XX01

F5 G7 B9

3
2X1.1/2"NPD
/E 1966'6.1/2"

S12

PS433-2
FOR SEC

FOR SECONDARY STEEL REFER
LINE NO 2"-R2-67181-SLPG-CS01-H

3
2X1.1/2"NPD
E 1962'1"

S11

PS201-2

SEE ISO
6820-R2-67216-05
E 1957'10.5/16"
S 2266'2.1/2"
EL +113'5.1/8"

S12

PS433-2
FOR SE

FOR SECONDARY STEEL REFER
LINE NO 2"-R2-67181-SLPG-CS01-H

Filler Material Requisition

Date: 3-5-25

Line Class: ARWW-XX01

WPS: N/A

Electrode: N/A

Signature: Glenn Sumrall, Jr



**TECHNIP
ENERGIES**

Information contained in this document is the work product of one or more legal entities of Technip Energies N.V. and embodies confidential and proprietary information of the applicable entity and/or its client. Use of this information is restricted in accordance with conditions specified by the contract. Technip Energies N.V. and its affiliates disclaim any and all liabilities for any changes or modifications to this document which are made by any person other than the entity that issued the document under the applicable client contract.

THIS DOCUMENT IS UNCONTROLLED WHEN REPRODUCED

0	2025-02-28	RVA	ISSUED FOR CONSTRUCTION	SAD	KJK	SMR	GR
REV	DATE	BY	DESCRIPTION	CHKD	MTD	STRESS	APRVD

PIPE SUPPORTS				
11	2	PS201-2	PS201	2
12	2	PS433-2	PS433	2

PIPE SUPPORTS

11	2	PS201-2	PS201	2
12	2	PS433-2	PS433	2

Turner Industries Group, LLC
Received
MARCH 4, 2025
DOCUMENT CONTROL

NOTES:

1. FOR LINE PRESSURES, TEMPERATURES, INSULATION TYPE AND THICKNESS, ETC. REFER TO LATEST REVISION OF LDT.
2. FOR STANDARD PIPE SUPPORT DETAILS SEE PROJECT STANDARD.
3. FIELD SHIM TO SUIT UNLESS OTHERWISE NOTED.
4. FOR PWHT REQUIREMENTS REFER TO LINE CLASS SPECIFICATION.
5. ALL THREADED PIPE LINE SYSTEMS, FIELD SHALL VERIFY DIMENSION PRIOR TO ERECTION.
6. FFW DESIGNATION AT WELDS INDICATES FIELD FIT WELD, WHERE PIPE FABRICATOR IS TO ADD 9 INCH OF PIPE TO THE ISOMETRIC DIMENSION TO ENABLE THE PIPE TO CUT TO FIT AT SITE.
7. REFER TO 202998C-000-W1-1300-0001 FOR FRP AND DUAL-LAM FABRICATION.

SERVICE: R2	VAPOR/LIQUID: V	INSUL TYPE: Per LDT	INSUL THK: Per LDT	SHOP: N	FIELD: Y	PAINT CODE: Per LDT	MODULE: -
				P&ID: 202998C-001-PID-0031-0967			
				UNIT#: 6800	EMP AREA: 6820	SPEC: ARWW-XX01	STRESS CALC #: -
				LINE No. 2"-R2-67216-ARWW-XX01-N			
				OxyChem Redstone Battleground PROJECT			
				DRAWING NUMBER 6820-R2-67216-06		REV. 0	

SERVICE: R2	VAPOR/LIQUID: V	INSUL TYPE: Per LDT	INSUL THK: Per LDT	SHOP: N	FIELD: Y	PAINT CODE: Per LDT	MODULE: -
				P&ID: 202998C-001-PID-0031-0967			
				UNIT#: 6800	EMP AREA: 6820	SPEC: ARWW-XX01	STRESS CALC #: -
				LINE No. 2"-R2-67216-ARWW-XX01-N			
				OxyChem Redstone Battleground PROJECT			
				DRAWING NUMBER 6820-R2-67216-06		REV. 0	

27 FEB 2025 06:59

