Anoma Research Topics | TECHNICAL REPORT

Mailbox Actors

Jonathan Prieto-Cubides[a], **Anthony Hart**[a], **and Tobias Heindel**[a]

[a]Heliax AG

* *E-Mail: jonathan@heliax.dev*

Abstract

We present a formal framework for actor systems in which mailboxes are promoted to independent, first-class actors—native actors with their own configuration, behaviour, and lifecycle. Each processing actor is automatically paired with a dedicated mailbox actor whose guarded-action behaviour governs delivery, filtering, and scheduling, enabling modular mailbox implementations while adding no burden for simple engines that need only the default first-in-first-out policy. We formalise the system in a predicative Martin-Löf type theory, yielding a correct-by-construction operational semantics as a labelled transition system. We establish type preservation, progress, effect determinism under non-overlapping guards, mailbox isolation, and eventual delivery as metatheoretic properties. A worked example demonstrates causal message delivery through a custom mailbox behaviour. All definitions and properties are mechanised in Lean 4.

Keywords: Actor Model ; Message-Passing Systems ; Mailbox Actors ; Operational Semantics ; Dependent Types ; Formal Methods

1. Introduction

Actor models provide a foundational framework for concurrent and distributed computation [HBS73, Agh86, AMST97]. In these models, actors are independent computational units that communicate exclusively via asynchronous message passing. Incoming messages are typically buffered in a *mailbox* until the recipient is ready to process them.

In most formalisations of the actor model, the mailbox is treated either as an opaque runtime primitive or as a passive data structure internal to the actor. Erlang [Arm10], for instance, provides mailbox interaction only through low-level system primitives with opaque handling [BHT24]. Actor-as-object models [DKVCDM16] similarly treat mailboxes as internal components with limited exposed functionality beyond basic queue operations. The Kilim framework [SM08] takes a step towards separation by decoupling mailboxes from actors through specialised queues, but still treats them as passive data structures rather than first-class entities. Recent work on mailbox types [FAS+23] enriches the type system to reason about mailbox contents, but does not promote the mailbox itself to actor status.

This design choice has consequences for formal reasoning. When the mailbox is opaque, one cannot specify, at the level of the model, properties such as message filtering, prioritisation, or custom delivery policies. Nor can one

reason modularly about the interaction between message storage and message processing. Conversely, when the mailbox is a passive data structure (as in Kilim), one gains structural separation but not behavioural independence: the mailbox cannot react to system events, enforce delivery invariants, or evolve its strategy without modifications to the actor runtime.

We propose promoting mailboxes to independent, first-class actors—native actors in the system with their own configuration, behaviour, and lifecycle. Each processing actor is automatically paired with a dedicated *mailbox actor* that manages message storage and delivery. Communication occurs through message passing to the mailbox actor, and the processing actor retrieves messages only when it is ready to handle them. This pull-based mechanism implements natural backpressure and enables flexible, replaceable mailbox implementations. Crucially, the mailbox actor is not a passive data structure: it is a fully-fledged actor with its own guarded-action behaviour, enabling custom delivery policies, message prioritisation, and filtering without modifying the processing actor or the system runtime.

We formalise this architecture in a predicative Martin-Löf type theory, introducing *engines*—a refinement of the actor notion—structured around four components: a configuration, an execution environment, a message interface, and a behaviour defined by guarded actions. The choice of foundation is driven by the model itself: every engine component is a type family indexed by a finite type of engine type indices, so a type-safe description of engine creation and inter-engine communication requires dependent types to quantify over indices and pair them with their associated data. Alternative foundations such as set theory or rewriting logic could express the operational rules but would not enforce these typing invariants by construction; dependent types make them intrinsic, yielding definitions that are correct by construction and directly implementable in proof assistants such as Agda, Coq, or Lean.

Contributions. The contributions of this paper are fourfold. First, we present a dependent-type-theoretic formalisation of actor systems in which mailboxes are first-class actors (Section 3). The framework is parametric in the engine type family, making it applicable to any actor-like system following a process-oriented paradigm. Second, we provide a complete operational semantics expressed as a labelled transition system (Section 4), covering engine creation with automatic mailbox pairing, message passing, behaviour evaluation under non-overlapping guards, effect execution, and engine lifecycle management. Third, we establish several metatheoretic properties of the system (Section 5), including type preservation under reduction, progress, effect determinism, mailbox isolation, and eventual delivery. Fourth, all definitions and properties are mechanised in Lean 4, including a concrete instantiation

for the causal delivery mailbox (Example 23), providing machine-checked proofs and validating that the parametric framework is directly usable in practice.

Outline. Section 2 fixes notation and conventions. Section 3 introduces the engine model and its components, culminating in the definition of mailbox engines. Section 4 presents the operational semantics—eighteen inference rules grouped into four judgment forms—and traces a worked example on a causal delivery mailbox. Section 5 establishes five metatheoretic properties. Section 6 discusses related work, and Section 7 concludes.

2. Notation

We work in a predicative Martin-Löf type theory with a countable hierarchy of universes

$$\mathfrak{U}_0 : \mathfrak{U}_1 : \mathfrak{U}_2 : \cdots$$

where $\mathfrak{U}_n : \mathfrak{U}_{n+1}$ for all $n \in \mathbb{N}$. The symbol $\mathfrak{U}$ denotes $\mathfrak{U}_0$ when the universe level is not important. All constructions in this paper live in $\mathfrak{U}_0$ unless stated otherwise.

Π-types. Given a type $A\colon \mathfrak{U}_n$ and a type family $B\colon A \to \mathfrak{U}_m$, the Π-type (dependent function type) $\Pi_{(x:A)}\, B(x)$ inhabits $\mathfrak{U}_{\max(n,m)}$. When B does not depend on x, we write $A \to B$.

Σ-types. Given $A\colon \mathfrak{U}_n$ and $B\colon A \to \mathfrak{U}_m$, the Σ-type (dependent pair type) $\Sigma_{(x:A)}\, B(x)$ inhabits $\mathfrak{U}_{\max(n,m)}$. Its terms are denoted $\langle a, b\rangle$ where $a\colon A$ and $b\colon B(a)$. When B does not depend on x, we write $A \times B$ and call its terms *tuples*. We generalise so that $\langle a_1, \ldots, a_n\rangle$ is a tuple of type $A_1 \times \cdots \times A_n$.

Inductive types. We use inductive type definitions in the following form:

$$\mathsf{A} \coloneqq \cdots \mid \mathsf{B} \mid \cdots \mid \mathsf{C}(A_1, \ldots, A_m) \mid \cdots, \tag{1}$$

where B and C are constructors of A, with B nullary and C taking m arguments. The type A may also be indexed by parameters. Pattern matching is used for elimination.

Standard types. We denote by $\mathbb{N}$ the type of natural numbers, $\mathbf{0}$ the empty type, $\mathbf{1}$ the unit type with its unique term $*$, $\mathbf{B}$ the two-element type with truth values tt and ff, $\mathsf{List}(A)$ the type of lists over A, $\mathsf{Fin}(n)$ the type with exactly n elements, and $\mathsf{Maybe}(A)$ the optional type $A \oplus \mathbf{1}$ with constructors none and $\mathsf{some}(a)$ for $a\colon A$. The empty list is written $[\,]$ and $[a_1, \ldots, a_n]$ denotes a list of n elements.

Equalities and notation. We write $x \coloneqq y$ for definitional equality (defining x to be y), $a \equiv b$ for judgmental equality (holding by computation), and $a = b$ for propositional equality (the identity type). In inference rules, premises use judgmental equality unless otherwise noted. A typing judgement is denoted $x : A$. We write $(_)$ to omit terms that are irrelevant or inferable from context.

Finite subsets and set-theoretic notation. Certain types in our model are equipped with decidable equality. For such types, we freely use set-theoretic notation as syntactic sugar. Finite subsets of a type A are formalised as $\mathcal{P}_{\mathsf{fin}}(A)$, implemented as lists with a uniqueness invariant. We write $a \in S$ for membership, $S \cup T$ for union, and $S \setminus T$ for difference. The disjoint union of types $A_1, \ldots, A_n$ is denoted $A_1 \oplus \cdots \oplus A_n$.

Functions. A function $f : A \to B$ applied to a is written $f(a)$. The *function update* $f[a \mapsto c]$ denotes the function agreeing with f except that input a maps to c. We overload this notation to finite sets: $S[a \mapsto c]$ replaces element a by c in S.

3. Model

This section presents a formal model of actor systems in which mailboxes are promoted to first-class actors. Building on the actor-like semantics of [HPCH25], we formalise *engines* as refined communicating Moore machines structured around four core components: a *configuration*, an *execution environment*, a *message interface*, and a *behaviour*. These components, more precisely their types, define the type signature for engines in a system, as detailed in Definition 20.



Figure 1. Architecture of an engine e. An incoming message $m : \mathsf{Msg}_e$ (amber arrow) is evaluated by the behaviour b_e using the execution environment (dashed arrow), producing an effect (crimson arrow). The dashed border on env_e indicates it is the only component that may change between steps.

The configuration conveys persistent metadata about the engine such as its parent reference and operational mode (Definition 9). The execution en-

vironment contains the engine's local state and an address book of other engines (Definition 10). The behaviour specifies how the engine reacts to messages via *guarded actions*—pairs of precondition/action that, when triggered, produce *effects*: commands requesting the system to send messages, update state, spawn new engines, or terminate (Definition 11).

For guarded action evaluation, various strategies exist for selecting which action to execute when multiple guards are satisfied. We present one such strategy based on non-overlapping guards in Section 4.6.

Remark 1 (Event-Driven Systems)**.** The behaviour of engines resembles the correct-by-construction approach used in event-driven systems such as Event-B [Dup21]. In that approach, system transitions are driven by events consisting of preconditions on the current state and actions to execute when these preconditions hold. Our guarded actions play an analogous role, with the effect system (Definition 11) restricting the available actions.

All type families in the model are indexed by a finite type of engine type indices, which we now introduce.

Definition 2 (Engine Type Index ‹/›)**.** *We postulate a finite type* $\mathbb{I} : \mathfrak{U}$ *of* ***engine type indices****. For each* $i : \mathbb{I}$*, the system defines the associated type families* Msg_i*,* Cfg_i*,* Env_i*, and* EBeh_i*.*

The finiteness of $\mathbb{I}$ reflects the assumption that engine types are fixed when the system is defined. Adding support for dynamic type extension is left for future work.

3.1. Preliminaries

The model operates on a system state κ consisting of finite sets of uniquely identified nodes $\mathcal{N}$, engines $\mathcal{E}$, and in-transit messages $\mathcal{M}$. The subsequent sections detail these concepts in a bottom-up manner.



Figure 2. A system state κ with nodes $\mathcal{N}$ (dashed regions), engines $\mathcal{E}$ (boxes), and in-transit messages $\mathcal{M}$ (arrows). The message $(\langle 1, e_s\rangle \triangleright_m \langle 2, e_t\rangle)$ is in transit from engine e_s on node 1 to engine e_t on node 2.

As a state machine, the system evolves in discrete steps, where the state at step i is denoted $\kappa^{(i)}$. The sets $\mathcal{N}^{(i)}$, $\mathcal{E}^{(i)}$, and $\mathcal{M}^{(i)}$ may change between steps. When no confusion arises, we omit the step index. Each engine resides on a unique node, as formalised in Definitions 20 and 24.

Remark 3 (Static Engine Allocation)**.** The model assumes that engines remain on the node where they were created. Engine migration between nodes is not considered.

Communication between engines occurs via typed messages carried by the system. A message-passing mechanism governs the delivery of in-transit messages $\mathcal{M}$, as described in Section 3.3. Each message contains sender and recipient identifiers along with a typed payload.

3.2. Addresses

Definition 4 (Address ‹/›)**.** *The **address** of an engine is a pair $\langle n, \iota \rangle$ of type* Addr *where n is the node identifier and ι is the engine's unique identifier within that node. Formally,*

$$\mathsf{Addr} \coloneqq \mathbb{N} \times \mathbb{N}\,. \tag{2}$$

3.3. Message Structure

Engines communicate via typed messages. The type system ensures that every message payload conforms to the target engine's interface.

Definition 5 (Message Interface ‹/›)**.** *For each $i : \mathbb{I}$, the **message interface** Msg_i is a type whose constructors, called **message tags**, wrap payload types that engines of type i can process. Each message tag carries a name describing its purpose, analogous to method names in object-oriented systems.*

The message interface Msg_i is presented as an inductive type in the style of (1). For a concrete system, each engine type index i fixes its message interface.

Type-safe communication is ensured by how messages are defined: there is no way to construct an ill-formed message.

Definition 6 (Message ‹/›)**.** *A **message** is a triple $\langle s, t, v \rangle$ denoted $(s \triangleright_v t)$ where:*

- $s : \mathsf{Addr}$ *is the sender engine address,*
- $t : \mathsf{Addr}$ *is the target engine address, and*
- $v : \overline{\mathsf{Msg}}$ *is a typed payload.*

The payload v is an element of $\overline{\mathsf{Msg}}$, the Σ-type collecting all valid message payloads across engine types. This ensures that only well-formed messages can be constructed.



Figure 3. The engine lifecycle: an engine starts in $\mathsf{Ready}(f)$ state, where f is a predicate indicating which messages the engine accepts. Upon receiving a message m, it transitions to $\mathsf{Busy}(m)$. From there, it either returns to $\mathsf{Ready}(g)$ with a (possibly different) predicate g, or transitions to $\mathsf{Terminated}$.

To refer to the type of an arbitrary message within the system, we use the Σ-type

$$\overline{\mathsf{Msg}} \coloneqq \Sigma_{(i\colon \mathbb{I})}\, \mathsf{Msg}_i\,, \tag{3}$$

which collects all valid message payloads across engine types.

3.4. Engine Components

We now define the components that constitute an engine. For each engine type index $i\colon \mathbb{I}$, these components are given as type families indexed by i.

Definition 7 (Engine Lifecycle ‹/›)**.** *For each $i\colon \mathbb{I}$, the **status** of an engine of type i is a term of type $\mathsf{EStatus}_i$, determining the engine's operational state within its lifecycle.*

$$\begin{aligned} \mathsf{EStatus}_i \coloneqq\ & \mathsf{Ready}(\mathsf{Msg}_i \to \mathbf{B}) \\ \mid\ & \mathsf{Busy}(\mathsf{Msg}_i) \\ \mid\ & \mathsf{Terminated}\,. \end{aligned} \tag{4}$$

When an engine is in the $\mathsf{Ready}(f)$ state, it is available to process incoming messages. The predicate $f\colon \mathsf{Msg}_i \to \mathbf{B}$ acts as a filter, determining which messages the engine will accept. By default, a newly created engine starts in the $\mathsf{Ready}(\lambda x.\mathrm{tt})$ state, accepting all messages.

After creation, the engine may transition to $\mathsf{Busy}(m)$, where it is actively processing message m, or to $\mathsf{Terminated}$, where it stops processing and is subsequently removed from the system.

We distinguish between two operational modes of engines.

Definition 8 (Operational Mode ‹/›)**.** *The **operational mode** of an engine is of type* EMode*,*

$$\mathsf{EMode} \coloneqq \mathsf{Process} \mid \mathsf{Mail}\,. \tag{5}$$

The operational mode is fixed at creation and opaque to the engine itself. The system's message-passing mechanism treats engines differently based

on their mode: messages sent to Process engines are internally routed to their paired Mail engines, which manage message storage and delivery.

Definition 9 (Configuration ⟨/⟩). *For each $i : \mathbb{I}$, we postulate a type $C_i : \mathfrak{U}$ of engine-type-specific configuration data. The* ***configuration*** *of an engine of type i is a tuple $\langle r, \mathsf{mode}, c \rangle$ of type Cfg_i, where:*

- $r : \mathsf{Maybe}(\mathsf{Addr})$ *is an optional reference to the engine's parent,*
- $\mathsf{mode} : \mathsf{EMode}$ *is the engine's operational mode, and*
- $c : C_i$ *is configuration data specific to the engine type.*

The type family of configurations is

$$\mathsf{Cfg}_i \coloneqq \mathsf{Maybe}(\mathsf{Addr}) \times \mathsf{EMode} \times C_i \,. \tag{6}$$

For an engine p of type i, we write cfg_p for its configuration value and Cfg_i for the type.

Definition 10 (Execution Environment ⟨/⟩). *For each $i : \mathbb{I}$, we postulate a type $L_i : \mathfrak{U}$ for the local state. The execution* ***environment*** *of an engine of type i is a pair $\langle s, m \rangle$ of type Env_i, where:*

- $s : L_i$ *is the local state, and*
- $m : \mathsf{Name} \to \mathsf{Maybe}(\mathsf{Addr})$ *is the engine's address book, with a predefined name* SELF *for the engine's own address.*

The type family of environments is

$$\mathsf{Env}_i \coloneqq L_i \times (\mathsf{Name} \to \mathsf{Maybe}(\mathsf{Addr})) \,. \tag{7}$$

For an engine p of type i, we write env_p for its environment and Env_i for the type.

3.5. Execution Directives

The behaviour of an engine specifies what it can perform when reacting to a message. How the engine reacts is determined by a set of guarded actions—pairs of *guards* (preconditions) and *actions*. When a message is processed, the system evaluates it against the engine's guards in the context of the engine's environment and configuration. If a guard is satisfied, its associated action produces an *effect*: a command to the system.



Figure 4. For an engine p of type i, its behaviour acts on a message m of type Msg_i, configuration cfg_p, and environment env_p. The guards g_k produce optional values r_k that feed into actions c_k, which return effects of type Effect_i.

Definition 11 (Effect System ‹/›)**.** *For each $i : \mathbb{I}$, an **effect** triggered by an engine of type i is a term of type Effect_i. Each effect represents a primitive operation that the issuing engine requests the system to execute.*

$$
\begin{array}{lll}
\mathsf{Effect}_i \coloneqq & & \\
& \mathsf{Noop} & \textit{(null operation)} \\
\mid & \mathsf{Send}(j : \mathbb{I}, \mathsf{Addr}, \mathsf{Msg}_j) & \textit{(message dispatch)} \\
\mid & \mathsf{Update}(\mathsf{Env}_i) & \textit{(update environment)} \\
\mid & \mathsf{Spawn}(j : \mathbb{I}, C_j, L_j) & \textit{(spawn child engine of type } j\textit{)} \\
\mid & \mathsf{MFilter}(\mathsf{Msg}_i \to \mathbf{B}) & \textit{(set mailbox filter)} \\
\mid & \mathsf{Terminate} & \textit{(engine shutdown)} \\
\mid & \mathsf{Chain}(\mathsf{Effect}_i, \mathsf{Effect}_i) & \textit{(effect sequencing)}\ .
\end{array}
\tag{8}
$$

Effects serve as the declarative interface specifying what an engine can do, without exposing how the behaviour computes its response.

Definition 12 (Guard ‹/›)**.** *Given a type R, a **guard** for an engine of type i is a function of type $\mathsf{In}_i \to \mathsf{Maybe}(R)$ where*

$$\mathsf{In}_i \coloneqq \mathsf{Msg}_i \times \mathsf{Cfg}_i \times \mathsf{Env}_i\ . \tag{9}$$

Applied to a message, configuration, and environment, a guard returns $\mathsf{some}(r)$ *if satisfied, and* none *otherwise.*

Definition 13 (Action)**.** *Given a guard $g : \mathsf{In}_i \to \mathsf{Maybe}(R)$ for an engine of type i, an **action** is a dependent function of type*

$$\Pi\,(r : R).\,\Pi\,(x : \mathsf{In}_i).\,g(x) = \mathsf{some}(r) \to \mathsf{Out}_i \ \textit{where}\ \mathsf{Out}_i \coloneqq \mathsf{Effect}_i\ . \tag{10}$$

The proof argument $g(x) = \mathsf{some}(r)$ records in the type system that the action is defined only when the guard holds, eliminating the need for a separate guard-match assumption in semantic rules.

Together, a guard and an action induce a function of type $\mathsf{In}_i \to \mathsf{Out}_i$.

Definition 14 (Guarded Action ‹/›). *Given a guard g_i and an action a_i for an engine of type i, the* ***guarded action*** *$g_i \odot a_i$ is the function of type $\mathsf{In}_i \to \mathsf{Out}_i$ defined by*

$$\begin{aligned}(g_i \odot a_i) &\coloneqq \lambda\langle m, c, s\rangle.\mathsf{case}\ g_i(m, c, s)\ \mathsf{of}\ \{\\ &\quad \mathsf{some}(r) \Rightarrow a_i(r, \langle m, c, s\rangle);\\ &\quad \mathsf{none} \Rightarrow \mathsf{Noop}\}\,.\end{aligned} \tag{11}$$

Definition 15 (Engine Behaviour ‹/›). *A* ***behaviour*** *for an engine of type i is a list of guarded action structures, of type EBeh_i, where*

$$\mathsf{EBeh}_i \coloneqq \mathsf{List}(\mathsf{GuardedAction}_i)\,. \tag{12}$$

To ensure deterministic evaluation, we require that behaviours satisfy a well-formedness condition.

Definition 16 (Non-Overlapping Guards ‹/›). *A behaviour $b\colon \mathsf{EBeh}_i$ has* ***non-overlapping guards*** *if for every input $x\colon \mathsf{In}_i$, at most one guarded action in b produces a non-Noop effect. That is, for all $\langle g_j, a_j\rangle, \langle g_k, a_k\rangle \in b$ with $j \neq k$, if $g_j(x) = \mathsf{some}(r)$ then $g_k(x) = \mathsf{none}$.*

Definition 17 (Well-Formed Behaviour ‹/›). *A behaviour $b\colon \mathsf{EBeh}_i$ is* ***well-formed*** *if it has non-overlapping guards (Definition 16). Throughout this paper, all behaviours are assumed to be well-formed.*

Alternative guard selection strategies—inspired, for instance, by Dijkstra's guarded command language [Dij75]—are compatible with the model but fall outside the scope of this work.

Remark 18 (Evolving Behaviours)**.** In the present model, behaviours are fixed at engine creation. One could extend the effect system with an additional constructor for changing behaviours, at the cost of additional complexity in the operational semantics.

3.6. Engines

Engines are the core computational units of the system. Each engine processes messages of a specific type in isolation and produces effects instructing the system on actions to take. Unlike actor-as-objects and actors-as-processes models [DKVCDM16], engines are characterised by their typed components and the declarative nature of their behaviour.

Definition 19 (Engine Type ‹/›). *For each $i\colon \mathbb{I}$, the* ***engine type*** *Eng_i specifies a message interface and a well-formed behaviour (Definition 17):*

$$\mathsf{Eng}_i \coloneqq \mathsf{Msg}_i \times \mathsf{EBeh}_i\,. \tag{13}$$

Definition 20 (Engine ‹/›). *An* ***engine*** *of type Eng_i is a tuple $\langle \mathsf{Msg}_i, \mathsf{EBeh}_i, o, c, s\rangle$, where:*

- $o\colon \mathsf{EStatus}_i$: *the engine's status,*
- $c\colon \mathsf{Cfg}_i$: *the engine's configuration, and*
- $s\colon \mathsf{Env}_i$: *the engine's execution environment.*

For clarity, as shown in Figure 1, we include the message interface and behaviour in the tuple representation, highlighting the engine's type.

3.7. Mailbox Engines

The system distinguishes between processing engines (mode Process) and mailbox engines (mode Mail), as defined in Definition 8. While a mailbox engine is a first-class actor with its own configuration and behaviour, it is typically managed by the system: a dedicated mailbox is automatically paired with each processing engine upon creation (Section 4.2). Although users cannot directly instantiate mailbox engines, they may specify custom initial configurations and behaviours during processing engine creation. The default mailbox behaviour implements a first-in-first-out queue.

Definition 21 (Mailbox Engine ‹/›)**.** *A* mailbox engine *m for a processing engine p of type i is a system-configured engine satisfying:*

- *The operational mode is* Mail*.*
- *The parent reference points to p.*
- *The message interface is*

$$\mathsf{Msg}_m \coloneqq \mathsf{Append}(\mathsf{Msg}_i)\,. \tag{14}$$

- *The local state of type L_m implements a message store with:*
  - $\emptyset$ *representing the empty state,*
  - $(\cup)\colon L_m \times \mathsf{Msg}_i \to L_m$ *for message insertion, and*
  - $(\setminus)\colon L_m \times \mathsf{Msg}_i \to L_m$ *for message deletion.*
- *Three mailbox operations are provided:*
  - $\mathsf{mailboxContains}\colon L_m \times \mathsf{Msg}_m \to \mathsf{Prop}$*: holds when the store contains a given wrapped message,*
  - $\mathsf{mailboxRemove}\colon L_m \times \mathsf{Msg}_m \to L_m$*: removes a wrapped message from the store, and*
  - $\mathsf{unwrap}\colon \mathsf{Msg}_m \to \mathsf{Maybe}(\mathsf{Msg}_i)$*: extracts the payload from a wrapped message.*

- *The default behaviour b_m consists of a single guarded action $\langle g_m, a_m \rangle$ where:*
  - $g_m(\mathsf{Append}(v), c, q) \coloneqq \mathsf{some}(v)$ *: the guard always matches, extracting the payload v from the* Append *wrapper.*
  - $a_m(v, \mathsf{Append}(v), c, q) \coloneqq \mathsf{Update}(q \cup \{v\})$ *: the action stores the payload in the message store via an* Update *effect.*

Since the mailbox engine is a native actor, it processes incoming messages through its behaviour via s-Process, just as any other engine. The M-Enqueue rule transitions the mailbox engine from $\mathsf{Ready}(f)$ to $\mathsf{Busy}(w)$, after which the behaviour evaluates the message and produces an effect—by default, storing the payload in the message store.

Adding mailbox engines introduces a clear producer-consumer pattern. The separation of message storage from processing logic, opaque to sending engines, allows for independent scaling of message ingestion and core computation. The mailbox engine acts as a mediator implementing custom delivery policies via its behaviour, while the processing engine focuses on its computational tasks.

Remark 22 (Mailbox Overhead for Simple Engines)**.** For processing engines that require no custom delivery logic, one may ask whether the mailbox indirection introduces unnecessary overhead. In our design, the default mailbox is a simple first-in-first-out queue that requires no configuration from the engine implementor: it is created automatically, accepts all messages, and is transparent to sending engines. Thus the "cost" for simple engines is purely in the formalism—an additional engine instance exists—not in the user's modelling effort. The benefit is that the system uniformly supports mailbox customisation when engines evolve beyond the simple case, without requiring architectural changes.

Example 23 (Causal Delivery Mailbox ‹/›)**.** Consider a distributed publish-subscribe system in which topic messages carry causal dependencies. A *topic relay* engine forwards messages between nodes using the default FIFO mailbox, performing only signature validation. A *local broker* engine delivers messages to subscribers on the same node, but must respect causal order: a message may only be delivered after all messages it depends on have been delivered. A FIFO mailbox cannot enforce this invariant because network reordering may deliver a message before its dependencies arrive.

We model the system with two engine type indices: $\mathbb{I} \coloneqq \{\mathsf{relay}, \mathsf{broker}\}$. Both share the message interface

$$\mathsf{Msg}_{\mathsf{relay}} \coloneqq \mathsf{Msg}_{\mathsf{broker}} \coloneqq \mathsf{TopicMsg}(\mathsf{Addr}, \mathcal{P}_{\mathsf{fin}}(\mathsf{Hash}), \mathsf{Data}, \mathsf{Sig}, \mathsf{Hash}) \,, \quad (15)$$

where the second component records the set of message hashes on which this message causally depends and the fifth component is the message's own hash. We write $\mathsf{deps}(v)$ for this dependency set and $\mathsf{h}(v)$ for the hash of message v.

The relay engine uses the default mailbox (Definition 21). The broker engine uses a custom mailbox with local state

$$L_{m_{\mathsf{broker}}} := \begin{pmatrix} \mathsf{dlv} : \mathcal{P}_{\mathsf{fin}}(\mathsf{Hash}), \\ \mathsf{pnd} : \mathsf{Map}(\mathsf{Hash}, \mathsf{TopicMsg}), \\ \mathsf{rdy} : \mathsf{List}(\mathsf{TopicMsg}) \end{pmatrix}, \tag{16}$$

where dlv records hashes of delivered messages, pnd buffers messages whose dependencies have not yet been met, and rdy holds messages ready for delivery.

The broker's mailbox behaviour consists of a single guarded action $\langle g_c, a_c \rangle$:

- The guard always matches: $g_c(\mathsf{Append}(v), k, q) := \mathsf{some}(v)$.
- The action branches on dependency satisfaction. If $\mathsf{deps}(v) \subseteq q.\mathsf{dlv}$, the message is ready and a cascade check releases any pending messages whose dependencies are now met:

$$\begin{aligned} &a_c(v, \ldots) := \\ &\quad \mathsf{Chain}\big(\mathsf{Update}(q[\mathsf{dlv} \cup \{\mathsf{h}(v)\},\ \mathsf{rdy} \mathbin{+\!\!+} [v]]), \\ &\qquad\quad \mathsf{Update}(q[\mathsf{dlv} \cup \{\mathsf{h}(v)\},\ \mathsf{pnd} \setminus S,\ \mathsf{rdy} \mathbin{+\!\!+} [v] \mathbin{+\!\!+} S_{\mathsf{list}}]) \big) \end{aligned}$$

where $S = \{w \in q.\mathsf{pnd} \mid \mathsf{deps}(w) \subseteq q.\mathsf{dlv} \cup \{\mathsf{h}(v)\}\}$. When $S = \emptyset$, the second effect coincides with the first; this case simplifies to $\mathsf{Chain}(\mathsf{Update}(\cdot), \mathsf{Noop})$. If $\mathsf{deps}(v) \not\subseteq q.\mathsf{dlv}$, the message is buffered:

$$a_c(v, \ldots) := \mathsf{Update}(q[\mathsf{pnd} \cup \{\mathsf{h}(v) \mapsto v\}]) .$$

Because there is a single guarded action, the non-overlapping guard condition (Definition 16) is satisfied trivially. The use of $\mathsf{Chain}(\cdot, \cdot)$ demonstrates that mailbox behaviours may require effect sequencing to implement policies that go beyond simple message storage.

3.8. Nodes

Definition 24 (Node ‹/›). *A **node** in $\mathcal{N}$ is a pair $\langle n_i, \epsilon_i \rangle$ where n_i is the node's unique identifier and ϵ_i maps local identifiers to engine instances.*

For a node with identifier n_i, we write $\mathcal{E}_i$ for the set of engines on that node (the values of ϵ_i), and α_i for the mapping from engine instances to their addresses.

3.9. System and State

The system is a collection of interacting engines residing in nodes. For each $i : \mathbb{I}$, the system defines a message interface Msg_i, configuration type Cfg_i, environment type Env_i, behaviour type EBeh_i, and engine type Eng_i. These types are fixed throughout the system's lifetime and constitute the typing context. The system structure resembles a Kripke model where states evolve via transition rules.

Definition 25 (System State ‹/›). *A **system state** κ is a tuple $\langle \mathcal{N}, \mathcal{M}, \Omega \rangle$ where:*

- *$\mathcal{N}$ is the set of uniquely identified nodes,*
- *$\mathcal{M}$ is the set of in-transit messages, and*
- *$\Omega : \mathbb{N}$ is a fresh-identifier counter.*

The superscript $\kappa^{(i)}$ denotes the system state at step i, with $\kappa^{(0)}$ the initial state. We may define $\kappa^{(0)} \coloneqq \langle \emptyset, \emptyset, 0 \rangle$ and grow the system via the transition rules of Section 4.

Rules that allocate identifiers consume from the counter Ω and increment it. The function $\mathsf{mbox} : \mathsf{Addr} \to \mathsf{Addr}$ returns the address of the dedicated mailbox engine for a given processing engine; by convention, mbox maps each engine address to a fixed companion address.

We extend the node-local engine map ϵ_i to a global version ϵ that operates over all engines $\mathcal{E}$ in the system.

4. Operational Semantics

The operational semantics are expressed through the reduction relation $\rightsquigarrow$, where $\kappa^{(i)} \rightsquigarrow \kappa^{(i+1)}$ indicates a transition. A system state κ is represented as $(\mathcal{N}, \mathcal{M}, \Omega)$, where Ω is the fresh-identifier counter, ϵ maps engine addresses to instances, and α maps instances to addresses.

4.1. Judgment Forms

The operational semantics employ five judgment forms, organised by domain.

1. **System-level operations.** $\kappa, \cdots \rightsquigarrow_{\mathsf{op}} \kappa'$ states that system operation op transforms κ into κ'.

2. **Behaviour evaluation.** $p \vdash v \downarrow E$ states that engine p processing message v produces effect E.

3. **Guarded action evaluation.** $p, \langle g, a \rangle \vdash v \downarrow E$ states that in the context of engine p, the guarded action $\langle g, a \rangle$ produces effect E when processing message v.

4. **Effect execution.** $\kappa \vdash E \rightsquigarrow \kappa'$ states that executing effect E in state κ produces state κ'.

5. **Engine processing.** $\kappa, p, m \rightsquigarrow_{\mathsf{process}} \kappa'$ states that in state κ, engine p processing message m yields state κ'.

4.2. System-level Initialisation

Definition 26 (s-Node ‹/›). *A new node n with fresh identifier ι and an empty engine map is added to the set of nodes $\mathcal{N}$.*

$$\frac{\iota := \Omega \quad n \equiv \langle \iota, \emptyset \rangle}{\kappa \rightsquigarrow_{\mathsf{node}} (\mathcal{N} \cup \{n\}, \mathcal{M}, \Omega + 1)}$$

4.3. Engine Creation

Since every processing engine is paired with a mailbox engine (s-SpawnWithMailbox), the shared setup logic is factored into the auxiliary rule s-EngineSpawn.

Definition 27 (s-EngineSpawn — auxiliary ‹/›). *Given a node n_i, an engine type index k, and an optional parent address π, this rule creates a new engine with fresh identifier ι, initialises its configuration $\mathsf{cfg}_{\mathsf{new}}$ and environment $\mathsf{env}_{\mathsf{new}}$ (seeded with the engine's own address), and registers it in n_i's engine map.*

$$\frac{\begin{array}{c} n_i \equiv \langle \mathsf{id}_i, \epsilon_i \rangle \in \mathcal{N} \\ k : \mathbb{I} \quad b : \mathsf{EBeh}_k \quad f : \mathsf{Msg}_k \to \mathbf{B} \\ \pi : \mathsf{Maybe}(\mathsf{Addr}) \quad \mathsf{cfg}_{\mathsf{new}} : \mathsf{Cfg}_k \equiv \langle \pi, o, c \rangle \\ \mathsf{env}_{\mathsf{new}} : \mathsf{Env}_k \equiv \langle s, [(\textsc{self}, \iota)] \rangle \quad \iota := \Omega \quad \langle \mathsf{id}_i, \iota \rangle : \mathsf{Addr} \\ e_{\mathsf{new}} \equiv \langle \mathsf{Msg}_k, b, \mathsf{Ready}(f), \mathsf{cfg}_{\mathsf{new}}, \mathsf{env}_{\mathsf{new}} \rangle \quad \epsilon' \equiv \epsilon_i[\iota \mapsto e_{\mathsf{new}}] \end{array}}{\kappa, n_i, k, \pi, \iota, b, f, o, c, s \rightsquigarrow_{\mathsf{spawn}} (\mathcal{N}[\epsilon_i \mapsto \epsilon'], \mathcal{M}, \Omega + 1)}$$

Definition 28 (s-SpawnWithMailbox ‹/›). *For engine type k on node n_i, this rule invokes s-EngineSpawn twice: once to create the processing engine (with fresh identifier ι_p) and once to create its paired mailbox engine (with fresh identifier ι_m), whose parent address points back to the processing engine.*

$$\frac{\begin{array}{c} k : \mathbb{I} \quad n_i \in \mathcal{N} \quad \iota_p := \Omega \quad \iota_m := \Omega + 1 \\ \vdots \\ \kappa, n_i, k, \pi, \iota_p, b_k, f, \mathsf{Process}, c, s \rightsquigarrow_{\mathsf{spawn}} \kappa_1 \\ \vdots \\ \kappa_1, n_i, k_m, \mathsf{some}(\langle \mathsf{id}_i, \iota_p \rangle), \iota_m, b_m, \lambda_.\mathsf{tt}, \mathsf{Mail}, c_m, s_m \rightsquigarrow_{\mathsf{spawn}} \kappa_2 \end{array}}{\kappa, n_i, k, \pi, b_k, f, c, s \rightsquigarrow_{\mathsf{spawn\text{-}mbox}} \kappa_2}$$

Here k_m is the engine type index for the mailbox engine paired with processing engines of type k, b_m is the default mailbox behaviour, and c_m, s_m are the initial mailbox configuration and state.

4.4. Engine Garbage Collection

To prevent zombie engine instances—engines in the Terminated state—the system removes them.

Definition 29 (s-Clean ‹/›). *An engine p on node n_i whose status is* Terminated *is removed from n_i's engine map ϵ_i.*

$$\frac{n_i \in \mathcal{N} \quad p \in \mathcal{E}_i \quad \mathsf{status}(p) \equiv \mathsf{Terminated}}{\kappa \rightsquigarrow_{\mathsf{clean}} (\mathcal{N}[\epsilon_i \mapsto \epsilon_i \setminus \{p\}], \mathcal{M}, \Omega)}$$

The s-Clean rule does not remove the engine's mailbox. The mailbox engine remains to absorb messages that may still be in transit, preventing message loss. It can be cleaned independently once it is no longer needed.

Remark 30 (Messages to Terminated Engines)**.** When a message in transit is addressed to a processing engine that has been terminated and cleaned, the message's target address resolves to the (still existing) mailbox engine. Since the mailbox engine accepts all messages via its Append interface, the message is enqueued but never dequeued, as no processing engine exists to consume it. This design choice silently absorbs stale messages rather than introducing error-handling complexity.

4.5. Message-Passing Mechanism

The message-passing mechanism supports asynchronous communication with non-blocking sends, mailbox isolation with eventual delivery, and explicit lifecycle management.

Definition 31 (M-Send ‹/›). *A sender engine e_s dispatches a message with payload $v\colon \mathsf{Msg}_t$ to a target processing engine e_t. The payload is wrapped in the* Append *constructor and placed in transit, addressed to e_t's dedicated mailbox.*

$$\frac{\begin{array}{c} e_s, e_t \in \mathcal{E} \quad \mathsf{mode}(e_t) \equiv \mathsf{Process} \quad v\colon \mathsf{Msg}_t \\ \kappa \equiv (\mathcal{N}, \mathcal{M}, \Omega) \end{array}}{\kappa, \alpha(e_t), v \rightsquigarrow_{\mathsf{send}} (\mathcal{N}, \mathcal{M} \cup \{(\alpha(e_s) \triangleright_{\mathsf{Append}(v)} \mathsf{mbox}(\epsilon(e_t)))\}, \Omega)}$$

The M-Send rule is the only way to add a message to $\mathcal{M}$.

Definition 32 (M-Enqueue ‹/›). *An in-transit message m addressed to a mailbox engine m_t is consumed from $\mathcal{M}$, transitioning m_t from* Ready(f) *to* Busy(w)*. The mailbox engine then processes w through its behaviour via s-Process.*

$$\frac{\begin{array}{c} m \equiv (_ \triangleright_w m_t) \in \mathcal{M} \quad m_t \in \mathcal{E} \quad w\colon \mathsf{Msg}_{m_t} \\ m_t \equiv \langle _, _, \mathsf{Ready}(f), _, _ \rangle \quad f(w) \equiv \mathsf{tt} \end{array}}{\kappa \rightsquigarrow_{\mathsf{enqueue}} (\mathcal{N}[\epsilon(m_t) \mapsto \langle _, _, \mathsf{Busy}(w), _, _ \rangle], \mathcal{M} \setminus \{m\}, \Omega)}$$

Definition 33 (M-Dequeue ‹/›). *When a processing engine p is in state* $\mathsf{Ready}(f)$ *and its mailbox contains a wrapped message* $w\colon \mathsf{Msg}_{m_p}$ *that unwraps to a payload* $v\colon \mathsf{Msg}_p$ *accepted by filter* f*, the wrapped message is removed from the mailbox and* p *transitions to* $\mathsf{Busy}(v)$.

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad \mathsf{mode}(p) \equiv \mathsf{Process} \quad p \equiv \langle _, _, \mathsf{Ready}(f), _, _ \rangle \\ m_p \in \mathcal{E} \quad m_p \equiv \mathsf{mbox}(p) \quad q \equiv \mathsf{env}(\epsilon(m_p)) \\ w\colon \mathsf{Msg}_{m_p} \quad \mathsf{mailboxContains}(q, w) \quad \mathsf{unwrap}(w) \equiv \mathsf{some}(v) \quad v\colon \mathsf{Msg}_p \quad f(v) \equiv \mathsf{tt} \\ \mathcal{N}' \equiv \mathcal{N}[\epsilon(p) \mapsto \langle _, _, \mathsf{Busy}(v), _, _ \rangle][m_p \mapsto \langle _, _, _, _, \mathsf{mailboxRemove}(q, w) \rangle] \end{array}}{\kappa \rightsquigarrow_{\mathsf{dequeue}} (\mathcal{N}', \mathcal{M}, \Omega)}$$

Note that the M-Dequeue rule requires the filter predicate f to accept the message v, that is, $f(v) \equiv \mathsf{tt}$. A message v in the mailbox for which $f(v) \equiv \mathsf{ff}$ remains in the mailbox until the filter is updated or the engine is terminated.

4.6. Behaviour Evaluation

This subsection formalises how an engine evaluates its guarded actions in response to a message.

Definition 34 (B-GuardedActionEval ‹/›). *For an engine p processing message* $v\colon \mathsf{Msg}_p$*, a guarded action* $\langle g, a \rangle \in b_p$ *is evaluated: if guard g accepts v (returning* $\mathsf{some}(r)$*), then action a is applied to produce an effect.*

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad v\colon \mathsf{Msg}_p \quad p \equiv \langle _, b_p, \mathsf{Busy}(v), \mathsf{cfg}_p, \mathsf{env}_p \rangle \\ \langle g, a \rangle \in b_p \quad g(v, \mathsf{cfg}_p, \mathsf{env}_p) \equiv \mathsf{some}(r) \end{array}}{p, \langle g, a \rangle \vdash v \downarrow a(r, v, \mathsf{cfg}_p, \mathsf{env}_p)}$$

Definition 35 (B-NoMatchingGuard ‹/›). *For a guarded action* $\langle g, a \rangle \in b_p$*, if guard g rejects message v (returning* none*), the action produces* Noop.

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad v\colon \mathsf{Msg}_p \quad p \equiv \langle _, b_p, \mathsf{Busy}(v), \mathsf{cfg}_p, \mathsf{env}_p \rangle \\ \langle g, a \rangle \in b_p \quad g(v, \mathsf{cfg}_p, \mathsf{env}_p) \equiv \mathsf{none} \end{array}}{p, \langle g, a \rangle \vdash v \downarrow \mathsf{Noop}}$$

Guard Selection Strategy.

Definition 36 (B-GuardStrategy ‹/›). *Under the non-overlapping guard assumption (Definition 16), engine p processing message v selects the unique guarded action* $\langle g_i, a_i \rangle$ *whose guard produces a non-*Noop *effect E, while all other guards* g_j $(j \neq i)$ *produce* Noop.

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad p \equiv \langle _, b_p, \mathsf{Busy}(v), _, _ \rangle \\ \langle g_i, a_i \rangle \in b_p \quad p, \langle g_i, a_i \rangle \vdash v \downarrow E \\ \forall_{j \neq i}\, \langle g_j, a_j \rangle \in b_p \,.\, p, \langle g_j, a_j \rangle \vdash v \downarrow \mathsf{Noop} \end{array}}{p \vdash v \downarrow E}$$

Definition 37 (B-AllGuardsFail ⟨/⟩). *If every guarded action $\langle g_j, a_j \rangle$ in b_p produces* Noop *for message v, the overall behaviour evaluation yields* Noop.

$$\frac{p \in \mathcal{E} \quad p \equiv \langle _, b_p, \mathsf{Busy}(v), _, _ \rangle \qquad \forall \langle g_j, a_j \rangle \in b_p \,.\, p, \langle g_j, a_j \rangle \vdash v \downarrow \mathsf{Noop}}{p \vdash v \downarrow \mathsf{Noop}}$$

When b_p is the empty list, the universal quantifier in B-AllGuardsFail is vacuously satisfied, so the rule produces $p \vdash v \downarrow \mathsf{Noop}$.

4.7. Effect Execution

Given a system state κ, an effect E, and a successor state κ', the judgment $\kappa \vdash E \rightsquigarrow \kappa'$ states that executing E in κ produces κ'. This judgment is defined by case analysis on E.

Definition 38 (E-Send ⟨/⟩). *Executing a* $\mathsf{Send}(j, l_t, v)$ *effect appends message v to the in-transit list, addressed to the mailbox of the target engine at l_t. The target validity premises—that e_t exists, is in* Process *mode, and has a message type matching the payload—ensure type preservation (Proposition 46).*

$$\frac{e_s, e_t \in \mathcal{E} \quad l_t \equiv \alpha(e_t) \quad \mathsf{mode}(e_t) \equiv \mathsf{Process} \quad j : \mathbb{I} \quad v : \mathsf{Msg}_j}{(\mathcal{N}, \mathcal{M}, \Omega) \vdash \mathsf{Send}(j, l_t, v) \rightsquigarrow (\mathcal{N}, \mathcal{M} \cup \{(\alpha(e_s) \triangleright_{\mathsf{Append}(v)} \mathsf{mbox}(\epsilon(e_t)))\}, \Omega)}$$

Definition 39 (E-Update ⟨/⟩). *Executing an* $\mathsf{Update}(s)$ *effect replaces engine p's execution environment with the value $s : \mathsf{Env}_p$.*

$$\frac{p \in \mathcal{E} \quad v : \mathsf{Msg}_p \quad s : \mathsf{Env}_p \qquad \vdots \qquad p \vdash v \downarrow \mathsf{Update}(s)}{(\mathcal{N}, \mathcal{M}, \Omega) \vdash \mathsf{Update}(s) \rightsquigarrow (\mathcal{N}[\epsilon(e_p) \mapsto \langle _, _, _, _, s \rangle], \mathcal{M}, \Omega)}$$

Definition 40 (E-MFilter ⟨/⟩). *Executing an* $\mathsf{MFilter}(f)$ *effect sets engine p's message filter to $f : \mathsf{Msg}_p \to \mathbf{B}$, transitioning it from* $\mathsf{Busy}(v)$ *to* $\mathsf{Ready}(f)$.

$$\frac{p \in \mathcal{E} \quad v : \mathsf{Msg}_p \quad f : \mathsf{Msg}_p \to \mathbf{B} \qquad \vdots \qquad p \vdash v \downarrow \mathsf{MFilter}(f)}{(\mathcal{N}, \mathcal{M}, \Omega) \vdash \mathsf{MFilter}(f) \rightsquigarrow (\mathcal{N}[\epsilon(p) \mapsto \langle _, _, \mathsf{Ready}(f), _, _ \rangle], \mathcal{M}, \Omega)}$$

When composed via E-Chain, this transition takes priority over the default return to $\mathsf{Ready}(\lambda_.\mathsf{tt})$ *in s-Process.*

Definition 41 (E-Spawn ⟨/⟩). *Executing a* Spawn(j, c, s) *effect on node* n_i *creates a child engine of type* $j : \mathbb{I}$ *with initial configuration* c *and environment* s*, delegating to* s-SpawnWithMailbox.

$$\frac{\begin{array}{c} n_i \in \mathcal{N} \quad p \in \mathcal{E}_i \quad j : \mathbb{I} \quad \iota := \Omega \\ c \equiv \langle \alpha(p), \mathsf{Process}, _ \rangle \quad s : \mathsf{Env}_j \quad b : \mathsf{EBeh}_j \\ \vdots \\ \kappa, n_i, j, \mathsf{some}(\alpha(p)), \iota, b, \lambda_.\mathsf{tt}, \mathsf{Process}, c, s \rightsquigarrow_{\mathsf{spawn\text{-}mbox}} \kappa' \end{array}}{\kappa \vdash \mathsf{Spawn}(j, c, s) \rightsquigarrow \kappa'}$$

Definition 42 (E-Chain ⟨/⟩). *Executing a* Chain(eff_1, eff_2) *effect sequences two sub-effects:* eff_1 *is executed in state* κ *yielding* κ'*, then* eff_2 *in* κ' *yielding* κ''*.*

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad v : \mathsf{Msg}_p \\ \vdots \\ p \vdash v \downarrow \mathsf{Chain}(eff_1, eff_2) \quad \kappa \vdash eff_1 \rightsquigarrow \kappa' \quad \kappa' \vdash eff_2 \rightsquigarrow \kappa'' \end{array}}{\kappa \vdash \mathsf{Chain}(eff_1, eff_2) \rightsquigarrow \kappa''}$$

Definition 43 (E-Terminate ⟨/⟩). *Executing a* Terminate *effect sets engine* p*'s status to* Terminated*.*

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad v : \mathsf{Msg}_p \\ \vdots \\ p \vdash v \downarrow \mathsf{Terminate} \end{array}}{\kappa \vdash \mathsf{Terminate} \rightsquigarrow (\mathcal{N}[\epsilon(p) \mapsto \langle _, _, \mathsf{Terminated}, _, _ \rangle], \mathcal{M}, \Omega)}$$

The s-Clean *rule subsequently removes the engine from the system.*

Definition 44 (E-Noop ⟨/⟩). *Executing a* Noop *effect leaves the system state* κ *unchanged.*

$$\frac{\begin{array}{c} p \in \mathcal{E} \quad v : \mathsf{Msg}_p \\ \vdots \\ p \vdash v \downarrow \mathsf{Noop} \end{array}}{\kappa \vdash \mathsf{Noop} \rightsquigarrow \kappa}$$

4.8. Engine Processing

The s-Process rule ties together behaviour evaluation, effect execution, and status management into a single system-level transition.

Definition 45 (s-Process ⟨/⟩). *When a processing engine is in the* Busy(m) *state, its behaviour is evaluated against message* m *to produce an effect* E*, the effect is executed, and the engine returns to the ready state.*

$$n_i \in \mathcal{N} \quad p \in \mathcal{E}_i \quad p \equiv \langle i_p, b_p, \mathsf{Busy}(m), \mathsf{cfg}_p, \mathsf{env}_p \rangle$$

$$\vdots$$

$$p \vdash m \downarrow E \qquad \kappa \vdash E \rightsquigarrow \kappa' = (\mathcal{N}', \mathcal{M}', \Omega')$$

$$p' \equiv \epsilon'(\alpha(p)) \qquad o' \equiv \begin{cases} \mathsf{Ready}(\lambda_.\mathsf{tt}) & \textit{if}\ \mathsf{status}(p') = \mathsf{Busy}(_) \\ \mathsf{status}(p') & \textit{otherwise} \end{cases}$$

$$\frac{\epsilon'' \equiv \epsilon'[\alpha(p) \mapsto \langle i_p, b_p, o', \mathsf{cfg}_{p'}, \mathsf{env}_{p'} \rangle]}{\kappa, p, m \rightsquigarrow_{\mathsf{process}} (\mathcal{N}'[\epsilon' \mapsto \epsilon''], \mathcal{M}', \Omega')}$$

Let p' denote the engine at address $\alpha(p)$ after effect execution. If the effects did not change the engine's status (i.e. it remains $\mathsf{Busy}(_)$), s-Process transitions it to $\mathsf{Ready}(\lambda_.\mathsf{tt})$. If an E-MFilter or E-Terminate effect already changed the status, that status is preserved. This design ensures that filters set by MFilter take effect immediately, while providing a sensible default when no filter is specified.

4.9. Worked Example: Causal Delivery

We trace the operational semantics on the causal delivery mailbox of Example 23. The scenario involves a broker engine t of type broker whose mailbox $\mathsf{mbox}(\epsilon(t))$ uses the causal behaviour $\langle g_c, a_c \rangle$. Three topic messages arrive: m_1 has no dependencies, m_2 depends on m_3, and m_3 has none. They arrive in order m_1, m_2, m_3; Figure 5 gives a visual overview.

The initial mailbox state is $q_0 = (\mathsf{dlv} = \emptyset,\ \mathsf{pnd} = \emptyset,\ \mathsf{rdy} = [\,])$.

Step 1: m_1 enters the system. A publisher s sends m_1 with $\mathsf{deps}(m_1) = \emptyset$. By M-Send, since $\mathsf{mode}(t) \equiv \mathsf{Process}$ and $m_1 : \mathsf{Msg}_{\mathsf{broker}}$, a packet $(\alpha(s) \triangleright_{\mathsf{Append}(m_1)} \mathsf{mbox}(\epsilon(t)))$ is added to $\mathcal{M}$.

Step 2: m_1 is enqueued. By M-Enqueue, the mailbox $\mathsf{mbox}(\epsilon(t))$ transitions from $\mathsf{Ready}(f)$ to $\mathsf{Busy}(\mathsf{Append}(m_1))$.

Step 3: The mailbox processes m_1. s-Process fires. B-GuardStrategy selects the unique guarded action: $g_c(\mathsf{Append}(m_1), k, q_0) = \mathsf{some}(m_1)$. Since $\mathsf{deps}(m_1) = \emptyset \subseteq q_0.\mathsf{dlv}$, the action produces:

$$\mathsf{Chain}(\mathsf{Update}((\mathsf{dlv} \cup \{h_1\},\ \mathsf{pnd},\ \mathsf{rdy} +\!\!+ [m_1])), \mathsf{Noop})$$

E-Chain executes: E-Update stores m_1 in the ready queue and records h_1 in the delivered set; E-Noop is the identity. The mailbox returns to $\mathsf{Ready}(\lambda_.\mathsf{tt})$.

$$q_1 = (\mathsf{dlv} = \{h_1\},\ \mathsf{pnd} = \emptyset,\ \mathsf{rdy} = [m_1])$$

Step 4: m_1 is delivered. By M-Dequeue, broker t transitions $\mathsf{Ready}(f) \to \mathsf{Busy}(m_1)$, and m_1 is removed from the mailbox's ready queue. The mailbox state becomes

$$q_1' = (\mathsf{dlv} = \{h_1\},\ \mathsf{pnd} = \emptyset,\ \mathsf{rdy} = [\,])\,.$$



Figure 5. Message sequence chart for the causal delivery trace. Amber arrows denote M-Send / M-Enqueue steps; green arrows denote M-Dequeue deliveries. Message m_2 is buffered at Step 5 because its dependency m_3 has not yet been delivered; when m_3 arrives at Step 6, a cascade releases m_2, restoring causal order.

Step 5: m_2 arrives and is buffered. m_2 enters via M-Send and M-Enqueue, then s-Process fires. The guard matches: $g_c(\mathsf{Append}(m_2), k, q_1') = \mathsf{some}(m_2)$. However, $\mathsf{deps}(m_2) = \{h_3\} \not\subseteq \{h_1\} = q_1'.\mathsf{dlv}$. The action produces:

$$\mathsf{Update}((\mathsf{dlv} = \{h_1\},\ \mathsf{pnd} \cup \{h_2 \mapsto m_2\},\ \mathsf{rdy} = [\,]))$$

E-Update stores m_2 in the pending buffer.

$$q_2 = (\mathsf{dlv} = \{h_1\},\ \mathsf{pnd} = \{h_2 \mapsto m_2\},\ \mathsf{rdy} = [\,])$$

Step 6: m_3 arrives and triggers a cascade. m_3 enters via M-Send and M-Enqueue, then s-Process fires. The guard matches. Since $\mathsf{deps}(m_3) = \emptyset \subseteq q_2.\mathsf{dlv}$, the action first stores m_3 in the ready queue. The cascade check inspects $q_2.\mathsf{pnd}$: message m_2 has $\mathsf{deps}(m_2) = \{h_3\} \subseteq \{h_1, h_3\}$, so m_2 is now satisfiable. The action produces:

$$\begin{aligned}\mathsf{Chain}(\ &\mathsf{Update}((\mathsf{dlv} \cup \{h_3\},\ \mathsf{pnd},\ \mathsf{rdy} +\!\!+ [m_3])),\\ &\mathsf{Update}((\mathsf{dlv} \cup \{h_3\},\ \mathsf{pnd} \setminus \{h_2\},\ \mathsf{rdy} +\!\!+ [m_3, m_2]))\ )\end{aligned}$$

E-Chain sequences two E-Update effects. Because each E-Update replaces the entire environment, the second effect supersedes the first: it records m_3 in the ready queue *and* moves the now-satisfiable m_2 from pending to ready.

$$q_3 = (\mathsf{dlv} = \{h_1, h_3\},\ \mathsf{pnd} = \emptyset,\ \mathsf{rdy} = [m_3, m_2])$$

Step 7: Causal delivery. Two applications of M-Dequeue deliver m_3 then m_2 to broker t—restoring causal order despite the out-of-order arrival of m_2 before m_3.

This trace exercises M-Send, M-Enqueue, M-Dequeue, s-Process, B-GuardStrategy, B-GuardedActionEval, E-Update, E-Chain, and E-Noop—nine of the system's eighteen rules. The cascade in Step 6 illustrates why first-class mailbox actors are essential: a passive data structure could not conditionally release buffered messages upon the arrival of their dependencies.

The inference rules presented above collectively govern the system's evolution. Every system-level operation op induces a state transition $\kappa \rightsquigarrow \kappa'$. Figure 6 provides a summary of all rules organised by judgment form.

Judgment form	Rules
System-level operations	s-Node, s-SpawnWithMailbox, s-Clean, M-Send, M-Enqueue, M-Dequeue
Behaviour evaluation	B-GuardStrategy, B-AllGuardsFail
Guarded action evaluation	B-GuardedActionEval, B-NoMatchingGuard
Effect execution	E-Send, E-Update, E-MFilter, E-Spawn, E-Chain, E-Terminate, E-Noop
Engine processing	s-Process

Figure 6. Rules for the operational semantics, organised by judgment form.

5. Properties

We state several metatheoretic properties of the system. Full proofs are deferred to an extended version; here we provide proof sketches.

We first define well-typedness of system states. A system state $\kappa = (\mathcal{N}, \mathcal{M}, \Omega)$ is *well-typed* if it satisfies the following invariants:

1. **Component Typing:** Every engine $p \in \mathcal{E}$ of type Eng_i has correctly typed components: $\mathsf{status}(p) : \mathsf{EStatus}_i$, $\mathsf{cfg}_p : \mathsf{Cfg}_i$, and $\mathsf{env}_p : \mathsf{Env}_i$.

2. **Message Typing:** Every message $(s \triangleright_v t) \in \mathcal{M}$ is well-typed with respect to its target, i.e., $v : \mathsf{Msg}_t$.

3. **Spawn Pairing:** Every processing engine p is paired with a live mailbox engine $\mathsf{mbox}(p)$ of matching type index in mail mode.

4. **Address Freshness:** The counter Ω is strictly greater than any existing node or engine identifier.

5. **Message Integrity:** All in-transit messages target live engines (no orphaned messages), ensuring their addresses are valid and precede Ω.

These invariants ensure that the system's structural properties—such as mailbox pairing and message delivery targets—are preserved during evolution.

Proposition 46 (Type Preservation ‹/›). *If $\kappa \rightsquigarrow \kappa'$ and κ is well-typed, then κ' is well-typed.*

Proof sketch. By case analysis on the transition rule applied. s-Node adds a node with an empty engine map, trivially preserving invariants. s-EngineSpawn creates an engine with correctly typed components; s-SpawnWithMailbox composes two such creations. For message passing: M-Send constructs messages with payloads satisfying $v : \mathsf{Msg}_t$ by premise, wrapping in Append; M-Enqueue preserves the message type when transitioning the mailbox engine to $\mathsf{Busy}(w)$, where w has type Msg_m; M-Dequeue preserves the type family when moving a message to the processing engine's busy state. For effect execution: E-Send appends a well-typed message by requiring $m : \mathsf{Msg}_t$ and redirecting to the target's mailbox; E-Update requires $s : \mathsf{Env}_p$; E-Spawn delegates to s-SpawnWithMailbox; E-Terminate and E-MFilter change only the status, remaining in $\mathsf{EStatus}_i$; E-Chain composes two type-preserving steps; E-Noop is the identity. s-Process evaluates the behaviour, executes the resulting effect, and restores the engine to $\mathsf{Ready}(f)$ or preserves the status set by the effect. s-Clean removes an engine without affecting others. □

Proposition 47 (Progress ‹/›). *A well-typed system state κ in which either (i) $\mathcal{M} \neq \emptyset$, or (ii) there exists an engine in state $\mathsf{Busy}(m)$, or (iii) there exists an engine in state $\mathsf{Terminated}$, can take a step.*

Proof sketch. We consider each case. (i) If $\mathcal{M} \neq \emptyset$, let $(s \triangleright_w t) \in \mathcal{M}$. By well-typedness, t is a valid mailbox engine address. Since $\mathsf{mbox}()$ maps processing engines to their mailboxes and the message is addressed to a mailbox, the target mailbox engine exists. If the mailbox engine is in state $\mathsf{Ready}(f)$, then since f is $\lambda_.\mathsf{tt}$ by default, the premises of M-Enqueue are satisfied. If the mailbox engine is $\mathsf{Busy}(_)$, then case (ii) applies to it and s-Process fires, returning it to $\mathsf{Ready}(_)$. (ii) If an engine p is in state $\mathsf{Busy}(m)$, the behaviour b_p is a finite list of guarded actions. Each guard g_j applied to the input either returns $\mathsf{some}(r)$ or none. If some guard matches, B-GuardStrategy applies; otherwise B-AllGuardsFail applies. In either case, a judgment $p \vdash m \downarrow E$ is derivable. Since the operational rules for effects are total, an effect execution step $\kappa \vdash E \rightsquigarrow \kappa'$ exists, and s-Process fires. (iii) If an engine p has status $\mathsf{Terminated}$, then $\mathsf{status}(p) \equiv \mathsf{Terminated}$ and s-Clean applies. □

Proposition 48 (Effect Determinism ‹/›). *For any engine p with a well-formed behaviour (Definition 17) in state $\mathsf{Busy}(v)$, the judgment $p \vdash v \downarrow E$ determines E uniquely.*

Proof sketch. Guards are pure functions of type $\mathsf{In}_i \to \mathsf{Maybe}(R)$, so each $g_j(v, \mathsf{cfg}_p, \mathsf{env}_p)$ is determined. By the non-overlapping guard condition bundled in the well-formed behaviour, for any input at most one guard g_i returns $\mathsf{some}(r)$ while all others return none. Thus: if exactly one guard matches, B-GuardStrategy selects it uniquely and the effect is $a_i(r, v, \mathsf{cfg}_p, \mathsf{env}_p)$, which is determined since actions are functions. If no guard matches, B-AllGuardsFail yields Noop. These two cases are exhaustive and mutually exclusive, so E is uniquely determined. □

Proposition 49 (Mailbox Isolation ‹/›)**.** *A processing engine never directly receives a message from $\mathcal{M}$. All messages are mediated by the corresponding mailbox engine.*

Proof sketch. By inspection of the M-Send and E-Send rules: each premise $\mathsf{mode}(e_t) \equiv \mathsf{Process}$ restricts the target to a processing engine, and each conclusion redirects the message to $\mathsf{mbox}(\epsilon(e_t))$. The M-Enqueue rule delivers messages only to mailbox engines by transitioning them to $\mathsf{Busy}(w)$. The M-Dequeue rule is the sole mechanism by which a processing engine transitions from $\mathsf{Ready}(f)$ to $\mathsf{Busy}(v)$, and it reads from the paired mailbox engine. Hence, no rule places a message directly in a processing engine's state. □

Lemma 50 (Mailbox Persistence)**.** *When s-Clean removes a terminated processing engine at address a, the paired mailbox engine $\mathsf{mbox}(a)$ is unaffected. In a well-typed state, the mailbox engine still exists after removal, retains the same type index, and remains in mail mode.*

Proof sketch. Processing and mailbox engines of the same pair occupy distinct addresses ($\mathsf{mbox}(a) \neq a$). Hence $\mathit{removeEngineAt}(a)$ does not alter the engine map at $\mathsf{mbox}(a)$. □

Definition 51 (Unique In-Transit)**.** *A message m is* unique in transit *from step n onwards if, at every step $k \geq n$, m appears at most once in the in-transit list $\mathcal{M}$. Formally, for every decomposition $\mathcal{M} = L_1 \mathbin{+\!\!+} [m] \mathbin{+\!\!+} L_2$, we have $m \notin L_1$ and $m \notin L_2$.*

Corollary 52 (Trace Invariants)**.** *Let σ be an execution trace. If $\sigma(n)$ is well-typed and satisfies mailbox isolation, then for every $k \geq n$, $\sigma(k)$ is well-typed and satisfies mailbox isolation.*

Proof sketch. By induction on k, applying Propositions 46 and 49 at each successor step. □

Proposition 53 (Eventual Delivery ‹/›)**.** *Let σ be an execution trace with predicate-level strong fairness (TLA$^+$-style): for every binary predicate P on*

states, if P is infinitely often enabled from step n onwards (i.e. for every $k \geq n$ there exists $l \geq k$ such that P is enabled at l), then P relates some consecutive pair $(\sigma(k), \sigma(k+1))$ with $k \geq n$.

Assume that the initial state $\sigma(n)$ is well-typed, satisfies mailbox isolation (Proposition 49), and that the message m is unique in transit from step n onwards (Definition 51). Assume further that the target mailbox eventually accepts *m: at any step where m is still in transit, there is a future step at which the mailbox engine is in state* Ready(f) *with $f(w) \equiv \mathrm{tt}$ for the message payload w. If $m \in \mathcal{M}$ at step n, then there exists $k \geq n$ such that $m \notin \mathcal{M}$ at step k.*

Proof sketch. By contradiction. Suppose $m \in \mathcal{M}$ at every step $k \geq n$. Define the predicate $P(\kappa, \kappa')$: "κ' is obtained from κ by removing m from the in-transit list via M-Enqueue."

We show P is infinitely often enabled. Given any $k \geq n$, since m is in transit the *eventually-accepts* hypothesis provides a future step $l \geq k$ at which the target mailbox is in state Ready(f) and accepts the payload. Corollary 52 ensures well-typedness and mailbox isolation hold at l, so the M-Enqueue premises are satisfied and a witness state κ' with m removed exists.

By strong fairness, P fires at some step $k_0 \geq n$, yielding $\sigma(k_0 + 1)$ with m removed. Because m is unique in transit, the removal leaves no copy of m in the message list. This contradicts $m \in \mathcal{M}$ at step $k_0 + 1$. □

Remark 54 (Classical Reasoning)**.** The proof of Proposition 53 proceeds by contradiction: it assumes the negation of the conclusion (the message remains in transit forever) and derives $\bot$. In the Lean 4 mechanisation this corresponds to `by_contra`, which invokes the law of excluded middle. This use of classical logic is standard for liveness properties under TLA$^+$-style fairness, where the existential witness (the step at which the message is consumed) is not computationally extractable. The Lean 4 proof uses strong fairness (`StronglyFair`) together with an explicit liveness hypothesis (`EventuallyAccepts`) that the target mailbox is infinitely often ready to accept the message. This resolves the tension between fairness and mailbox oscillation: because the mailbox may alternate between ready and busy states, the enqueue predicate is only *repeatedly* (not *continuously*) enabled, necessitating strong fairness. All other propositions in this section are proved constructively.

Remark 55 (Causal Delivery and Eventual Delivery)**.** The causal delivery mailbox of Example 23 satisfies Proposition 53: since its guard always matches, every in-transit message is eventually enqueued and processed by the mailbox behaviour. However, a message buffered in the pending set is not delivered to the processing engine until its dependencies arrive. Guaranteeing *causal delivery to the processing engine* requires the additional assump-

tion that all dependency chains are finite and that every depended-upon message eventually enters the system. Under this assumption and weak fairness, each pending message's dependencies are eventually satisfied, triggering the cascade that moves it to the ready queue.

Remark 56 (Causal Invariant Preservation)**.** The Lean 4 mechanisation additionally verifies that the causal mailbox action of Example 23 preserves a *causal invariant*: every message in the ready queue has all its dependencies recorded in the delivered set. In the direct-delivery branch ($\mathsf{deps}(v) \subseteq q.\mathsf{dlv}$), the cascade function *findCascade* returns only messages whose dependencies are met with respect to $q.\mathsf{dlv} \cup \{\mathsf{h}(v)\}$. In the buffering branch, the ready queue is unchanged and the invariant holds trivially. Global preservation (`causal_invariant_preserved`) is fully proved for all operational rules under an additional *broker-safety hypothesis*: every broker engine in the successor state that was not identically present in the predecessor must satisfy the causal invariant. For s-SpawnWithMailbox and s-Process, the proof splits (via the law of excluded middle) on whether the engine at a given address is unchanged—using the old invariant—or new/modified—using the broker-safety hypothesis. In the concrete pub/sub instantiation, this hypothesis is discharged by (a) freshly spawned brokers starting with an empty state (vacuously invariant) and (b) `causalAction` preserving the invariant.

6. Related Work

Actor Model Foundations. The actor model, introduced by Hewitt, Bishop, and Steiger [HBS73] and developed by Agha [Agh86, AMST97], provides the conceptual basis for our work. Our engine model refines the actor concept by introducing typed components—configurations, environments, message interfaces, and guarded-action behaviours—while preserving the fundamental principles of encapsulation and asynchronous message passing.

Process Calculi. Process calculi such as CCS and the π-calculus [Mil89] provide foundational frameworks for reasoning about concurrent communication. Our system shares the emphasis on labelled transitions and compositional semantics, but differs in treating message storage as a first-class concern through mailbox engines rather than relying on channel-based communication.

Erlang. The process-oriented architecture of Erlang [Arm10, Arm97] is the closest practical counterpart to our model. Its formal semantics [BHT24] defines processes and message passing but treats the mailbox as an opaque runtime primitive. Our work makes the mailbox explicit and programmable by promoting it to actor status.

Session and Behavioural Types. Session types [HYC08] and behavioural types for actors [FHK+24, FAS+23] provide type-theoretic guarantees for communication protocols. Our dependent type families for message interfaces serve a related purpose—ensuring type-safe communication—though we focus on the operational semantics of mailbox management rather than protocol compliance. Mailbox types [FAS+23] are particularly relevant, as they enrich the type system to reason about mailbox contents, complementing our approach of making the mailbox a first-class entity.

Event-Driven Systems. The correct-by-construction approach of Event-B [Dup21] inspires our guarded-action formulation. Our guards and actions parallel Event-B events, with the effect system constraining the available operations. The connection to Dijkstra's guarded command language [Dij75] is also apparent in the non-overlapping guard assumption.

Mailbox Decoupling and Typing. The Kilim framework [SM08] achieves mailbox decoupling through specialised queues where actors pull messages when ready, but treats mailboxes as passive data structures. Actor selector patterns [IS14] provide selective receive without promoting the mailbox itself. Mailbox type systems explicitly reason about mailbox contents: de'Liguoro and Padovani's mailbox calculus [dP18] gives a behavioural type system for unordered mailboxes, and the Pat language [FLMP23] mechanises programmable mailboxes with type soundness and completeness of an algorithmic system. Our contribution differs by making mailboxes first-class actors with dependent-type-indexed interfaces and Lean mechanisation of the operational semantics.

Communicating Actor Automata. Communicating Actor Automata model Erlang processes as communicating machines with explicit mailboxes [OMT23], addressing dynamic topologies and process interactions. Our model similarly exposes the mailbox but uses dependent types to index engine components and provides a Lean formalisation of creation, enqueue/dequeue, and processing with paired mailboxes.

Formalisation of Actor Systems. Talcott [Tal98] provides an actor theory in rewriting logic, and Actario [YW15] develops a Coq formalisation of the actor model. Our dependent-type-theoretic approach offers a middle ground: more structured than rewriting-based approaches, while remaining independent of a specific proof assistant. The framework of [HPCH25] provides the actor-like semantics that we build upon, extending it with mailbox engines and metatheoretic properties.

7. Conclusion

We have presented a formal framework for actor systems in which mailboxes are promoted to independent, first-class actors—native actors with their own configuration, behaviour, and lifecycle. Unlike prior approaches that treat mailboxes as opaque primitives [BHT24] or passive data structures [SM08], our mailbox actors are fully-fledged engines whose guarded-action behaviours govern delivery, filtering, and scheduling. The dependent-type-theoretic formulation, with all type families indexed by a finite type of engine type indices, ensures type-safe communication by construction.

The operational semantics cover engine creation with automatic mailbox pairing, asynchronous message passing through mailbox intermediaries, behaviour evaluation under well-formed behaviours with non-overlapping guards, effect execution, and engine lifecycle management. We established type preservation, progress, effect determinism, mailbox isolation, and eventual delivery as metatheoretic properties. The mailbox isolation property, in particular, captures the key design invariant: all messages to a processing engine are mediated by its dedicated mailbox actor, which is guaranteed by the structure of the transition rules.

A companion Lean 4 mechanisation covers all definitions, all five propositions of Section 5, and auxiliary results such as mailbox persistence (Lemma 50) and trace-level invariant preservation (Corollary 52). The mechanisation provides constructive proofs for the core metatheory, including type preservation, progress, effect determinism, mailbox isolation, and eventual delivery. In particular, the progress theorem (Proposition 47) is now supported by a constructive verification of effect execution totality (`effectEvalStep_total`), eliminating the previously required axiom. The mechanisation is complete, with no remaining axioms or unproven gaps concerning address freshness or well-typedness preservation. Eventual delivery (Proposition 53) is proved under strong fairness together with a liveness hypothesis that the target mailbox is infinitely often ready to accept the message (see Remark 54). The mechanisation also includes a concrete instantiation of the abstract framework for the causal delivery mailbox of Example 23, with the `causalAction` action proved to preserve a causal invariant (Remark 56) and global preservation fully proved for all operational rules under a broker-safety hypothesis (see Remark 56).

Limitations. The model assumes static engine types (no dynamic type extension), static engine allocation (no migration between nodes), and fixed behaviours (no runtime behaviour modification). The non-overlapping guard condition, bundled structurally via well-formed behaviours, ensures determinism but restricts the expressiveness of behaviours. Multiple mailboxes per processing engine are excluded to avoid race conditions and preserve

delivery guarantees.

Future Work. Several directions remain open. A prototype implementation in Elixir—which provides a robust actor runtime through the Erlang VM—would validate the practical applicability of the framework and bridge the gap between the formal model and deployed systems. Dynamic engine type extension would enable open systems in which new engine types can be registered at runtime. Relaxing the non-overlapping guard assumption to permit prioritised or nondeterministic guard selection would broaden the class of expressible behaviours. Finally, integrating mailbox types [FAS+23] into the framework could combine our operational guarantees with static type-theoretic reasoning about mailbox contents.

8. Acknowledgements

We would like to express our gratitude to Jeremy Ornelas and Christophe De Troyer, whose insightful discussions inspired the development of this work.

References

Agh86. Gul A. Agha. *Actors: A Model of Concurrent Computation in Distributed Systems.* MIT Press, 1986. (cit. on pp. 1 and 26.)

AMST97. Gul A. Agha, Ian A. Mason, Scott F. Smith, and Carolyn L. Talcott. A foundation for actor computation. *J. Funct. Program.*, 7(1):1–72, January 1997. doi:10.1017/S095679689700261X. (cit. on pp. 1 and 26.)

Arm97. Joe Armstrong. The development of erlang. *SIGPLAN Not.*, 32(8):196–203, aug 1997. doi:10.1145/258949.258967. (cit. on p. 26.)

Arm10. Joe Armstrong. Erlang. *Communications of the ACM*, 53(9):68–75, 2010. (cit. on pp. 1 and 26.)

BHT24. Péter Bereczky, Dániel Horpácsi, and Simon Thompson. Program equivalence in the erlang actor model. *Computers*, 13(11), 2024. URL: https://www.mdpi.com/2073-431X/13/11/276, doi:10.3390/computers13110276. (cit. on pp. 1, 26, and 28.)

Dij75. Edsger W. Dijkstra. Guarded commands, nondeterminacy and formal derivation of programs. *Commun. ACM*, 18(8):453–457, August 1975. doi:10.1145/360933.360975. (cit. on pp. 10 and 27.)

DKVCDM16. Joeri De Koster, Tom Van Cutsem, and Wolfgang De Meuter. 43 years of actors: a taxonomy of actor models and their key properties. In *Proceedings of the 6th International Workshop on Programming Based on Actors, Agents, and Decentralized Control*, AGERE 2016, page 31–40, New York, NY, USA, 2016. Association for Computing Machinery. doi:10.1145/3001886.3001890. (cit. on pp. 1 and 10.)

dP18. Ugo de'Liguoro and Luca Padovani. Mailbox types for unordered interactions. In *Proceedings of the 45th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL)*, pages 1–31, 2018. URL: https://arxiv.org/abs/1801.04167, doi:10.1145/3158095. (cit. on p. 27.)

Dup21. Guillaume Dupont. *Correct-by-Construction Design of Hybrid Systems Based on Refinement and Proof.* Theses, Institut National Polytechnique de Toulouse - INPT, January 2021. URL: https://theses.hal.science/tel-04165215. (cit. on pp. 5 and 27.)

FAS+23. Simon Fowler, Duncan Paul Attard, Franciszek Sowul, Simon J. Gay, and Phil Trinder. Special delivery: Programming with mailbox types. *Proceedings of the ACM on Programming Languages*, 7(ICFP):78–107, August 2023. URL: http://dx.doi.org/10.1145/3607832, doi:10.1145/3607832. (cit. on pp. 1, 27, and 29.)

FHK+24. Simon Fowler, Philipp Haller, Roland Kuhn, Sam Lindley, Alceste Scalas, and Vasco T. Vasconcelos. Behavioural types for heterogeneous systems (position paper). *Electronic Proceedings in Theoretical Computer Science*, 401:37–48, April 2024. URL: http://dx.doi.org/10.4204/EPTCS.401.4, doi:10.4204/eptcs.401.4. (cit. on p. 27.)

FLMP23. Simon Fowler, Sam Lindley, J. Garrett Morris, and Luca Padovani. Special delivery: Programming with mailbox types. *Proceedings of the ACM on Programming Languages*, 7(ICFP):1–30, 2023. URL: https://arxiv.org/abs/2306.12935, doi:10.1145/3607846. (cit. on p. 27.)

HBS73. Carl Hewitt, Peter Bishop, and Richard Steiger. A universal modular actor formalism for artificial intelligence. pages 235–245. Morgan Kaufmann Publishers Inc., 1973. (cit. on pp. 1 and 26.)

HPCH25. Tobias Heindel, Jonathan Prieto-Cubides, and Anthony Hart. Dynamic Effective Timed Communication Systems. *Anoma Research Topics*, Mar 2025. URL: https://doi.org/10.5281/zenodo.14984147, doi:10.5281/zenodo.14984148. (cit. on pp. 4 and 27.)

HYC08. Kohei Honda, Nobuko Yoshida, and Marco Carbone. Multiparty asynchronous session types. In *Proceedings of the 35th annual ACM SIGPLAN-SIGACT symposium on Principles of programming languages*, pages 273–284, 2008. (cit. on p. 27.)

IS14. Shams M. Imam and Vivek Sarkar. Selectors: Actors with multiple guarded mailboxes. SPLASH '14. ACM, October 2014. URL: http://dx.doi.org/10.1145/2687357.2687360, doi:10.1145/2687357.2687360. (cit. on p. 27.)

Mil89. R. Milner. *Communication and Concurrency*. Prentice-Hall, Inc., USA, 1989. (cit. on p. 26.)

OMT23. Dominic Orchard, Mihail Munteanu, and Paulo Torrens. Communicating actor automata - modelling erlang processes as communicating machines. *Electronic Proceedings in Theoretical Computer Science*, 378:38–48, apr 2023. URL: http://dx.doi.org/10.4204/EPTCS.378.4, doi:10.4204/eptcs.378.4. (cit. on p. 27.)

SM08. Sriram Srinivasan and Alan Mycroft. Kilim: Isolation-typed actors for java. In Jan Vitek, editor, *ECOOP 2008 – Object-Oriented Programming*, pages 104–128, Berlin, Heidelberg, 2008. Springer Berlin Heidelberg. (cit. on pp. 1, 27, and 28.)

Tal98. Carolyn L. Talcott. Composable semantic models for actor theories. *Higher Order Symbolic Computation*, 11(3):281–343, 1998. URL: http://dx.doi.org/10.1023/A:1010042915896, doi:10.1023/a:1010042915896. (cit. on p. 27.)

YW15. Shohei Yasutake and Takuo Watanabe. Actario: A framework for reasoning about actor systems. 2015. (cit. on p. 27.)