## Efficient and Robust CT Image Segmentation with a Level Set Network

Jonas A. Actor, <sup>1</sup> Béatrice Rivière, <sup>1</sup> and David Fuentes <sup>2</sup>

<sup>1</sup>Computational and Applied Mathematics, Rice University

<sup>2</sup>Imaging Physics, University of Texas MD Anderson Cancer Center







Goal: accurate, efficient, fast, robust image segmentation

## Why automate image segmentation?


- necessary for treatment plans for radiation therapy
- costly to perform by hand
- less interobserver variability


# Current automated segmentation methods

### Method 1 : Solve a PDE

- Evolution via expansion, convection, curvature
- Well-established theory to analyze approximation, stability
- Semiautomated : requires initialization by user
- Reliant on edge information + image gradients
- Robust to perturbation








 $\partial_t u - \gamma \nabla g_I \cdot \nabla u - g_I \left(\alpha + \beta \kappa(u)\right) \|\nabla u\| = 0$ convection
mean curvature

#### Method 2: Use a Neural Network

- Fast, accurate, state-of-the-art prediction capabilities
- "Black box": unclear why these work so well
- Fully automated, but requires hyperparameter to train
- Reliant on training data for generalization
- Sensitive to perturbation, adversarial attack



Both PDEs and CNNs use the same operations: convolutions followed by ReLU activations.

## Our proposed method

## Method 3: PDE structure + CNN learning

- PDE structure to leverage image properties
- PDE numerical discretization for stability, robustness
- Learning kernels to obtain CNN accuracy
- Fewer parameters for more efficient learning

## How to create a Level Set Network (LSN)

- Numerical discretization of PDE equation
- Replace derivatives with learned convolutions
- Upwind scheme becomes activation functions
- Timesteps become residual updates

**I**mage

Truth


PDE


LSN


CNN











Results

Method	PDE	LSN	CNN
# Parameters	3	69K	32M
Training Time	10mn	24hr	78hr
Avg DSC	0.745	0.804	0.955

**Results:** Parameters and DSC scores from three segmentation methods.

## Conclusions

- CNNs more accurate than PDE methods, LSN
- PDE methods, LSN provide analytical structure
- Mechanism for converting between PDEs and CNNs