

Understanding Neural Networks for Image Segmentation

Jonas Actor


Rice University

2 November 2019




jonasactor@rice.edu

Target application: medical image segmentation



Abdominal CT scan



Liver and tumor segmentation

Why automate?

- needed for treatment plans
- costly (time+effort) to perform by hand
- less interobserver variability → better accuracy

errors in segmentation = errors in radiation treatment


Goal: understand why CNNs work so well

- 1 Compare PDEs to CNNs
- 2 Build CNNs like PDEs
- 3 Analyze kernels and explain performance
 - Entrywise comparison
 - SVD comparison

Table of Contents


- 1 Compare PDEs to CNNs
- 2 Build CNNs like PDEs
- 3 Analyze kernels and explain performance
 - Entrywise comparison
 - SVD comparison

Classical Approach: Solve a PDE




Level Set Equation: time = 200

Classical Approach: Solve a PDE




Level Set Equation: time = 200

Classical Approach: Solve a PDE




Level Set Equation: time = 500

Classical Approach: Solve a PDE




Level Set Equation: time = 500

Classical Approach: Solve a PDE




Level Set Equation: time = 1100

Classical Approach: Solve a PDE



Level Set Equation: time = 1100

Classical Approach: Solve a PDE



Level Set Equation: time = 1500

Classical Approach: Level Set Equation

$$\partial_t u - \alpha \underbrace{g_I}_{\text{balloon force}} - \beta \underbrace{g_I \kappa(u)}_{\text{mean curvature}} - \gamma \underbrace{\nabla g_I \cdot \nabla u}_{\text{convection}} = 0$$

- Well-established theory to analyze approximation, stability
- Upwind finite differences + fast marching method
- Semiautomated : requires initialization by user
- Works for simple problems only : relies on edge information

Comparison: LSE vs CNN

| | Can analyze? | Accurate? |
|-----|--------------|-----------|
| LSE | yes | sometimes |
| CNN | no | yes |

Goal: accurate method we can analyze

Similarities between LSE and CNN

| | LSE | CNN |
|-------------|--|--|
| Convolution | finite difference kernel $\frac{1}{h^2} \begin{bmatrix} 0 & 1 & 0 \\ 1 & -4 & 1 \\ 0 & 1 & 0 \end{bmatrix}$ | learned kernel $\begin{bmatrix} k_{11} & k_{12} & k_{13} \\ k_{21} & k_{22} & k_{23} \\ k_{31} & k_{32} & k_{33} \end{bmatrix}$ |
| ReLU | upwind scheme $\max(0, D^+ * u) + \min(0, D^- * u)$ | activation function $\max(0, K * x + b)$ |

Table of Contents

- 1 Compare PDEs to CNNs
- 2 Build CNNs like PDEs
- 3 Analyze kernels and explain performance
 - Entrywise comparison
 - SVD comparison

Build a CNN like a LSE solver

Level Set Equation \longrightarrow Level Set Network

- 1 Discretize Level Set Equation
 - Explicit forward Euler in time
 - Upwind finite differences in space
- 2 Forward Euler \longrightarrow residual skip connections
- 3 Upwind finite differences \longrightarrow convolutions and ReLU

Forward Euler time discretization

$$\frac{u^{(t+1)} - u^{(t)}}{\delta_t} - \alpha g_I - \beta g_I \kappa(u^{(t)}) - \gamma \nabla g_I \cdot \nabla u^{(t)} = 0$$

Edge indicator g_I

$$g_I(x) = \frac{1}{1 + \|\nabla I(x)\|^2}$$

becomes

$$g_I(x) = \frac{1}{1 + \sum_{j=1}^{N_{conv}} (\sigma_j * I(x))^2}$$

Convection term: Upwind Finite Differences

$$\begin{aligned}\nabla g_I \cdot \nabla u^{(k)} &= \max\{0, \partial_x g_I\} D_x^+ * u^{(k)} - \max\{0, -\partial_x g_I\} D_x^- * u^{(k)} \\ &\quad + \max\{0, \partial_y g_I\} D_y^+ * u^{(k)} - \max\{0, -\partial_y g_I\} D_y^- * u^{(k)} \\ &= \text{ReLU}(\partial_x g_I) D_x^+ * u^{(k)} - \text{ReLU}(-\partial_x g_I) D_x^- * u^{(k)} \\ &\quad + \text{ReLU}(\partial_y g_I) D_y^+ * u^{(k)} - \text{ReLU}(-\partial_y g_I) D_y^- * u^{(k)}\end{aligned}$$

Curvature term $\kappa(u)$

$$\kappa(u^{(k)}) = \nabla \cdot \left(\frac{\nabla u^{(k)}}{\|\nabla u^{(k)}\|} \right)$$

becomes

$$\begin{aligned}\nabla \hat{u}^{(k)} &= \sum_{i=1}^{N_{conv}} \rho_i * u^{(k)} \\ \kappa(u^{(k)}) &= \sum_{j=1}^{N_{conv}} \sigma_j * \frac{\nabla \hat{u}^{(k)}}{\|\nabla \hat{u}^{(k)}\| + \varepsilon}\end{aligned}$$

Implementation

- If convolution kernels are finite difference kernels, we recover LSE
- If convolution kernels are learned, we construct LSN
- Python + Tensorflow / Keras implementation
- Our LSE agrees with ITK-SNAP, a common LSE-segmentation program

LSN: Results

| K-Fold | LSE | LSN Test | LSN Validation | UNet |
|---------|-------|----------|----------------|-------|
| 0 | 0.736 | 0.837 | 0.619 | 0.912 |
| 1 | 0.600 | 0.847 | 0.729 | 0.919 |
| 2 | 0.483 | 0.116 | 0.005 | 0.874 |
| 3 | 0.730 | 0.827 | 0.606 | 0.895 |
| 4 | 0.643 | 0.831 | 0.596 | 0.915 |
| Avg | 0.604 | 0.692 | 0.511 | 0.903 |
| Avg—{2} | 0.640 | 0.837 | 0.638 | 0.911 |

Table: DSC scores for each fold, from training the level set network.

Table of Contents

- 1 Compare PDEs to CNNs
- 2 Build CNNs like PDEs
- 3 Analyze kernels and explain performance
 - Entrywise comparison
 - SVD comparison

Identification of Kernels

- Are CNN convolution kernels finite difference stencils?
- Are they *close* to finite difference stencils?
- What about other standard image processing kernels?


Numerical analysis kernels

- Laplacian
- Edge detection
- Identity

Image processing kernels

- Gaussian blur
- Local mean
- Sharpen

Setup of CNN



Trained on MICCAI LiTS 2017 dataset for liver segmentation

Kernel Analysis: Comparing entries

- For each layer, separate each channel's 3×3 convolution kernel
- Flatten each 3×3 kernel into a vector $\in \mathbb{R}^9$
- Cluster with k-means
- Project down using PCA
- Project known numerical analysis and image processing kernels

Kernel Clustering Results




Figure: Convolution Layer 11 (encoder)

Kernel Clustering Results




Figure: Convolution Layer 14 (decoder)

Kernel Analysis: Comparing actions

- 1 Construct matrix $A_{[K]} \in \mathbb{R}^{n_x n_y \times n_x n_y}$ describing convolution with K
- 2 Compute singular values of linear operator
- 3 Compute singular values of clinical image processing kernels
- 4 Assign closest clinical feature F that has smallest spectral distance to K

Kernel Analysis: Comparing actions

$$\text{Kernel } K = \begin{bmatrix} k_{-1,-1} & k_{-1,0} & k_{-1,1} \\ k_{0,-1} & k_{0,0} & k_{0,1} \\ k_{1,-1} & k_{1,0} & k_{1,1} \end{bmatrix}$$

Kernel Analysis: Comparing actions

For $i \in \{-1, 0, 1\}$,

$$T_i = \begin{bmatrix} k_{i,0} & k_{i,1} & & & \\ k_{i,-1} & \ddots & \ddots & & \\ & \ddots & \ddots & \ddots & \\ & & \ddots & \ddots & k_{i,1} \\ & & & k_{i,-1} & k_{i,0} \end{bmatrix} \in \mathbb{R}^{n_x \times n_x}$$

Kernel Analysis: Comparing actions

$$A_{[K]} = \begin{bmatrix} T_0 & T_1 & & & \\ T_{-1} & \ddots & \ddots & & \\ & \ddots & \ddots & \ddots & \\ & & \ddots & \ddots & T_1 \\ & & & T_{-1} & T_0 \end{bmatrix} \in \mathbb{R}^{n_x n_y \times n_x n_y} \quad n_y \times n_y \text{ blocks}$$


Kernel Analysis: Comparing actions

$$\begin{aligned}A_{[K]} &= U_K \Sigma_K V_K^T & \forall K \in \{\text{layers}\} \\A_{[F]} &= U_F \Sigma_F V_F^T & \forall F \in \{\text{features}\}\end{aligned}$$

$$\text{find } \arg \min_{F \in \{\text{features}\}} \|\Sigma_K - \Sigma_F\|_1$$

Label as ‘indeterminate’ if not within 10% of largest singular value

Kernel Analysis Results



Conclusions

- Level Set Equation \neq Level Set Network \neq UNet
- Framework for using same operations (convolutions + ReLU) for both NNs and PDEs
- Framework for GPU-supported finite differences in Tensorflow
- Examine how learned CNN kernels change across different layers

JAA is supported by the NLM Training Program in Biomedical Informatics & Data Science (T15LM007093), supplemented by the Ken Kennedy Institute Computer Science & Engineering Enhancement Fellowship, funded by the Rice Oil & Gas HPC Conference.

