# Diagnosis, Fault-tolerant and Robust Control for a Torsional Control System

Mandatory assignment in DTU course 31320

Part A

Dimitrios Papageorgiou

February, 2022

Table 1: Revision history version changes date description 10.02.2022 all pages new new


1.a

## Assignment part A - 2022

### Introduction

This exercise presents a model of the ECP M205a system. It is a three-mass system that comprises three identical disks, connected in parallel via a flexible low-damped shaft. The system is equipped with three incremental position encoders (one for each disk) and two actuators, i.e. a motor applying torques to the bottom disk and one more for the middle disk.

The control goal is to ensure that either of the disks tracks a specified motion profile. The system considered is sketched in Figure 1. The variables are explained in Table 2.



The normal behaviours of the systems are described by the following con-

Table 2: List of variables

variable	$\mathbf{unit}$	description	
$ heta_1$	$\operatorname{rad}$	angular position of bottom disk	
$\omega_1$	$\rm rads^{-1}$	angular velocity of bottom disk	
$ heta_2$	rad	angular position of middle disk	
$\omega_2$	$\rm rads^{-1}$	angular velocity of middle disk	
$ heta_3$	rad	angular position of top disk	
$\omega_3$	$\rm rads^{-1}$	angular velocity of top disk	
$u_1$	Nm	torque command for the bottom disk	
$u_2$	Nm	torque command for the middle disk	
$y_1$	rad	measured angular position of bottom disk	
$y_2$	$\operatorname{rad}$	measured angular position of middle disk	
$y_3$	rad	measured angular position of top disk	

straints:

$$c_{1}: 0 = \dot{\theta}_{1} - \omega_{1}$$

$$c_{2}: 0 = J_{1}\dot{\omega}_{1} - u_{1} + b_{1}\omega_{1} + k_{1} (\theta_{1} - \theta_{2}) + d$$

$$c_{3}: 0 = \dot{\theta}_{2} - \omega_{2}$$

$$c_{4}: 0 = J_{2}\dot{\omega}_{2} - u_{2} + b_{2}\omega_{2} + k_{1} (\theta_{2} - \theta_{1}) + k_{2} (\theta_{2} - \theta_{3})$$

$$c_{5}: 0 = \dot{\theta}_{3} - \omega_{3}$$

$$c_{6}: 0 = J_{3}\dot{\omega}_{3} + b_{3}\omega_{3} + k_{2} (\theta_{3} - \theta_{2})$$

$$d_{7}: 0 = \dot{\theta}_{1} - \frac{d\theta_{1}}{dt}$$

$$d_{8}: 0 = \dot{\omega}_{1} - \frac{d\omega_{1}}{dt}$$

$$d_{9}: 0 = \dot{\theta}_{2} - \frac{d\theta_{2}}{dt}$$

$$d_{10}: 0 = \dot{\omega}_{2} - \frac{d\omega_{2}}{dt}$$

$$d_{11}: 0 = \dot{\theta}_{3} - \frac{d\theta_{3}}{dt}$$

$$d_{12}: 0 = \dot{\omega}_{3} - \frac{d\omega_{3}}{dt}$$

$$m_{13}: 0 = y_{1} - \theta_{1}$$

$$m_{14}: 0 = y_{2} - \theta_{2}$$

$$m_{15}: 0 = y_{3} - \theta_{3}$$

where  $d \triangleq T_C(\omega_1)$  is a function of the bottom disk angular velocity and represents the *unknown* Coulomb friction torque on that disk. The control input saturates at 2 Nm, i.e.  $u_1 \in [-2,2]$  Nm. The parameters in the forgoing con-

straints are listed in Table 3.

Table 3: List of parameters

Table 9. List of parameters				
${f symbol}$	value	$\operatorname{unit}$	$\operatorname{description}$	
$\overline{J_1}$	0.0025	$\mathrm{kgm^2}$	Bottom disk moment of inertia	
$J_2$	0.0018	$\mathrm{kgm^2}$	Middle disk moment of inertia	
$J_3$	0.0018	$\mathrm{kgm^2}$	Top disk moment of inertia	
$k_1$	2.7	$Nmrad^{-1}$	Stiffness of the bottom shaft	
$k_2$	2.6	$Nmrad^{-1}$	Stiffness of the middle shaft	
$b_1$	0.0029	$Nmsrad^{-1}$	Damping/friction on the bottom disk	
$b_2$	0.0002	$Nmsrad^{-1}$	Damping/friction on the middle disk	
$b_3$	0.00015	$Nmsrad^{-1}$	Damping/friction on the top disk	

A Simulink model and a parameter initialisation file have been uploaded to DTU Learn in the  $File\ share/Matlab\ and\ Simulink\ files/Mandatory\ Assignment\ Part\ A$  folder for your convenience.

#### Question 1

Make a structural analysis:

- 1. Determine a complete matching on the unknown variables.
- 2. Find the parity relations in symbolic form.
- 3. Investigate other properties you find relevant from a structural analysis.
- 4. Reformulate the parity relations to an analytic form, as functions only of known variables and the system parameters.

#### Practical notes

- The deadline for the report is Wednesday March 16, 2022, at 23:55 hours.
- Please note that max. 20 pages are allowed for part A, excluding front matter. Any pages in excess of 20 (excluding front matter) will be discarded.
- Layout must be reasonable: A4 paper, 20mm margins and font size 11pt.
- The report need be delivered in electronic form, as a .pdf file, via the DTULearn assignment system. Only pdf files are accepted.
- Group-work is encouraged (max 2 persons in one group).

• Please do write your name(s) and student number(s) at the front page and as running heading on each page of your report. In addition, do not forget page numbers.