

---

---

# Digital Guitar Effects

---

---

Project Report  
Group 17gr641

Aalborg University  
Electronic Engineering and IT

Copyright © Group 17gr641, Electronic Engineering and IT P6, Aalborg University 2018

This report is compiled in L<sup>A</sup>T<sub>E</sub>X. Additionally is Mathworks MATLAB, Adobe Illustrator, Inkscape, Lucidcharts.com, Altium Designer, and Xfig used to draw figures and charts.



**AALBORG UNIVERSITY**  
STUDENT REPORT

**Electronic Engineering and IT**  
Aalborg University  
<http://www.aau.dk>

**Title:**

Digital Guitar Effects

**Theme:**

Signal processing

**Project Period:**

BSc, 6th Semester 2017

**Project Group:**

Group 17gr641

**Participants:**

Mohamed Gabr  
Jonas Buchholdt  
Sebastian Schiøler

**Supervisor:**

Sofus Nielsen

**Number of Pages:** 22

**Date of Completion:**

26th may 2017

**Abstract:**

The paper deals with the creation of different sound effects for an electric guitar on the a Digital Signal Processor. Some of these effects are the reverb, the flanger and the equalizer. The report includes a thorough explanation of each of the effects followed by the used design approach. Simulations on MATLAB were done to verify the design. All the effects have been coded in assembly for the DSP implementation. The Assembly code works with the TMS320C5515 DSP from Texas Instruments. In order to make the DSP usable on a variety of electric guitars, a preamplifier was built. All details relating to the design and the implementation of this component are included in the paper as well.

*The content of this report is freely available, but publication may only be pursued with reference.*



# Preface

This report is composed by group 17gr641 during the 6th semester of Electronic Engineering and IT at Aalborg University. The general purpose of the report is the development and implementation of a digital guitar effects which is a part of the overall theme *Signal processing*.

For citations, the report employs the Harvard method. If citations are not present by figures or tables, these have been made by the authors of the report. Units are indicated according to the SI standard.

This project uses the Assembly language for the TMS320C5515 processor, and furthermore, the C programming standard C99.

Aalborg University, February 9, 2018

*Mohamed Gabr*  
<mgabr16@student.aau.dk>

*Jonas Buchholdt*  
<jbuchh13@student.aau.dk>

*Sebastian Schiøler*  
<sschia14@student.aau.dk>

# Contents

<b>Preface</b>	<b>v</b>
<b>Glossary</b>	<b>1</b>
<b>1 Introduction</b>	<b>3</b>
1.1 preliminary problem statement . . . . .	4
<b>I Analysis &amp; Requirements</b>	<b>5</b>
<b>2 Analysis of single source</b>	<b>7</b>
2.1 Single speaker source . . . . .	7
<b>3 Product Requirements</b>	<b>9</b>
<b>II Design &amp; Construction</b>	<b>11</b>
<b>4 Component Choices</b>	<b>13</b>
<b>III Tests</b>	<b>15</b>
<b>5 Tests of the Stated Requirements</b>	<b>17</b>
<b>IV Discussion and Conclusion</b>	<b>19</b>
<b>V Appendix</b>	<b>21</b>

# Glossary

**dB** Decibel. 3

**SPL** Sound pressure level. 3






# Chapter 1

## Introduction

The directivity of a loudspeaker is a daily issue for sound events, because the loudspeaker produce sound outside the voluntary audience area. The sound from a speaker can therefore be defined as two main subject, sound for voluntary audience and sound for non voluntary audience, which is perceived the sound as noise. The following Figure 1.1 visualise the problem.



**Figure 1.1:** Normalized Sound pressure level (SPL) in colour, red is high SPL where blue is low SPL

Figure 1.1 shows the total sound pressure level SPL in Decibel (dB) from 20 Hz to 20 kHz for the voluntary audience and the non voluntary audience doing a concert. The voluntary audience condensing area is defined as participants area and is limited by the red area in figure Figure 1.1. The non voluntary audience will be exposed by sound in a limited frequency area, when they are located outside but still in the neighbourhood of the red area. This area is defined as the neighbourhood area. The noise is cause by omnidirectionality of the line source module and have a limited frequency range.

The directivity control of mid- and high frequency have a known solution which have been applied for many years. The solution is a horn design which is designed for a defined radiation pattern. Due to the long wave length in low/mid- and low

frequency range, the horn principle will become a heavy solution for long wave length. Therefore other space saving solution have been analysed and implemented for about one decade. The commonly space saving solution is one subwoofer pointing forward and one subwoofer pointing backward with signalprocessing applied. This solution is both made by one box and two boxes.

This project aims to apply a new principle from D&B audiotechnik SL-series, where the low/mid frequency directivity is controlled by signal processing tree speaker unit. One unit arranged in the front and two arranged on the side of the line source module, one on each side.

## 1.1 preliminary problem statement

The following questions are made with the intention of gathering the necessary knowledge, to be able to answer a later stated problem statement. The preliminary questions, which will be answered in the analysis, are:

- In which frequency area do the line source speaker behave omnidirectional?
- Which known technique is used to do the speaker cardioid?
- Can a simulation be made which support D&B audiotechnik claim?

## Part I

# Analysis & Requirements



## Chapter 2

# Analysis of single source

### 2.1 Single speaker source

This section aims to introduce and analyse the fundamental for a single source, by analyse the behaviour of a linesource shaped as the diaphragm. The pressure around the speaker will be analysed analytically, to determine the radiation of a single speaker from 60 Hz and upwards. The 60 Hz lower limit enable the simulation to be validated by measurement in the AAU anacoid chamber and is a used lower limit for the low/mid driver in some line source array. The analyse shall end out with a limited frequency range, where the directivity have to be controlled.

#### 2.1.1 Pressure analysis around a single source

To characterised the directions properties of a single source, the source will be modulated as a linesource shaped as the diaphragm of a speaker. To

#### 2.1.2 polar directivity pattern of the single source



## Chapter 3

# Product Requirements





# **Part II**

## **Design & Construction**



## Chapter 4

# Component Choices



## **Part III**

## **Tests**



## Chapter 5

# Tests of the Stated Requirements





## **Part IV**

# **Discussion and Conclusion**



**Part V**

**Appendix**

