

# Ansible\_

## Variablen

# Recap

---

## Konfigurationsmanagement

Konfiguration von Systemen - Infrastructure as Code

## Verteilung und Orchestrierung von Software

Orchestrierung von Systemen

Zero-Downtime Updates

## Ad-hoc Kommandos

Operation am offenen Herzen

# Basics

## **Automation macht wiederholenden Einsatz einfach**

Nicht alle Systeme sind identisch

Status/Variablen der remote Maschine beeinflussen die Konfiguration

Buchstaben [A-Z,a-z], Zahlen [0-9] und Unterstrich [\_]

```
foo_port  
foo5
```

```
foo.port  
foo port  
foo-port  
12
```

Variablen in Inventory

Variablen in Playbook

Variablen in Include und Rollen

## Variablen in Inventory

### Host

```
[atlanta]  
host1 http_port=80  
host2 http_port=303
```

### Group

```
[atlanta]  
host1  
host2  
  
[dacota]  
host3  
host4  
  
[atlanta:vars]  
http_port=303
```

## Variablen in Playbook

```
- hosts: webservers
  vars:
    http_port: 80
```



## Variablen in Include und Rollen

### Include

tasks:

- include: wordpress.yml
- vars:
- wp\_user: timmy
  - ssh\_keys:
    - keys/one.txt
    - keys/two.txt

### Rollen

---

- hosts: webservers
- roles:
- common
  - { role: foo\_app\_instance, app\_port: 5000 }

**/defaults**

**/vars**

## jinja2 Templating Engine

My amp goes to {{ max\_amp\_value }}

template: src=foo.cfg.j2 dest={{ remote\_install\_path }}/foo.cfg

## Gotcha

```
- hosts: app_servers
  vars:
    app_path: {{ base_path }}/22
```



```
- hosts: app_servers
  vars:
    app_path: "{{ base_path }}/22"
```

# Facts

## Daten des remote Systems auslesen

```
ansible hostname -m setup
```

## Können in Tasks verwendet werden

```
{{ ansible_hostname }}
```

## Deaktivieren

```
- hosts: whatever  
  gather_facts: no
```

# Variablen - Benutzerdefinierte Facts

## Facts, die vom Benutzer festgelegt werden

```
/etc/ansible/facts.d
```

## Abrufen

```
ansible all -i inventory -m setup -a "ansible_local"
```

## Referenzen zu anderen Hosts nutzen

```
{{ hostvars['asdf.example.com']['ansible_os_family'] }}
```

**Entweder im Play bereits vorher von `asdf.example.com` gelesen**

**Oder Caching in `ansible.cfg` konfigurieren:**

```
[defaults]
gathering = smart
fact_caching = redis
fact_caching_timeout = 86400 # seconds
```

```
[defaults]
gathering = smart
fact_caching = jsonfile
fact_caching_connection = /path/to
fact_caching_timeout = 86400
```

S

# Erweiterte Themen

## Ergebnisse eines Task-Runs wiederverwenden

- hosts: web\_servers

tasks:

- shell: /usr/bin/foo  
register: foo\_result

- shell: /usr/bin/bar  
when: foo\_result.rc == 5

**Conditionals**



## Ergebnisse eines Task-Runs wiederverwenden

```
---  
- name: Installiere Webserver  
  hosts: all  
  tasks:  
    - name: Installiere apache  
      apt: name=apache2 state=present  
        when: ansible_os_family=="Debian"  
  
    - name: Installiere httpd  
      yum: name=httpd state=present  
        when: ansible_os_family=="Centos"
```

## Logische Verknüpfungen

```
when: (ansible_distribution == "CentOS") or  
      (ansible_distribution == "Debian" and ansible_distribution_version == "7")
```

```
when:  
  - ansible_distribution == "Debian"  
  - ansible_distribution_version == "7"
```

is defined, is undefined, true/false, filter **möglich**

# Variablen - Komplexe Datenstrukturen

```
> ansible all -m setup
```

```
"ansible_eth0": {  
    "ipv4": {  
        "address": "192.168.10.14",  
        "broadcast": "192.168.10.15",  
        "netmask": "255.255.255.240",  
        "network": "192.168.10.0"  
    },  
    "ipv6": [  
        {  
            "address": "fe80::1a:46ff:fe47:30c1",  
            ...  
        }  
    ],  
    ...  
},
```

```
{{ ansible_eth0["ipv4"]["address"] }}
```

```
{{ ansible_eth0.ipv4.address }}
```

# Variablen - Komplexe Datenstrukturen

```
> ansible all -m setup
```

```
"ansible_interfaces": [  
    "lo",  
    "eth0"  
],
```

```
{{ ansible_interfaces[0] }}
```

**Variablen, die keine Facts sind und vom User nicht definiert wurden:**

hostvars

group\_names

groups

inventory\_hostname **manchmal besser nutzen als** ansible\_hostname

## Externe Dateien mit Variablen einbinden:

```
- hosts: all
  remote_user: root
  vars:
    favcolor: blue
  vars_files:
    - /vars/external_vars.yml
```

/vars/external\_vars.yml

```
---
somevar: somevalue
password: magic
```

## Generalisierte Playbooks - bei der Ausführung Variablen nutzen

```
ansible-playbook release.yml --extra-vars "version=1.23.45 env=stage"
```

# Variablen - An welchen Ort?

**Wir haben viele Möglichkeiten gesehen, variablen zu platzieren:**

Variablen am richtigen Ort platzieren - nicht explizit Überschreibungen nutzen

Keep it simple!

**Idee: Je expliziter die Angabe - desto höher die Priorität der Variable**



# Variablen - An welchen Ort?

```
role defaults < inventory group_vars/all < playbook group_vars/all <
  inventory group_vars/* < playbook group_vars/* < inventory host_vars <
  playbook host_vars < host facts < play vars < play vars_files <
  roles vars < block vars < task vars < role params < include params <
  set_facts < extra vars
```

# Variablen - Templating

## jinja2

```
{% if 'webserver' in group_names %}  
    # some part of a configuration file that only applies to webserver  
{% endif %}
```

```
{% for host in groups['app_servers'] %}  
    # something that applies to all app servers.  
{% endfor %}
```

```
{% for host in groups['app_servers'] %}  
    {{ hostvars[host]['ansible_eth0']['ipv4']['address'] }}  
{% endfor %}
```

# Variablen - Loops

## Simple

- name: add several users
- user:
  - name: "{{ item }}"
  - state: present
  - groups: "wheel"
- with\_items:
  - testuser1
  - testuser2

## Nested

- name: give users access to multiple databases
- mysql\_user:
  - name: "{{ item[0] }}"
  - priv: "{{ item[1] }}.\*:ALL"
  - append\_privs: yes
  - password: "foo"
- with\_nested:
  - [ 'alice', 'bob' ]
  - [ 'clientdb', 'employeedb', 'providerdb' ]

## Weitere Loops:

with\_files

```
with_file:  
  - first_example_file  
  - second_example_file
```

## Weitere Loops:

with\_files

with\_fileglobs

```
with_fileglob:  
  - "/playbooks/files/fooapp/*"
```

## Weitere Loops:

with\_files

with\_fileglobs

with\_together

```
---  
alpha: [ 'a', 'b', 'c', 'd' ]  
numbers: [ 1, 2, 3, 4 ]
```

```
with_together:  
- "{{ alpha }}"  
- "{{ numbers }}"
```

## Weitere Loops:

with\_files

with\_fileglobs

with\_together

with\_subelements

```
with_subelements:  
  - "{{ users }}"  
  - "{{ mysql.hosts }}"
```

## Weitere Loops:

with\_files

with\_fileglobs

with\_together

with\_subelements

with\_inventory\_hostnames

```
with_inventory_hostnames:  
  - all:!www
```

[https://docs.ansible.com/ansible/playbooks\\_loops.html](https://docs.ansible.com/ansible/playbooks_loops.html)



# Variablen - Blocks

```
tasks:
  - block:
      - yum: name={{ item }} state=installed
        with_items:
          - httpd
          - memcached

      - template: src=templates/src.j2 dest=/etc/foo.conf

      - service: name=bar state=started enabled=True

  when: ansible_distribution == 'CentOS'
  become: true
  become_user: root
```

# Variablen - Block error handling

```
tasks:  
- block:  
  - debug: msg='i execute normally'  
  - command: /bin/false  
  - debug: msg='i never execute, cause ERROR!'  
rescue:  
  - debug: msg='I caught an error'  
  - command: /bin/false  
  - debug: msg='I also never execute :-( '  
always:  
  - debug: msg="this always executes"
```

# Variablen - Block error handling

```
tasks:
  - block:
      - debug: msg='i execute normally'
        notify: run me even after an error
      - command: /bin/false
  rescue:
      - name: make sure all handlers run
        meta: flush_handlers
handlers:
  - name: run me even after an error
    debug: msg='this handler runs even on error'
```