

OpenCaseLaw: A Verifiable Multilingual Citation Graph for Swiss Jurisprudence

Jonas Hertner

OpenCaseLaw
jonashertner@protonmail.ch

May 25, 2026

Abstract

We release **OpenCaseLaw**, an open, verifiable retrieval substrate for Swiss case law: a resolved cross-court citation graph bridged to statute articles, Federal Council legislative-history materials, and scholarly commentaries, with a Swiss-native identifier scheme and cryptographic provenance. The release contains **972,882** court decisions across **109 courts** in 28 jurisdictional layers (DE/FR/IT, 1875–2026), **8.05 M** resolved citation tokens (92.9 % coverage of 8.66 M extracted tokens) expanded to **8.10 M** (source-decision, target-decision) link edges, **11.28 M** decision-to-statute edges across **5,516** federal and **15,722** cantonal laws, **362** CC-BY/CC-BY-SA commentaries, and **8,124** article-level Materialien anchors. Every decision carries a Swiss-native `cli:ch` identifier with a Council-of-EU ECLI projection and per-decision inclusion-proof verification against a 2026-05-21 RFC6962/OpenTimestamps integrity root; the corpus is served as a live MCP/REST endpoint at `mcp.opencaselaw.ch`. As descriptive characterization of the released graph, we report row-normalised cross-language citation flow (Italian-language decisions cite outside Italian 84.6 % of the time, French 44.3 %, German 15.0 %; aggregate 34.0 %), quality-control precision proxies (recorded-date chronology violations 1.53 %, *not* a lower bound on precision), a 400-sample rule-based consistency check (400/400 mechanically consistent with the resolver rules; Wilson 95 % CI [99.0 %, 100.0 %] for the checked property), and explicitly delimit unresolved per-language resolution-rate confounders. Corpus CC0 on Hugging Face; code MIT. Snapshot 2026-05-21.

1 Introduction

Swiss legal NLP has lacked a public substrate joining the objects legal practitioners actually move between: court decisions, case citations, statute articles, legislative materials, doctrinal commentary, identifiers, and provenance. Existing Swiss datasets are valuable for tasks such as prediction, summarisation, translation, and metadata analysis, but they do not provide a cross-court graph that can be queried, audited, and cited as infrastructure. *OpenCaseLaw* fills that gap.

The resource is deployed infrastructure, not a one-shot dataset dump. The corpus is served as a live MCP/REST endpoint at `https://mcp.opencaselaw.ch`. Daily dataset-health audits, integrity proofs, and per-decision inclusion-proof verification are published alongside the corpus for any consumer to verify independently.

Given Switzerland’s multilingual legal order, cross-language citation is expected: federal supreme-court decisions are authoritative in German, French, or Italian, and practitioners cite across those boundaries. The contribution is therefore the released graph that makes citation flow measurable, inspectable, and reusable at edge level across 109 courts and adjacent statute/Materialien layers. As a single descriptive characterization of the released graph: DE-language decisions cite cross-language in 15.0 % of resolved links, FR in 44.3 %, IT in




Figure 1: Resource shape. Each Decision is the centre node of five joined layers: case-to-case citations (8.10 M edges), decision-to-statute references (11.28 M edges), Materialien anchoring at the statute-article level (8,124 anchors), scholarly commentaries, and a layered identifier (`cli:ch` + ECLI) with per-decision cryptographic inclusion proofs.

84.6 %; aggregate 34.0 % (full matrix in Section 4). We treat this matrix as descriptive corpus telemetry, not a standalone result — per-source-language resolution-rate differentials remain a measurement-artefact concern (Section 9).

Why this substrate was missing. The existing open Swiss-law resources are either pre-training text [6], task benchmarks [5, 7, 10, 11], or court-specific metadata datasets such as the Swiss Federal Supreme Court Dataset (SCD) [1]. These resources are valuable, but they do not resolve a cross-court citation graph at scale, and they do not link case law to the Federal Council Botschaften that drive teleological statutory interpretation under Swiss civil-law doctrine. The infrastructure required for a reusable Swiss legal graph — federated cantonal-level decision coverage, multilingual docket normalisation, BGE/ATF/DTF prefix-form aliasing, pin-cite-aware resolution, article-level statute anchoring, and integrity proofs — did not exist as an open release.

Contributions. Four:

1. A resolved multilingual citation graph for Swiss jurisprudence at 92.9 % coverage, with a documented pin-cite-aware resolver, automated precision proxies, and a 400-sample stratified audit set: mechanically adjudicated by rule, queued for human semantic adjudication.
2. A statute graph (11.28 M edges over 283,330 provisions) and an article-level Materialien bridge from federal statutory articles to Federal Council Botschaften.
3. A corpus characterization: row-normalised citation flow by source language (DE 15 %, FR 44 %, IT 85 % out-of-language), reported as descriptive telemetry for the released graph and subject to per-language resolution-rate confounders (Section 9).
4. A Swiss-native `cli:ch` identifier with a Council-of-EU ECLI projection in JSON-LD, plus an RFC-6962 Merkle root anchored on Bitcoin via OpenTimestamps and a per-decision inclusion-proof API.

The companion evaluation paper covers cross-lingual retrieval diagnostics with multi-annotator inter-annotator agreement, audit-rail adversarial probes, human calibration of the LLM grounding judge, and the manual annotation of the 400-sample citation-precision audit set.

Resource shape (one-figure overview). Figure 1 sketches what is joined into what. Every decision is the centre node; the surrounding layers (citation graph, statute graph, Materialien, identifier, provenance) are the five orthogonal axes the resource lets a downstream user pivot on.

2 Related work

Open legal corpora (international). The Caselaw Access Project [3] releases 6.7M US decisions; Harvard’s Library Innovation Lab released a CAP citation graph as a static CSV in 2020.¹ CAP is single-jurisdiction (US) and monolingual; CAP’s published graph is not paired with a statute graph, legislative-history bridge, or live retrieval API. The *Open Legal Data* platform [8] releases German court decisions with a citation network covering law and court nodes; OLD is single-jurisdiction (Germany), monolingual, with no article-resolved bridge to legislative materials. *LeCNet* [2] introduces an Indian-judicial-context citation-network benchmark (26k case-judgment nodes) for missing-citation recommendation. A very recent Ukrainian release extracts 502M citation links from 99.5M court-decision full texts, with topology and ontology analyses over a national monolingual corpus [9]. *Pile of Law* [4] and *MultiLegalPile* [6] are pretraining corpora and do not publish a resolved citation graph at this scale.

Swiss legal NLP benchmarks and datasets. Four task benchmarks on Swiss legal text precede our resource: *Swiss-Judgment-Prediction* [5] (binary outcome prediction); the *One Law, Many Languages* benchmark [11] (multi-task suite spanning document-to-document IR, court-view generation, leading-decision summarisation, citation extraction, classification across five languages); *Swiss Landmark Decisions Summarisation* [10] (20k BGE landmark rulings paired with DE/FR/IT headnotes for cross-lingual summarisation, 1954–2024); and *SwiLTra-Bench* [7] (180k aligned Swiss legal translation pairs across DE/FR/IT/RM/EN spanning federal laws, BGE headnotes, and Federal Supreme Court press releases). The Swiss Federal Supreme Court Dataset (SCD) records 120,368 Federal Supreme Court cases through 2023 with structured metadata, including citation and publication-status variables [1]. These resources target specific downstream tasks or one federal-court layer; they do not publish a resolved cross-court citation graph or a statute-anchored Materialien layer. The Federal Supreme Court layer represented in these resources is one of 28 jurisdictional layers we federate.

Comparison. Table 1 positions OpenCaseLaw against these prior releases. Inclusion criterion: open releases that publish a retrieval substrate over court-decision text — a citation graph, a statute-decision link layer, or a live retrieval endpoint — against which downstream RAG and legal-research pipelines can be built. Excluded: task benchmarks (SwiLTra, SLDS, OLML, SJP) and pretraining corpora (Pile of Law, MultiLegalPile), which publish task data or large text dumps rather than retrieval substrates; these are discussed in the prose above. SCD is a borderline case (it ships structured metadata over BGE but not a graph layer); we include it to make the criterion transparent.

¹Library Innovation Lab, *Caselaw Access Project Citation Graph*, 2020-04-22, <https://lil.law.harvard.edu/blog/2020/04/22/caselaw-access-project-citation-graph/>.

Table 1: Comparison of selected open legal-data resources along dimensions relevant for retrieval-augmented Swiss legal research. “Citation graph” = resolved citation network (case-to-case unless noted); “Statute graph” = decision-to-statute-article edges with resolved targets; “Leg. history” = statute-article-to-legislative-history links (e.g. Botschaften, Hansard, committee reports) at article granularity; “Live API” = continuously served retrieval endpoint; “Cross-lang links” = the resource publishes a link layer where edges span ≥ 2 official languages (independent of whether the underlying corpus is multilingual). SCD covers DE/FR/IT Federal Supreme Court text but ships metadata variables, not a cross-language link layer. The table foregrounds retrieval-substrate features rather than task-benchmark coverage; pretraining corpora such as Pile of Law and MultiLegalPile, and Swiss task datasets such as SwiLTra/SLDS/OLML/SJP, are discussed in text.

Resource	Jurisdiction	Cross-lang links	Citation graph	Statute graph	Leg. history	Live API
Caselaw Access Project [3]	US	no	static CSV	no	no	no
Open Legal Data [8]	Germany	no	law/court nodes	no article graph	no	no
LeCNet [2]	India	no	26k bench	no	no	no
Ukrainian citation graph [9]	Ukraine	no	502M extracted links	no	no	no
SCD [1]	CH	no	metadata variables	no	no	no
<i>OpenCaseLaw</i>	CH (+ECHR Swiss)	yes	yes, 8.05M resolved	yes, 11.28M edges	yes, 8,124 anchors	yes

3 Corpus

The OpenCaseLaw corpus comprises **972,882 decisions** from **109 distinct courts** across **26 Swiss cantons plus federal and ECHR jurisdictions** (28 jurisdictional layers). Coverage spans **1875–2026** and three official languages: German (450,435 / 46.3 %), French (441,673 / 45.4 %), Italian (80,774 / 8.3 %). The federal Supreme Court (BGer) is refreshed hourly (Mon–Fri 05:00–16:00 UTC) via a dedicated Neuheiten poller; all other federations are refreshed by a nightly publish at 03:00 UTC. The federation aggregates source-specific scrapers and adapters covering federal courts (BGer, BGE, BVGer, BStGer, BPatGer), per-canton portals, the European Court of Human Rights (Swiss subset), historical archives, and federal regulatory authorities (FINMA, WEKO, and five others).

ECHR Swiss subset. The Swiss-relevant subset of European Court of Human Rights jurisprudence (**2,788 decisions**: 1,153 chamber + 93 grand-chamber + 230 committee + 835 HUDOC entries + 477 BGE-EGMR mirror) is integrated as a first-class federation. The subset matters because ECHR jurisprudence is directly applicable in Swiss litigation, and the official versions of ECHR-Switzerland judgments are typically French and English rather than German or Italian, which requires a multilingual retrieval substrate.

Completeness. Some source portals impose access restrictions (geographic, rate, or contractual). We document affected sources in the per-source coverage report, do not claim full coverage where access is restricted, and use only legally authorised collection methods. For closed historical archives where contemporaneous collection is no longer possible, we recover from publicly archived snapshots (e.g. Wayback Machine; ~903 BL ALS judgments).

Licensing and governance. Court decisions in Switzerland are official acts under URG/CopA Art. 5 (excluded from copyright). Corpus packaging is CC0; commentaries retain their upstream CC-BY-4.0 / CC-BY-SA-4.0 terms; code is MIT. Per-record licenses, the FADP (Swiss data protection) posture, and the correction/removal procedure are in the Data Card (Section 8) and the public governance policy.

Table 2: OpenCaseLaw corpus overview. Snapshot 2026-05-21.

Quantity	Value
Total decisions	972,882
Distinct courts	109
Cantons + federal	28
Date range	1875–2026
German (de)	450,435 (46.3%)
French (fr)	441,673 (45.4%)
Italian (it)	80,774 (8.3%)

4 Multilingual citation graph

Denominator taxonomy. Counts in this section use one frozen 2026-05-21 snapshot. We use four distinct denominators:

- $E_{\text{extracted}} = \mathbf{8,663,860}$: distinct (source-decision, citation-token) pairs extracted by full-text scan over the corpus.
- $E_{\text{resolved}} = \mathbf{8,047,620}$: subset of $E_{\text{extracted}}$ whose token resolves to ≥ 1 target decision (92.9%).
- $E_{\text{link}} = \mathbf{8,102,236}$: rows of the published `citation_targets` table, expanded for target multiplicity (a small fraction of citation tokens resolve to multiple targets, e.g. BGE form references that match several published BGEs by docket).
- $E_{\text{link,lang}} = \mathbf{8,102,236}$: subset of E_{link} where both source and target language are in {de, fr, it}; in this snapshot, all link rows satisfy this.

The cross-lingual share (34.0%, Section 1) is computed over $E_{\text{link,lang}}$; the 92.9% resolution rate is computed over $E_{\text{extracted}}$. The precision proxies below are computed over $E_{\text{link}} = 8,102,236$ on the same 2026-05-21 frozen graph, grouped by `match_type`; the cross-language matrix and the precision proxies share the same release denominator.

Table 3: Citation graph. Edges extracted by full-text scanning every decision in the corpus; resolved means the cited target is identified in the corpus. Snapshot 2026-05-21.

Quantity	Value
Decisions analysed for outgoing citations	972,880
Citation edges (source $\rightarrow$ target reference)	8,663,860
Edges with target resolved to a corpus decision	8,047,620 (92.9%)
Distinct decisions cited at least once	261,677
Decisions cited ≥ 100 times	10,750
Decisions cited $\geq 1,000$ times	975
Decisions cited $\geq 10,000$ times	40

Table 4: Cross-lingual citation matrix. Rows are source decision languages; columns are cited (target) decision languages. Cells give resolved citation edges. Off-diagonal = 2,753,134 / 8,102,236 = 34.0% of resolved citations with identified source and target language.

	$\rightarrow$ DE	$\rightarrow$ FR	$\rightarrow$ IT
DE $\rightarrow$	2,779,288	459,563	31,940
FR $\rightarrow$	1,939,860	2,522,708	63,497
IT $\rightarrow$	168,741	89,533	47,106

Resolution at scale. We extract citation tokens by full-text scanning every decision in the corpus (972,880 decisions in the reference-graph snapshot; the FTS5 search index carries 2 more decisions ingested between graph rebuild and FTS5 swap), recovering $E_{\text{extracted}} = 8,663,860$. Resolution proceeds in three exact-match passes (general docket-normalisation; BGE/ATF/DTF prefix-form; bare BGE numeric form), augmented by a *pin-cite-aware fallback* for Swiss legal citations such as *BGE 125 V 352* that pinpoint into the body of a case starting at *BGE 125 V 351*. The pin-cite resolver matches each unresolved BGE-form reference to the nearest preceding first-page in the same volume + division within 30 pages, contributing 652,547 additional matches at a -0.10 confidence discount versus exact matches. The deployed 92.9% resolution is a 17.7 pp lift over an internal pre-fix resolver baseline of 75.2%, recovered by fixing two implementation bugs: docket-normalisation drift in 2007–2009 Bundesgericht dockets stored with a space (8C 862_2008) versus the underscore form (8C_862_2008) emitted by the citation extractor, and the pin-cite mismatch above.

Heavy-tailed centrality. The citation graph is heavy-tailed (Table 3): 40 decisions are cited 10,000+ times, 935 are cited 1,000–9,999 times, and most cited decisions sit in the long tail. The single most-cited decision is BGE 125 V 351 (66,883 incoming citations after canonical-form aggregation across BGE id variants). Of the 50 most-cited decisions, 38 are DE-originals, 12 are FR, and none are IT — a distinct cut of the graph (citation reception, not direction).

Precision proxies. The 92.9% resolution number is a *coverage* metric and does not bound precision. To characterise precision risk we compute three automated proxies (Table 5). The proxies surface *recorded-date chronology violations*: each detected case is a logical inconsistency conditional on the source and target decision dates being themselves correct. We preserve source-portal-provided dates (Section 9), so a violation is a strong but not infallible indicator of a false-positive resolution. Date-consistent, non-self pairs may still be false positives for reasons our automated proxies do not see (e.g., a docket-form citation that resolves to the wrong case with the same docket pattern). *Date-order sanity* (target decision not dated after source) finds violations in 1.53% of E_{link} rows with both dates known (weighted across match types). This bounds precision on the released graph at *at most* 98.47% on date-covered pairs conditional on

Table 5: Citation-resolution precision proxies computed over the 8,102,236 link-edge rows of the released graph (matching E_{link} , Section 4; re-run on the 2026-05-21 frozen snapshot). Date-sanity pass = % of pairs where target decision date is not after the source’s; violations are recorded-date chronology inconsistencies and indicate likely false-positive resolutions (conditional on the recorded source/target dates themselves being correct; we preserve source-portal-provided dates, see Limitations), not a lower bound on precision. Self-cite = pairs where source = target. Conf. p50 = median resolver confidence per stratum. A rule-based mechanical consistency check over the shipped 400-row audit set is reported below; full human semantic adjudication remains companion-paper scope.

match_type	n	date sanity	self-cite	conf p50
docket_norm	3,288,460	97.25%	0	0.99
bge_bare	2,944,527	99.75%	0	0.85
bge_norm	1,216,702	99.26%	0	0.75
bge_pincite	652,547	97.35%	0	0.75
Overall	8,102,236	98.47%	0	—

the recorded dates; it does *not* establish a lower bound on precision.

The pin-cite stratum scores lowest (2.65 % violation rate), consistent with its heuristic nature; the exact-match strata (bge_bare, bge_norm) sit above 99.2 % pass. *Self-citation* is zero across all 8,102,236 rows.

Rule-based consistency adjudication on the 400-sample audit set. As an orthogonal complement to the chronology proxy, we apply a mechanical per-row consistency adjudication to every sample in the shipped 400-row stratified audit set (benchmarks/citation_precision_sample_400.jsonl; rules at benchmarks/citation_precision_audit_rules.py). Each row is checked against the documented per-stratum canonicalisation rules: BGE-form parsing for bge_bare/bge_norm; docket-pattern suffix matching for docket_norm; the 30-page window for the pin-cite heuristic. Result: **400/400 samples** pass the consistency checks (Wilson 95 % CI [99.0 %, 100.0 %] for the checked property overall; bge_bare 100/100, bge_norm 80/80, bge_pincite 100/100, docket_norm 120/120). This is evidence that the published target identifiers are mechanically consistent with the resolver’s own rules on this sample, and that the sample contains no rule-visible malformed identifiers or pin-cite range overflows. It does *not* verify semantic correctness: whether the resolver picked the right case when multiple cases share a docket pattern, whether a rule-consistent pin-cite points into the intended case, or whether the source text correctly identified the cited decision remains companion-paper scope (multi-annotator human adjudication).

Cross-language citation flow. Table 4 and Figure 2 report the language-by-language citation matrix over $E_{\text{link,lang}} = 8,102,236$ as descriptive characterization of the released resolved graph. The aggregate cross-language share is **34.0 %**; row-normalisation by source language (Section 1, lead table) makes the per-language structure of the released graph visible: German-language decisions cite outside German in only **15.0 %** of their resolved links; French-language decisions cross language in **44.3 %**; Italian-language decisions cross language in **84.6 %**. FR→DE links (**1.94 M**) outweigh DE→FR (**0.46 M**) by **4.2×**; IT→DE/FR (**0.26 M** combined) outweighs IT→IT (**47 k**) by **5.5×**. These ratios are computed over the population of resolved link edges with both languages known; there is no sampling uncertainty, but there is measurement uncertainty from unresolved tokens and possible language-pair resolution bias. We do not claim a structural cause from this observation alone — unresolved citation tokens have no target language, and the resolver was tuned on BGE-form citations, which are predominantly DE-target, so a per-source-language or per-language-pair resolution-rate differential




Figure 2: Row-normalised citation-language flow over the released resolved graph. Each cell gives the share within a source-language row and the underlying resolved link-edge count.

could partly inflate the FR and IT cross-lingual shares (Section 9); the proper control is a language-pair human precision audit (queued, Section 9).

5 Statute graph and Materialien bridge

Statute graph. We resolve **11,276,187 decision-to-statute edges** touching **283,330 distinct provisions**. The statute layer is grounded in two parallel mirrors: a federal layer of **5,516 SR-numbered Fedlex laws** (400,405 article rows summed across the parallel DE/FR/IT versions; ~ 133 k articles per language) and a cantonal layer of **15,722 laws** (353,437 articles) covering all 26 cantons via direct portal scraping (LexWork, 18 cantons; SIL, 2 cantons; ZH OpenData, ZH; TI RL, TI), with LexFind PDF fallback supplementing 4 cantons for laws missing from their primary portals. After alias canonicalisation across 20 major DE/FR/IT statute-abbreviation pairs, the top-referenced provisions are dominated by federal-court procedural code: *BGG/LTF* Art. 100 (**205,725** decisions, 30-day appeal deadline), Art. 42 (**201,897**, statement-of-grounds), and Art. 113 (**122,514**, subsidiary constitutional complaint). Beyond procedural code, *ATSG/LPGA* Art. 61 (social-insurance procedure, 85,207) and *BV/Cst./Cost.* Art. 29 (procedural fundamental rights, 79,115) lead the non-BGG/LTF substantive provisions. Alias canonicalisation is lexical only; temporal validity — mapping a 1998 *OG* reference to its current SR location, or distinguishing repealed-vs-current article versions — is left for future work.

Table 6: Statute and doctrinal graph layers. Decision-to-statute edges plus federal/cantonal mirrors plus *Materialien* (Federal Council Botschaften) and open commentaries.

Quantity	Value
Decision → statute edges	11,276,187
Distinct provisions referenced	283,330
Federal laws (Fedlex SR series)	5,516
Federal articles (DE/FR/IT parallel)	400,405
Cantonal laws (all 26 cantons; 22 direct, 4 LexFind fallback)	15,722
Cantonal articles	353,437
<i>Materialien</i> (Botschaft documents, DE/FR/IT)	5,292
<i>Materialien</i> paragraphs (full-text)	381,711
Article-anchored <i>Materialien</i> links	8,124
Open commentaries (CC-BY/CC-BY-SA)	362

Materialien graph. A distinguishing feature of Swiss civil-law interpretation is the *teleological* reading of statutes via *Materialien* — legislative-history documents (Federal Council messages, parliamentary debates) that record legislative intent. We discover Botschaft documents via the Fedlex JOLUX SPARQL endpoint (`typeDocument=23`) from 2003 (earliest year with a parliamentary-chain anchor) to the 2026-05-21 snapshot date, ingesting **5,292** documents at paragraph granularity (**381,711 paragraphs**) from Akoma Ntoso XML where available, PDF fallback otherwise. Per-language coverage reflects the upstream Botschaft’s own publication (not all are translated into all three official languages).

Materialien graph: anchoring. We anchor Botschaft documents to specific (`SR`, `article`) pairs by traversing the official parliament chain: `parliamentDraftId` → enacted `oc` (Official Compilation) → codified `cc` (consolidated codification) → `SR` (Systematic Register). This yields **8,124** article-to-Botschaft anchors (DE 2,798, FR 2,742, IT 2,584). The link is at the Botschaft-document→SR-article level (not paragraph→article); finer-grained paragraph-to-article anchoring is left for future work. Known failure modes: (i) Botschaften that propose amendments which were rejected by Parliament have no enacted-`oc` side and therefore no SR anchor; (ii) Botschaften that bundle amendments to multiple statutes generate one link per affected statute, which inflates the link count relative to the document count; (iii) article-renumbering events in the codification step (rare but observed) currently anchor the *Materialien* link to the post-renumbering article identifier only. We have not yet computed an end-to-end precision audit for the article-to-Botschaft anchoring, so the present release treats this layer as a high-recall legislative-history discovery index rather than as an adjudicated alignment benchmark. The layer is queryable via `search_materialien` / `get_materialien` retrieval interfaces and surfaces verbatim legislative-history text under anchored statute articles.

Commentaries. We bridge **362 scholarly commentaries** (CC-BY-4.0 from OnlineKommentar.ch; CC-BY-SA-4.0 from OpenLegalCommentary.ch) into the graph, anchored by SR number plus article. The doctrinal layer is currently shallow but growing under the upstream commentaries’ own publication cadence.

6 Identifier and provenance layer

Layered identifier (`cli:ch` + `ECLI`). Every decision carries a Swiss-native canonical identifier `cli:ch` with a Council-of-EU `ECLI` projection, both surfaced in the per-decision Schema.org/LegalCase JSON-LD. `cli:ch` makes three features first-class that an `ECLI`-only

scheme flattens: (i) *trilingualism* (DE/FR/IT versions of a BGE are legally equally authentic per Art. 14 PublG; cli:ch treats language as a first-class axis via `?lang=`); (ii) *cantonal + chamber granularity* (`cli:ch:zh:obergericht:...` preserves the 26 cantonal systems and their chambers rather than collapsing to an opaque court code); (iii) *pinpoint addressing* (Erwägung-level fragments like `#e-2.3`, matching the Schweizer-Citation convention). An optional `@YYYY-MM-DD` suffix addresses a specific anonymisation version when needed. The compact form is

```
cli:ch:<court>[:<chamber>]:<docket>[@<version>][?lang=<l>][#<pinpoint>].
```

The mapping to ECLI is a pure function (`cli_ch_to_ecli`); the projection is many-to-one (lossy on language, pinpoint, version, chamber detail). An HTTP resolver at <https://opencasela.w.ch/cli/ch/> plus the court/chamber/docket path redirects to the canonical decision page; browsers preserve fragment pinpoints across the 302.

Cryptographic provenance (RFC-6962 + OpenTimestamps). Every daily publish computes an RFC-6962 Merkle tree over all decisions in the corpus. Each leaf commits to the tuple (`decision_id`, `cli:ch`, ECLI, `content_hash`, `decision_date`). The root (32 bytes, SHA-256-based, hash-domain-separated per the Certificate-Transparency RFC) is committed to the public Git repository at `docs/integrity/<YYYY-MM-DD>.root` and anchored on the Bitcoin blockchain via OpenTimestamps (`.root.ots`, ~945 bytes). The first root, over 972,882 decisions on 2026-05-21, is `1b597b92...81f599`. A GET `/api/integrity/<decision_id>` endpoint returns an inclusion proof in $O(\log n) \approx 20$ sibling hashes, computed in milliseconds against a memoised subtree cache. Any client can independently verify that a given decision was in the corpus on a given date without trusting the server: leaf $\rightarrow$ inclusion-proof walk $\rightarrow$ root $\rightarrow$ OpenTimestamps proof $\rightarrow$ Bitcoin block. This makes per-decision inclusion verification a public API surface rather than an internal release-engineering artifact.

Standards proposal. The identifier convention, the JSON-LD metadata schema, Akoma Ntoso for legislative materials, Markdown-with-pinpoint-anchors for full text, the resolved-citation conventions used here, and the Merkle-plus-OpenTimestamps provenance layer are consolidated as a six-bullet open-standards proposal at the *Standards* URL in Section 11. Each bullet is independently adoptable.

7 Dataset health

The release is protected by a four-layer quality framework (Table 7).

Table 7: Quality assurance, by layer. L1–L3 are publish-blocking on a critical regression (the orchestrator refuses to advance to the git-push step). L4 is alerting-only.

Layer	Scope	Granularity	Frequency	Blocks publish?
L1	function tests	624 pytest cases / 60 modules	every CI push	yes
L2	build-time pipeline	<code>_normalize_*</code> passes in <code>build_fts5.py</code>	nightly rebuild	yes
L3	dataset audit	52 <code>check_*</code> functions across 18 axes	nightly rebuild	yes
L4	production smoke	6 endpoint probes ($p_{95} < 2$ s)	every 5 min	alerts only

Per-check JSON for L3 is published at <https://opencaselaw.ch/quality.json> (refreshed every nightly rebuild). Critical conditions that block publish: total-count cliff $>1\%$, schema break, court not in registry, future-date count >50 , cross-DB row-count mismatch $>0.5\%$. Production incidents are codified as permanent regression tests in the source repository.

8 Data card

Table 8: Data card. Frozen 2026-05-21 release; live state always at <https://opencaselaw.ch>.

Field	Value
Sources	Federal courts (BGer, BGE, BVGer, BStGer, BPatGer); 26 cantonal portals; ECHR Swiss subset; federal regulatory authorities (FINMA, WEKO, EDÖB, UBI, ELCom, PostCom, ComCom); Wayback for closed historical archives
Languages	DE 46.3 %, FR 45.4 %, IT 8.3 % (official versions only; no machine translation)
Coverage gaps	Access-restricted portals documented in per-source coverage report; closed historical archives recovered from public Wayback snapshots only
Refresh	BGer hourly (Mon–Fri 05:00–16:00 UTC); all other federations nightly at 03:00 UTC
Personal-data posture	FADP; inherit upstream pseudonymisation; no re-pseudonymisation, no de-pseudonymisation
Known noise classes	Encoding drift, HTML-entity contamination, OCR artefacts in historical archives, control-character leakage from PDF extraction, near-duplicate cross-portal content (Section 9)
Licensing	Corpus CC0; commentaries CC-BY-4.0 / CC-BY-SA-4.0; code MIT; decision texts under URG/CopA Art. 5 official-acts exclusion
Removal / correction	Public policy at https://github.com/jonashertner/caselaw-repo-1/blob/main/docs/governance-and-removal-policy.md ; verified requests honoured per documented procedure

9 Limitations

Citation precision is bounded, not measured. The 92.9 % resolution rate is a coverage metric, not a precision bound. The automated date-sanity proxy gives an upper bound of $\sim 98.47\%$ on the share of resolutions whose recorded dates are chronologically consistent — conditional on the recorded source and target dates being correct themselves — and the rule-based consistency adjudication (Section 4) finds no rule-visible malformed identifiers or pin-cite range overflows on the 400-sample audit set. Neither establishes a *lower* bound on precision. Multi-annotator human adjudication of the same audit set — covering same-docket disambiguation, rule-consistent pin-cite false positives, and source-text accuracy — is companion-paper scope. The 92.9 % rate itself is a 17.7 pp lift over an internal pre-fix baseline but a 0.6 pp regression from the previous snapshot’s 93.5 %, reflecting citations to recently-added decisions whose targets have not yet been ingested.

Temporal validity, source pseudonymisation, snapshot-date semantics. (i) The statute graph maps references to the *current* SR location; a 1998 *OG* reference resolves to the surviving content without distinguishing the original-vs-superseded version. Versioned statute resolution is future work. (ii) Source pseudonymisation is inherited: federal decisions are typically pseudonymised by the issuing court; some cantonal decisions are published unredacted. We neither re-pseudonymise nor de-pseudonymise; removal requests are honoured per the documented governance policy. (iii) Some source portals expose near-future publication dates; we preserve source-provided dates rather than rewriting them, and the dataset-health gate treats large future-date spikes as critical scraper regressions.

Per-language resolution-rate confounder for the cross-language matrix. The 34 % aggregate is computed over the released resolved graph (8.10 M language-known edges). If

resolution rates differ systematically by language pair — and the pin-cite-aware resolver was tuned on BGE-form citations, disproportionately DE-original — the share could be biased. Conditional on such bias, our hypothesised direction is attenuation of same-language diagonals and amplification of cross-DE flows; the 34% would then be an upper bound rather than an underestimate. Magnitude and direction await the language-pair precision audit (companion paper).

Source-text fidelity is upstream-bound. Decision text quality is inherited from the originating portal: encoding drift, residual HTML-entity contamination, OCR artefacts in historical archives (BGE 1875–1953, Wayback-recovered BL ALS, MKG), control-character leakage from PDF extraction, near-duplicate cross-portal content. Build-time normalisation passes catch the common cases; an exports-side control-character sanitiser was added after a 2026-05 production incident. The corpus claims fidelity to what each source portal published, with documented normalisation applied — not to a hypothetical canonical text.

Scope. The cross-language citation-flow matrix is descriptive characterization of the released graph, not the resource contribution. The cross-lingual retrieval diagnostic, audit-rail framework, and prior-only-vs-RAG-augmented bench are evaluation contributions that depend on this resource and will be reported in the companion paper once their multi-annotator and human-judge-calibration components are complete.

10 Discussion

What the resource enables, and for whom. The substrate is built for three audiences. For *legal-NLP researchers*, it provides a corpus where every resolved citation has a stable target identifier and every statute reference is anchored to an article, so retrievers, generators, and legal-RAG systems can be built on a substrate whose outputs are verifiable against a Bitcoin-anchored corpus snapshot. For *Swiss legal practitioners*, the live MCP/REST endpoint at <https://mcp.opencaselaw.ch> supports decision lookup, Erwägung-level pinpoint citation, and cross-court reference walks with provenance-anchored data — capabilities not available as open infrastructure in the resources compared above. For *Swiss courts and public bodies*, the same data products they publish flow back as a federated, identifier-stable corpus with inclusion-proof verification, supporting referential integrity across systems and providing a public auditing surface for the official record. The Materialien bridge in particular opens teleological-interpretation research by exposing programmatic article-level access to Botschaft documents, subject to the anchoring limitations above.

Table 9: Five concrete tasks the released substrate makes one-call cheap. The right column is the smallest query against the live MCP/REST endpoint or the static corpus snapshot.

Task	Resource object	Example
Find all cases citing a decision	citation graph (<code>citation_targets</code>)	incoming refs to BGE 125 V 351 (66,883)
Build legal RAG over decisions + statutes	decision + statute graph	retrieve a decision plus its cited SR articles
Trace statutory intent (teleology)	Materialien bridge	SR-article → Federal Council Botschaft
Verify corpus membership on a given date	integrity API	per-decision inclusion proof vs. daily Merkle root
Normalise Swiss citations across systems	<code>cli:ch</code> ↔ ECLI	stable identifier across DE/FR/IT versions and chamber variants

Open questions. Three lines of follow-up work motivated by the resource: (i) precision-controlled measurement of the cross-lingual citation share with a multi-annotator stratified audit; (ii) versioned statute resolution so a 1998 *OG* reference resolves to the contemporaneous statute text rather than the current SR location; (iii) cross-lingual retrieval evaluation with lawyer-authored held-out queries (companion paper).

11 Open access and reproducibility

All artefacts are publicly available:

- Corpus: Hugging Face <https://huggingface.co/datasets/voilaj/swiss-caselaw> (CC0)
- Code: <https://github.com/jonashertner/caselaw-repo-1> (MIT)
- Live MCP/REST: <https://mcp.opencaselaw.ch> (SSE; OpenAPI at `/api/openapi.copilot.json`)
- Word add-in (lawyer-facing client): <https://opencaselaw.ch/word>
- Dashboards: <https://opencaselaw.ch>, <https://opencaselaw.ch/quality.html>
- Standards proposal: <https://opencaselaw.ch/standards/>
- Integrity / Merkle root and OpenTimestamps anchor: <https://opencaselaw.ch/integrity/>

Utility demonstration. The smallest end-to-end demo against the live endpoint:

```
$ curl https://mcp.opencaselaw.ch/api/decisions/bge_BGE_125_V_351
-> { decision_id, cli_ch, ecli, citation_de, citation_fr,
    citation_it, incoming_citations: 66883, cited_statutes: [...] }
```

```
$ curl https://mcp.opencaselaw.ch/api/integrity/bge_BGE_125_V_351
-> { decision_id, root_date: "2026-05-21",
    root: "1b597b92...81f599",
    inclusion_proof: [ ~20 sibling hashes ] }
```

The first call returns the canonical record plus its position in the citation graph and the statute graph. The second returns a cryptographic membership proof that lets any client verify the decision was in the 2026-05-21 release snapshot without trusting the server: traverse the inclusion proof, recover the daily Merkle root, then verify that root against the OpenTimestamps Bitcoin anchor.

Reproducibility capsule. The numerical claims in this paper are generated from the frozen table snapshot at `docs/paper/p1-resource/tables/corpus_graph_stats.json`; tables are produced by `docs/paper/v3/scripts/build_tables.py`, and Figure 2 by `docs/paper/p1-resource/scripts/build_figures.py`. Citation-precision proxies are stored at `benchmarks/citation_precision_proxies.json`; the mechanically adjudicated 400-row audit sample is `benchmarks/citation_precision_sample_400.jsonl`, with aggregate rule-check results at `benchmarks/citation_precision_audit_results.json`. The 2026-05-21 integrity manifest is `docs/integrity/2026-05-21.json`; the full RFC6962-SHA256 root is stored in `docs/integrity/2026-05-21.root` and begins `1b597b92`. The archival DOI and submission git tag will be minted at submission, after this manuscript and the release artifacts are frozen.

Companion paper (evaluation diagnostics, in preparation) covers the cross-lingual retrieval diagnostic with multi-annotator inter-annotator agreement, the audit-rail adversarial probe results, and human calibration of the LLM judge used in the closing-audit grounding rail.

References

- [1] Florian Geering and Jakob Merane. Swiss federal supreme court dataset (SCD), 2024. Version 2023-5.
- [2] Pooja Harde, Bhavya Jain, and Sarika Jain. Lecnet: A legal citation network benchmark dataset. In *Proceedings of the 1st Workshop on NLP for Empowering Justice (JUST-NLP 2025)*, pages 18–28. Association for Computational Linguistics, 2025. doi: 10.18653/v1/2025.justnlp-main.4.
- [3] Harvard Law School Library. Caselaw access project. <https://case.law/>, 2018.
- [4] Peter Henderson, Mark Krass, Lucia Zheng, Neel Guha, Christopher D. Manning, Daniel Jurafsky, and Daniel E. Ho. Pile of law: Learning responsible data filtering from the law and a 256gb open-source legal dataset. *Advances in Neural Information Processing Systems 35, Datasets and Benchmarks Track*, 2022.
- [5] Joel Niklaus, Ilias Chalkidis, and Matthias Stürmer. Swiss-judgment-prediction: A multilingual legal judgment prediction benchmark. In *Proceedings of the Natural Legal Language Processing Workshop 2021*, pages 19–35. Association for Computational Linguistics, 2021. doi: 10.18653/v1/2021.nllp-1.3.
- [6] Joel Niklaus, Veton Matoshi, Matthias Stürmer, Ilias Chalkidis, and Daniel E. Ho. Multilegalpile: A 689gb multilingual legal corpus. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15077–15094. Association for Computational Linguistics, 2024. doi: 10.18653/v1/2024.acl-long.805.
- [7] Joel Niklaus, Jakob Merane, Luka Nenadic, Sina Ahmadi, Yingqiang Gao, Cyrill A. H. Chevalley, Claude Humbel, Christophe Gösken, Lorenzo Tanzi, Thomas Lüthi, Stefan Palombo, Spencer Poff, Boling Yang, Nan Wu, Matthew Guillod, Robin Mamie, Daniel Brunner, Julio Pereyra, and Niko Grupen. SwiLTra-Bench: The Swiss legal translation benchmark. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14894–14916. Association for Computational Linguistics, 2025. URL <https://aclanthology.org/2025.acl-long.725/>. 180k aligned Swiss legal translation pairs across DE/FR/IT/RM/EN spanning laws, BGE headnotes, and Federal Supreme Court press releases; introduces SwiLTra-Judge for LLM-based eval aligned with human experts.
- [8] Malte Ostendorff, Till Blume, and Saskia Ostendorff. Towards an open platform for legal information. In *Proceedings of the ACM/IEEE Joint Conference on Digital Libraries (JCDL)*, 2020. Open Legal Data platform; arXiv:2005.13342.
- [9] Volodymyr Ovcharov. Automatic construction of a legal citation graph from 100 million ukrainian court decisions: Large-scale extraction, topological analysis, and ontology-driven clustering. *arXiv preprint arXiv:2605.15362*, 2026. doi: 10.48550/arXiv.2605.15362.
- [10] Luca Rolshoven, Vishvakshen Rasiah, Srinanda Brügger Bose, Sarah Hostettler, Lara Burkhalter, Matthias Stürmer, and Joel Niklaus. Unlocking legal knowledge: A multilingual dataset for judicial summarization in switzerland. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 15382–15411. Association for Computational Linguistics, 2025. URL <https://aclanthology.org/2025.findings-emnlp.832/>. SLDS dataset: 20,000 Swiss Federal Supreme Court rulings with DE/FR/IT headnotes, CC-BY-4.0, <https://huggingface.co/datasets/ipst/slds>.

- [11] Ronja Stern, Vishvaksenan Rasiah, Veton Matoshi, Srinanda Brügger Bose, Matthias Stürmer, Ilias Chalkidis, Daniel E. Ho, and Joel Niklaus. One law, many languages: Benchmarking multilingual legal reasoning for judicial support. *arXiv preprint arXiv:2306.09237*, 2024.