

toolbox.e3d

Contents

Introduction	1
Command-line interaction with EROSION-3D	2
Installation	2
Test setup	2
Determination of calibration parameters skinfactor and resistance to erosion	3
Fitting of skinfactor to different calibration targets	3
Fitting of resistance to erosion to different calibration targets	4
Validation modelling	6
Create model folders	6
Soil set	6
Digital elevation Model and relief set	8
Create rainfall file	8
Run calculation	8
Delete model folder	9
References	9

Introduction

The R wrapper package toolbox.e3d was created to perform often occurring tasks done with the soil erosion model EROSION-3D in an easy usable and reproducible way. It requires a licensed EROSION-3D installation on a Windows system. A download link and license conditions for this software are available from Geognostics (http://bodenerosion.com/e3d_demo.html).

EROSION-3D is designed as software with Graphical User Interface (GUI) with limited command-line support introduced in version 3.15. The toolbox.e3d uses only the command-line interaction, for fully reproducible work. Each manual change in modelling is seen as non-reproducible or at least failure-prone (GMD executive editors 2019).

The toolbox.e3d was developed with the 32-bit EROSION-3D version 3.2.0.9. As the command-line interaction was sparsely used up to now, several functions may not work with older versions of EROSION-3D.

Command-line interaction with EROSION-3D

There are three basic commands to run EROSION-3D from command-line (Werner 2007):

- ‘/c’ for calculation
- ‘/r’ for preprocessing of relief set
- ‘/s’ for preprocessing of soil set (available from version 3.2.0.9)

All further options (paths to input files, modelling options) are set in a *.PAR file.

For Example, this command would run an EROSION-3D calculation from the R-environment:

```
system2("e3d", '/c "C:/E3Dmodel/model/run.par"', wait=TRUE)
```

and as pure command-line call:

```
e3d /r C:/E3Dmodel/model/run.par
```

Installation

Use the following commands in R to install toolbox.e3d:

```
# Install devtools from CRAN
install.packages("devtools")

# Install toolbox.e3d
devtools::install_github("jonaslennz/toolbox.e3d")
```

EROSION-3D needs to be installed and licensed separately, please refer to the EROSION-3D web page or the handbook for specific installation instructions (Werner 2003).

Test setup

Once EROSION-3D is installed and activated and toolbox.e3d is installed, their interaction can be tested using:

```
toolbox.e3d::get_version.E3D()
#> Duplicating single soil entry to allow calculation.
#> NULL
#> [1] "3.2.0.9"
```

This function checks, if EROSION-3D can be found in the system PATH-Variable. If it is not present in PATH it searches for EROSION-3D in the registry and adds it temporarily to PATH for the current R-session.

If this function fails with error message “cannot access e3d installation” you should check the installation of EROSION-3D and add the installation folder manually to system PATH.

When successful this function runs a dummy erosion-3D model and returns the version number in the created file result.log.

Determination of calibration parameters skinfactor and resistance to erosion

The soil input parameters of EROSION-3D include the two calibration parameters skinfactor and resistance to erosion. Determination of these two needs to be done to fit the model output with runoff/soil-loss measurement data obtained in rainfall simulations in field. In previous works these parameters were determined manually with the hillslope-erosion modelling tool EROSION-2D (Michael 2000; Schindewolf and Schmidt 2012). Both erosion-modelling tools share basic algorithms, but show differences in available model options and possible input accuracy of parameters.

For fully reproducible results, synthetic land-use and Digital Elevation Models (DEM) are used to model rainfall simulation plots in EROSION-3D. Multiple independent plots - identical in relief but differing in target calibration parameter - are calculated simultaneously. The model output is analyzed and used to iterate calibration parameter values, until a certain accuracy is reached.

Fitting of skinfactor to different calibration targets

The skinfactor is a calibration parameter to saturated hydraulic conductivity in the infiltration submodule in EROSION-3D. It can be fitted to the cumulative runoff from the plot or to an infiltration rate at a certain timestep.

Calibration target cumulative runoff

To fit the calculated to the measured cumulative runoff for an experiment on a soil with

- 30 mass-% clay **Cl**
- 40 mass-% silt **Si**
- 30 mass-% sand **Sa** (clay+silt+sand must equal 100 mass-%)
- 1.3 mass-% - content of organic bound carbon **Corg**
- 1300 kg/m^3 dry bulk density **Bulk**
- 22 vol-% initial soil moisture at start of experiment **Moist**

which produced

- 100 litres total runoff **CumRunoff** after 30 minutes **endmin**

with experimental settings of

- 0.5 mm/min rainfall intensity **intensity**
- 1 m wide plot **plotwidth**
- 10 m long plot **plotlength**
- 10 % slope inclination **slope**

with model option

- limitation of potential infiltration to available water **ponding** = TRUE
- display output of calibration parameter values for each iteration step **silent** = FALSE

the skinfactor can be determined by:

```
skin_cum <-  
toolbox.e3d::determine.skin.runoff.E3D(Cl = 30, Si = 40, Sa = 30,  
    Corg = 1.3, Bulk = 1300, Moist = 22,  
    CumRunoff = 100, intensity = 0.5,  
    plotwidth = 1, plotlength = 10,  
    slope = 10,  
    endmin = 30,  
    ponding = TRUE, silent = FALSE)  
#> Duplicating single soil entry to allow calculation.  
#> NULL  
#> 1 : 1e-08 100  
#> 2 : 0.000220513073990305 0.000278255940220713  
#> 3 : 0.000227886500951164 0.000228422512505557  
skin_cum  
#> [1] 0.0002283277
```

Calibration target infiltration rate

Using the same values as in the preceeding example with a differing fitting target of:

- 0.2 mm/min infiltration rate **infiltrate** after 30 minutes **endmin**

the skinfactor can be determined by:

```
skin_inf <-  
toolbox.e3d::determine.skin.infil.E3D(Cl = 30, Si = 40, Sa = 30,  
    Corg = 1.3, Bulk = 1300, Moist = 22,  
    infiltrate = 0.2, intensity = 0.5,  
    plotwidth = 1, plotlength = 10,  
    slope = 10,  
    endmin = 30,  
    ponding = TRUE, silent = FALSE)  
#> Duplicating single soil entry to allow calculation.  
#> NULL  
#> 1 : 1e-08 100  
#> 2 : 0.000890215085445039 0.00112332403297803  
#> 3 : 0.000998826021204293 0.00100117535864183  
skin_inf  
#> [1] 0.0009989564
```

Fitting of resistance to erosion to different calibration targets

Resistance to erosion is a calibration parameter of the particle detachment calculation in the erosion submodule in EROSION-3D. It can be fitted to the cumulative soil loss from the plot or to a sediment concentration at a certain timestep.

The erosion submodule of EROSION-3D uses nine grain-size fractions instead of the three used in the infiltration submodule. Therefore **Cl**, **Si** and **Sa** are separated in fine, middle and coarse fractions for the determination functions.

Calibration target cumulative soil loss

To fit the calculated to the measured cumulative soil loss for an experiment on a soil with

- 5 mass-% fine clay **FCI**, 10 mass-% middle clay **MCI**, 15 mass-% coarse clay **CCI**
- 10 mass-% fine silt **FSi**, 20 mass-% middle silt **MSi**, 10 mass-% coarse silt **CSi**
- 15 mass-% fine sand **FSa**, 10 mass-% middle sand **MSa**, 5 mass-% coarse sand **CSa** (total sum must equal 100 mass-%)
- 1.3 mass-% - content of organic bound carbon **Corg**
- 1300 kg/m³ dry bulk density **Bulk**
- 22 vol-% initial soil moisture at start of experiment **Moist**
- skinfactor **Skin** from previous determination (100 litres total runoff after 30 minutes **endmin**)
- a total soil loss of 1 kg **Soilloss**
- 0.05 s/m^{1/3} manning's-*n* hydraulic surface roughness **Roughness**
- 20 % soil cover by plants, plant residues, stones, ... **Cover**

with experimental settings of

- 0.5 mm/h rainfall intensity **intensity**
- 1 m wide plot **plotwidth**
- 10 m long plot **plotlength**
- 10 % slope inclination **slope**

with model option

- limitation of potential infiltration to available water **ponding** = TRUE
- output of calibration parameter values for each iteration step **silent** = FALSE

resistance to erosion can be determined by:

```
eros_cum <-  
  toolbox.e3d::determine.eros.cumsed.E3D(FCI=5,MCI=10,CCI=15,  
                                          FSi=10,MSi=20,CSi=10,  
                                          FSa=15,MSa=10,CSa=5,  
                                          Corg = 1.3, Bulk = 1300, Moist = 22,  
                                          Skin = skin_cum, Roughness=0.05, Cover = 20,  
                                          Soilloss = 1,  
                                          intensity = 0.5, plotwidth = 1,  
                                          plotlength = 10, slope = 10,  
                                          endmin = 30, ponding = TRUE, silent = FALSE)  
  
#> Duplicating single soil entry to allow calculation.  
#> NULL  
#> 1 : 1e-08 100  
#> 2 : 0.000559081018251222 0.000705480231071865  
#> 3 : 0.000662119897452795 0.000663677268837001  
eros_cum  
#> [1] 0.0006635907
```

Calibration target sediment concentration

To be added ...

Validation modelling

Validation modelling can be used to check how input parameters and model options will affect modelling results. Due to the high number of possible combinations this section shall describe a possible workflow demonstrating fully reproducible work with EROSION-3D.

The effect of differing skinfactor values (from two determination methods) on the modelled runoff volume and soil loss is used as example. The models are run on synthetic elevation and landuse models with independent slope stripes, as described in (Lenz 2017).

Create model folders

As first step folders are created including a basic EROSION-3D model:

```
path <- toolbox.e3d::create_folders.E3D(path = "C:/E3Dmodel_toolbox/")
```

Soil set

EROSION-3D needs at least two files for the soil set:

- a landuse.asc, defining an ID for each raster cell,
- and a soil_params.csv defining soil parameters for each ID in landuse.asc.

To apply changes to soil parameters soil_params.csv can be read and modified:

```
soils <- read.csv(file.path(path, "soil/soil_params.csv"))[1,]

# soil parameters are set according to example in parameter determination
soils$BLKDENSITY <- 1300
soils$CORG       <- 1.3
soils$INITMOIST  <- 22
soils$FT         <- 5
soils$MT         <- 10
soils$GT         <- 15
soils$FU         <- 10
soils$MU         <- 20
soils$GU         <- 10
soils$FS         <- 15
soils$MS         <- 10
soils$GS         <- 5
soils$ROUGHNESS  <- 0.05
soils$COVER      <- 20
soils$ERODIBIL   <- eros_cum

# parameters derived automaticly by EROSION-3D are set to 0
soils$THETA_R <- 0
```

```

soils$THETA_S <- 0
soils$ALPHA <- 0
soils$NORDPOL <- 0

# a second soil parameter entry is created
soils[2,] <- soils[1,]

# ID of second entry is set
soils$POLY_ID<- 1:nrow(soils)

# skinfactors are set for each entry separately
soils$SKINFACOR[1] <- skin_cum
soils$SKINFACOR[2] <- skin_inf

write.csv(soils,file.path(path,"soil/soil_params.csv"),
          row.names = FALSE, quote = FALSE)

```

The synthetic landuse.asc can be created with:

```

toolbox.e3d::write.landuse.E3D(POLY_ID = soils$POLY_ID, length = 10,
                              path = file.path(path,"soil/"), filename = "landuse.asc")

```

Soil set creation since version 3.2.0.9

Since version 3.2.0.9 EROSION-3D can preprocess the soil set from a given landuse raster and a soil_params file. This allows the analysis of parameters derived by EROSION-3D (*.pid files, THETA_R, THETA_S, ALPHA, ...)

The input files must be written to the model parent folder:

```

# write files to parent folder
write.csv(soils,file.path(path,"soil_params.csv"),
          row.names = FALSE, quote = FALSE)
toolbox.e3d::write.landuse.E3D(POLY_ID = soils$POLY_ID, length = 10,
                              path = file.path(path), filename = "landuse.asc")

```

They must be defined in the *.par file:

```

# read, modify and rewrite *.par
run_par <- ini::read.ini(file.path(path,"run.par"))
run_par[["Soil_landuse"]][["rdb_dat"]] <- file.path(path,"soil_params.csv")
run_par[["Soil_landuse"]][["rdb_grd"]] <- file.path(path,"landuse.asc")
ini::write.ini(run_par,filepath = file.path(path,"run.par"))

```

And can then be pre-processed by:

```

# preprocess soil set
system2("e3d", paste0('/s "',normalizePath(file.path(path,"run.par")),'"'), wait=TRUE)

```

Digital elevation Model and relief set

A synthetic DEM is created with:

```
toolbox.e3d::write.relief.E3D(POLY_ID = soils$POLY_ID, length = 10, slope = 11,
                             path = path, filename = "dem.asc")
```

where **length** (in metres) and **slope** (inclination in %) define the slope geometry.

The number of elements in POLY_ID defines the number of independent slopes simulated in parallel.

The EROSION-3D relief set can be created with:

```
system2("e3d", paste0('/r "', normalizePath(file.path(path, "run.par")), "''), wait=TRUE)
```

Since vertical DEM resolution is limited to 2 decimal digits (i.e. to 0.01 m) in EROSION-3D, step-like artifacts can be introduced. To check for such artifacts one can read unique values from the slope file created by EROSION-3D:

```
slope_E3D <- raster::raster(normalizePath(file.path(path, "relief/slope.asc")))
unique(raster::values(slope_E3D))
#> [1] 6.277298
```

If only one value is returned all slope values are equal and no step artifacts were introduced.

Create rainfall file

An EROSION-3D compatible rainfall file can be written by:

```
toolbox.e3d::write.rainfile.E3D(time = c(0,30*60), intens = c(0.5,0), path,
                                filename = "rain_e3d.csv")
```

- **Time** and **intens** are numeric vectors of equal length.
- **Time** gives the timesteps in seconds, at which rainfall-intensity changes occur.
- **Intens** gives the rainfall-intensity for the following time period in mm/min.

Run calculation

Once all input files are prepared the simulation can be run:

```
# command-line call to run EROSION-3D
system2("e3d", paste0('/c "', normalizePath(file.path(path, "run.par")), "''), wait=TRUE)
```

Afterwards, the results can be analyzed:

```
#read runoff in litres (*1000)
runoff <- raster::raster(file.path(path, "result/sum_q.asc"))[,1]*1000
sed <- raster::raster(file.path(path, "result/sum_sedvol.asc"))[,1]

cbind(soils[,c("POLY_ID", "SKINFACOR")], runoff, sed)
#> Warning in data.frame(..., check.names = FALSE): row names were found from a
```



```
#> short variable and have been discarded
#> POLY_ID SKINFACOR runoff sed
#> 1      1 0.0002283277 99.99995 1.028949
#> 2      2 0.000989564 99.99995 1.028949
#> 3      1 0.0002283277 99.99995 1.028949
#> 4      2 0.000989564 99.99995 1.028949
#> 5      1 0.0002283277 47.34490 0.410924
#> 6      2 0.000989564 47.34490 0.410924
#> 7      1 0.0002283277 47.34490 0.410924
#> 8      2 0.000989564 47.34490 0.410924
```

The hypothetical results show, that runoff and soil loss calculated with the skinfactor fitted to cumulative runoff meet the expectations (100 l runoff, 1 kg soil loss) quite well, whereas the results calculated with the skinfactor fitted to infiltration rate are less than half the expected value.

Delete model folder

To clear the workspace and delete all model files run:

```
unlink(file.path("C:/E3Dmodel_toolbox/"), force = T, recursive = T)
```

References

- GMD executive editors. 2019. “Editorial: The Publication of Geoscientific Model Developments V1.2.” *Geoscientific Model Development* 12 (6): 2215–25. <https://doi.org/10.5194/gmd-12-2215-2019>.
- Lenz, Jonas. 2017. “Konzeptionelle Studie Zur Überprüfung Der Anwendbarkeit Verfügbarer Daten Zur Erosions- / Abflussmodellierung Mit EROSION-3d in Punjab, Indien.” PhD thesis, Halle (Saale): Martin-Luther-Universität Halle-Wittenberg.
- Michael, Anne. 2000. “Anwendung Des Physikalisch Begründeten Erosionsprognosemodells EROSION 2d/3d - Empirische Ansätze Zur Ableitung Der Modellparameter. Dissertation.” PhD thesis, Freiberg: TU Bergakademie Freiberg.
- Schindewolf, Marcus, and Jürgen Schmidt. 2012. “Parameterization of the EROSION 2d/3d Soil Erosion Model Using a Small-Scale Rainfall Simulator and Upstream Runoff Simulation.” *CATENA*, Experiments in Earth surface process research, 91 (April): 47–55. <https://doi.org/10.1016/j.catena.2011.01.007>.
- Werner, Michael von. 2003. *EROSION-3d Ver. 3.0 User Manual*. Berlin: GeoGnostics Software. <http://www.bodenerosion.com/demos/e3d300/manual.pdf>.
- . 2007. *EROSION-3d Ver. 3.15 Benutzerhandbuch*. Berlin: GeoGnostics Software.