

Run an Application Container



Dan Wahlin

Wahlin Consulting

@DanWahlin www.codewithdan.com


Overview




- **Use docker pull to retrieve a custom image from a registry**
- **Run an application container**
- **View container logs**
- **Create a container volume**

Run an Application Container

Images and the Layered File System



Images, Containers and File Layers



Pulling an Image from a Registry

```
docker pull <imageName>
```

Running a Container

```
docker run -p <externalPort>:<internalPort> <imageName>
```

Using docker run


View Container Logs

Using docker logs to View Container Logs


```
docker logs <containerId>
```

Using Container Volumes


Storing Data Outside of a Container



Volume Mounts



Volume Mounts



Creating a Container Volume

Data in folder should be
stored on the container host



```
docker run -p <ports> -v /var/www/logs <imageToRun>
```

Defining a Host Location (Mac/Linux)

Data in folder should be
stored on the container host

```
docker run -p <ports> -v $(pwd) : /var/www/logs <imageToRun>
```

Print working directory
(Mac/Linux)

Key Volume Scenarios

Production Scenarios
(logs, database files and more)

Development Scenarios
(develop using containers)

Defining a Host Location (Windows)

Print working directory
(Windows PowerShell)



```
docker run -p <ports> -v ${PWD}:/var/www/logs <imageToRun>
```

Create a Container Volume

Summary



- **Docker pull can be used to retrieve an image from a registry**
- **docker run allows an image to be run as a container**
- **Access container logs using docker logs**
- **Volumes provide persistent storage**