PREDICTING LINEAR RELATIONAL DECODABILITY WITHOUT THE RELATION

Anonymous authors
Paper under double-blind review

ABSTRACT

Linear relational embeddings (LREs) approximate a language model's subject-to-object mapping with an affine function. Their faithfulness varies enormously across relations, from near zero for PERSON_FATHER to the ceiling for COUNTRY_CAPITAL_CITY. We investigate the factors that contribute to this variation and demonstrate that it can be significantly predicted from a readout that is not aware of the underlying relationship. To do so, we propose a novel form of the Jacobian lens, the *entity lens*. Whereas the Jacobian lens is estimated across all tokens and concepts, the entity lens EL_t is trained to predict what the model will output for an entity of type t; e.g., we train ELs for countries and for persons. **1 <<< sg: I don't understand the above sentence: "what the mdoel will output" is too vague. Is it about next-token predictions or about any future token? (Edit after reading the intro: I think we should mention that it's under the neutral prompt "is known for".)** >>> After estimating an entity lens, we measure how highly it ranks the model's answer for a relation without using any relation-specific information in estimation and prediction. Across 28 relations of the LRE dataset on Olmo-3-7B this relation-agnostic score correlates with LRE faithfulness at $\rho = 0.7355$ ($p < .01$). This suggests that linear decodability is largely a property of what a subject's representation already carries, rather than of the relation being decoded. **2 <<< sg: I don't completely agree with the above sentence: the entity lens also depends on the set of subjects, in other words the entity type** >>> Moving the unit of analysis from the relation to the individual fact, we conclude that new relation datasets and analysis methods are needed to address several problems in existing datasets, most prominently semantically weak first tokens (e.g., most predicted universities' first token is "University") and reference competition (e.g., the LLM associates obscure actor names with competing non-actor entities that have the same last name). **3 <<< sg: In this example, do we have to mention the actor/non-actor contrast or can we just say it's about persons with the same last name? I think this would help the reader focus on the essential aspect.** >>>

1 INTRODUCTION

4 <<< sg: Here and/or in related work, we could mention Yuetian's paper on the relationship between relational linearity and hallucinations. I think this could be helpful to convince readers that the LRE topic is interesting. >>>

Hernandez et al. (2024) showed that a language model's mapping from a subject to the object of a relation is often well approximated by an affine function of the subject's hidden state, a *linear relational embedding* (LRE). They also showed that this works far better for some relations than others. On Olmo-3-7B, we reproduce the same spread: an LRE fitted on COUNTRY_CAPITAL_CITY agrees with the model's own prediction 87.5% of the time while one fitted on PERSON_FATHER agrees 7.5% of the time.

Why? The natural reading is that some relations are "more linear" than others: linearity is a property of the relation. We report evidence that it is better understood as a property of the *subject's representation*. Concretely, we show that one can predict how faithful an LRE will be *before fitting it*, and without using the relation at all.

Building on recent work by Gurnee et al. (2026), we introduce the *entity lens* EL_t, which is trained on subjects of type t placed in the the neutral prompt `"{} is known for"` and evaluates the Jacobian at entities of type t. This readout is about factual knowledge and, more specifically, about factual knowledge about an entity of a particular type. The question it answers, *what factual knowledge is this model ready to produce about this entity?*, is specific to the entity type, but not specific to any relation.

We estimate the entity lens under the single neutral prompt (shared by every relation), at one layer fixed in advance, and ask how highly it ranks the model's own answer. The lens sees no relation template, no objects and no (subject, object) pairs, yet its score correlates with LRE faithfulness across 28 relations at $\rho = 0.7355$. **5 <<< sg: We should avoid repeating ourselves, so maybe merge this paragraph with the previous one? >>>**

We make four contributions. (i) We introduce the entity lens, a supervision-free readout of what a model is disposed to say about an individual entity of a specific entity type. (ii) We turn it into a relation-agnostic diagnostic of linear decodability and show that it predicts LRE faithfulness. (iii) We show the prediction holds up under leave-one-type-out and under controls for object cardinality and answer-token frequency. (iv) Moving the unit of analysis from the relation to the individual fact, we provide an analysis of several problems in existing datasets that hinder further progress on understanding LREs in language models, most prominently semantically weak first tokens and reference competition.

2 Background

An LRE for relation r approximates the model's computation as

$$o \;\approx\; \beta\, W s + b_\beta, \tag{1}$$

where s is the hidden state at the subject's final token and o the output state. Write f for the model's own map between the two: f sends the subject's hidden state at an intermediate layer ℓ to the final-layer state at the last position. We average local first-order approximations of f over a small set $\{s_i\}$ of reference subjects and scale their subject-dependent terms by β:

$$W = \mathrm{mean}_i\, J_i, \qquad b_\beta = \mathrm{mean}_i[\, f(s_i) - \beta J_i s_i \,], \tag{2}$$

where J_i is the Jacobian of f at s_i. At $\beta = 1$, this is the averaged first-order Taylor approximation (Hernandez et al., 2024).

This prediction decomposes into a subject-dependent term and a constant: expanding b_β gives

$$\beta W s + b_\beta \;=\; \mathrm{mean}_i[\, f(s_i) + \beta J_i (s - s_i) \,], \tag{3}$$

in which only the second term depends on which subject s is being decoded. Left unscaled, the shared anchor $\mathrm{mean}_i\, f(s_i)$ dominates and the operator returns much the same object for every subject. Setting $\beta > 1$ amplifies the subject-specific contribution relative to that anchor, and so does change which object is ranked first. Hernandez et al. (2024) fit β per relation alongside the layer; we follow their protocol and select it from $\{0.5, 1, 1.5, 2, 3, 5\}$.

Faithfulness is the rate at which decoding $\beta W s + b_\beta$ over the full vocabulary reproduces the *model's own* top-1 prediction (not the gold object). It is therefore a measure of how well an affine map captures what the model does. Faithfulness defined this way is the quantity we predict.

3 Related work

Linear relational embeddings. Treating relations as linear maps between concept representations goes back to Paccanaro & Hinton (2000); Hernandez et al. (2024) carried the idea over to transformer language models (Vaswani et al., 2017), and subsequent work has asked why the resulting LREs

are faithful for some relations and not others. Merullo et al. (2025) trace part of this variation to pretraining data: LREs are more faithful when subjects and objects frequently co-occur in the corpus (we compare against such frequency measures in Appendix A.1). A further question is whether such structure reflects what a model has learned or only the particular parametrization that realizes it, since many parametrizations induce the same next-token distribution. Existing results point to the former, since under suitable conditions, relational linearity holds either in all distribution-equivalent models or in none, and it has been shown empirically, through a probe based on the Kullback–Leibler divergence, to vary across models, layers and phrasings of the relation (Marconato et al., 2024; Valer et al., 2026). These works evaluate and explain linearity at the level of the relation. We ask instead how much of it can be predicted from how the model represents the subject, using a readout estimated without the relation or any of its objects. **6 <<< sg: I'm unhappy with the term "object cardinality", at least before we define it. I would take this to mean the number of possible objects, which is not what we mean here. >>>**

Subject representations in factual recall. Mechanistic studies converge on the view that much factual knowledge is attached to the subject before the relation is processed. According to Geva et al. (2021); Meng et al. (2022), feed-forward layers operate as key–value memories whose keys respond to patterns in the input and whose values induce distributions over the output vocabulary, and in middle layers at the last subject token they are where causal tracing localizes factual associations and where targeted edits change individual facts. Building on these findings, factual recall has been decomposed into stages: MLP layers enrich the subject representation with many of its attributes, a lookup that depends largely on the subject's name rather than on the preceding context; the relation is propagated to the final position; and attention heads extract the requested attribute (Geva et al., 2023; Nanda et al., 2023). Gottesman et al. (2026) show that knowledge acquisition tracks how often subject and answer co-occur, though frequency alone does not fully explain learning, which is why we treat the corpus-frequency baselines in Appendix A.1 as a comparison rather than an explanation. Our approach can be read as a probe of this enrichment, since it reports what the model is prepared to say about a subject before any relation is given. This allows us to connect two lines of work: We hypothesize that the enrichment the lens diagnoses contributes to the relational linearity found by Hernandez et al. (2024). The lens predicts LRE faithfulness across relations in all seven models we test, and the association persists when controlling for object cardinality and answer-token frequency (§6). **7 <<< sg: I think the Gottesman TACL paper is indeed relevant to ours, but it doesn't fit in this paragraph. Or maybe we should change the title of the paragraph to something more vague like "explaining factual recall" (which would likely mean merging this paragraph with the one below). >>>**

How facts are stored. Theoretical work offers two accounts of how transformers store facts. Nichani et al. (2025) model attention and MLP weights as associative memories and prove that a one-layer transformer can store a number of facts that scales linearly with its parameter count, with storage traded off between self-attention and MLP parameters. Ravfogel et al. (2026) study a geometric form of storage: in a controlled one-layer setting, subject embeddings encode linear superpositions of their associated attributes, and a small MLP selects among them conditioned on the relation. In pretrained models the two need not compete: lookup-like computation can enrich the subject representation over the early and middle layers, and the geometric picture then describes the enriched state from which a relation selects. Our hypothesis concerns this enriched state: a relation should be linearly decodable to the extent that its attribute is prominently encoded in the subject representation after enrichment.

Lenses. Lenses read out intermediate hidden states in terms of the output vocabulary and differ mainly in the map they apply: the model's own unembedding (nostalgebraist, 2020), an affine translator learned per layer (Belrose et al., 2023), or the model's input–output Jacobian averaged over a large corpus and applied to raw activations, with the aim of identifying representations the model is poised to verbalize (Gurnee et al., 2026). Our entity lens instead evaluates the Jacobian at reference entities of the subject's type under a single neutral factual prompt, so that the readout concerns what the model is prepared to say about entities of that type rather than about any concept. Its contrastive variant further applies the Jacobian to differences between entity representations, subtracting what the references share. **8 <<< sg: An important work that is missing**

here is Patchscopes (Ghandeharioun et al., ICML 2024 I think), which unifies all "lenses" in a common framework. >>>

4 THE ENTITY LENS

Gurnee et al. (2026)'s Jacobian lens is broadly similar to LRE. But instead of a relation-specific prompt and a focused target position (the object), it computes the average $W = \text{mean}_i\, J_i$ over many diverse prompts and many output positions. The Jacobian lens also does not use the "anchor", the zero-order term of the Taylor expansion; so it is simply $W = \text{mean}_i\, J_i$.

We derive our *contrastive entity lens* from Eq. 3, restated as:

$$f(s) \approx \beta W s + b_\beta \;=\; \text{mean}_i[\, f(s_i)] + \beta\, \text{mean}_i[\, J_i(s - s_i)\,] \tag{4}$$

Following Gurnee et al. (2026), we also drop the anchor term $\text{mean}_i[\, f(s_i)]$; see discussion in §10. This also means that we do not need β since the scaling does not change the output distribution over tokens. The final form of the contrastive entity lens is then:

$$\text{CEL}(e) = \text{mean}_i[\, J_i(s_e - s_i)\,] \tag{5}$$

CEL takes into account the difference between s_e and the reference point s_i, as it should if we want to approximate $f(s_e)$ using the first derivative. Our original motivation was that we are not interested in what the model associates with an entity like "Russia" in general (e.g., "Europe"). Instead we are interested in what the model associates with "Russia", but not with other reference entities like "Spain" and "Italy". Examples of such contrastive associations for "Russia" are "vodka" and "Kremlin". Our hypothesis was that such top-ranked contrastive associations give rise to linearity.

In initial experiments, we found that the contrastive entity lens is quite sensitive to the reference set. For example, if s_e is a French person and a Spanish person is the reference entity s_i, then the vector difference in Eq. 5 will enhance "French". But if s_i is another French person, then "French" will be demoted. This is bad for answering questions about s_e's nationality and native language. We therefore also consider the following noncontrastive entity lens, which drops the reference set differences:

$$\text{NEL}(e) = \text{mean}_i[\, J_i s_e\,] \tag{6}$$

In what follows, EL refers to both NEL and CEL and "entity lens" refers to NEL unless further specified.

To instantiate the entity lens (for both NEL and CEL) for factual relations, we need (i) a prompt that evokes factual associations and (ii) a reference set of entities for computing the Jacobians J_i (both NEL and CEL) and for serving as the s_i in the vector differences $s_e - s_i$ (for CEL).

As the prompt we adopt `"{} is known for"`. This a neutral prompt, i.e., it is not customized for any specific factual relations. We use it for all our experiments unless otherwise stated.

As the reference set, we use entities of the same type as the subject, e.g., other countries if the subject is a country, other landmarks if the subject is a landmark etc. NEL applied to an input s outputs anything the model is likely to say in a context in which an entity of the same type as s occurs, including features it shares with other same-type entities. CEL outputs only what differentiates s from other same-type entities.

Computation. We do not compute J_i explicitly, but obtain each Jacobian–vector product $J_i u$ by the double-backward construction (Pearlmutter, 1994), at the cost of a constant number of forward and backward passes; this is what makes Eq. 5 affordable at $d_{\text{model}} = 4096$ (Appendix B).

The relation score. We decode $\text{EL}(e)$ over the full vocabulary and record the rank of m_e, the model's own top-1 answer for relation r, obtained under the relation's in-context prompt (§5). Writing $\text{rk}_{\text{EL}(e)}(m_e)$ for that rank, the diagnostic for a relation is

$$A_r \;=\; -\,\text{median}_e\, \log_{10} \text{rk}_{\text{EL}(e)}(m_e), \tag{7}$$

so higher A_r means the lens agrees with the model more.

What makes A_r relation-agnostic. Eq. 5 is not specific to r: the prompt is neutral and shared, the layer is fixed at 17 for all relations (Appendix C) and no (subject, object) pair of the relation is used in estimation. Relation-specificity enters in exactly one place, the *target* m_e, the quantity faithfulness is defined against.

5 EXPERIMENTAL SETUP

Models. Our primary analysis is conducted on OLMo-3-7B because it combines performance with full replication resources for detailed analysis. Results for six additional models appear in Appendix A. Inference details are in Appendix B.

Relations. The LRE dataset (Hernandez et al., 2024) contains 47 relations. Our prompt presupposes an entity subject, so we fixed a subject-type filter in advance using the dataset's declared `domain_name` field: the 28 relations with named-entity subjects (*person*, *country*, *name*, *company*, *landmark*, *superhero*, *city*, *pokemon*, *product*, *star*). Excluded are relations over words as words (*verb*, *adjective*, *word*) and over abstracts (*occupation*, *task*, *characteristic*, *degree*), for which `"{} is known for"` is a category error. No other relation was excluded.

Measurement. Both quantities are read off the same prompt, so that they are comparable. Following Hernandez et al. (2024), a relation is presented to the model *in context*: eight (subject, object) examples of that relation are concatenated, one per line, and the query subject is appended without its object, so that the model's next token is its answer. This is what defines "the model's own prediction" for both measures. The subjects of a relation are shuffled once and partitioned into three disjoint sets: eight in-context examples, eight reference subjects from which W and b_β are estimated, and the remainder as scored test subjects.

Faithfulness is then recomputed for all 28 relations under this protocol. Layer and β are chosen on a 6×6 grid consisting of six candidate layers for the subject state $(5, 11, 14, 17, 20, 23)$ crossed with six values of β $(0.5, 1, 1.5, 2, 3, 5)$. Selection is based on the mean over the test subjects. Hernandez et al. (2024) likewise fit both per relation; the six layers span the network at roughly even spacing and the β range brackets the values they report.

The lens scores 11–20 subjects per relation, depending on how many remain once the in-context and reference sets are removed. For the results in §6, the lens and the LRE sample their splits independently, so the particular subjects entering each set differ between the two measurements. Independent splits introduce sampling variation into this comparison. Because the LRE hyperparameters are selected on the scored subjects, its reported faithfulness is an in-sample estimate; these results do not establish performance on a separate held-out evaluation set.

Crucially, the in-context prompt is used only to obtain the *target*; the lens itself is always computed under the neutral prompt of §4.

6 RESULTS

9 <<< hs: fig:main: ideally, all relation points that are part of the discussion (e.g., second half of section6) should be labeled, the same way that country capital and personmother/father are >>>

10 <<< hs: is the labeling of person mother/father correct? i think not: we need two labels pointing to two different points >>>

Figure 1 shows the result. The relation-agnostic score predicts LRE faithfulness at Spearman $\rho = 0.7355$ ($p = 8.24 \times 10^{-6}$).

The correlation is not carried by cardinality. Relations differ greatly in how many distinct objects they have; k, the mean number of subjects per object, ranges from 1.0 to 189. High k should make faithfulness easier, and k is indeed associated with faithfulness on its own, though only weakly ($\rho = 0.355$, $p = 0.064$). But k is essentially uncorrelated with the lens score ($\rho = 0.086$). Removing




Figure 1: LRE faithfulness against the relation-agnostic lens score, 28 relations. The lens sees no relation template, no objects, and no (subject, object) pairs, and uses one fixed layer throughout. Triangles mark the two relations with numeric objects, rescored as described in Appendix D.

k *raises* the correlation to $\rho = 0.757$ ($p = 4.90 \times 10^{-6}$): k and the lens are independent predictors of faithfulness, so removing the variance attributable to k sharpens rather than weakens the lens signal.[1]

Nor by answer frequency. A relation whose answers are frequent tokens might be easy for both measures. We estimate the model's prior over each answer token by averaging its log-probability across ten neutral contexts. This predicts neither faithfulness ($\rho = -0.111$) nor the lens score ($\rho = 0.098$), and removing it leaves the correlation unchanged at 0.755. The correlation is 0.784 with both cardinality and answer frequency removed.

Nor by one domain. Eleven of the 28 relations have *person* subjects, raising the worry that one domain (i.e., one subject type) drives the result. Holding out each subject domain in turn leaves $\rho \in [0.570, 0.700]$, median 0.656.

7 Analysis of the entity lens

7.1 Salience

We test the interpretation of Eq. 5 used by our analysis. Readouts of this kind are normally taken to surface what a model is internally disposed to say (Gurnee et al., 2026), and we have read $\mathrm{EL}(s)$ the same way: as what the subject's representation makes available, before any relation has been named. The account of Figure 1 rests on that reading. If it is right, a relation should be linearly decodable to the extent that its answer is already part of what the subject evokes; that is, the object should be *salient* for the subject. This section performs a sanity check (a check that is external to the lens) on that assumption by measuring salience by the model's own free generation.

For each test subject we greedily generate 90 tokens from each of `"{} is best known for"` and `"Here are some facts about {}. First,"`, and record whether any distinctive word of the gold

[1] All variables here are ordinal, so we work throughout with ranks. To remove the effects of a set of covariates, we rank-transform the lens score, faithfulness, and each covariate; regress the ranked lens score and ranked faithfulness separately on the ranked covariates using ordinary least squares with an intercept; and report the Pearson correlation between the resulting residual vectors. This is the standard partial Spearman correlation, and it asks how much of the lens–faithfulness association remains once everything the covariates can linearly explain about either variable has been removed.

Table 1: Object prominence, measured by the model's own free generation and therefore independently of the lens, against how often the lens surfaces the gold object in its top five. Spearman $\rho = 0.614$ ($p = 0.019$, $n = 14$). See §9.1 for discussion of the outlier star_constellation.

relation	prom.	n	gold∈lens	n
city_in_country	1.00	5	0.65	17
person_plays_pro_sport	0.60	40	0.35	20
star_constellation	0.60	40	0.05	20
country_capital_city	0.50	8	0.56	16
landmark_in_country	0.47	40	0.25	20
product_by_company	0.33	40	0.05	20
person_occupation	0.30	40	0.10	20
country_currency	0.29	14	0.00	20
person_university	0.28	29	0.00	20
country_largest_city	0.25	8	0.25	16
person_father	0.13	39	0.06	18
company_hq	0.12	40	0.00	20
superhero_archnemesis	0.05	39	0.05	19
person_mother	0.03	40	0.00	20

object appears in either continuation.[2] This is a forward pass under different prompts, and involves no Jacobian.

We refer to this rate as the object's *prominence*. Across the 14 relations for which it can be measured it ranges from 1.00 (CITY_IN_COUNTRY) and 0.50 (COUNTRY_CAPITAL_CITY) down to 0.13 (PERSON_FATHER), 0.05 (SUPERHERO_ARCHNEMESIS) and 0.03 (PERSON_MOTHER). It predicts how often the lens surfaces the gold object in its top five: Spearman $\rho = 0.614$ ($p = 0.019$, $n = 14$). Table 1 gives both quantities per relation. The check passes: what the lens surfaces is predicted by a measurement of salience that never consults the lens.

7.2 Reference sets

§4 motivated NEL by the observation that CEL is sensitive to the reference set: if the reference entities s_i share the answer with the subject e, the difference $s_e - s_i$ removes it. We now measure that effect.

PERSON_NATIVE_LANGUAGE is the right place to see it. Of its 100 subjects, 69 are French speakers, and for 65 of those 69 the model's own answer m_e is the single token "French", so the answer is one token and cancellation has somewhere visible to show up. We designate eight French and eight non-French reference entities in advance and remove them from the test set, so that all four reference sets are scored on the *same* 61 French and 23 non-French subjects and composition is the only thing that varies.

Table 2 shows the result. Under CEL, moving from non-French to French reference entities costs 1.10 in median $\log_{10}$ rank, a factor of 13. Under NEL the same four reference sets span 1.71 to 1.81 and nothing happens. Tracking the answer token itself rather than each subject's own target makes the mechanism plain: the rank of "French" rises monotonically with the number of French reference entities, $47 \to 115 \to 665$ for zero, four and eight, and the effect is monotone for 52 of the 61 subjects individually. The control is the last column. *The same eight French reference entities* leave "French" at rank 55 under NEL, its best value for any reference set. The collapse is therefore a property of the subtraction, not of the reference entities.

An example. For Joseph Laniel, whose answer is "French", NEL ranks "French" first. CEL ranks it third with non-French reference entities, and 623rd with French ones, where the top of the readout

[2] Titles, particles and words shared with the subject's own name are excluded, so that *The* Joker is not matched by any occurrence of "the" and *Johann Georg Kant* is not matched by a passage about Immanuel Kant. The lens's own prompt cannot be used here: `"{} is known for"` makes Olmo-3-7B emit a multiple-choice quiz rather than prose, so the object is never named.

Table 2: The reference set's effect on the two lenses, on PERSON_NATIVE_LANGUAGE. All four reference sets are scored on the same 61 French subjects. Left: median $\log_{10}$ rank of the model's own answer m_e. Right: median rank of the token "French" itself. CEL degrades as the reference entities come to share the subject's answer; NEL, which takes no difference, does not.

	median $\log_{10}$ rank of m_e		median rank of "French"	
reference set	CEL	NEL	CEL	NEL
8 non-French	1.62	1.81	47	64
8 from other relations	1.88	1.72	102	70
4 French, 4 non-French	1.93	1.79	115	82
8 French	2.72	1.71	665	55

is "sculpt", "dancing", "singing", "dance", "chore", "piano". The subject, the layer and the prompt are identical in the two cases; only the reference set differs.

The effect reverses. On the 23 non-French subjects the ordering is the other way round: the eight French reference entities are the *best* set (median $\log_{10}$ rank 0.78) and the eight non-French ones the worst (1.97). The same reference set helps or hurts depending on what is being asked, so reference quality is not a property of the set alone.

What is subtracted. CEL is $\mathrm{mean}_i[J_i s_e] - \mathrm{mean}_i[J_i s_i]$, and it is tempting to read the second term as the answer. It is not: decoded over the vocabulary it gives "Cin", "La", "Une", "fils". These are French vocabulary items, not the token "French". This is expected, since $\mathrm{mean}_i[J_i s_i]$ is what the model has loaded about those people under `"{} is known for"`, which is French cultural material rather than an answer to a question about language. The answer is suppressed because the two terms share the French direction, not because the subtracted term is the answer.

Consequence. A reference set of the same type as the subject (§4) does not guarantee that the set is neutral with respect to the relation being read out, and no choice of reference entities can be neutral for every relation at once. This is why we report NEL alongside CEL throughout.

8 OBJECT CARDINALITY

The correlation in Figure 1 is highly significant, but many relations deviate from the trend. We investigate the tails of this distribution, the relations with the largest positive and negative deviations, and find that extreme object cardinality k can partially explain these tails. Concretely, we order the relations by their residual from the least-squares fit in Figure 1; this residual is in units of faithfulness, so $+0.30$ means thirty points more faithful than the lens score predicts.

The largest positive residuals, faithful despite a low lens score, with their cardinality are LANDMARK_ON_CONTINENT ($+0.242$, $k = 189$), NAME_GENDER (-0.374, $k = 9.5$) and PERSON_NATIVE_LANGUAGE ($+0.118$, $k = 30.6$). In each, the LRE chooses among a handful of possible answers, and can be faithful without the answer being salient for any particular subject: no name is chiefly "known for" its gender, but there are only two answers to pick between.

The largest negative residuals, unfaithful despite the lens, are PERSON_FATHER (-0.403), PERSON_MOTHER (-0.330) and COMPANY_CEO (-0.297), all with $k \approx 1$ and answer spaces in the hundreds. For these relations, faithfulness is near its floor due to the difficulty of the task and the details of the representation apparently do not change that.

Our account thus holds in the middle of the cardinality range and degrades at both ends, in opposite directions. Cardinality is the same variable whose removal raises the correlation to 0.757 (§6). Our analysis in this section gives that number an interpretation: k is a source of deviation in the salience account rather than merely a nuisance correlate.

9 FACT-LEVEL ANALYSIS

Linearity emerges as a phenomenon at the relation level, not the fact level; it would not make sense to investigate linearity for the facts of a relation that is not represented linearly. But once there is evidence for at least partial linearity of a relation, we can ask for individual facts how well the entity lens predicts the degree to which they are integrated into the linear structure.

To analyze relations at the fact level, we compute ρ between lens $\log_{10}$ rank and LRE $\log_{10}$ rank for each relation. The values of ρ are in the range [-0.401,0.664] with a median of 0.235. We found that several shortcomings of the experimental setup currently used for investigating relations in LMs that result in these low values. We now analyze these shortcomings and give guidance for future relation datasets that may better support research on how LMs represent facts.

9.1 REFERENCE COMPETITION

The three relations PERSON_UNIVERSITY (ρ=-0.401), PERSON_OCCUPATION (ρ=-0.388) and PERSON_PLAYS_INSTRUMENT (ρ=-0.035) have the lowest correlations. They exemplify the problem of *reference competition*. An example is Rolf Thommessen who is listed as an actor in LRE. The highest ranked token given by the lens is "whistlebl". This indicates that the most prominent entity associated with the last name Thommessen by Olmo-3-7B is Advokatfirmaet Thommessen, a law firm known for their digital whistleblowing tool. One might hope that the first name "Rolf" disambiguates which subject is intended, but apparently this is not the case. In general, the last few tokens seem to dominate which entity is represented and used by the LM. For the actor Barry Sobel, the lens top-ranks "kosher", "Jewish", "Rabbi", correct associations for the Brazilian Rabbi Henry Sobel. For the actress Vondell Darr, the lens top-ranks "criminal", "murders", "felon", plausible associations for the wrongfully convicted Acacia Lyn-Darr. For the actor Simon Gosejohann, the lens top-ranks "Johann", "Hann", "German", suggesting the LM simply uses the string "Johann" as the representation. While we did not conduct an extensive analysis, it is likely that reference competition is a problem for many relations whose subjects are persons. Many of those persons share the properties that result in Barry Sobel, Vondell Darr and Simon Gosejohann being misrepresented by the model.

The relation STAR_CONSTELLATION also suffers from reference competition due to the complex names of many stars. For example, the most prominent associations of the stars "rho01 Cnc" and "Alnair" (tokenized Al-n-air) are "machining", "drilled", "CNC" (Computerized Numerical Control) and "flying", "flown", "Flight", respectively.

9.2 SEMANTICALLY WEAK FIRST TOKENS

PERSON_UNIVERSITY further exemplifies the problem of *semantically weak first tokens*. Many universities have names that start with "University". So the LM learns to predict this common prefix as the target token for many persons. The standard setup is to count such a prediction as correct. But this is not an effective evaluation: The correct generation of "University" is not a reliable indicator of the factual competence of the LM.

The collapse rate is the fraction of a relation's distinct objects that share a first token with another. **6 of 40 relations exceed 25%**, led by PERSON_MOTHER (61%), PERSON_FATHER (58%) and PERSON_UNIVERSITY (45%: 29 of 69 objects begin with UNIVERSITY).

Restricting each relation to objects whose first token identifies them repairs this on the gold side. It is only a partial remedy: faithfulness (which compares the LRE against the *model's* top-1, not gold) is inflated by counting the model's own answer as "faithful". In PERSON_UNIVERSITY, after filtering, the model still answers UNIVERSITY for 7 of 29 subjects and the LRE agrees on every one. A complete fix would condition on the prediction being distinctive.

The direction of the bias differs by relation. Where the collapse is on the gold side it makes faithfulness easier: 41 distinct fathers all count as JOHN. Our PERSON_FATHER figure is therefore an upper bound, and the corrected value is lower still ($0.07 \rightarrow 0.05$). Where the model itself emits the shared token, the collapse manufactures agreement that is not an accurate response at all.

Both LRE and the lens work on the token level, the residual stream vector at the last layer, which is focused on producing the correct next token and may not represent reliable information about the

		subject term			controls	
relation	n	own	foreign	NEL	anchor alone	wrong donor
COUNTRY_CAPITAL_CITY	22	12	12	7	0	0
COUNTRY_LARGEST_CITY	22	12	8	4	0	0
PERSON_PLAYS_POSITION	24	19	21	18	7	6
PERSON_PLAYS_PRO_SPORT	24	22	21	21	6	3

Table 3: Recombining an LRE's anchor with different subject terms, $\beta = 3$. Counts are how often the decoded top-1 is the relation's gold object. *Own* is the unmodified operator; *foreign* uses the paired relation's subject term; *NEL* is the noncontrastive entity lens, which never sees a relation; *anchor alone* drops the subject term; *wrong donor* uses another subject's NEL. The model answers all 22 countries correctly, but the operator itself reproduces only 12 (Appendix E).

tokens to follow. This single-token regime is highly problematic for the standard setup because we are effectively investigating a relation in which all objects have been shortened to their first token. This might be a nonsensical relation even to humans and it is clearly different from the intended relations whose objects are full entity names.

9.3 Towards better fact datasets

Our analysis motivates two requirements for future evaluations. First, answer scoring should distinguish complete objects rather than credit a shared, semantically weak first token. Filtering for identifying first tokens provides one diagnostic, but excludes some relations and does not ensure that the model's own prediction is distinctive. Evaluation methods that score complete answers are therefore needed for relations with unavoidable prefix overlap.

Second, a subject name should refer to the intended entity for the model under study. Dataset construction alone may not ensure this, because different models can resolve the same name differently. Evaluations should examine the entity that a model associates with each subject, document ambiguity, and distinguish errors of subject identification from errors in relational decoding. These are methodological directions motivated by the observed failures, rather than solutions evaluated in this study.

10 What the operator's two terms carry

The LRE of Eq. 2 is the sum of an *anchor* b_β, which does not depend on the subject, and a *subject term* $\beta W s$. The subject term has the form of NEL (Eq. 6), except that its Jacobians are taken under the relation's own prompt. We ask what each term carries by recombining them. If the anchor carries the relation, pairing it with a *foreign* subject term from another relation should still produce this relation's object; and if NEL captures the subject, it should be able to stand in for the subject term.

We use two relation pairs that share their subjects: COUNTRY_CAPITAL_CITY and COUNTRY_LARGEST_CITY over 22 countries whose capital is not their largest city and for which the model answers both relations correctly, and PERSON_PLAYS_POSITION_IN_SPORT and PERSON_PLAYS_PRO_SPORT over 24 athletes. Each subject is read with the others as references, at $\beta = 3$. Appendix E describes the experiments in full.

The anchor carries the relation. A foreign subject term leaves the answer largely intact (Table 3): with the largest-city subject term the capital anchor still names 12 capitals, as many as with its own, and each person anchor keeps 21 of 24 subjects with the other relation's subject term. The anchor alone names no country's capital or largest city, so these hits are composed rather than read off the anchor. Nor do they depend on the particular references: over 500 anchors estimated from references disjoint from the test subjects, the foreign subject term stays on average within one to two subjects of the operator's own on all four relations.

The lens stands in for the subject term, but only moderately. NEL, computed under the neutral prompt with no relation anywhere, recovers the operator for sport (21 against 22) and largely for

position (18 against 19), but for only 7 of the 12 capitals and 4 of the 12 largest cities that the operator itself gets right. What it supplies is subject-specific: another subject's NEL falls to or below the anchor alone. It is also less stable than the foreign subject term. Over the same 500 anchors it ranges from 7 to 20 of 24 for position, and for the country pair neither the anchor's references nor NEL's own references dominate its variance.

11 LIMITATIONS

The study covers only 28 relations with partially small sample size. The relationship is correlational: we show that a relation-agnostic readout predicts LRE faithfulness, not that the representation it reads is what the LRE exploits.

The account has a scope condition we can state but not yet explain (§8). It is weakest where the answer space is very small, since an LRE can then be faithful by elimination rather than by reading anything from the subject, and where the answer space is very large and each answer near-unique, since faithfulness is then close to its floor regardless. We show that these are the two tails of a single variable, but we do not have a principled account of where the boundaries lie, and with 28 relations we cannot fit one.

We also probe salience through a limited set a neutral prompts. That phrasing asks what an entity is *noted* for, which need not coincide with everything its representation carries; attributes such as gender may be well encoded without being something a name is "known for". A different neutral prompt, or an average over several, might track salience more broadly.

Seven of the 28 relations have fewer than ten test items after the in-context and reference subjects are removed, so their faithfulness estimates are coarse (for three of them, quantized to thirds); a rotating-split protocol would sharpen these.

Finally, the diagnostic is defined only for relations whose subjects are entities, which excludes 19 of the dataset's 47 relations.

12 CONCLUSION

Whether a relation is linearly decodable from a language model is substantially predictable without the relation. A Jacobian lens estimated from subject differences under a neutral prompt, at a fixed layer, ranks the model's own answer highly for exactly those relations whose LREs turn out to be faithful.

The reading we favor is that salience is the mechanism rather than a confound: a relation admits a faithful linear operator to the extent that its answer is already part of what the subject's representation makes the model disposed to say. On that view the wide spread of LRE faithfulness across relations is less a fact about the relations than about the entities they are asked about. The exceptions are informative: they fall at the two ends of the answer-space range where faithfulness can be achieved, or prevented, without the subject's representation mattering much either way.

11 <<< hs: do we explain how the subset of facts was selected that the experiments are done for? for example, i think we're only using 100 from person-occupration? if not: add an appendix section on this and refer to it in the text >>>

AI USE STATEMENT

We used generative AI tools for brainstorming, assisting with software code, and initial drafting and rewriting of parts of the manuscript. All AI-assisted code and text were reviewed and verified by the authors, and generated code was tested for correctness. The authors take responsibility for the final content of this work, including all text, claims, results, and artifacts produced with the aid of generative AI.

REPRODUCIBILITY STATEMENT

We provide sufficient details to reproduce all experiments in the main text and appendix, including the datasets, model checkpoints, prompt templates, evaluation procedures, and hyperparameters used throughout. All experiments use publicly available model checkpoints and datasets. We report the procedures used to estimate linear relational embeddings and the contrastive Jacobian lens, as well as the definitions of all faithfulness and ranking metrics. Additional implementation details, robustness analyses, and per-relation results are provided in the appendix. Code for reproducing the experiments and figures will be released upon publication.

REFERENCES

Nora Belrose, Igor Ostrovsky, Lev McKinney, Zach Furman, Logan Smith, Danny Halawi, Stella Biderman, and Jacob Steinhardt. Eliciting latent predictions from transformers with the tuned lens. *arXiv preprint arXiv:2303.08112*, 2023.

Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. Transformer feed-forward layers are key-value memories. In *Proceedings of the 2021 conference on empirical methods in natural language processing*, pp. 5484–5495, 2021.

Mor Geva, Jasmijn Bastings, Katja Filippova, and Amir Globerson. Dissecting recall of factual associations in auto-regressive language models. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 12216–12235, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.751. URL https://aclanthology.org/2023.emnlp-main.751/.

Daniela Gottesman, Alon Gilaie-Dotan, Ido Cohen, Yoav Gur-Arieh, Marius Mosbach, Ori Yoran, and Mor Geva. Lment: A suite for analyzing knowledge in language models from pretraining data to representations. *Transactions of the Association for Computational Linguistics*, 14:1654–1691, 07 2026. ISSN 2307-387X. doi: 10.1162/TACL.a.746. URL https://doi.org/10.1162/TACL.a.746.

Wes Gurnee, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, T. Ben Thompson, David Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey. Verbalizable representations form a global workspace in language models. *Transformer Circuits Thread*, 2026. URL https://transformer-circuits.pub/2026/workspace/index.html.

Evan Hernandez, Arnab Sen Sharma, Tal Haklay, Kevin Meng, Martin Wattenberg, Jacob Andreas, Yonatan Belinkov, and David Bau. Linearity of relation decoding in transformer language models. In *Proceedings of the Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=w7LU2s14kE.

Emanuele Marconato, Sébastien Lachapelle, Sebastian Weichwald, and Luigi Gresele. All or none: Identifiable linear properties of next-token predictors in language modeling. *arXiv preprint arXiv:2410.23501*, 2024. URL https://arxiv.org/abs/2410.23501.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. *Advances in Neural Information Processing Systems*, 35, 2022.

Jack Merullo, Noah A. Smith, Sarah Wiegreffe, and Yanai Elazar. On linear representations and pretraining data frequency in language models. In *Proceedings of the Thirteenth International*

Conference on Learning Representations (ICLR), 2025. URL https://arxiv.org/abs/2504.12459.

Neel Nanda, Senthooran Rajamanoharan, János Kramár, and Rohin Shah. Fact finding: Attempting to reverse-engineer factual recall on the neuron level. Alignment forum, December 2023. URL https://www.alignmentforum.org/posts/iGuwZTHWb6DFY3sKB/fact-finding-attempting-to-reverse-engineer-factual-recall.

Eshaan Nichani, Jason Lee, and Alberto Bietti. Understanding factual recall in transformers via associative memories. In *International Conference on Learning Representations*, volume 2025, pp. 4166–4207, 2025.

Rob nostalgebraist. Interpreting gpt: The logit lens. *Blog Post*, 2020.

Alberto Paccanaro and Geoffrey E. Hinton. Learning distributed representations by mapping concepts and relations into a linear space. In Pat Langley (ed.), *Proceedings of the Seventeenth International Conference on Machine Learning (ICML 2000), Stanford University, Stanford, CA, USA, June 29 - July 2, 2000*, pp. 711–718. Morgan Kaufmann, 2000.

Barak A. Pearlmutter. Fast exact multiplication by the Hessian. *Neural Computation*, 6(1):147–160, 1994.

Shauli Ravfogel, Gilad Yehudai, Joan Bruna, and Alberto Bietti. Geometric factual recall in transformers. *CoRR*, abs/2605.12426, 2026. doi: 10.48550/ARXIV.2605.12426. URL https://doi.org/10.48550/arXiv.2605.12426.

Giovanni Valer, Luigi Gresele, Marco Bronzini, and Emanuele Marconato. Relational linear properties in language models: An empirical investigation. *arXiv preprint arXiv:2605.22532*, 2026. URL https://arxiv.org/abs/2605.22532.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

A BASELINE COMPARISONS

The first two tables report Spearman correlations with LRE faithfulness across the LRE Dataset.

Table 4: **Entity lenses and readout baselines across seven models.** Spearman correlation ρ with LRE faithfulness.

Model	Contrastive entity lens	Noncontrastive entity lens	Logit lens	Differential logit lens	Attribute rate
OLMo 3 7B	0.7355	**0.7650**	0.2056	0.4390	−0.4016
GPT-J 6B	0.4346	0.4196	**0.4669**	0.2020	−0.1035
Mistral 7B	0.6561	**0.6711**	0.6581	0.5186	−0.2202
Gemma 2 9B	**0.6889**	0.6868	0.4728	0.3436	−0.5515
Qwen3 8B Base	0.6647	0.6232	**0.7908**	0.5952	−0.0557
Qwen3.8 27B	0.5539	**0.5717**	0.3404	0.4492	−0.0099
Pythia 6.9B†	0.5027	**0.5063**	−0.2047	0.1845	0.0041

Bold marks the largest point estimate within each model, not a significant difference. All columns use the contrastive entity lens's same evaluation rows, including demonstrations and references, and the same model-specific year exclusions. †Pythia has 2,663 empty filtered prediction sets; Gemma has one. Their attribute rates are assigned zero, retaining every evaluation row.

Readout definitions. For subject state s_e, reference states s_i, and reference Jacobians J_i, the differential and raw Jacobian readouts decode $\mathrm{mean}_i\, J_i(s_e - s_i)$ and $\mathrm{mean}_i\, J_i s_e$, respectively. Logit lens decodes s_e; differential logit lens decodes $s_e - \mathrm{mean}_i\, s_i$. Each relation's score is the negative median $\log_{10}(\mathrm{rank} + 1)$ of the model's answer token.

Attribute rate. Following Geva et al. (2023), we measure overlap between filtered top-50 logit-lens predictions and subject attributes retrieved from Wikipedia. The index uses the union of current test subjects; the source stopword, length, and retrieval filters are retained. Relation scores average the percentage overlap. Undefined rates are handled as noted in the table; matched-row sensitivity results remain in the accompanying data.

Raw Jacobian has a larger point estimate than differential Jacobian in five models. All seven paired 95% relation-bootstrap intervals for their difference include zero; these results do not establish a general advantage for either readout. LRE hyperparameter selection remains in sample.

A.1 OLMo CORPUS-FREQUENCY BASELINES

Table 5: **Frequency baselines for OLMo 3 7B.** Correlations with LRE faithfulness using document counts from OLMo's three published training mixes combined.

Frequency measure	Spearman ρ	p-value
Marginal frequencies		
Subject frequency, c_s	0.1380	0.484
Object frequency, c_o	0.5712	0.001
Co-occurrence		
Joint frequency, c_{so}	0.4568	0.015
Mean of $\log(1 + c_{so})$	0.4191	0.026
$\log(1 + \text{mean}(c_{so}))$	0.4568	0.015
Conditional frequencies		
Forward conditional, $P(o \mid s)$	0.4486	0.017
Reverse conditional, $P(s \mid o)$	-0.4149	0.028
Directional difference, $P(o \mid s) - P(s \mid o)$	0.4826	0.009
Micro-averaged $P(o \mid s)$	0.5504	0.002
Micro-averaged $P(s \mid o)$	-0.1453	0.461

Counts denote binary document presence. Means use the current test rows with both marginals observed; micro averages are ratios of summed counts. The p-values are two-sided and unadjusted.

Counting and aggregation. A document contributes at most one mention per subject/object string. Matching uses normalized literal names with Unicode word boundaries, without alias resolution or a proximity constraint. With subject, object, and joint counts c_s, c_o, and c_{so}, the conditionals are $P(o \mid s) = c_{so}/c_s$ and $P(s \mid o) = c_{so}/c_o$. Macro features average row-level quantities where both marginals are observed. Micro conditionals divide summed joint counts by summed marginals. The log of the mean joint count has the same Spearman correlation as the mean joint count because the transformation is monotonic.

Interpretation and reproducibility. These are exploratory associations. Relations can share subjects and objects, and the reported p-values are unadjusted. Conditional direction also reflects marginal frequency: when $c_{so} > 0$, $P(o \mid s)/P(s \mid o) = c_o/c_s$.

A.2 NEUTRAL-PROMPT VARIATIONS

Table 6 collects the prompt experiments for the differential Jacobian lens. For Qwen3 8B Base, we compare the original prompt with six alternatives and the subsequently measured newline control. The checkpoint, layer 19, reference and test rows, relation-prompt answer tokens, and LRE outcomes are fixed.

Table 6: **Neutral-prompt variations.** Spearman ρ between differential-Jacobian scores and retained LRE faithfulness.

Qwen3 8B Base: prompt wording and prefix

Neutral prompt	ρ
`{s} is known for`	0.268
`{s}`	−0.057
`{s} is`	0.166
`{s} can be described as`	0.372
`Information about {s}:`	0.733
`Facts about {s}:`	0.788
`Entity: {s} is known for`	0.728
`\n{s} is known for`	0.729

B JACOBIAN–VECTOR PRODUCTS

Neither the operator nor the lens ever needs J_i itself, only products $J_i u$: for the lens this is explicit in Eq. 5, and for the LRE it is what the expansion in Eq. 3 buys, since it turns $W = \mathrm{mean}_i\, J_i$ into a sum of such products. We obtain each one by the standard double-backward construction (Pearlmutter, 1994): differentiate $\langle u', f(h)\rangle$ with respect to h with u' held as a free variable, then differentiate the result with respect to u' in the direction u. Each product therefore costs a constant number of forward and backward passes rather than the d_{model} passes a materialized Jacobian would need. The construction requires `float32` and eager attention, as the fused attention kernels are not twice differentiable.

C LAYER SELECTION

Layer 17 is roughly half-way through the network, the region in which such lenses are usable at all (Gurnee et al., 2026), and is the modal best layer for the LRE itself in our sweep (10 of 28 relations; the rest spread over 5, 11, 14, 20 and 23). A single layer is used for *every* relation, without per-relation tuning. However, this does not establish robustness to the layer choice: changing the layer can affect relations differently. A systematic sensitivity analysis is left to future work.

D NUMERIC-OBJECT TOKENIZATION CORRECTION

Both relations with numeric objects (PRESIDENTS_BIRTH_YEAR, PRESIDENTS_ELECTION_YEAR) initially scored faithfulness 1.000. This was spurious. In this tokenizer `" 1743"` segments as `[' ', '174', '3']`: digits never merge with a preceding space. First-token scoring therefore compared the model's top-1 against a bare space token on both sides, and faithfulness 1.000 meant only that the LRE and the model both emit a space.

The fix is to place the space in the prompt, so that the query ends with it and the next token is content. Rescored, the two relations give faithfulness 0.67 and lens scores of -4.24 and -4.17; the model does predict the year correctly once the space is consumed. Including the uncorrected values would have depressed the reported correlation from 0.658 to 0.427.

E RECOMBINING ANCHORS AND SUBJECT TERMS

This appendix describes the experiments of §10 in full.

The decomposition. We write the LRE in the form of Eq. 2, $\beta W s + b_\beta$, and call b_β the *anchor* and $\beta W s = \beta\, \mathrm{mean}_i\, J_i s$ the *subject term*. The anchor is fixed by the reference subjects alone; the subject term is NEL (Eq. 6) with the Jacobians taken under the relation's prompt. Their sum is the operator exactly, so the *own* arm is the unmodified LRE. The *foreign* arm replaces $\beta W_r s$ by $\beta W_{r'} s$, the paired relation's subject term, and keeps b^r_β. Because the constant $\mathrm{mean}_i\, J_i s_i$ stays inside the anchor b_β, a foreign subject term imports the other relation's W and nothing else. The *NEL* arm replaces the subject term by $\beta\,\mathrm{NEL}(e)$ under the neutral prompt; *anchor alone* is b_β; the *wrong donor* is $b_\beta + \beta\,\mathrm{NEL}(e')$ for a different subject e'.

Choice of relation pairs. A term can be swapped with nothing else changing only if the two relations share their subjects, and a substitute can only be measured against an operator that produces the answer in the first place. In the benchmark two pairs meet both conditions: COUNTRY_CAPITAL_CITY with COUNTRY_LARGEST_CITY, and PERSON_PLAYS_POSITION_IN_SPORT with PERSON_PLAYS_PRO_SPORT, over the 24 athletes the two share. Two further pairs fail the second condition. COUNTRY_CURRENCY shares its countries with the other country relations, but its own operator recovers the currency for only 6 of 12 countries at $\beta = 3$, 2 at $\beta = 5$ and none at $\beta = 10$; where an operator is this weak there is nothing for a substitute to reproduce. PERSON_FATHER and PERSON_MOTHER would be the strongest test: they share 748 subjects and have answers of the same kind, so the two relations cannot be told apart by the kind of answer. But their faithfulness is 0.06 and 0.12, and the operators essentially never produce the gold object.

Country subjects. A country tests the swap only if its capital differs from its largest city; otherwise one answer satisfies both relations and a hit cannot say which relation won. The benchmark has 9 such countries among the 18 that the two relations share. We extended the set from the list of sovereign states whose capital is not their largest city.[3] Of its 37 states we excluded seven whose capital or largest city the list marks as contested: Israel and Palestine (limited recognition), Taiwan (sovereignty), Nauru (de facto capital only), Bolivia (La Paz is the seat of government), South Africa (three capitals) and Equatorial Guinea (capital in transition). Of the 31 remaining we kept those the model answers correctly for *both* relations under the prompts used here, scoring the model's greedy continuation rather than its first token, with diacritics folded. All 9 benchmark countries and 13 of the 22 added ones pass, giving 22: Australia, Belize, Benin, Brazil, Cameroon, Canada, China, India, Ivory Coast, Kazakhstan, Morocco, Myanmar, New Zealand, Nigeria, Pakistan, Palau, Switzerland, Tanzania, Turkey, the United Arab Emirates, the United States and Vietnam. Every rejected country is one for which the model gives the *same* city for both questions: the capital for the largest city (Ecuador, Gambia, Liechtenstein, Malta, Micronesia, the Philippines, San Marino, Trinidad and Tobago), or the largest city for the capital (Burundi). The filter therefore removes exactly the countries on which the model does not distinguish the two relations.

Protocol. All states are read at layer 17. Each relation's prompt is its first template with eight in-context demonstrations drawn from its own samples outside the candidate set, so no test subject appears in any prompt. Each test subject is read with the remaining test subjects as references, for the operators and for NEL alike. We fix $\beta = 3$. It was chosen by inspecting an earlier version of this analysis on the same 24 athletes and on 12 countries, 7 of which are among the 22, so it is not independent of the evaluation; it is not re-tuned here. At this value the subject term is smaller than the anchor, $\beta\|Ws\|/\|b_\beta\| \approx 0.8$ for the country relations and 0.4–0.6 for the person relations. A hit is a decoded top-1 equal to the first token of the gold object; since the model answers every test country correctly, gold and model answer coincide for the country pair.

12 <<< claude: Sensitivity to β has not yet been re-run for this form of the decomposition. >>>

Full results. Table 7 adds one arm to Table 3: a subject term estimated under the prompt `"The official currency of {} is the"`, which shares nothing with either country relation. Conditional on the operator being right, the foreign subject term preserves the answer for 11 of 12 capitals and 8 of 12 largest cities, NEL for 7 of 12 and 4 of 12, and the currency subject term for 6 of 12 and 5 of 12.

relation	n	own	foreign	NEL	currency	anchor alone	wrong donor
COUNTRY_CAPITAL_CITY	22	12	12	7	6	0	0
COUNTRY_LARGEST_CITY	22	12	8	4	5	0	0
PERSON_PLAYS_POSITION	24	19	21	18	–	7	6
PERSON_PLAYS_PRO_SPORT	24	22	21	21	–	6	3

Table 7: All arms, $\beta = 3$, each subject read with the others as references. *Currency*: a subject term estimated under the official-currency prompt, which shares nothing with either country relation.

Where the operator fails. Although the model answers all 22 countries correctly, the operator reproduces only 12 per relation. It does much better on the benchmark's nine (7 capitals, 8 largest cities) than on the 13 added countries (5 and 5), which are rarer in text. On those it fails in recognizable ways: it echoes the country's own name (Kazakhstan, Tanzania, Vietnam), names a famous associated city (Paris for Ivory Coast and Morocco, Geneva for Switzerland), or produces a degenerate token. This is consistent with linear structure weakening for entities that are rarer in pretraining (Merullo et al., 2025).

Dependence on the reference sets. In the leave-one-out design above the references are the other test subjects, so they barely vary. To measure how much the results depend on them we held every subject term fixed and drew the *anchor's* eight references at random, 500 times, from subjects outside

[3] `https://en.wikipedia.org/wiki/List_of_countries_whose_capital_is_not_their_largest_city`, retrieved 2026-09-24.

the test set and outside every demonstration: 16 countries, and a fixed random 150 of the 1,206 eligible athletes in the two sport relations. Table 8 gives the result. The operator and the foreign subject term barely move; NEL is the arm that depends on the anchor, most for position, whose worst anchor brings it down to the anchor-alone level.

arm	capital (22)	largest (22)	position (24)	sport (24)
own	10.7 (10–14)	11.4 (10–12)	18.3 (17–20)	22.0 (21–23)
foreign	9.7 (9–11)	9.3 (8–10)	17.3 (15–21)	20.4 (16–23)
NEL	5.2 (1–8)	4.7 (4–5)	14.7 (7–20)	21.5 (16–24)
anchor alone	0.0 (0–1)	0.0 (0–0)	7.0 (7–7)	4.5 (1–7)

Table 8: Mean (range) hits over 500 anchors, each estimated from eight references drawn from outside the test set; subject terms fixed.

Part of the spread for position is composition. The athlete pool has fewer baseball players and more hockey players than the test set, and an anchor with more soccer players gives fewer position hits (Spearman $\rho = -0.31$ across anchors), plausibly because the anchor's typical position leans toward soccer's.

For the country pair we also varied the two reference sets jointly: 40 anchors crossed with 40 sets of references for NEL, drawn from the 30 countries outside the test set. Of the variance in NEL's hits, the anchor's references account for 36% (capital) and 26% (largest city), NEL's references for 38% and 42%, and their interaction for the rest. Neither source dominates.

Scoring. Hits compare the first token of the decoded output with the first token of the gold object. Three cases in the country pair are affected: the model writes São Paulo as "Sao", a different first token, and the gold "New Delhi" begins with "New", so the answer "Delhi" scores as a miss; conversely the first token of Ngerulmud, Palau's capital, is the single letter "N", so a bare "N" scores as a hit. In the own column these roughly cancel. Scoring the full continuation would remove all three.

F ALL RELATIONS

Table 9 gives faithfulness and the lens score for every relation in the study. Table 1 gives object prominence and the lens's top-five hit rate for the 14 relations on which prominence can be measured (Section 8).

G THE ANCHORED CONTRASTIVE JACOBIAN LENS

Here we report on an experiment with an "anchored" contrastive Jacobian lens rather than the non-anchored Jacobian lens defined in Eq. 5. Keeping the anchor requires choosing how to weight the anchor and subject term, which is what β does in Eq. 3.

In sample such a β slightly outperforms dropping the anchor, but the curve is flat across a wide range of β and the advantage does not survive selection: choosing β on 15 relations and evaluating on the remaining 10, across 2,000 random splits, beats the anchor-free readout in only 30% of them. We therefore drop the anchor, which leaves a readout with no hyperparameter at all. The decoder normalizes, so once the anchor is gone, scaling cannot change a ranking and β has nothing left to do. This gives the *contrastive Jacobian lens* that we defined in Eq. 5.

In summary, a single β shared by every relation would be a legitimate option, adding nothing relation-specific, but it turns out to have no advantage compared to the simpler form we adopted.

Table 9: All 28 relations, sorted by LRE faithfulness. k is the mean number of subjects per distinct object; A_r is the relation-agnostic lens score, higher meaning closer agreement with the model. †rescored for the numeric-object artifact (Appendix D); *fewer than ten test items, so faithfulness is coarsely quantized.

relation	k	faith.	A_r
country_language*	1.7	1.00	-1.22
country_largest_city*	1.0	0.92	-0.81
landmark_on_continent	189.4	0.92	-2.43
person_native_language	30.6	0.92	-1.69
name_birthplace	3.9	0.97	-1.32
name_religion	6.2	0.97	-1.40
person_plays_pro_sport	63.6	0.95	-1.23
person_plays_instrument	85.5	0.89	-1.72
landmark_in_country	9.2	0.80	-1.69
city_in_country	1.3	0.89	-0.48
person_occupation	26.5	0.71	-2.74
country_capital_city*	1.0	0.88	-0.85
name_gender*	9.5	0.53	-1.04
presidents_birth_year†	1.3	0.74	-4.44
presidents_election_year†	1.1	0.79	-3.45
product_by_company	17.4	0.68	-1.88
person_plays_position_in_sport	68.0	0.61	-3.64
person_band_lead_singer*	1.0	0.86	-1.49
person_university	1.3	0.59	-4.38
company_hq	4.1	0.54	-4.23
superhero_person	1.0	0.50	-2.62
star_constellation	11.7	0.47	-3.50
pokemon_evolutions	1.0	0.32	-3.45
country_currency	1.3	0.40	-4.49
superhero_archnemesis	1.1	0.30	-3.90
person_father	1.0	0.07	-3.71
company_ceo	1.0	0.05	-4.50
person_mother	1.0	0.07	-4.18