

CityTech TTP Summer Bootcamp

JavaScript, TypeScript, and React

2026-06-09

Agenda

1. Review
2. Follow-Ups
3. JavaScript and TypeScript
4. Code Along: Imports and Hierarchy
5. JSON, Objects, and Faker
6. DevTools

Review

What are the most important things you remember from yesterday?

Follow Up: GitHub Authentication

GitHub no longer accepts your **account password** for Git operations — you must use **token-based auth** (an SSH key or a personal access token).

- Why: passwords get reused and phished; **tokens are scoped, revocable, and safer**
- This is why we set up an **SSH key** in Week 1

Read more: <https://github.blog/security/application-security/token-authentication-requirements-for-git-operations/>

Are You on Token Auth?

Check how your repo connects to GitHub — look at the **origin** remote:

```
git remote -v
```

- `git@github.com:...` → **SSH** (uses your SSH key) ✓ — what we set up
- `https://github.com/...` → **HTTPS** (needs a personal access token)

Switching the Remote URL

Point `origin` at the other protocol if you need to:

```
# HTTPS → SSH
git remote set-url origin git@github.com:OWNER/REPO.git

# SSH → HTTPS
git remote set-url origin https://github.com/OWNER/REPO.git
```

Confirm with `git remote show origin`.

Follow Up: More React Resources

The **official** React docs — authoritative, but technical:

- **Learn React** — <https://react.dev/learn>
- **API Reference** — <https://react.dev/reference/react>

Friendlier, still reliable:

- **The Odin Project** — <https://www.theodinproject.com>
- **Scrimba** — <https://scrimba.com>
- **freeCodeCamp** — <https://www.freecodecamp.org>

Follow Up: Handling Form Data

- The example repo's input-reading code is **just okay** — fine for now
- In practice, I usually reach for **React Hook Form** to handle input, **sanitation**, and **validation**
- We'll cover that later

Intro to JavaScript

JavaScript (JS) is the programming language of the web — it runs in every browser and adds **behavior** to a page.

- Respond to clicks, update content, fetch data
- Runs in the browser (and on servers via Node)

JavaScript Everywhere

Thanks to **Node.js** — a runtime that runs JavaScript outside the browser — one language spans the whole stack:

- **Frontend** — in the browser (React, etc.)
- **Backend** — servers and APIs (Node.js, Express)
- **Desktop** — Electron (VS Code, Slack)
- **Mobile** — React Native

This is what makes **full-stack development** in a single language possible. (Code that runs on both client and server is called **isomorphic / universal JavaScript**.)

Intro to TypeScript

TypeScript (TS) is JavaScript **plus types** — it's built **on top of** JavaScript and compiles down to plain JS.

- JavaScript is **dynamically typed** — types are only checked as it runs
- TypeScript adds **static types** — mistakes are caught *before* it runs
- **Any valid JavaScript is valid TypeScript** — use pure JS, or mix JS and TS freely
- The browser never runs TS directly; it's compiled to JavaScript first

add — JavaScript vs. TypeScript

```
// JavaScript
function add(a, b) {
  return a + b;
}
```

```
// TypeScript
function add(a: number, b: number): number {
  return a + b;
}
```

- **Dynamic typing (JS)** — `a` and `b` can be anything; types are checked only when it runs, so a bad type fails at runtime
- **Static typing (TS)** — `a` and `b` are declared as `number`; a wrong type is caught as *you write*, before it runs

JavaScript and TypeScript References

- **MDN — JavaScript** (the JS reference)
<https://developer.mozilla.org/en-US/docs/Web/JavaScript>
- **javascript.info** (modern JS tutorial)
<https://javascript.info/>
- **TypeScript Handbook** (official docs)
<https://www.typescriptlang.org/docs/>

Code Along

Follow along **first** — we may be in slightly **different project states**, so let's stay in sync before you run ahead.

Import Statements

`import` pulls code and assets into a file:

```
import { useState } from "react"; // named import from a package
import "./styles.css";           // import a static file (CSS)
```

- **Named import** — `{ useState }` grabs a specific export from a package
- **Static file import** — e.g. a CSS file; the bundler includes it in the build

Relative vs. Absolute Paths


- **Relative** — from the current file: `./Button` , `../utils/format`
- **Absolute** — from a package or a configured root: `react` , `@/components/Button`
- **Prefer relative paths for now** — simpler, with no extra setup

Components Form a Hierarchy

Your app is a **tree** of components. What you import **high up** flows **down** to everything beneath it.

- Import a **CSS** file near the top (e.g. in `App`) and its styles apply across the whole tree
- (diagram on the next slide)

How a Top-Level Import Propagates



`App` imports global `styles.css`; `MessageList` imports a smaller-scoped CSS that only affects its own subtree.

Continue Coding

Keep working on your dummy chat app.

- What else do you think it needs?
- Can you think of a way to **simulate a person chatting back**?
- Capture your thoughts in a **design doc** — or at least a **TODO.md** file

Design Docs and TODO Files

- A **design doc** is a short written plan — *what* you're building, *why*, and *how* (approach, structure, open questions) — written as you design, before you write much code
- A **TODO.md** is a simple running checklist of tasks and ideas, kept in the repo
- Both make your thinking visible, keep you organized, and look great on your GitHub
- On a **team**, they're how everyone stays **in sync** — a shared plan and a shared to-do list

JavaScript Objects

A JS **object** groups related data as **key–value pairs**.

```
const user = {  
  name: "Maya",  
  age: 25,  
  isAdmin: false,  
};  
user.name; // "Maya"
```

- Keys are names; values can be any type — even other objects or arrays
- The core way to model "a thing" in JavaScript

JSON

JSON = **J**ava**S**cript **O**bject **N**otation — a text format for data, modeled on JS objects.

- The common language of **APIs** and config files — data sent as plain text
- Like a JS object, but keys and strings use **double quotes**; no functions or comments

```
{  
  "name": "Maya",  
  "age": 25,  
  "isAdmin": false  
}
```

Faker Libraries

Faker libraries generate realistic **fake data** — names, emails, dates, sentences, avatars.

- Perfect for **seeding** a UI before a real backend exists (e.g. your fake chatroom)
- Test with believable data instead of "test test test"

Install it:

```
yarn add @faker-js/faker
```

Then use it:

```
import { faker } from "@faker-js/faker";  
faker.person.fullName(); // "Maya Johnson"  
faker.lorem.sentence();  // "Quasi aut sint..."
```

Live Debugging with DevTools

Your browser's **DevTools** (Web Inspector) let you debug a running page. Open with **F12** or right-click → **Inspect**.

- **Elements** — inspect and live-edit the HTML and CSS
- **Console** — run JS, read logs and errors
- **Network** — watch requests and responses
- **Sources** — set **breakpoints** and step through code line by line