

Ian Escoe
COMP3310
Fall 2026
Assignment 1

Browser window showing the "Ian Profile App" running on localhost:61804. The app displays a "Navigation Menu" with items "My Hobbies" and "Favorite Pics".

The browser's developer tools are open, showing the "Elements" panel with the following HTML structure:

```
<!DOCTYPE html>
<html lang="en-US">
  <head>
  </head>
  <body f1t-embedding="full-page" f1t-renderer="canvaskit" f1t-build-mode="debug"
    spellcheck="false" style="position: fixed; inset: 0px; overflow: hidden; padding:
    g: 0px; margin: 0px; user-select: none; touch-action: none;" == $0
    <f1t-semantic-placeholder role="button" aria-live="polite" tabindex="0" aria-
    label="Enable accessibility" style="position: absolute; left: -1px; top: -1px;
    width: 1px; height: 1px;"></f1t-semantic-placeholder>
    <!--
      You can customize the "flutter_bootstrap.js" script.
      This is useful to provide a custom configuration to the Flutter loader
      or to give the user feedback during the initialization process.

      For more details:
      * https://docs.flutter.dev/platform-integration/web/initialization
    -->
    <script src="flutter_bootstrap.js" async></script>
    <p aria-hidden="true" style="position: fixed; bottom: 100%; visibility: hidde
    n; opacity: 0; pointer-events: none; width: auto; height: auto; white-space: n
    owrap; line-height: 100px; letter-spacing: 100px; word-spacing: 100px; margin:
    0px 0px 100px;">flutter typography measurement</p>
    <f1t-announcement-host>
    <flutter-view f1t-view-id="0" tabindex="0" style="position: absolute; inset:
    0px; width: 167px; height: 415px;">
  </body>
</html>
```

The "Styles" panel shows the default user agent styles for the body element:

```
body {
  display: block;
  margin: 0px;
}
```

A box model diagram is displayed, showing the dimensions of the body element and its nested elements. The diagram includes labels for position, margin, border, padding, and the content area (334x830).

lan Profile App

localhost:61804

Dimensions: Re 334 x 830 Fit Nc 'St'

My Hobbies

1 Making Music

2 Playing Video Games

3 Home Projects

4 Swimming

5 Traveling

<!DOCTYPE html>

<html lang="en-US">

<head>

</head>

<body f1t-embedding="full-page" f1t-renderer="canvaskit" f1t-build-mode="debug" spellcheck="false" style="position: fixed; inset: 0px; overflow: hidden; padding: 0px; margin: 0px; user-select: none; touch-action: none;" == \$0

<f1t-semantic-placeholder role="button" aria-live="polite" tabindex="0" aria-label="Enable accessibility" style="position: absolute; left: -1px; top: -1px; width: 1px; height: 1px;"></f1t-semantic-placeholder>

<!--

You can customize the "flutter_bootstrap.js" script.

This is useful to provide a custom configuration to the Flutter loader or to give the user feedback during the initialization process.

For more details:

* https://docs.flutter.dev/platform-integration/web/initialization

-->

<script src="flutter_bootstrap.js" async></script>

<p aria-hidden="true" style="position: fixed; bottom: 100%; visibility: hidden; opacity: 0; pointer-events: none; width: auto; height: auto; white-space: nowrap; line-height: 100px; letter-spacing: 100px; word-spacing: 100px; margin: 0px 0px 100px 0px;">flutter typography measurement</p>

<f1t-announcement-host>

</f1t-announcement-host>

<flutter-view f1t-view-id="0" tabindex="0" style="position: absolute; inset: 0px; width: 334px; height: 830px;">

</flutter-view>

</body>

</html>

html body

Styles Computed Layout Event Listeners DOM breakpoints Properties

Filter

element.style {

position: fixed;

inset: 0px;

overflow: hidden;

padding: 0px;

margin: 0px;

user-select: none;

touch-action: none;

}

body {

display: block;

margin: 0px;

}

position 0

margin 0

border 0

Ian Profile App

localhost:61804

Dimensions: Re 334 x 830 Fit Nc 'S: ' :>

← Favorite Pics

Picture 1

Picture 2

Picture 3

Picture 4

<!DOCTYPE html>
<html lang="en-US">
 <head>
 <body f1t-embedding="full-page" f1t-renderer="canvaskit" f1t-build-mode="debug" spellcheck="false" style="position: fixed; inset: 0px; overflow: hidden; padding: 0px; margin: 0px; user-select: none; touch-action: none;" == \$0
 <f1t-semantic<placeholder role="button" aria-live="polite" tabindex="0" aria-label="Enable accessibility" style="position: absolute; left: -1px; top: -1px; width: 1px; height: 1px;"></f1t-semantic<placeholder>
 <!--
 You can customize the "flutter_bootstrap.js" script.
 This is useful to provide a custom configuration to the Flutter loader or to give the user feedback during the initialization process.

 For more details:
 * https://docs.flutter.dev/platform-integration/web/initialization
 -->
 <script src="flutter_bootstrap.js" async></script>
 <p aria-hidden="true" style="position: fixed; bottom: 100%; visibility: hidden; opacity: 0; pointer-events: none; width: auto; height: auto; white-space: nowrap; line-height: 100px; letter-spacing: 100px; word-spacing: 100px; margin: 0px 0px 100px 0px;">Flutter typography measurement</p>
 <f1t-announcement-host>
 <flutter-view f1t-view-id="0" tabindex="0" style="position: absolute; inset: 0px; width: 334px; height: 830px;">
 </body>
</html>

html body

Styles Computed Layout Event Listeners DOM breakpoints Properties >>

Filter (*) show .cls + -

element.style {
 position: fixed;
 inset: 0px;
 overflow: hidden;
 padding: 0px;
 margin: 0px;
 user-select: none;
 touch-action: none;
}

body {
 display: block;
 margin: 0px;
}

position 0
margin 0
border 0

