

## [GETNET] – Configurar Monitoria

Máquinas:

Primary:

GNCASNPL08358 / GNCASNPL08361 – RAC Norte

Standby:

GNCASSPL08359 / GNCASSPL08360 – RAC Sul

- Criação dos Scripts

scripts: getm\_ora\_nodo\_db1.sh, getm\_ora\_monitora\_goldengate.sh, getm\_ora\_database\_db1.sh e getm\_ora\_asmfree\_v5.2.sh

Atenção: Alterar Script para o respectivo host

### 1. getm\_ora\_nodo\_db1.sh

```
su - oracle
cd bin/
ll
vi getm_ora_nodo_db1.sh

#!/bin/bash

geralog ()
{
    echo `date +"%y_%m_%d %H:%M:%S"` -> "$1 >> $log"
}

echofunc ()
{
    echo $1
}

geralog2 ()
{
    while read linfile; do
        geralog "$linfile"
    done < $tmp
}

echofunc2 ()
{
    while read linfile; do
        echofunc "$linfile"
    done < $tmp
}

#####
# Parametros configuraveis
#####

par_db=nodo_db1
par_home=/home/oracle
par_home_asm=/home/grid
par_num_porta=1521
par_qtd_porta=1
par_db_profile=db_profile
par_asm_profile=grid_profile
par_host_name=`hostname`
par_owner_encrypt=""
par_table_encrypt=""
par_column_encrypt=""
par_backup_rman_full="/u02/scripts/backup/rman"
par_backup_rman_arch="/u02/scripts/backup/rman"
par_alert_db="/u01/app/oracle_19c/diag/rdbms/prmctg/PRMCTG2/trace"
par_alert_crs="/u01/app/grid_19c/diag/crs/gncasnpl08361/crs/trace"
par_alert_asm="/u01/app/grid_19c/diag/asm/+asm/+ASM1/trace/"
```

```

par_gcagent_home=""
par_spfile=+DATA
par_standby="30"

source /home/oracle/db_profile
#####

#####

par1=$1

mkdir -p $par_home/bin/logs
mkdir -p $par_home/bin/tmp
log=$par_home/bin/logs/getm_`date +%Y_%m_%d`.log
tmp=/tmp/getm_`hostname`_`date +%Y_%m_%d_%H_%M_%N`_$_par_db.tmp

par1=ORA_INSTDB
if [ "$par1" = "ORA_INSTDB" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

qt_pmon=`ps -ef | grep ora_pmon_${ORACLE_SID} | grep -vw grep | wc -l`
qt_smon=`ps -ef | grep ora_smon_${ORACLE_SID} | grep -vw grep | wc -l`

if [ $qt_pmon -lt 1 -o $qt_smon -lt 1 ]; then
lin="ORA_INSTDB|1|Instancia ${ORACLE_SID} do servidor $par_host_name esta DOWN|NOK"
echofunc "$lin"
gerallog "$lin"
else
lin="ORA_INSTDB|1|OK|OK"
echofunc "$lin"
gerallog "$lin"
fi
else
lin="ORA_INSTDB|1|Nao configurado|OK"
echofunc "$lin"
gerallog "$lin"
fi
fi

#####

par1=ORA_LSNR
if [ "$par1" = "ORA_LSNR" ]; then
if [ "$par_num_porta" != "" -a "$par_qtd_porta" != "" ]; then
qt_lsnr=`ps -ef | grep tnslsnr | grep -vw grep | wc -l`
qt_port=`netstat -na | grep $par_num_porta | grep LISTEN | grep -vw grep | wc -l`

if [ $qt_lsnr -lt 1 -o $qt_port -lt $par_qtd_porta ]; then
lin="ORA_LSNR|1|Listener do servidor $par_host_name esta DOWN|NOK"
echofunc "$lin"
gerallog "$lin"
else
lin="ORA_LSNR|1|OK|OK"
echofunc "$lin"
gerallog "$lin"
fi
else
lin="ORA_LSNR|1|Nao configurado|OK"
echofunc "$lin"
gerallog "$lin"
fi
fi

#####

par1=ORA_WALL
if [ "$par1" = "ORA_WALL" ]; then
if [ "$par_db_profile" != "" ]; then

```

```

source $par_home/$par_db_profile

if [ "$par_owner_encrypt" != "" -a "$par_table_encrypt" != "" -a "$par_column_encrypt" != "" ]; then
$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
    v_encrypt $par_owner_encrypt.$par_table_encrypt.$par_column_encrypt%type ;
begin
    select $par_column_encrypt into v_encrypt from $par_owner_encrypt.$par_table_encrypt where rownum < 2;
    dbms_output.put_line('ORA_WALL|1|OK|OK');
exception
    when others then
        dbms_output.put_line('ORA_WALL|1|Wallet do banco $ORACLE_SID do servidor $par_host_name esta fechado|NOK');
end;
/
EOF
else
    echo "ORA_WALL|1|Sem encryptacao|OK" > $tmp
fi
else
    echo "ORA_WALL|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

par1=ORA_RMANFULL
if [ "$par1" = "ORA_RMANFULL" ]; then
if [ "$par_backup_rman_full" != "" ]; then

source $par_home/$par_db_profile

#logrman=`ls -1tr $par_backup_rman_full/bkp*.log`
logrman=`ls -1tr $par_backup_rman_full/logs/RMAN_$ORACLE_SID_INC0*.log |head -1`
errorman=`grep "RMAN-" $logrman | grep -vw "RMAN-08137" | wc -l`
erroora=`grep "ORA-" $logrman | wc -l`

if [ $errorman -gt 0 -o $erroora -gt 0 ]; then
    lin="ORA_RMANFULL|1|Erro no backup full do banco $ORACLE_SID no servidor $par_host_name|NOK"
    echofunc "$lin"
    gerallog "$lin"
else
    lin="ORA_RMANFULL|1|OK|OK"
    echofunc "$lin"
    gerallog "$lin"
fi
else
    lin="ORA_RMANFULL|1|Nao configurado|OK"
    echofunc "$lin"
    gerallog "$lin"
fi
fi

#####

par1=ORA_RMANARCH
if [ "$par1" = "ORA_RMANARCH" ]; then
if [ "$par_backup_rman_arch" != "" ]; then

source $par_home/$par_db_profile

#logrman=`ls -1tr $par_backup_rman_arch/bkp*.log`
logrman=`ls -1tr $par_backup_rman_arch/logs/RMAN_$ORACLE_SID_ARCH*.log |head -1`

```

```

errorman=`grep "RMAN-" $logrman | grep -vw "RMAN-08137" | wc -l`
erroora=`grep "ORA-" $logrman | wc -l`

if [ $errorman -gt 0 -o $erroora -gt 0 ]; then
    lin="ORA_RMANARCH|3|Erro no backup transacional do banco $ORACLE_SID no servidor $par_host_name|NOK"
    echofunc "$lin"
    geralog "$lin"
else
    lin="ORA_RMANARCH|3|OK|OK"
    echofunc "$lin"
    geralog "$lin"
fi
else
    lin="ORA_RMANARCH|3|Nao configurado|OK"
    echofunc "$lin"
    geralog "$lin"
fi
fi

#####

par1=ORA_LOGCRS
if [ "$par1" = "ORA_LOGCRS" ]; then
if [ "$par_alert_crs" != "" ]; then
if [ ! -f $par_home/bin/tmp/alertcrs_$par_db.tmp ]; then
    echo 0 > $par_home/bin/tmp/alertcrs_$par_db.tmp
fi
alertfile=`ls -ltr $par_alert_crs/alert*.log`
ultlntmp=`cat $par_home/bin/tmp/alertcrs_$par_db.tmp`
ultlinalert=`wc -l $alertfile | tr -s ' ' | cut -d ' ' -f1`
if [ $ultlntmp -gt $ultlinalert ]; then
    echo 0 > $par_home/bin/tmp/alertcrs_$par_db.tmp
    ultlntmp=0
fi
let gaplin=$ultlinalert-$ultlntmp
echo $ultlinalert > $par_home/bin/tmp/alertcrs_$par_db.tmp

#gaplin=$ultlinalert #instrucao para varrer todo o log de forma forçada
gaplin=`cat $par_alert_crs/alert*.log | wc -c` #instrucao para varrer todo o log de forma forçada

errocrs=`head -n $gaplin $alertfile | grep "CRS-" | grep -vw "CRS-1612" | grep -vw "CRS-1611" | grep -vw "CRS-1719" | wc -l`

if [ $errocrs -gt 0 ]; then
    lin="ORA_LOGCRS|1|Erro no log do cluster do banco $ORACLE_SID no servidor $par_host_name|NOK"
    echofunc "$lin"
    geralog "$lin"
else
    lin="ORA_LOGCRS|1|OK|OK"
    echofunc "$lin"
    geralog "$lin"
fi
else
    lin="ORA_LOGCRS|1|Nao configurado|OK"
    echofunc "$lin"
    geralog "$lin"
fi
fi

#####

par1=ORA_LOGDB
if [ "$par1" = "ORA_LOGDB" ]; then
if [ "$par_alert_db" != "" ]; then

source $par_home/$par_db_profile

if [ ! -f $par_home/bin/tmp/alertdb_$par_db.tmp ]; then
    echo 0 > $par_home/bin/tmp/alertdb_$par_db.tmp
fi

```

```

alertfile=`ls -1tr $par_alert_db/alert*.log`
ultlintmp=`cat $par_home/bin/tmp/alertdb_$par_db.tmp`
ultlinalert=`wc -l $alertfile | tr -s ' ' | cut -d' ' -f1`
if [ $ultlintmp -gt $ultlinalert ]; then
    echo 0 > $par_home/bin/tmp/alertdb_$par_db.tmp
    ultlintmp=0
fi
let gaplin=$ultlinalert-$ultlintmp
echo $ultlinalert > $par_home/bin/tmp/alertdb_$par_db.tmp

gaplin=$ultlinalert  #instrucao para varrer todo o log de forma forcada

#errocrs=`tail -n$gaplin $alertfile | grep "ORA-" | grep -vw "ORA-00060" | grep -vw "ORA-2396" | grep -vw "ORA-1652" | grep -vw "ORA-16040" | gr
ep -vw "ORA-28" | grep -vw "ORA-03135" | grep -vw "ORA-16055" | grep -vw "ORA-16401" | grep -vw "ORA-3136" | wc -l`
errocrs=`cat $alertfile | grep "ORA-" | grep -vw "ORA-00060" | grep -vw "ORA-2396" | grep -vw "ORA-1652" | grep -vw "ORA-16040" | grep -vw "OR
A-28" | grep -vw "ORA-03135" | grep -vw "ORA-16055" | grep -vw "ORA-16401" | grep -vw "ORA-3136" | grep -vw "ORA-609" | grep -vw "ORA-015
55" | wc -l`

if [ $errocrs -gt 0 ]; then
    lin="ORA_LOGDB|1|Erro no log do database do banco $ORACLE_SID no servidor $par_host_name|NOK"
    echofunc "$lin"
    geraldlog "$lin"
else
    lin="ORA_LOGDB|1|OK|OK"
    echofunc "$lin"
    geraldlog "$lin"
fi
else
    lin="ORA_LOGDB|1|Nao configurado|OK"
    echofunc "$lin"
    geraldlog "$lin"
fi
fi

#####

par1=ORA_LOGASM
if [ "$par1" = "ORA_LOGASM" ]; then
if [ "$par_alert_asm" != "" ]; then

source $par_home_asm/$par_asm_profile

if [ ! -f $par_home/bin/tmp/alertasm_$par_db.tmp ]; then
    echo 0 > $par_home/bin/tmp/alertasm_$par_db.tmp
fi
alertfile=`ls -1tr $par_alert_asm/alert*.log`
ultlintmp=`cat $par_home/bin/tmp/alertasm_$par_db.tmp`
ultlinalert=`wc -l $alertfile | tr -s ' ' | cut -d' ' -f1`
if [ $ultlintmp -gt $ultlinalert ]; then
    echo 0 > $par_home/bin/tmp/alertasm_$par_db.tmp
    ultlintmp=0
fi
let gaplin=$ultlinalert-$ultlintmp
echo $ultlinalert > $par_home/bin/tmp/alertasm_$par_db.tmp

# gaplin=$ultlinalert  #instrucao para varrer todo o log de forma forcada
gaplin=`cat $par_alert_asm/alert*.log | wc -c`          #instrucao para varrer todo o log de forma forcada

erroasm1=`head -n $gaplin $alertfile | grep "ORA-" | wc -l`
erroasm2=`head -n $gaplin $alertfile | grep "ERROR-" | wc -l`

if [ $erroasm1 -gt 0 -o $erroasm2 -gt 0 ]; then
    lin="ORA_LOGASM|1|Erro no log do ASM do banco $ORACLE_SID no servidor $par_host_name|NOK"
    echofunc "$lin"
    geraldlog "$lin"
else
    lin="ORA_LOGASM|1|OK|OK"
    echofunc "$lin"
    geraldlog "$lin"
fi
.

```

```

else
  lin="ORA_LOGASM|1|Nao configurado|OK"
  echofunc "$lin"
  geralog "$lin"
fi
fi

#####

par1=ORA_INSTASM
if [ "$par1" = "ORA_INSTASM" ]; then
if [ "$par_asm_profile" != "" ]; then

source $par_home_asm/$par_asm_profile

qt_pmon=`ps -ef | grep asm_pmon_${ORACLE_SID} | grep -vw grep | wc -l`
qt_smon=`ps -ef | grep asm_smon_${ORACLE_SID} | grep -vw grep | wc -l`

if [ $qt_pmon -lt 1 -o $qt_smon -lt 1 ]; then
  lin="ORA_INSTASM|1|Instancia ${ORACLE_SID} do servidor $par_host_name esta DOWN|NOK"
  echofunc "$lin"
  geralog "$lin"
else
  lin="ORA_INSTASM|1|OK|OK"
  echofunc "$lin"
  geralog "$lin"
fi
else
  lin="ORA_INSTASM|1|Nao configurado|OK"
  echofunc "$lin"
  geralog "$lin"
fi
fi

#####

par1=ORA_DISKGROUP
if [ "$par1" = "ORA_DISKGROUP" ]; then
if [ "$par_asm_profile" != "" ]; then

source $par_home_asm/$par_asm_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
  v_problema number(5) :=0;
begin
  for cur in (select name, state from v$asm_diskgroup) loop
    if cur.state <> 'MOUNTED' then
      dbms_output.put_line('ORA_DISKGROUP|1|Diskgroup '|cur.name||' esta com o status '|cur.state||' no servidor $par_host_name |NOK');
      v_problema := v_problema + 1;
    end if;
  end loop;
  if v_problema = 0 then
    dbms_output.put_line('ORA_DISKGROUP|1|OK|OK');
  end if;
end;
/
EOF
else
  echo "ORA_DISKGROUP|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

```

```

par1=ORA_GCAGENT
if [ "$par1" = "ORA_GCAGENT" ]; then
if [ "$par_gcagent_home" != "" ]; then

qt_agent=`ps -ef | grep -vw grep | wc -l`

if [ $qt_agent -lt 1 ]; then
lin="ORA_GCAGENT|3|Agente do grid control do servidor $par_host_name esta DOWN|NOK"
echofunc "$lin"
geralog "$lin"
else

qt_upload=`$par_gcagent_home/bin/emctl status agent | grep "Running" | grep "Ready" | wc -l`

if [ $qt_upload -lt 1 ]; then
lin="ORA_GCAGENT|3|Agente do grid control nao consegue fazer upload no servidor $par_host_name|NOK"
echofunc "$lin"
geralog "$lin"
else
lin="ORA_GCAGENT|3|OK|OK"
echofunc "$lin"
geralog "$lin"
fi
fi
else
lin="ORA_GCAGENT|3|Nao configurado|OK"
echofunc "$lin"
geralog "$lin"
fi
fi

#####

par1=ORA_SPFILE
if [ "$par1" = "ORA_SPFILE" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

if [ "$par_spfile" != "" ]; then
$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
v_achei number(5) :=0;
begin
for cur in (select name, value from v$parameter where name = 'spfile') loop
if instr(cur.value,'$par_spfile') > 0 then
dbms_output.put_line('ORA_SPFILE|1|OK|OK');
else
dbms_output.put_line('ORA_SPFILE|1|Instancia $ORACLE_SID iniciada com o pfile/spfile '||cur.value||'|NOK');
end if;
v_achei := 1;
end loop;
if v_achei = 0 then
dbms_output.put_line('ORA_SPFILE|1|Nao achei o parametro de inicializacao|NOK');
end if;
end;
/
EOF
else
echo "ORA_SPFILE|1|Nao configurado|OK" > $tmp
fi
else
echo "ORA_SPFILE|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp

```

```

geralog2 $tmp
fi

rm -f $tmp

#####

par1=ORA_STANDBY
if [ "$par1" = "ORA_STANDBY" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

if [ "$par_standby" != "" ]; then
$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
    v_status varchar2(20);
begin
    for cur in (select distinct case when CONTADOR = 0 then 'SUSPECT' when CONTADOR <> 0 then 'RUNNING' end status
                    from (select count(*) CONTADOR from
                        (select count(*) CONTADOR from v\${archived_log} where next_time =
                            (select max (next_time) from v\${archived_log} where applied = 'YES')
                            and next_time > sysdate-1/$par_standby group by applied ) DUAL)) loop
        v_status := cur.status;
    end loop;
    if v_status = 'RUNNING' then
        dbms_output.put_line('ORA_STANDBY|1|OK|OK');
    else
        dbms_output.put_line('ORA_STANDBY|1|Standby do banco $ORACLE_SID esta em modo SUSPECT|NOK');
    end if;
end;
/
EOF
else
echo "ORA_STANDBY|1|Nao configurado|OK" > $tmp
fi
else
echo "ORA_STANDBY|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
geralog2 $tmp
fi

rm -f $tmp

```

## 2.getm\_ora\_monitora\_goldengate.sh

```

su - oracle
cd bin/
ll

vi getm_ora_monitora_goldengate.sh

#!/bin/bash

geralog ()
{
    echo `date +"%y_%m_%d %H:%M:%S"` -> "$1 >> $log
}

echofunc ()
{
    echo $1
}

```



```

geralog2 ()
{
    while read linfile; do
        geralog "$linfile"
    done < $tmp
}

echofunc2 ()
{
    while read linfile; do
        echofunc "$linfile"
    done < $tmp
}

export ORACLE_BASE=/u01/app/oracle_19c
export ORACLE_HOME=$ORACLE_BASE/product/19.19.0/dbhome_1
export ORACLE_SID=PRMCTG2
PATH=$ORACLE_HOME/bin:$ORACLE_HOME/OPatch:$OGGHOME:$PATH
export ORACLE_HOME ORACLE_SID PATH ORACLE_BASE OH OGGHOME
LD_LIBRARY_PATH=$ORACLE_HOME/lib:/lib:/usr/lib:$OGGHOME
export GGATE=/ggs
export LD_LIBRARY_PATH=$ORACLE_HOME/lib:$GGATE
par_host_name=`hostname`
par_delay_goldengate="10"
par_home=/home/oracle
par_db_profile=db_profile
source /home/oracle/db_profile
log=$par_home/bin/logs/getmG_`date +"%Y_%m_%d"`.log
tmp=tmp/getmG_`hostname`_`date +"%Y_%m_%d_%H_%M_%N"`_$par_db.tmp

#LOGS
LOG_DIR=/u02/scripts/logs
LOG_FILE=monitora_goldengate.log
MONIT_FILE=${LOG_DIR}/${LOG_FILE}

#VALIDA
VAL_DIR=/u02/scripts/logs
VAL_FILE=validacao_goldengate.log
VAL_MONIT_FILE=${LOG_DIR}/${LOG_FILE}

#GG Logs
GG_DIR=/ggs
GG_FILE=ggserr.log
GG_MONIT_FILE=${GG_DIR}/${GG_FILE}
ABEND='ABEND|OK'
ERROLOG='ERROLOG|OK'

$GG_DIR/ggsci <<EOF > ${MONIT_FILE}
STATUS *
EOF

monitora=`cat ${MONIT_FILE} |grep "RUNNING" |wc -l`

if [ $monitora -ne 2 ]; then
    ABEND="ABEND|NOK"
fi

monitora=`tail -1000 ${GG_MONIT_FILE} |grep 'ERR\|WAR' |wc -l`
monitora=0
if [ $monitora -ne 0 ];
then
    ERROLOG='ERROLOG|NOK'
fi

echo $ABEND
echo $ERROLOG

# BEGIN ANSIBLE MANAGED BLOCK
#Envio de dados do goldengate ao Zabbix

```

```
#/usr/bin/zabbix_sender -c /etc/zabbix/zabbix_agentd.conf -k goldengateAbend -o "$ABEND" > /dev/null
#/usr/bin/zabbix_sender -c /etc/zabbix/zabbix_agentd.conf -k goldengateErrorLog -o "$ERROLOG" > /dev/null
# END ANSIBLE MANAGED BLOCK
```

### 3. getm\_ora\_database\_db1.sh

```
su - oracle
cd bin/
ll

vi getm_ora_database_db1.sh

#!/bin/bash
#
# Escrito por Adriano Rigo - Develop para uso do Getmonitor
# Versao 1.0 - 03/08/2010
#

gerallog ()
{
    echo `date +"%Y_%m_%d %H:%M:%S"` -> "$1 >> $log"
}

echofunc ()
{
    echo $1
}

gerallog2 ()
{
    while read linfile; do
        gerallog "$linfile"
    done < $tmp
}

echofunc2 ()
{
    while read linfile; do
        echofunc "$linfile"
    done < $tmp
}

#####
# Parametros configuraveis
#####
par_db=database_db1
par_home=/home/oracle
par_home_grid=/home/grid
par_db_profile=db_profile
par_asm_profile=grid_profile
par_host_name=`hostname`
par_verifica_part=true
par_except_parttable="EXAMPLE"
par_except_one="EXAMPLE" # <<< Sao as tabelas que ele verifica MES + 1 e nao MES + 2. O default seria MES + 2.
#####

#####

par1=$1

mkdir -p $par_home/bin/logs
log=$par_home/bin/logs/getm_`date +"%Y_%m_%d"`.log
tmp=/tmp/getm_`hostname`_`date +"%Y_%m_%d_%H_%M_%N"`_`$par_db`.tmp

par1=ORA_DATAFILE
if [ "$par1" = "ORA_DATAFILE" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile
```

```

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
  v_problema number(5) :=0;
begin
  for cur in (select file#, status from
              (select file#, status from gv\datafile where status not in ('SYSTEM','ONLINE')
               union
               select file#, status from gv$tempfile where status not in ('ONLINE'))
              order by file#) loop
    dbms_output.put_line('ORA_DATAFILE|1|Datafile '|cur.file#|'| esta com o status '|cur.status|'| no database $ORACLE_SID|NOK');
    v_problema := v_problema + 1;
  end loop;
  if v_problema = 0 then
    dbms_output.put_line('ORA_DATAFILE|1|OK|OK');
  end if;
end;
/
EOF
else
  echo "ORA_DATAFILE|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

par1=ORA_INDEXES
if [ "$par1" = "ORA_INDEXES" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 200
declare
  v_problema number(5) :=0;
begin
  for cur in (select dono, index_name, status, partition_name from
              (select owner dono, index_name, status, 'SEM PARTICAO' partition_name from dba_indexes where status = 'UNUSABLE'
               union all
               select index_owner dono, index_name, status, partition_name from dba_ind_partitions where status = 'UNUSABLE') order by dono, index_
name) loop
    dbms_output.put_line('ORA_INDEXES|1|Indice '|cur.dono|'| '|cur.index_name|'| ('|cur.partition_name|'|) esta com o status de '|cur.status|'| no
database $ORACLE_SID|NOK');
    v_problema := v_problema + 1;
  end loop;
  if v_problema = 0 then
    dbms_output.put_line('ORA_INDEXES|1|OK|OK');
  end if;
end;
/
EOF
else
  echo "ORA_INDEXES|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

par1=ORA_TABLESPACE

```

```

if [ "$par1" = "ORA_TABLESPACE" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 100
declare
v_problema number(5) :=0;
v_high_value varchar2(4000);
v_table_owner varchar2(70) := '-1';
v_table_name varchar2(70) := '-1';
v_achou number(1) := -1;
v_ano varchar2(4) := to_char(sysdate,'YYYY');
v_mes varchar2(2) := to_char(sysdate,'MM');
v_anomes_aux varchar2(4000);
begin
for cur in (select tablespace_name, status from dba_tablespaces where status <> 'ONLINE' order by tablespace_name) loop
dbms_output.put_line('ORA_TABLESPACE|1|Tablespace '||cur.tablespace_name||' esta com o status '||cur.status||' no database $ORACLE_SI
D|NOK');
v_problema := v_problema + 1;
end loop;

-----
-- Analisa Particionamento
-----

if upper('$par_verifica_part') = 'TRUE' then

for c_part in (
select a.table_owner, a.table_name, a.high_value
from dba_tab_partitions A,dba_part_tables B
where a.table_owner not in ('ANONYMOUS','CTXSYS','DBSNMP','DIP','DMSYS','EXFSYS',
'MDDATA','MDSYS','MGMT_VIEW','OLAPSYS','ORDPLUGINS',
'ORDSYS','OUTLN','SI_INFORMTN_SCHEMA','SYS','SYSMAN',
'SYSTEM','TSMSYS','WMSYS','XDB')
and a.table_owner = b.owner and
a.table_name = b.table_name
and b.interval is null
order by a.table_owner, a.table_name
) loop

v_high_value := c_part.high_value;
if (instr(upper(v_high_value),'TO_DATE') > 0 or instr(upper(v_high_value),'TIMESTAMP') > 0) and (instr('$par_except_parttable',c_part.table
owner||'.'||c_part.table_name) = 0) then

v_ano := to_char(sysdate,'YYYY');
v_mes := to_char(sysdate,'MM');

if instr('$par_except_one',c_part.table_owner||'.'||c_part.table_name) > 0 then
v_mes := v_mes + 1;
else
v_mes := v_mes + 2;
end if;

if v_mes > 12 then
v_ano := v_ano + 1;
v_mes := v_mes - 12;
end if;
v_ano := lpad(v_ano,4,'0');
v_mes := lpad(v_mes,2,'0');

if (v_table_owner <> c_part.table_owner) or (v_table_name <> c_part.table_name) then
if v_achou <> -1 then
if v_achou = 0 then
dbms_output.put_line('ORA_TABLESPACE|1|Tabela '||v_table_owner||'.'||v_table_name||' nao possui a particao '||v_mes||'/'||v_ano||'
NOK');
v_problema := v_problema + 1;

```

```

        end if;
        end if;
        v_table_owner := c_part.table_owner;
        v_table_name := c_part.table_name;
        v_achou := 0;
    end if;
    v_anomes_aux := c_part.high_value;
    v_anomes_aux := ltrim(substr(v_anomes_aux,instr(v_anomes_aux,'')+1));
    v_anomes_aux := rtrim(substr(v_anomes_aux,1,instr(v_anomes_aux,'')));
    v_anomes_aux := substr(v_anomes_aux,1,7);
    if v_anomes_aux = v_ano || '-' || v_mes then
        v_achou := 1;
    end if;
end if;

end loop;
if v_achou = 0 then
    dbms_output.put_line('ORA_TABLESPACE|1|Tabela '|v_table_owner||'.'|v_table_name||' nao possui a particao '|v_mes||'/'|v_ano||'|NOK');
    v_problema := v_problema + 1;
end if;

end if;

if v_problema = 0 then
    dbms_output.put_line('ORA_TABLESPACE|1|OK|OK');
end if;
end;
/
EOF
else
    echo "ORA_TABLESPACE|1|Nao configurado|OK" > $tmp
fi

echofunc2 $tmp
geralog2 $tmp
fi

#####

par1=ORA_FREESPACE
if [ "$par1" = "ORA_FREESPACE" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 200
declare
    v_problema number(5) :=0;
begin
    for cur in (select tablespace_name,
        (select trunc(sum(bytes/1024/1024)) from dba_free_space where tablespace_name = dbatbs.tablespace_name) livre,
        (select trunc(sum(bytes/1024/1024)) from dba_data_files where tablespace_name = dbatbs.tablespace_name) ocupado,
        (select trunc(sum(decode(autoextensible, 'NO',bytes,'YES',maxbytes)/1024/1024)) from dba_data_files where tablespace_name = db
atbs.tablespace_name) total,
        (100-round(100-nvl((select trunc(sum(bytes/1024/1024)) from dba_segments where tablespace_name = dbatbs.tablespace_name),0)
*100/(select trunc(sum(decode(autoextensible, 'NO',bytes,'YES',maxbytes)/1024/1024)) from dba_data_files where tablespace_name = dbatbs.tabl
espace_name),0)) percocupado
        from dba_tablespaces dbatbs where tablespace_name not in (select distinct(tablespace_name) from dba_temp_files) order by tablesp
ace_name) loop
    if cur.percocupado >= 80 then

        dbms_output.put_line('ORA_FREESPACE|1|Tablespace '|cur.tablespace_name||' esta com '|cur.percocupado||'%' ocupado (Ocupado: '|cur.oc
upado||'mb Livre: '|cur.livre||'mb Total Possivel: '|cur.total||'mb'|'|cur.percocupado||'')|'|cur.total);
        v_problema := v_problema + 1;
    end if;
    end loop;
    if v_problema = 0 then

```

```

    dbms_output.put_line('ORA_FREESPACE|1|OK|0|0');
end if;
end;
/
EOF
else
echo "ORA_FREESPACE|1|Nao configurado|0|0" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

par1=ORA_FREESPACE
if [ "$par1" = "ORA_FREESPACE" ]; then
if [ "$par_db_profile" != "" ]; then

source $par_home/$par_db_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on
set linesize 200
declare
    v_problema number(5) :=0;
begin
    for cur in (select ss.tablespace_name,
                    tot.mb_total total,
                    sum(ss.used_blocks*tot.block_size)/1024/1024 ocupado,
                    tot.mb_total-sum(ss.used_blocks*tot.block_size)/1024/1024 livre,
                    round(((sum(ss.used_blocks*tot.block_size)/1024/1024)*100/tot.mb_total),0) percocupado
                from v\sort_segment ss,
                    (select tbs.name, fil.block_size, SUM (fil.bytes)/1024/1024 mb_total
                     from v$tablespace tbs, v$tempfile fil
                     where tbs.ts#= fil.ts#
                     group by tbs.name, fil.block_size) tot
                where ss.tablespace_name = tot.name
                group by ss.tablespace_name, tot.mb_total
                order by ss.tablespace_name) loop
        dbms_output.put_line('ORA_FREESPACE|1|Tablespace "|cur.tablespace_name|" esta com "|cur.percocupado|"% ocupado (Ocupado: "|cur.oc
upado|"%mb Livre: "|cur.livre|"%mb Total Possivel: "|cur.total|"%mb|")|cur.percocupado|")|cur.total);
        v_problema := v_problema + 1;
    end loop;
    if v_problema = 0 then
        dbms_output.put_line('ORA_FREESPACE|1|OK|0|0');
    end if;
end;
/
EOF
else
echo "ORA_FREESPACE|1|Nao configurado|0|0" > $tmp
fi

echofunc2 $tmp
gerallog2 $tmp
fi

#####

par1=ORA_ASMFREE
if [ "$par1" = "ORA_ASMFREE" ]; then
if [ "$par_asm_profile" != "" ]; then

source $par_home_grid/$par_asm_profile

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF > $tmp
set feedback off
set serveroutput on

```

```

set linesize 200
declare
  v_problema number(5) :=0;
begin
  for cur in (select name, total_mb total, (total_mb-free_mb) ocupado, free_mb livre, round((total_mb-free_mb)*100/total_mb,0) percocupado
    from v\asm_diskgroup order by name) loop
    dbms_output.put_line('ORA_ASMFREE|1|Diskgroup '||cur.name||' esta com '||cur.percocupado||'% ocupado (Ocupado: '||cur.ocupado||'mb Livr
e: '||cur.livre||'mb Total Possivel: '||cur.total||'mb'||cur.percocupado||' '||cur.total);
    v_problema := v_problema + 1;
  end loop;
  if v_problema = 0 then
    dbms_output.put_line('ORA_ASMFREE|1|OK|0|0');
  end if;
end;
/
EOF
else
  echo "ORA_ASMFREE|1|Nao configurado|0|0"
fi

echofunc2 $tmp
gerallog2 $tmp
fi

rm -f $tmp

```

#### 4. getm\_ora\_asmfree\_v5.2.sh

```

su - oracle
cd bin/
ll

vi getm_ora_asmfree_v5.2.sh

#####
#!/bin/bash
#
# Escrito por Eder Santos
# Versao 5.2 - Junho de 2019
#
# Deve ser chamado passando três argumentos:
# /home/oracle/bin/getm_ora_asmfree_v5.2.sh <DISKGROUP> <TOTAL_SIZE> <FREE_SIZE>
#
#####

#####
# Releases:
#####
# 2019/06/06 - Verifica se é RAC ONE
# 2019/06/06 - Imprime nome dos servidores do RAC ONE
# 2019/06/10 - Informa caso não seja RAC e nem RAC ONE
# 2019/06/11 - Corrigida checagem para verificar se é cluster
#####

#####
# Parametros configuraveis
#####
par_homegrid=/home/grid
par_asm_profile=grid_profile
asm_dg=$1
total_mb=$2
free_mb=$3
threshold=20
server=`hostname`
#####

. $par_homegrid/$par_asm_profile

if [ "$asm_dg" != "" -a "$total_mb" -gt 0 -a "$free_mb" -ge 0 ]; then

```

```

$ORACLE_HOME/bin/sqlplus -S / as sysdba << EOF
set feedback off
set serveroutput on
set linesize 200

spool /home/oracle/asm_free.log

declare
v_disk_size number := 0;
v_disk_qnt number := 0;
v_node varchar2(30) := "";
v_cluster varchar2(10) := 'FALSE';
v_msg varchar2(30);
begin
-- Retorna o tamanho do maior disco no diskgroup
select max(a.total_mb)
into v_disk_size
from v\asm_disk a, v\asm_diskgroup g
where a.group_number = g.group_number and g.name = '$asm_dg';

--Baseado no threshold, espaço livre atual e tamanho do maior disco no diskgroup, realiza o cálculo do número de discos
v_disk_qnt := ceil(($total_mb * ($threshold - ($free_mb * 100 / $total_mb)) / 100) / v_disk_size);

--Verifica se a quantidade de discos é positiva
if v_disk_qnt > 0 then
dbms_output.put_line('Engenharia (Infra),');
dbms_output.put_line('Favor disponibilizar '||v_disk_qnt||' devices de '||v_disk_size||'MB para serem adicionados ao diskgroup $asm_dg.');
```

--Verifica se é um cluster

```

select value
into v_cluster
from v\parameter p
where name = 'cluster_database';

--Se for cluster...
if v_cluster = 'TRUE' then
--Verifica se é um RAC normal, se não retornar nenhuma linha, vai para a EXCEPTION NO_DATA_FOUND
select i.host_name
into v_node
from gv$instance i
where upper(i.host_name) not like upper('%%$server%');

--Se for RAC normal, imprime os nomes dos servidores no RAC
dbms_output.put_line('RAC: '||v_node||' / $server');
dbms_output.put_line('RAC ONE: FALSE');
```

else

```

--Informa que não é cluster
dbms_output.put_line('RAC: FALSE');
dbms_output.put_line('RAC ONE: FALSE');
```

end if;

```

else
dbms_output.put_line(' AVISO: verifique se voce informou os argumentos corretamente!');
dbms_output.put_line(' O numero de discos nao pode ser negativo!');
end if;
```

exception

```

when NO_DATA_FOUND then
dbms_output.put_line('RAC: FALSE');
--Informa que é um RACONE
dbms_output.put_line('RAC ONE: TRUE');
```

end;

```

/
EOF

if [ `grep "RAC ONE: TRUE" /home/oracle/asm_free.log | wc -l` -gt 0 ]; then
#Se for RAC ONE, imprime o nome dos servidores que fazem parte do cluster
srvctl status nodeapps | grep daemon | awk '{print $NF}'
fi
else
echo ""
echo " AVISO: voce precisa informar os tres argumentos ao executar o script!!!"

```



```
echo "      /home/oracle/bin/getm_ora_asmfree_v5.2.sh <DISKGROUP> <TOTAL_SIZE> <FREE_SIZE>"
echo ""
fi
```

Permissões:

```
chmod +x "script"
```

Obs:

Alguns Scripts terão que rodar "chmod 750" no respectivo path por falta de permissão.

- **Configurar o Crontab**

1. delete\_logs\_grid.sh

```
su - root
./home/grid/grid_profile
cd /u02/scripts
vi delete_logs_grid.sh
#!/bin/bash
find /u01/app/grid_19c/diag/asm/+asm/+ASM1/incident -mtime +7 -exec rm -f {} \;
find /u01/app/grid_19c/diag/asm/+asm/+ASM1/alert/ -name "*.xml" -mtime +7 -exec rm -f {} \;
find /u01/app/grid_19c/diag/asm/+asm/+ASM1/trace/ -name "*.tr*" -mtime +7 -exec rm -f {} \;
find /u01/app/19.19.0/grid/rdbms/audit/ -name "*.aud" -mtime +7 -exec rm -f {} \;

chown grid:oinstall delete_logs_grid.sh
chmod +x delete_logs_grid.sh
```

## 2. delete\_logs\_oracle.sh

```
su - root
./home/oracle/db_profile
cd /u02/scripts

vi delete_logs_oracle.sh
#!/bin/bash
find /u01/app/oracle_19c/diag/rdbms/prmctg/PRMCTG1/trace -name "*.tr*" -mtime +7 -exec rm -f {} \;
find /u01/app/oracle_19c/diag/rdbms/prmctg/PRMCTG1/cdump -name "*.tr*" -mtime +7 -exec rm -f {} \;
find /u01/app/oracle/product/19.19.0/dbhome_1/rdbms/audit -name "*.aud" -mtime +1 -exec rm -f {} \;
find /u01/app/oracle_19c/admin/PRMCTG/adump -name "*.aud" -mtime +1 -exec rm -f {} \;

chown oracle:oinstall delete_logs_oracle.sh
chmod +x delete_logs_oracle.sh
```