

NAME

dd – convert and copy a file

SYNOPSIS

dd [option=value] ...

DESCRIPTION

Dd copies the specified input file to the specified output with possible conversions. The standard input and output are used by default. The input and output block size may be specified to take advantage of raw physical I/O.

<i>option</i>	<i>values</i>
if=	input file name; standard input is default
of=	output file name; standard output is default
ibs=	input block size (default 512)
obs=	output block size (default 512)
bs=	set both input and output block size, superseding <i>ibs</i> and <i>obs</i> ; also, if no conversion is specified, it is particularly efficient since no copy need be done
cbs=<i>n</i>	conversion buffer size
skip=<i>n</i>	skip <i>n</i> input records before starting copy
count=<i>n</i>	copy only <i>n</i> input records
conv=ascii	convert EBCDIC to ASCII
ebcdic	convert ASCII to EBCDIC
lcase	map alphabetics to lower case
ucase	map alphabetics to upper case
swab	swap every pair of bytes
noerror	do not stop processing on an error
sync	pad every input record to <i>ibs</i>
... , ...	several conversions separated by commas

Where sizes are specified, a number of bytes is expected. A number may end with **k**, **b** or **w** to specify multiplication by 1024, 512, or 2 respectively; a pair of numbers may be separated by **x** to indicate a product.

Cbs is used only if *ascii* or *ebcdic* conversion is specified. In the former case *cbs* characters are placed into the conversion buffer, converted to ASCII, and trailing blanks trimmed and new-line added before sending the line to the output. In the latter case ASCII characters are read into the conversion buffer, converted to EBCDIC, and blanks added to make up an output record of size *cbs*.

After completion, *dd* reports the number of whole and partial input and output blocks.

For example, to read an EBCDIC tape blocked ten 80-byte EBCDIC card images per record into the ASCII file *x*:

```
dd if=/dev/rmt0 of=x ibs=800 cbs=80 conv=ascii,lcase
```

Note the use of raw magtape. *Dd* is especially suited to I/O on the raw physical devices because it allows reading and writing in arbitrary record sizes.

SEE ALSO

cp(I)

BUGS

The ASCII/EBCDIC conversion tables are taken from the 256 character standard in the CACM Nov, 1968. It is not clear how this relates to real life.

Newlines are inserted only on conversion to ASCII; padding is done only on conversion to EBCDIC. These should be separate options.