W24J12811

RELEASED

Printed Oct 21, 2026

Bundle Wrapping System 2 Inspection (Stopped) - 1 Weeks - Preventive Maintenance - Mechanical

SITE	AA	WORK TYPE	PPM	PRIORITY	P2
ASSET	S9386 - Bundle Wrapping System 2	LOCATION	L-S9386	CONDITIONS	Stopped
JOB PLAN	AAS9386W1PPMM1	PM	S9386W1PPMM1	DURATION (H)	2.5
SUPERVISOR	STEFVLAD	REPORTED	Sep 3 07:47	TARGET	Sep 10 11:00 - Sep 10 13:30
CHILD WOS	14		-		-

TASKS

#	TASK	NOTES / MEASUREMENTS
10	General 1. Strictly follow all IKO, plant and common sense safety procedures when executing each and all tasks. 2. Clean off all debris from asset being worked on and related work area. 3. Record all work done and all parts used, and all observations as each task is executed. 4. Ensure all applicable IKO SOP's are followed when performing each task. 5. If any suspect conditions or components are found that may cause operating problems before the next PM cycle, immediately report these to the maintenance supervisor or designate.	
20	Wrapper 2 Weekly Inspection (Stopped)	
30	Completion 1. Remove any garbage from area and dispose. 2. Ensure that all tools are removed from the area and returned to their proper storage location. 3. Clean all lubricate surfaces and areas. 4. Remove all lock outs. 5. Review the work orders assuring that all reported requirements have been fully satisfied, all parts that consumed are documented, and all adjustments made are recorded. If any concern still exists about the condition of this piece of equipment notify the supervisor immediately. 6. Record the time taken to execute the whole work order. 7. Hand in all replaced components with work order to Supervisor for analysis.	

ASSIGNED LABOR

LABOR	NAME	CRAFT	SKILL	HRS
MAJONA		PROD		2.50

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

PLANNED TOOLS

ITEM	DESCRIPTION	QTY	HRS	RATE
GL40FT	Aerial lift, 40 ft (demo)	1	2	125.00/h

NOTE: Planned Materials / Planned Tools rows in this sample are placeholders for layout review only - this work order tree has none planned. Planned Labor rows are live data (from the IKOMXWODETAIL object structure).

COMPLETED BY / DATE

TIME / HOURS

REVIEWED BY

W24J12815

RELEASED

Wrapper 2 Feed Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9388 - Wrapper 2 Feed Conveyor | Location L-S9388 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
20	Inspect Belt(Conveyor) Inspect the belt(conveyor) for following conditions: 1. Presence of dust, dirt, buildup - Clean the belt if required 2. Abnormal Wear (Visual) 3. Damage (Rips, Tears, Fraying) 4. Splice Failure - Lace separation. - Edges of splice are not flush. - Cracks, voids If any of the above in 2,3, & 4 are found then report for corrective action. 5. Incorrect Tension. - If required, adjust the tension of the belt if the position of the tensioner is within the limits. - If the tensioner has reached its maximum position, report for replacement of belt. 6. Mistracking - If belt is mistracking, report for corrective action	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12818

RELEASED

Wrapper 2 Acceleration Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9390 - Wrapper 2 Acceleration Conveyor | Location L-S9390 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
40	Inspect Belt(Conveyor) Inspect the belt(conveyor) for following conditions: 1. Presence of dust, dirt, buildup - Clean the belt if required 2. Abnormal Wear (Visual) 3. Damage (Rips, Tears, Fraying) 4. Splice Failure - Lace separation. - Edges of splice are not flush. - Cracks, voids If any of the above in 2,3, & 4 are found then report for corrective action. 5. Incorrect Tension. - If required, adjust the tension of the belt if the position of the tensioner is within the limits. - If the tensioner has reached its maximum position, report for replacement of belt. 6. Mistracking - If belt is mistracking, report for corrective action	
50	Inspect Roller 1. Inspect the condition of the rollers for any of the following: - Grooves - Nicks - Holes If any of above is found, then report for corrective action. 2. Make sure all rollers spin freely. If rollers do not spin freely then lubricate roller. 3. If the roller still does not spin freely then replace roller.	
60	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	
70	Inspect Arm 1.Inspect the arm for any of the following: - Wear - Damage. 2.Verify all arms and shaft mounting are securely fastened with no missing bolts or set screws	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12824

RELEASED

Wrapper 2 Plastic Wrap Unwind Stand - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9392 - Wrapper 2 Plastic Wrap Unwind Stand | Location L-S9392 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Cylinders (Actuator) Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	
20	Inspect Arm 1.Inspect the arm for any of the following: - Wear - Damage. 2.Verify all arms and shaft mounting are securely fastened with no missing bolts or set screws	
30	Inspect Roll(Steel) Applicable for steel rolls. Inspect the condition of the roll for the following: 1. Excessive wear,uneveness of length 2. Damage (Grooves, Nicks, Holes) 3. Loose / Missing bolts Verify the roll assemblies are securely fastened to the frame with no missing bolts or set screws. Replace if there are any missing bolts or set screws.	
40	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
50	Inspect Cylinders (Tensioner) Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12830

RELEASED

Wrapper 2 Plastic Wrap Dispensing System - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9410 - Wrapper 2 Plastic Wrap Dispensing System | Location L-S9410 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
30	Inspect Roller 1. Inspect the condition of the rollers for any of the following: - Grooves - Nicks - Holes If any of above is found, then report for corrective action. 2. Make sure all rollers spin freely. If rollers do not spin freely then lubricate roller. 3. If the roller still does not spin freely then replace roller.	
40	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
50	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12834

RELEASED

Wrapper 2 Plastic Wrap Accumulator - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9414 - Wrapper 2 Plastic Wrap Accumulator | Location L-S9414 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Arm 1.Inspect the arm for any of the following: - Wear - Damage. 2.Verify all arms and shaft mounting are securely fastened with no missing bolts or set screws	
20	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	
30	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
40	Inspect Roller 1. Inspect the condition of the rollers for any of the following: - Grooves - Nicks - Holes If any of above is found, then report for corrective action. 2. Make sure all rollers spin freely. If rollers do not spin freely then lubricate roller. 3. If the roller still does not spin freely then replace roller.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12839

RELEASED

Wrapper 2 Plastic Wrap Feed System - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9416 - Wrapper 2 Plastic Wrap Feed System | Location L-S9416 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12841

RELEASED

Wrapper 2 Plastic Wrap Film Cutter - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9418 - Wrapper 2 Plastic Wrap Film Cutter | Location L-S9418 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Knife(Carbide) 1. Inspect blade for following - abnormal wear - damage(chipping, crack, dent) of knives 2. If any of ther conditions as above are present, replace the knife along with the bolts. 2. Inspect gap bewteen cutting edge of knife and anvil roll, by using a feeler gauge. 3. If gap is less than 0.004" thou or greater than 0.006", re gap the cylinder within the requried tolerance.	
20	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	
30	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12845

RELEASED

Wrapper 2 Flight Bar - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9426 - Wrapper 2 Flight Bar | Location L-S9426 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Chain 1. Inspect the condition of the chain for any of the following: - Tight joints - Rust and pitting of chain - Stretching 2. Measure the chain by wear gauge, tolerance usually about 10%, https://www.ibtinc.com/how-to-measure-chain-stretch/ 3. Verify if the chain tension is correct and adjust if required. (inspect any looseness or movement of the chain on sprocket, tighten if necessary) 4. Verify if the chain alignment is correct and adjust if required.(by using laser alignment) 5. Check lubrication and lubricate chain if required	
20	Lubricate Chain Lubricate the chain and sprocket	
30	Inspect Guide 1. Inspect the guides for any of the following: - Wear - Damage. 2. Verify the guides are securely fasten to the laminator frame.	
40	Clean Guides Clean the guide: ensure guide is free of debris by using narrow scraper or flat tip screwdriver and compressed air	
50	Clean Bar Clean the flight bar track, remove the buildup and dirt. Clean the flight bar sprockets underneath and lubricate.	
60	Inspect Bar 1. Inspect the sheet support assembly's flat bars that the sheet rides on for any of the following: - Wear - Damage. 2. Measure the bars thickness and record.	
70	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	
80	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12854

RELEASED

Wrapper 2 Flight Bar Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9428 - Wrapper 2 Flight Bar Conveyor | Location L-S9428 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
20	Inspect Chain 1. Inspect the condition of the chain for any of the following: - Tight joints - Rust and pitting of chain - Stretching 2. Measure the chain by wear gauge, tolerance usually about 10%, https://www.ibtinc.com/how-to-measure-chain-stretch/ 3. Verify if the chain tension is correct and adjust if required. (inspect any looseness or movement of the chain on sprocket, tighten if necessary) 4. Verify if the chain alignment is correct and adjust if required.(by using laser alignment) 5. Check lubrication and lubricate chain if required	
30	Replace Chain Replace the chain and lubricate sprocket. Clean and lubricate the existing chain. Store the chain in designated area for next shutdown.	
40	Inspect Belt(Conveyor) Inspect the belt(conveyor) for following conditions: 1. Presence of dust, dirt, buildup - Clean the belt if required 2. Abnormal Wear (Visual) 3. Damage (Rips, Tears, Fraying) 4. Splice Failure - Lace separation. - Edges of splice are not flush. - Cracks, voids If any of the above in 2,3, & 4 are found then report for corrective action. 5. Incorrect Tension. - If required, adjust the tension of the belt if the position of the tensioner is within the limits. - If the tensioner has reached its maximum position, report for replacement of belt. 6. Mistracking - If belt is mistracking, report for corrective action	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12859

RELEASED

Wrapper 2 Bundle Transfer Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9430 - Wrapper 2 Bundle Transfer Conveyor | Location L-S9430 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
40	Inspect Roller 1. Inspect the condition of the rollers for any of the following: - Grooves - Nicks - Holes If any of above is found, then report for corrective action. 2. Make sure all rollers spin freely. If rollers do not spin freely then lubricate roller. 3. If the roller still does not spin freely then replace roller.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12862

RELEASED

Wrapper 2 Gas-operated Heat Shrink Tunnel - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9436 - Wrapper 2 Gas-operated Heat Shrink Tunnel | Location L-S9436 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
20	Inspect Tunnel Clean out all loose film and product debris from inside the tunnel.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12865

RELEASED

Wrapper 2 Gas-operated Tunnel Conveyor (Chain) - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9438 - Wrapper 2 Gas-operated Tunnel Conveyor (Chain) | Location L-S9438 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
20	Inspect Belt(Conveyor) Inspect the belt(conveyor) for following conditions: 1. Presence of dust, dirt, buildup - Clean the belt if required 2. Abnormal Wear (Visual) 3. Damage (Rips, Tears, Fraying) 4. Splice Failure - Lace separation. - Edges of splice are not flush. - Cracks, voids If any of the above in 2,3, & 4 are found then report for corrective action. 5. Incorrect Tension. - If required, adjust the tension of the belt if the position of the tensioner is within the limits. - If the tensioner has reached its maximum position, report for replacement of belt. 6. Mistracking - If belt is mistracking, report for corrective action	
30	Inspect Chain 1. Inspect the condition of the chain for any of the following: - Tight joints - Rust and pitting of chain - Stretching 2. Measure the chain by wear gauge, tolerance usually about 10%, https://www.ibtinc.com/how-to-measure-chain-stretch/ 3. Verify if the chain tension is correct and adjust if required. (inspect any looseness or movement of the chain on sprocket, tighten if necessary) 4. Verify if the chain alignment is correct and adjust if required.(by using laser alignment) 5. Check lubrication and lubricate chain if required	
40	Lubricate Chain Lubricate the chain and sprocket	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12870

RELEASED

Wrapper 2 Cooling Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9453 - Wrapper 2 Cooling Conveyor | Location L-S9453 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____

W24J12872

RELEASED

Wrapper 2 Bundle Drop Down Conveyor - 1 Weeks - Preventive Maintenance - Mechanical

Asset S9455 - Wrapper 2 Bundle Drop Down Conveyor | Location L-S9455 | Child of W24J12811

TASKS

#	TASK	NOTES / MEASUREMENTS
10	Inspect Bolt 1. Inspect the looseness of bolt by checking the alignment of the match mark if it is in place, otherwise check manually for looseness. 2. If bolts are failed then replace or request for replacement 3. while replacing bolt, please ensure bolt is torqued to required specification and also a match mark is made on bolt head and body and washer. 4. If bolts and nuts loosen repeatedly even after proper torqueing, then consider using Bellville washer or NordLock wedge washer with proper torque to prevent future loosening.	
20	Inspect Chain 1. Inspect the condition of the chain for any of the following: - Tight joints - Rust and pitting of chain - Stretching 2. Measure the chain by wear gauge, tolerance usually about 10%, https://www.ibtinc.com/how-to-measure-chain-stretch/ 3. Verify if the chain tension is correct and adjust if required. (inspect any looseness or movement of the chain on sprocket, tighten if necessary) 4. Verify if the chain alignment is correct and adjust if required.(by using laser alignment) 5. Check lubrication and lubricate chain if required	
30	Lubricate Chain Lubricate the chain and sprocket	
40	Inspect Roller 1. Inspect the condition of the rollers for any of the following: - Grooves - Nicks - Holes If any of above is found, then report for corrective action. 2. Make sure all rollers spin freely. If rollers do not spin freely then lubricate roller. 3. If the roller still does not spin freely then replace roller.	
50	Inspect Cylinders Check Oil level in the Filter Regulator Lubricator unit. If oil level is low then replenish oil.	

PLANNED MATERIALS

ITEM	DESCRIPTION	QTY	STOREROOM
13252258	Plastic film wrap 16" x 1500m (demo)	1 RL	PKG-AA
C-440012	Dry film lubricant spray (demo)	1 EA	SB-AA

Completed by: _____ Date: _____