Binary Timeseries File Format Specification

Jonathan Schilling

November 19, 2019

1 Scope

This is the specification for a really simple binary file format for storing a regularly-spaced sequence of single-channel measurement data in an efficiently writeable and readable format. The basic assumption is that the time axis t_i of a series of N measurements can be computed on the fly from the array indices:

$$t_i = t_0 + i \cdot \Delta t$$
 for $i = 0, 1, ..., (N - 1)$, (1)

where t_0 is the (reference) timestamp of the first sample and Δt is the sampling interval.

The data values y_i are stored as raw values \hat{y}_i , optionally with an offset o and a scaling factor s:

$$y_i = \hat{y}_i$$
 for $i = 0, 1, ..., (N-1)$ without scaling,
 $y_i = o + s \cdot \hat{y}_i$ for $i = 0, 1, ..., (N-1)$ with scaling. (2)

The number of samples is limited by the maximum value of the (signed 32-bit) int type, which is

$$2^{31} = 2147483648 \approx 2.1 \cdot 10^9 \quad . \tag{3}$$

In case of raw double values, the corresponding maximum file size is $(64+8\cdot2\,147\,483\,648)$ bytes $\approx 16\,\mathrm{GB}$, where 64 bytes are reserved for the file header information.

Suppose an ADC samples at a given frequency f. Then, the sampling interval $\Delta t = f^{-1}$. Using this time series file format, a maximum of 2^{31} samples can be stored, which then corresponds to a total duration T_{max} of

$$T_{\text{max}} = 2^{31} \cdot \Delta t \quad . \tag{4}$$

For a $f = 1 \,\mathrm{Mhz}$ sampling rate, $\Delta t = 1 \,\mu\mathrm{s}$ and $T_{\mathrm{max}} \approx 2147 \,\mathrm{s}$.

2 Definitions

In Tab. 1 you find an overview of the types for raw data considered in this specification.

type	size in bytes	identifier value	ok for time	ok for scaling	ok for data
None	0	0	no	yes	no
byte	1	1	no	yes	yes
short	2	2	no	yes	yes
int	4	3	no	yes	yes
long	8	4	yes	yes	yes
float	4	5	no	yes	yes
double	8	6	yes	yes	yes

Table 1: Data types considered relevant for time series data.

The first column lists the Java-style name of the given types. In the second column, the size of the corresponding type in bytes is listed. The third column lists the numeric value of the dtype bytes identifying the type of data in the file (see below). The last three columns tell you if a given type can be used to specify the time axis (ok for time), the scaling of the raw data (ok for scaling) and the raw data values (ok for data).

Throughout this document, the data types refer to the signed version of these. Unsigned versions of the data types are not considered here, as they are not available in certain programming languages (e.g. Java).

3 File Structure

The contents of the files are structured as shown in Tab. 2.

offset	size	type	allowed values	description
0	2	short	1	used to verify correct endianess
2	1	byte	4 or 6	data type of time: 4 (long) or 6 (double)
3	8	long or double	any	t_0 : reference timestamp
11	8	long or double	any	Δt : time interval between two samples
19	1	byte	0 6	data type of scaling for data values;
				0 (None) indicates that scaling is disabled
[20]	8	varying	any	offset o of data values
[28]	8	varying	any	scaling factor s for data values
36	23	reserved	reserved	reserved for future use, e.g. units
59	1	byte	1 6	dtype of raw data: 1 (byte) to 6 (double)
60	4	int	> 0	number N of data values
64	varying	varying	any	data values \hat{y}_i of type given by dtype

Table 2: Structure of the binary timeseries files. The values in the columns "offset" and "size" are in bytes. The rows where the offset is in [] are not valid and should contains zeros in the file if no scaling for the data values is used.

The first field at offset 0 in the file is a short, which is always 1. It should be read using a readShort() or similar function, which implicitly assumes the system's endianess. Then it should be checked if the returned value is 1 or -128. In the latter case, the endianess of the reading method is wrong and needs to be flipped in order to proceed.

The next field at offset 2 defines the data type of the time axis definition values t_0 and Δt . If it is equal to 3, the time definition is given as long. If it is equal to 5, the time definition is given as double. No assumption should be made on the unit of these values, although it is recommended to reserve double for seconds and long for nanoseconds.

The next field at offset 3 defines the reference timestamp t_0 and has to be read as a long or double, depending on the value read at offset 2. The next field at offset 11 defines the sampling interval Δt and has to be read as a long or double, depending on the value read at offset 2. The time axis definition values t_0 and Δt always have to be of the same data type and should use the same unit.

The field at offset 19 defines the data type of the scaling parameters o and s to come. If its value is zero, no scaling is used and the next sixteen bytes can be ignored.

At offset 20, the constant offset o of the raw data is stored. Its size can range from one byte to at most eight bytes and it is always stored from offset 20 on; the remaining (unused) bytes in case of a type smaller than 8 bytes are ignored and should be written as zeros. Right after the data offset value, at an offset of 28, the scaling factor s is stored. Its size can range from one byte to at most eight bytes and it is always stored from offset 28 on; the remaining (unused) bytes in case of a type smaller than 8 bytes are ignored and should be written as zeros. The scaling parameters o and s always have to be of the same data type and should use the same unit.

The bytes at offsets 36 to 58 are reserved for future use.

The next field at offset 59 defines the data type of the raw data. Right after the raw data type, at an offset of 60, the number of data values N to come is stored. From offset 64 on, the raw data values \hat{y}_i are stored, which have to be read as the data type defined by the value at offset 59.

4 Subset Reading

The main goal of this file format is to allow easy and fast reading of subsets of the whole time series data. Having an equally spaced time axis allows to compute the data indices inside a given time interval and using the definitions in Sec. 3, the offsets in the file can be computed for seeking to the computed position in the file and reading only from there on.

Suppose you have read t_0 and Δt from the binary timeseries file header and now want to read all available samples inside the interval $[t_l, t_u]$ where $t_l < t_u$ and the subscript l (u) stand for lower (upper). This situation is illustrated in Fig. 1 (SVG, EPS).




Figure 1: Time axis of a time series, where all data between t_l and t_u should be read. The resulting interval to be read includes indices from i to j and is indicated by the grey rectangle.

It is evident that the timestamps t_l and t_u are not necessarily aligned with the time axis of the available data. Therefore, rounding has to be used to compute the indices of data:

• double timestamps: $t_0, \Delta t \in \mathbb{R}_{64 \, \text{bit}}$

$$i = \left\lceil \frac{t_l - t_0}{\Delta t} \right\rceil \in \mathbb{N} \tag{5}$$

$$j = \left| \frac{t_u - t_0}{\Delta t} \right| \in \mathbb{N} \tag{6}$$

• long timestamps: $t_0, \Delta t \in \mathbb{Z}_{64 \text{ bit}}$

$$i = \frac{t_l - t_0 + \Delta t - 1}{\Delta t} \in \mathbb{N} \tag{7}$$

$$i = \frac{t_l - t_0 + \Delta t - 1}{\Delta t} \in \mathbb{N}$$

$$j = \frac{t_u - t_0}{\Delta t} \in \mathbb{N}$$
(7)

In case of the long timestamps, implicit computation of the floor of the division result is assumed. Using these formulas, the relevant part of the file to be read starts at index i and ends at index j. Note that these formulas are only valid if $t_0 < t_l < t_u < t_{N-1}$ holds.

5 Finalizing Remarks

An implementation of this file format in Java and Python is available on GitHub:

https://github.com/jonathanschilling/BinaryTimeseries

and the Java version is also available on Maven Central:

<dependency>

<groupId>de.labathome

<artifactId>BinaryTimeseries</artifactId>

<version>1.0.0

</dependency>

In case of questions or bug reports, please contact the author via an eMail to

jonathan.schilling@mail.de