செம்மல் | Semmal

0G pitch: 3-minute script

Tracks: **Physical AI: Agents with a Body** and **Build with 0G Private Computer** · deck: `docs/pitch/zerog-deck.html` (press **p** to present).

The first 30 seconds: the problem (say it word for word):
"Robots now act on what an AI tells them. But nobody can see what the AI was shown, whether the camera images stayed private, who paid for the decision, or whether it was real at all. When the cloud AI is slow or down, a robot either guesses or freezes. And the record of what it decided lives in the operator's logs. That's what we fixed with 0G."

Minute by minute

Time	Slide	Say	Show / point at
0:00–0:30	1 · Problem	The problem paragraph above.	Let the headline sit.
0:30–0:50	2 · What we built	"Semmal's robot can't pass a checkpoint without 0G. It drives on its own, hires and pays an AI agent in 0G, decides with a private model on 0G Private Computer, and records it on 0G Storage. Motion and safety stay on the robot."	The five-step flow.
0:50–1:35	3 · Private decision, request ID	"This is a real call the customer sees: 0gm in private mode, TEE providers only, the request ID, 24 seconds, billed to the agent's own capped key. Toys on the floor at 0.95. The robot checks the format, the action and the confidence, then clears them itself. The model can only pick from five actions; it never touches motors or money."	Request ID, checks, 'Did'.
1:35–2:05	4 · Robot pays its agents	"The robot has its own wallet. The customer pays its signed quote; the robot pays each agent's owner once per job in native 0G, and the payment is checked on chain before 0G is called. Whatever it doesn't spend goes back."	The four arrows.
2:05–2:45	5 · 0G Storage + safe stop	"Every job ends as a bundle signed by the robot on 0G Storage, with a request ID per decision. And if 0G doesn't answer, the robot holds, retries once, then stops safely. It never invents a decision, and that's tested. A motor fault stops it locally with no network at all."	Bundle; SAFE_STOP card.
2:45–3:00	6 · Close	"Remove 0G and the robot can't decide at a single checkpoint: it safe-stops, no job done, no agent paid. That's Semmal."	Links.

Deliverables to point at

Requirement	Where
Physical AI: 0G call inside the decision loop	`services/robot-master/src/mission.ts` (stop loop); "How it decided"
Episode log on 0G Storage with a request ID per decision	`evidence.ts`; bundle `decisions[].providerRequestId`; root on Arkiv
Replayable simulation	Gazebo house / warehouse / forest from `scripts/robot/scenario.sh`; shown in the video
Safe stop, no faked decision	test "0G fails twice: hold, SAFE_STOP, nothing invented"
0G PC in the main flow, with request IDs	every booked job; "How it decided" shows each request ID
What breaks if 0G is removed (one sentence)	"The robot can't decide at any checkpoint, so it safe-stops: no job done, no agent paid."
Name, description, repo + setup, video, live link, addresses, team	README "ETHGlobal Mumbai submission"; no contracts deployed (addresses listed)

Likely questions

- **Is the private answer verified?** Private mode routes only to TEE providers; the Router returns no per-answer signature, and we say so on screen. A non-TEE model is never used for a private job.
- **Why 24 seconds?** It's a checkpoint decision, not motor control; the robot holds while waiting.
- **Separate 0G accounts per agent?** Each agent has its own Router key with a daily cap; all keys draw on one deposit: a per-agent cap and usage record, not a separate wallet.

