

STOW Door System



Product datasheet



Door can be closed into secondary frame

Door is now safely locked into secondary frame



The STOW door system allows the safe locking of the door leaf in the open position.

The STOW door system is used in a service-user en-suite bathroom areas to provide a door that can be 'stowed' away into a secondary frame to allow increased patient observation and reduce risk from the moving door if decided by the staff team.

The secondary frame sections are supplied loose for on-site installation and ensure that the door leaf is shrouded when locked into the frame, the system is available for door that open 180 degrees and also 90 degrees, depending on the wall positions.

Technical Specs

Leaf Thickness:
44mm and 54mm

Available Facings:
Classic Veneer, Classic Laminate or Signature Laminate (see Finishes Swatch Book).

Core Structure:
Solid timber core of 3 layer hardwood

Maximum Leaf Dimensions:
1000mm (W) x 2100mm (H)

Vision Panel Options:
Duralux, Visilux or Pyrolux ranges - but not normally used with STOW as generally for patient en-suite bathroom applications.

Fire Rating:
NFR /FD30S / FD60S

Product Code:
STW01 (44mm single door leaf)
STW02 (54mm single door leaf)

Guarantee:
5-year guarantee as per 'Kingsway Group Product Guarantee document, a copy of which is available on request.

Anti-ligature Disclaimer

Anti-ligature Disclaimer The anti-ligature design characteristics of this product are not intended to replace or substitute the need for necessary supervision of those who may be at risk, or for other necessary protective measures to be taken in the specific circumstances of usage. Kingsway Group, Inc. does not offer any products for sale as being 'ligature-free' and will not be liable for any claims arising from ligature attachment on it's products. It is the customer's responsibility to ensure that products purchased and installed are suitable for the environments they are installed in.

