

SOLO Single Action Door System



Product datasheet

The SOLO door system is for single action doors in challenging environments.



The SOLO single action door system has been created to provide a robust solution for all door openings that have a single direction of opening, with a wide range of vision panel, hardware and locking options the SOLO door system can be specified to the exact requirements of the project.

Technical Specs

Leaf Thickness:

44mm or 54mm

Available Facings:

Classic Veneers, Classic Laminates and Signature Laminate - see Finishes Swatch Book.

Lippings for Veneer Facings:

Hardwood 10mm to all four sides concealed

Lippings for Laminate Facings:

Hardwood 10mm to all four sides exposed

Maximum Leaf Dimensions:

1000mm (W) x 2100mm (H)

Core Structure:

Solid timber core of 3 layer hardwood

Vision Panel Options:

Duralux, Visilux or Pyrolux ranges

Door Closer Options

KG21 Recessed side mounted door closer

KG35 standard, KG36 hold-open and KG37 free-swing transom mounted door closers.

Fire Rating:

NFR / FD30S / FD60S

Product Codes:

SOD01 (44mm single leaf)

SOD02 (54mm single leaf)

SOD03 (44mm leaf & half)

SOD04 (54mm leaf & half)

SOD05 (44mm double leaf)

SOD06 (54mm double leaf)

Guarantee:

5-year guarantee as per 'Kingsway Group Product Guarantee document, a copy of which is available on request.

Anti-ligature Disclaimer

Anti-ligature Disclaimer The anti-ligature design characteristics of this product are not intended to replace or substitute the need for necessary supervision of those who may be at risk, or for other necessary protective measures to be taken in the specific circumstances of usage. Kingsway Group, Inc. does not offer any products for sale as being 'ligature-free' and will not be liable for any claims arising from ligature attachment on it's products. It is the customer's responsibility to ensure that products purchased and installed are suitable for the environments they are installed in.

