



H1007		H1008	
Design Press. min. Chamber 1 / 2	-1 barg	-1 barg	-1 barg
Design Press. max. Chamber 1 / 2	60 barg	60 barg	60 barg
Design Temp. min. Chamber 1 / 2	-45 °C	-45 °C	-45 °C
Design Temp. max. Chamber 1 / 2	100 °C	100 °C	100 °C
Design Duty / Design Heat Transfer Area	33.1 kW / 66.8 m²	33.1 kW / 66.8 m²	33.1 kW / 66.8 m²
Design Case Pressure / Total Width	60 barg / 1.430 m	60 barg / 1.430 m	60 barg / 1.430 m
Material	1.4308	1.4308	1.4308

P4711		P4712	
Design Press. min. Chamber 1 / 2	-1 barg	-1 barg	-1 barg
Design Press. max. Chamber 1 / 2	60 barg	60 barg	60 barg
Design Temp. min. Chamber 1 / 2	-45 °C	-45 °C	-45 °C
Design Temp. max. Chamber 1 / 2	100 °C	100 °C	100 °C
Design Capacity / Design Press. Head	200 m³/h / 12 m	200 m³/h / 12 m	200 m³/h / 12 m
Design Speed / Design Power max. diam. shaft	6000 rpm / 60 kW	6000 rpm / 60 kW	6000 rpm / 60 kW
Material Case Press. side / Material Impeller	1.4308 / 1.4308	1.4308 / 1.4308	1.4308 / 1.4308

T4750	
Design Press. min. Chamber 1 / 2	-0.1 barg
Design Press. max. Chamber 1 / 2	0.1 barg
Design Temp. min. Chamber 1 / 2	-45 °C
Design Temp. max. Chamber 1 / 2	100 °C
Design Capacity / Design Press. Head	200 m³/h / 12 m
Design Speed / Design Power max. diam. shaft	6000 rpm / 60 kW
Material Case Press. side / Material Impeller	1.4308 / 1.4308

Oil & Gas, Inc.		SITE	
		PLANT SECTION	Utilities
		DATE	2016-04-03
		PROJECT	DEXPI example PID
		DRAWING NO	1231A63
		DESIGNER	1231A63