



Homework Assignment 5

Please submit the following files as indicated below: source code PDF file image file video file

Question 1 | 2 marks | In this assignment, we consider the linear elasticity problem

$$\begin{aligned} -c\Delta u + au &= f && \text{in } \Omega \\ u &= g && \text{on } \partial\Omega \end{aligned} \tag{1}$$

on a polygonal domain Ω . The function u can be interpreted as the elongation of a rubber membrane over the x_1x_2 -plane. The boundary values g prescribe the elongation on $\partial\Omega$, e.g. by means of a wire frame construction in which the membrane has been fixed. The real number $c > 0$ is the stiffness of the rubber material, $a > 0$ is a constant proportional to its mass density and the inhomogeneity f models external forces that act on the membrane.

- (a) Show that under the assumption of homogeneous boundary conditions, $g = 0$, the discretisation of (1) with linear finite elements reads

$$(cK^h + aM^h)\vec{u}^h = \vec{f}^h$$

where

$$k_{ij}^h = \int_{\Omega} \nabla \phi_i^h \cdot \nabla \phi_j^h \, dx$$

$$m_{ij}^h = \int_{\Omega} \phi_i^h \phi_j^h \, dx$$

$$f_i^h = \int_{\Omega} f \phi_i^h \, dx$$

ϕ_i^h = hat function centred at the i -th vertex

for $i, j = 1, \dots, N$. N is the number of effective degrees of freedom, i.e. the number of interior grid points which are not located on the boundary $\partial\Omega$.


Note that since the domain is assumed to be a polygon, we can cover it exactly with a triangulation \mathcal{T}^h such that $\Omega = \Omega^h$ (there is no mismatch on the boundary).

- (b) We can decompose the integrals that appear in the definition of the mass matrix into contributions from each triangle:

$$m_{ij}^h = \int_{\Omega} \phi_i^h \phi_j^h \, dx = \sum_{k=1}^{n_T} \int_{T_k} \phi_i^h \phi_j^h \, dx.$$

n_T is the number of triangles in the triangulation \mathcal{T}^h .

Let's look at one such triangle T , the vertices of which have the indices 1, 2 and 3. Note that only the three hat functions ϕ_1^h , ϕ_2^h and ϕ_3^h are non-zero on this triangle.




Show that the element mass matrix with entries

$$m_{ij,T}^h = \int_T \phi_i^h \phi_j^h \, dx \quad (i, j = 1, 2, 3)$$

is

$$M_T^h = \frac{|T|}{12} \begin{pmatrix} 2 & 1 & 1 \\ 1 & 2 & 1 \\ 1 & 1 & 2 \end{pmatrix}.$$

Hint: If you enjoy doing double integrals over triangles, you could use equation (2.21) from the notes. However, we don't want to mark endless calculations, so please use a different approach instead, similar to the mass matrix in 1D (Example 2.3.1, also available on Canvas under 'Pages' in the menu). Your solution should fit on the remainder of this page:

Question 2 | 3 marks |  Download the file `discretiseLinearElasticity.m`. We will turn this function into a finite-element solver for Problem (1) next week. Today we implement some core components.


The files `video10.mat` and `kiwi.mat` contain arrays `P`, `E` and `T` which define a triangulation on a polygonal computational domain Ω^h . Note that some versions of MATLAB's plotting functions from the PDE Toolbox require extra rows in `E` and `T`. If you are not using the PDE Toolbox, then you may delete all but the first two rows of `E` and all but the first three rows of `T`, as described in video #10.

To import the variables from `video10.mat` or `kiwi.mat` into a structure `msh`, you may use the `load` command.


- (a) Unlike the triangle in Question 1(b), the actual vertices of the k -th triangle are probably not 1, 2 and 3. For instance, the 5th triangle in video #10 has the vertices 7, 10 and 9. In general, the k -th triangle has the vertices `T(1,k)`, `T(2,k)` and `T(3,k)`.

Use Question 1(b) to complete the main function and the `assembleMass` subfunction. Can you do it without `for` loops?


Hint: In GNU Octave / MATLAB, the command `sparse` may be helpful.

- (b)  Write a script `hw5.m` to plot the triangular mesh and the sparsity pattern of the mass matrix that the function `discretiseLinearElasticity` returns (you don't have to remove the rows/columns corresponding to boundary points). Do this for both data sets `video10.mat` and `kiwi.mat`. Make sure your plots are not distorted by using the `axis equal` command.

Hint: In installations of MATLAB with the PDE Toolbox, the command `pdemesh` may be helpful. In GNU Octave and MATLAB without the PDE Toolbox, the command `trimesh` may be helpful.

- (c)  Add extra commands to this script to plot your favourite function u^h on the kiwi domain and compute its L^2 -norm. Constant functions are not allowed! Make sure your plots are not distorted.

Hint: The commands `pdeplot` or `trisurf` may be helpful.

Your Learning Progress |  What is the one most important thing that you have learnt from this assignment?

What is the most substantial new insight that you have gained from this course this week? Any *aha moment*?
