

# Weekly Meeting

Jon Earle

# Settings

Node-count intervals: 5, 7, 10, 12, 14, 17, 22, 32, 52, 77, 102

Simulations per interval: 20

Number of intervals: 11

Total simulations: 220

Simulation duration: 30 minutes

Random seed: 44

# Settings

Region: US

Channel number: 27

Operating frequency: 908.750 MHz

Transmit power: 20 dBm

Regional power limit: 30 dBm

Antenna gain: 2 dBi

Antenna height: 1.0 m

Modem preset: LONG\_FAST

Bandwidth: 250 kHz

Spreading factor: 11

Coding rate: 4/5

Receiver sensitivity: -131.5 dBm

CAD threshold: -134.5 dBm

Preamble length: 16 symbols

Payload length: 40 bytes

Header length: 16 bytes

ACK length: 2 bytes

Noise level: -119.25 dB

# Settings

Routing algorithm: MANAGED\_FLOOD

Node role: CLIENT

Router mode: False

Hop limit: 3

Maximum retransmissions: 3

Traffic type: Broadcast

Direct messages enabled: False

Mean message interval: 100 seconds

Message-generation distribution: Exponential

# Settings

Path-loss model number: 6

Path-loss model name: 3GPP metropolitan macro-cell

Gamma: 2.08

Reference distance: 40.0 m

Path loss at reference distance: 127.41 dB

Asymmetric links enabled: True

Asymmetric-link mean offset: 0 dB

Asymmetric-link standard deviation: 2 dB