

## ##### Problem 5 #####

```
import numpy as np
```

```
A = np.array( [ (3, 7, -4, 12),
                (-5, 9, 10, 2),
                (6, 13, 8, 11),
                (15, 5, 4, 1) ] )
```

```
v = A[:,1] # second column of A
```

```
print('Vector v: {} consists of values from 2nd column of A'.format(v))
```

```
w = A[1,:] # second row of A
```

```
print('Vector w: {} consists of values from 2nd row of A'.format(w))
```

```
Vector v: [ 7  9 13  5] consists of values from 2nd column of A
```

```
Vector w: [-5  9 10  2] consists of values from 2nd row of A
```

## ##### Problem 6 #####

```
# create a 4x3 array B of all elements in the 2nd thru 4th columns
```

```
B = A[:,1:4]
```

```
print('Array B:\n',B)
```

```
#C = # create a 3x4 array B of all elements in the 2nd thru 4th rows
```

```
C = A[1:4,:]
```

```
print('\nArray C:\n',C)
```

```
#D = # create a 2x3 of all elements in the first 2 rows and the last 3 columns
```

```
D = A[:2,1:]
```

```
print('\nArray D:\n',D)
```

```
↳ Array B:
[[ 7 -4 12]
 [ 9 10  2]
 [13  8 11]
 [ 5  4  1]]
```

```
Array C:
[[-5  9 10  2]
 [ 6 13  8 11]
 [15  5  4  1]]
```

```
Array D:
[[ 7 -4 12]
 [ 9 10  2]]
```

## ##### Problem 7 #####

```
x = [2,4,7]
```

```
y = [2, -4, 7]
```

```
z = [5+3j, -3+4j, 2-7j]
```

```
xLength = len(x)
```

```
xAbs = [abs(i) for i in x]
```

```
print('Vector x has length of {} and absolute values are {}'.format(xLength, xAbs))
```

```
yLength = len(y)
```

```
yAbs = [abs(i) for i in y]
```

```
print('Vector y has length of {} and absolute values are {}'.format(yLength, yAbs))
```

```
zLength = len(z)
```

```

zAbs = [abs(i) for i in z]
print('Vector z has length of {} and absolute values are {}'.format(zLength, zAbs))

Vector x has length of 3 and absolute values are [2, 4, 7]
Vector y has length of 3 and absolute values are [2, 4, 7]
Vector z has length of 3 and absolute values are [5.830951894845301, 5.0, 7.280109889280518]

```

#### ##### Problem 8 #####

```

# find max in min in each column
for val, column in enumerate(A.T):
    print('column', val, 'max is', column.max(), 'and min is', column.min())

print()

# find max in min in each row
for val, column in enumerate(A):
    print('row', val, 'max is', column.max(), 'and min is', column.min())

column 0 max is 15 and min is -5
column 1 max is 13 and min is 5
column 2 max is 10 and min is -4
column 3 max is 12 and min is 1

row 0 max is 12 and min is -4
row 1 max is 10 and min is -5
row 2 max is 13 and min is 6
row 3 max is 15 and min is 1

```

#### ##### Problem 9 #####

```

# sort each column and store the result in an array B
B = [sorted(column) for val, column in enumerate(A.T)]
B = np.array(B)
print('B:\n', B)

# sort each row and store the result in an array C
C = [sorted(row) for val, row in enumerate(A)]
C = np.array(C)
print('\nC:\n', C)

# add each column and store the result in an array
D = [sum(column) for val, column in enumerate(A.T)]
print('\nD:\n', D)

# add each row and store the result in an array
E = [sum(row) for val, row in enumerate(A)]
print('\nE:\n', E)

```

```

B:
[[-5  3  6 15]
 [ 5  7  9 13]
 [-4  4  8 10]
 [ 1  2 11 12]]

```

```

C:
[[-4  3  7 12]
 [-5  2  9 10]
 [ 6  8 11 13]
 [ 1  4  5 15]]

```

```
D:
[19, 34, 18, 26]

E:
[18, 16, 38, 25]
```

```
##### Problem 10 #####
```

```
A = [[1,4,2],
      [2, 4, 100],
      [7, 9, 7],
      [3, np.pi, 42]]

A = np.array(A)

B = np.log(A)

# select just the second row of B
b_row_2 = B[1,:]

print('B:\n', B)
print('\n2nd row of B:', b_row_2)
print('\nSum of 2nd row of B:', sum(b_row_2)) # evaluate the sum of the second row of B

# multiply the second column of B and the first column of A element by element

c = B[:,1] * A[:,0]

print('\nVector resulting from element-by-element multiplication')
print('of 2nd Column of B and 1st column of A:\n', c)
# eval the max value in the vector resulting from part c
print('\nMaximum value in vector above:', max(c))

e = A[0,:] / B[:3,2]
print('\nSum of the vector resulting from element-by-element division')
print('of 1st row of A by 1st 3 elements of 3rd column of B:\n', sum(e))

B:
[[0.          1.38629436 0.69314718]
 [0.69314718  1.38629436 4.60517019]
 [1.94591015  2.19722458 1.94591015]
 [1.09861229  1.14472989 3.73766962]]

2nd row of B: [0.69314718 1.38629436 4.60517019]

Sum of 2nd row of B: 6.684611727667928

Vector resulting from element-by-element multiplication
of 2nd Column of B and 1st column of A:
[ 1.38629436  2.77258872 15.38057204  3.43418966]

Maximum value in vector above: 15.380572041353537

Sum of the vector resulting from element-by-element division
of 1st row of A by 1st 3 elements of 3rd column of B:
3.3390806894349683
```