

CHAPTER

2

Regular Expressions, Text Normalization, Edit Distance

User: *You are like my father in some ways.*
ELIZA: *WHAT RESEMBLANCE DO YOU SEE*
User: *You are not very aggressive but I think you don't want me to notice that.*
ELIZA: *WHAT MAKES YOU THINK I AM NOT VERY AGGRESSIVE*
User: *You don't argue with me.*
ELIZA: *WHY DO YOU THINK I DON'T ARGUE WITH YOU*
User: *You are afraid of me.*
ELIZA: *DOES IT PLEASE YOU TO BELIEVE I AM AFRAID OF YOU*

Weizenbaum (1966)

ELIZA The dialogue above is from **ELIZA**, an early natural language processing system that could carry on a limited conversation with a user by imitating the responses of a Rogerian psychotherapist (Weizenbaum, 1966). ELIZA is a surprisingly simple program that uses pattern matching to recognize phrases like “You are X” and translate them into suitable outputs like “What makes you think I am X?”. This simple technique succeeds in this domain because ELIZA doesn’t actually need to *know* anything to mimic a Rogerian psychotherapist. As Weizenbaum notes, this is one of the few dialogue genres where listeners can act as if they know nothing of the world. Nonetheless Eliza’s mimicry of human conversation was remarkably successful: many people who interacted with ELIZA came to believe that it really *understood* them and their problems, many continued to believe in ELIZA’s abilities even after the program’s operation was explained to them (Weizenbaum, 1976), and even today such **chatbots** are a fun diversion.

Of course modern conversational agents are much more than a diversion; they can answer questions, book flights, or find restaurants, functions for which they rely on a much more sophisticated understanding of the user’s intent, as we will see in Chapter 24. Nonetheless, the simple pattern-based methods that powered ELIZA and other chatbots play a crucial role in natural language processing.

We’ll begin with the most important tool for describing text patterns: the **regular expression**. Regular expressions can be used to specify strings we might want to extract from a document, from transforming “You are X” in Eliza above, to defining strings like \$199 or \$24.99 for extracting tables of prices from a document.

text
normalization

We’ll then turn to a set of tasks collectively called **text normalization**, in which regular expressions play an important part. Normalizing text means converting it to a more convenient, standard form. For example, most of what we are going to do with language relies on first separating out or **tokenizing** words from running text, the task of **tokenization**. English words are often separated from each other by whitespace, but whitespace is not always sufficient. *New York* and *rock ’n’ roll* are sometimes treated as large words despite the fact that they contain spaces, while sometimes we’ll need to separate *I’m* into the two words *I* and *am*. For processing tweets or texts we’ll need to tokenize **emojicons** like :) or **hashtags** like #n1proc. Some languages, like Chinese, don’t have spaces between words, so word tokenization becomes more difficult.

tokenization

lemmatization

Another part of text normalization is **lemmatization**, the task of determining that two words have the same root, despite their surface differences. For example, the words *sang*, *sung*, and *sings* are forms of the verb *sing*. The word *sing* is the common *lemma* of these words, and a **lemmatizer** maps from all of these to *sing*. Lemmatization is essential for processing morphologically complex languages like Arabic. **Stemming** refers to a simpler version of lemmatization in which we mainly just strip suffixes from the end of the word. Text normalization also includes **sentence segmentation**: breaking up a text into individual sentences, using cues like periods or exclamation points.

stemming

sentence
segmentation

Finally, we'll need to compare words and other strings. We'll introduce a metric called **edit distance** that measures how similar two strings are based on the number of edits (insertions, deletions, substitutions) it takes to change one string into the other. Edit distance is an algorithm with applications throughout language processing, from spelling correction to speech recognition to coreference resolution.

2.1 Regular Expressions

SIR ANDREW: *Her C's, her U's and her T's: why that?*
Shakespeare, *Twelfth Night*

regular
expression

corpus

One of the unsung successes in standardization in computer science has been the **regular expression (RE)**, a language for specifying text search strings. This practical language is used in every computer language, word processor, and text processing tools like the Unix tools `grep` or Emacs. Formally, a regular expression is an algebraic notation for characterizing a set of strings. They are particularly useful for searching in texts, when we have a **pattern** to search for and a **corpus** of texts to search through. A regular expression search function will search through the corpus, returning all texts that match the pattern. The corpus can be a single document or a collection. For example, the Unix command-line tool `grep` takes a regular expression and returns every line of the input document that matches the expression.

A search can be designed to return every match on a line, if there are more than one, or just the first match. In the following examples we underline the exact part of the pattern that matches the regular expression and show only the first match. We'll show regular expressions delimited by slashes but note that slashes are *not* part of the regular expressions.

2.1.1 Basic Regular Expression Patterns

The simplest kind of regular expression is a sequence of simple characters. To search for *woodchuck*, we type `/woodchuck/`. The expression `/Buttercup/` matches any string containing the substring *Buttercup*; `grep` with that expression would return the line *I'm called little Buttercup*. The search string can consist of a single character (like `/!/`) or a sequence of characters (like `/urgl/`).

RE	Example Patterns Matched
<code>/woodchucks/</code>	"interesting links to <u>woodchucks</u> and lemurs"
<code>/a/</code>	"Mary Ann stopped by Mona's"
<code>/!/</code>	"You've left the burglar behind again!" said Nori

Figure 2.1 Some simple regex searches.

Regular expressions are **case sensitive**; lower case `/s/` is distinct from upper case `/S/` (`/s/` matches a lower case *s* but not an uppercase *S*). This means that the pattern `/woodchucks/` will not match the string *Woodchucks*. We can solve this problem with the use of the square braces `[` and `]`. The string of characters inside the braces specify a **disjunction** of characters to match. For example, Fig. 2.2 shows that the pattern `/[wW]/` matches patterns containing either *w* or *W*.

RE	Match	Example Patterns
<code>/[wW]oodchuck/</code>	Woodchuck or woodchuck	<u>“Woodchuck”</u>
<code>/[abc]/</code>	‘a’, ‘b’, or ‘c’	“In uo <u>o</u> mini, in soldati”
<code>/[1234567890]/</code>	any digit	“plenty of <u>7</u> to 5”

Figure 2.2 The use of the brackets `[]` to specify a disjunction of characters.

The regular expression `/[1234567890]/` specified any single digit. While such classes of characters as digits or letters are important building blocks in expressions, they can get awkward (e.g., it’s inconvenient to specify

`/[ABCDEFGH IJKLMNOPQRSTUVWXYZ]/`

to mean “any capital letter”). In cases where there is a well-defined sequence associated with a set of characters, the brackets can be used with the dash (`-`) to specify any one character in a **range**. The pattern `/[2-5]/` specifies any one of the characters 2, 3, 4, or 5. The pattern `/[b-g]/` specifies one of the characters *b*, *c*, *d*, *e*, *f*, or *g*. Some other examples are shown in Fig. 2.3.

RE	Match	Example Patterns Matched
<code>/[A-Z]/</code>	an upper case letter	“we should call it ‘ <u>D</u> renched Blossoms’ ”
<code>/[a-z]/</code>	a lower case letter	“ <u>m</u> y beans were impatient to be hoed!”
<code>/[0-9]/</code>	a single digit	“Chapter <u>1</u> : Down the Rabbit Hole”

Figure 2.3 The use of the brackets `[]` plus the dash `-` to specify a range.

The square braces can also be used to specify what a single character *cannot* be, by use of the caret `^`. If the caret `^` is the first symbol after the open square brace `[`, the resulting pattern is negated. For example, the pattern `/[^a]/` matches any single character (including special characters) except *a*. This is only true when the caret is the first symbol after the open square brace. If it occurs anywhere else, it usually stands for a caret; Fig. 2.4 shows some examples.

RE	Match (single characters)	Example Patterns Matched
<code>[^A-Z]</code>	not an upper case letter	“O <u>y</u> fn pripetchik”
<code>[^Ss]</code>	neither ‘S’ nor ‘s’	“ <u>I</u> have no exquisite reason for’t”
<code>[^\.]</code>	not a period	“ <u>o</u> ur resident Djinn”
<code>[e^]</code>	either ‘e’ or ‘^’	“look up <u>^</u> now”
<code>a^b</code>	the pattern ‘a^b’	“look up <u>a^b</u> now”

Figure 2.4 Uses of the caret `^` for negation or just to mean `^`. We discuss below the need to escape the period by a backslash.

How can we talk about optional elements, like an optional *s* in *woodchuck* and *woodchucks*? We can’t use the square brackets, because while they allow us to say “s or S”, they don’t allow us to say “s or nothing”. For this we use the question mark `/?/`, which means “the preceding character or nothing”, as shown in Fig. 2.5.

We can think of the question mark as meaning “zero or one instances of the previous character”. That is, it’s a way of specifying how many of something that

RE	Match	Example Patterns Matched
woodchucks?	woodchuck or woodchucks	"woodchuck"
colou?r	color or colour	"colour"

Figure 2.5 The question mark ? marks optionality of the previous expression.

we want. Specifying how many is another useful regular expression features For example, consider the language of certain sheep, which consists of strings that look like the following:

```
baa!
baaa!
baaaa!
baaaaa!
...
```

Kleene * This language consists of strings with a *b*, followed by at least two *a*'s, followed by an exclamation point. The set of operators that allows us to say things like "some number of *a*'s" are based on the asterisk or *, commonly called the **Kleene *** (generally pronounced "cleany star"). The Kleene star means "zero or more occurrences of the immediately previous character or regular expression". So `/a*/` means "any string of zero or more *a*'s". This will match *a* or *aaaaaa*, but it will also match *Off Minor* since the string *Off Minor* has zero *a*'s. So the regular expression for matching one or more *a* is `/aa*/`, meaning one *a* followed by zero or more *a*'s. More complex patterns can also be repeated. So `/[ab]*/` means "zero or more *a*'s or *b*'s" (not "zero or more right square braces"). This will match strings like *aaaa* or *ababab* or *bbbb*.

For specifying multiple digits (useful for finding prices) we can extend `/[0-9]/`, the regular expression for a single digit. An integer (a string of digits) is thus `/[0-9][0-9]*/`. (Why isn't it just `/[0-9]*/?`)

Kleene + Sometimes it's annoying to have to write the regular expression for digits twice, so there is a shorter way to specify "at least one" of some character. This is the **Kleene +**, which means "one or more of the previous character". Thus, the expression `/[0-9]+/` is the normal way to specify "a sequence of digits". There are thus two ways to specify the sheep language: `/baaa*/` or `/baa+!`.

One very important special character is the period (`/./`), a **wildcard** expression that matches any single character (*except* a carriage return), as shown in Fig. 2.6.

RE	Match	Example Patterns
<code>/beg.n/</code>	any character between <i>beg</i> and <i>n</i>	<u>begin</u> , <u>beg'n</u> , <u>begun</u>

Figure 2.6 The use of the period . to specify any character.

The wildcard is often used together with the Kleene star to mean "any string of characters". For example, suppose we want to find any line in which a particular word, for example, *aardvark*, appears twice. We can specify this with the regular expression `/aardvark.*aardvark/`.

Anchors **Anchors** are special characters that anchor regular expressions to particular places in a string. The most common anchors are the caret `^` and the dollar sign `$`. The caret `^` matches the start of a line. The pattern `/^The/` matches the word *The* only at the start of a line. Thus, the caret `^` has three uses: to match the start of a line, to indicate a negation inside of square brackets, and just to mean a caret. (What are the contexts that allow `grep` or `Python` to know which function a given caret is supposed to have?) The dollar sign `$` matches the end of a line. So the pattern `_^$` is a useful

pattern for matching a space at the end of a line, and `/^The dog\.$/` matches a line that contains only the phrase *The dog*. (We have to use the backslash here since we want the `.` to mean “period” and not the wildcard.)

There are also two other anchors: `\b` matches a word boundary, and `\B` matches a non-boundary. Thus, `/\bthe\b/` matches the word *the* but not the word *other*. More technically, a “word” for the purposes of a regular expression is defined as any sequence of digits, underscores, or letters; this is based on the definition of “words” in programming languages. For example, `/\b99\b/` will match the string *99* in *There are 99 bottles of beer on the wall* (because *99* follows a space) but not *99* in *There are 299 bottles of beer on the wall* (since *99* follows a number). But it will match *99* in *\$99* (since *99* follows a dollar sign (\$), which is not a digit, underscore, or letter).

2.1.2 Disjunction, Grouping, and Precedence

disjunction

Suppose we need to search for texts about pets; perhaps we are particularly interested in cats and dogs. In such a case, we might want to search for either the string *cat* or the string *dog*. Since we can’t use the square brackets to search for “cat or dog” (why can’t we say `/[catdog]?/`), we need a new operator, the **disjunction** operator, also called the **pipe** symbol `|`. The pattern `/cat|dog/` matches either the string *cat* or the string *dog*.

Precedence

Sometimes we need to use this disjunction operator in the midst of a larger sequence. For example, suppose I want to search for information about pet fish for my cousin David. How can I specify both *guppy* and *guppies*? We cannot simply say `/guppy|ies/`, because that would match only the strings *guppy* and *ies*. This is because sequences like *guppy* take **precedence** over the disjunction operator `|`. To make the disjunction operator apply only to a specific pattern, we need to use the parenthesis operators `(` and `)`. Enclosing a pattern in parentheses makes it act like a single character for the purposes of neighboring operators like the pipe `|` and the Kleene*. So the pattern `/gupp(y|ies)/` would specify that we meant the disjunction only to apply to the suffixes *y* and *ies*.

The parenthesis operator `(` is also useful when we are using counters like the Kleene*. Unlike the `|` operator, the Kleene* operator applies by default only to a single character, not to a whole sequence. Suppose we want to match repeated instances of a string. Perhaps we have a line that has column labels of the form *Column 1 Column 2 Column 3*. The expression `/Column_+[0-9]+_*/` will not match any number of columns; instead, it will match a single column followed by any number of spaces! The star here applies only to the space `_` that precedes it, not to the whole sequence. With the parentheses, we could write the expression `/(Column_+[0-9]+_*)*/` to match the word *Column*, followed by a number and optional spaces, the whole pattern repeated any number of times.

operator precedence

This idea that one operator may take precedence over another, requiring us to sometimes use parentheses to specify what we mean, is formalized by the **operator precedence hierarchy** for regular expressions. The following table gives the order of RE operator precedence, from highest precedence to lowest precedence.

Parenthesis	<code>()</code>
Counters	<code>* + ? {}</code>
Sequences and anchors	<code>the ^my end\$</code>
Disjunction	<code> </code>

Thus, because counters have a higher precedence than sequences,

`/the*/` matches *theeee* but not *thethe*. Because sequences have a higher precedence than disjunction, `/the|any/` matches *the* or *any* but not *theny*.

Patterns can be ambiguous in another way. Consider the expression `/[a-z]*/` when matching against the text *once upon a time*. Since `/[a-z]*/` matches zero or more letters, this expression could match nothing, or just the first letter *o*, *on*, *onc*, or *once*. In these cases regular expressions always match the *largest* string they can; we say that patterns are **greedy**, expanding to cover as much of a string as they can.

2.1.3 A Simple Example

Suppose we wanted to write a RE to find cases of the English article *the*. A simple (but incorrect) pattern might be:

```
/the/
```

One problem is that this pattern will miss the word when it begins a sentence and hence is capitalized (i.e., *The*). This might lead us to the following pattern:

```
/[tT]he/
```

But we will still incorrectly return texts with **the** embedded in other words (e.g., *other* or *theology*). So we need to specify that we want instances with a word boundary on both sides:

```
/\b[tT]he\b/
```

Suppose we wanted to do this without the use of `/\b/`. We might want this since `/\b/` won't treat underscores and numbers as word boundaries; but we might want to find *the* in some context where it might also have underlines or numbers nearby (*the_* or *the25*). We need to specify that we want instances in which there are no alphabetic letters on either side of the *the*:

```
/[^a-zA-Z][tT]he[^a-zA-Z]/
```

But there is still one more problem with this pattern: it won't find the word *the* when it begins a line. This is because the regular expression `[^a-zA-Z]`, which we used to avoid embedded instances of *the*, implies that there must be some single (although non-alphabetic) character before the *the*. We can avoid this by specifying that before the *the* we require *either* the beginning-of-line or a non-alphabetic character, and the same at the end of the line:

```
/(^[^a-zA-Z])[tT]he([a-zA-Z]|$)/
```

false positives
false negatives

The process we just went through was based on fixing two kinds of errors: **false positives**, strings that we incorrectly matched like *other* or *there*, and **false negatives**, strings that we incorrectly missed, like *The*. Addressing these two kinds of errors comes up again and again in implementing speech and language processing systems. Reducing the overall error rate for an application thus involves two antagonistic efforts:

- Increasing **precision** (minimizing false positives)
- Increasing **recall** (minimizing false negatives)

2.1.4 A More Complex Example

Let's try out a more significant example of the power of REs. Suppose we want to build an application to help a user buy a computer on the Web. The user might want “any machine with more than 6 GHz and 500 GB of disk space for less than \$1000”. To do this kind of retrieval, we first need to be able to look for expressions like *6 GHz* or *500 GB* or *Mac* or *\$999.99*. In the rest of this section we'll work out some simple regular expressions for this task.

First, let's complete our regular expression for prices. Here's a regular expression for a dollar sign followed by a string of digits. Note that regular expression parsers are smart enough to realize that \$ here doesn't mean end-of-line; how might they know that?

```
/[$[0-9]+/
```

Now we just need to deal with fractions of dollars. We'll add a decimal point and two digits afterwards:

```
/[$[0-9]+\.[0-9][0-9]/
```

This pattern only allows *\$199.99* but not *\$199*. We need to make the cents optional and to make sure we're at a word boundary:

```
/\b$[0-9]+(\.[0-9][0-9])?\b/
```

How about specifications for processor speed? Here's a pattern for that:

```
/\b[0-9]+\s*(GHz|[Gg]igahertz)\b/
```

Note that we use `/\s*/` to mean “zero or more spaces” since there might always be extra spaces lying around. We also need to allow for optional fractions again (*5.5 GB*); note the use of `?` for making the final *s* optional:

```
/\b[0-9]+(\.[0-9]+)?\s*(GB|[Gg]igabytes?)\b/
```

2.1.5 Advanced Operators

There are also some useful advanced regular expression operators. Figure 2.7 shows some aliases for common ranges, which can be used mainly to save typing. Besides the Kleene `*` and Kleene `+` we can also use explicit numbers as counters, by enclosing them in curly brackets. The regular expression `/\{3}/` means “exactly 3 occurrences of the previous character or expression”. So `/a\.{24}z/` will match *a* followed by 24 dots followed by *z* (but not *a* followed by 23 or 25 dots followed by a *z*).

RE	Expansion	Match	Examples
<code>\d</code>	<code>[0-9]</code>	any digit	Party_of_5
<code>\D</code>	<code>[^0-9]</code>	any non-digit	Blue_moon
<code>\w</code>	<code>[a-zA-Z0-9_]</code>	any alphanumeric/underscore	Daiyu
<code>\W</code>	<code>[^\w]</code>	a non-alphanumeric	!!!!
<code>\s</code>	<code>[\r\t\n\f]</code>	whitespace (space, tab)	
<code>\S</code>	<code>[^\s]</code>	Non-whitespace	in_Concord

Figure 2.7 Aliases for common sets of characters.

RE	Match
*	zero or more occurrences of the previous char or expression
+	one or more occurrences of the previous char or expression
?	exactly zero or one occurrence of the previous char or expression
{ <i>n</i> }	<i>n</i> occurrences of the previous char or expression
{ <i>n</i> , <i>m</i> }	from <i>n</i> to <i>m</i> occurrences of the previous char or expression
{ <i>n</i> ,}	at least <i>n</i> occurrences of the previous char or expression

Figure 2.8 Regular expression operators for counting.

A range of numbers can also be specified. So `{n,m}` specifies from *n* to *m* occurrences of the previous char or expression, and `{n,}` means at least *n* occurrences of the previous expression. REs for counting are summarized in Fig. 2.8.

Newline Finally, certain special characters are referred to by special notation based on the backslash (`\`) (see Fig. 2.9). The most common of these are the **newline** character `\n` and the **tab** character `\t`. To refer to characters that are special themselves (like `.`, `*`, `[`, and `\`), precede them with a backslash, (i.e., `\.`, `*`, `\[`, and `\\`).

RE	Match	Example Patterns Matched
<code>*</code>	an asterisk “ <code>*</code> ”	“ <code>K_A*P*L*A*N</code> ”
<code>\.</code>	a period “ <code>.</code> ”	“ <code>Dr. Livingston, I presume</code> ”
<code>\?</code>	a question mark	“ <code>Why don’t they come and lend a hand?</code> ”
<code>\n</code>	a newline	
<code>\t</code>	a tab	

Figure 2.9 Some characters that need to be backslashed.

2.1.6 Regular Expression Substitution, Memory, and ELIZA

substitution An important use of regular expressions is in **substitutions**. For example, the substitution operator `s/regex1/pattern/` used in Perl and in Unix commands like `vim` or `sed` allows a string characterized by a regular expression to be replaced by another string:

```
s/colour/color/
```

It is often useful to be able to refer to a particular subpart of the string matching the first pattern. For example, suppose we wanted to put angle brackets around all integers in a text, for example, changing *the 35 boxes* to *the <35> boxes*. We’d like a way to refer to the integer we’ve found so that we can easily add the brackets. To do this, we put parentheses (`(` and `)`) around the first pattern and use the **number** operator `\1` in the second pattern to refer back. Here’s how it looks:

```
s/([0-9]+)/<\1>/
```

The parenthesis and number operators can also specify that a certain string or expression must occur twice in the text. For example, suppose we are looking for the pattern “the Xer they were, the Xer they will be”, where we want to constrain the two X’s to be the same string. We do this by surrounding the first X with the parenthesis operator, and replacing the second X with the number operator `\1`, as follows:

```
/the (.*?)er they were, the \1er they will be/
```

Here the `\1` will be replaced by whatever string matched the first item in parentheses. So this will match *The bigger they were, the bigger they will be* but not *The bigger they were, the faster they will be*.

The number operator can be used with other numbers. If you match two different sets of parenthesis, \2 means whatever matched the *second* set. For example,

/the (.*)er they (.*) , the \1er we \2/

register

will match *The faster they ran, the faster we ran* but not *The faster they ran, the faster we ate*. These numbered memories are called **registers** (e.g., register 1, register 2, register 3). This memory feature is not part of every regular expression language and is often considered an “extended” feature of regular expressions.

Substitutions using memory are useful in implementing simple chatbots like ELIZA (Weizenbaum, 1966). Recall that ELIZA simulates a Rogerian psychologist by carrying on conversations like the following:

```
User1:   Men are all alike.
ELIZA1: IN WHAT WAY
User2:   They're always bugging us about something or other.
ELIZA2: CAN YOU THINK OF A SPECIFIC EXAMPLE
User3:   Well, my boyfriend made me come here.
ELIZA3: YOUR BOYFRIEND MADE YOU COME HERE
User4:   He says I'm depressed much of the time.
ELIZA4: I AM SORRY TO HEAR YOU ARE DEPRESSED
```

ELIZA works by having a series or cascade of regular expression substitutions that each match some part of the input lines and changes them. The first substitutions change all instances of *my* to *YOUR*, and *I'm* to *YOU ARE*, and so on. The next set of substitutions matches and replaces other patterns in the input. Here are some examples:

```
s/. * I'M (depressed|sad) . */I AM SORRY TO HEAR YOU ARE \1/
s/. * I AM (depressed|sad) . */WHY DO YOU THINK YOU ARE \1/
s/. * all . */IN WHAT WAY/
s/. * always . */CAN YOU THINK OF A SPECIFIC EXAMPLE/
```

Since multiple substitutions can apply to a given input, substitutions are assigned a rank and applied in order. Creating patterns is the topic of Exercise 2.3.

2.2 Words and Corpora

corpus
corpora

Before we talk about processing words, we need to decide what counts as a word. Let's start by looking at a **corpus** (plural **corpora**), a computer-readable collection of text or speech. For example the Brown corpus is a million-word collection of samples from 500 written texts from different genres (newspaper, fiction, non-fiction, academic, etc.), assembled at Brown University in 1963–64 (Kučera and Francis, 1967). How many words are in the following Brown sentence?

(2.1) He stepped out into the hall, was delighted to encounter a water brother.

Example (2.1) has 13 words if we don't count punctuation marks as words, 15 if we count punctuation. Whether we treat period (“.”), comma (“,”), and so on as words depends on the task. Punctuation is critical for finding boundaries of things (commas, periods, colons) and for identifying some aspects of meaning (question marks, exclamation marks, quotation marks). For some tasks, like part-of-speech

tagging or parsing or speech synthesis, we sometimes treat punctuation marks as if they were separate words.

The Switchboard corpus of telephone conversations between strangers was collected in the early 1990s; it contains 2430 conversations averaging 6 minutes each, totaling 240 hours of speech and about 3 million words (Godfrey et al., 1992). Such corpora of spoken language don't have punctuation but do introduce other complications with regard to defining words. Let's look at one utterance from Switchboard; an **utterance** is the spoken correlate of a sentence:

(2.2) I do uh main- mainly business data processing

This utterance has two kinds of **disfluencies**. The broken-off word *main-* is called a **fragment**. Words like *uh* and *um* are called **fillers** or **filled pauses**. Should we consider these to be words? Again, it depends on the application. If we are building a speech transcription system, we might want to eventually strip out the disfluencies.

But we also sometimes keep disfluencies around. Disfluencies like *uh* or *um* are actually helpful in speech recognition in predicting the upcoming word, because they may signal that the speaker is restarting the clause or idea, and so for speech recognition they are treated as regular words. Because people use different disfluencies they can also be a cue to speaker identification. In fact Clark and Fox Tree (2002) showed that *uh* and *um* have different meanings. What do you think they are?

Are capitalized tokens like *They* and uncapitalized tokens like *they* the same word? These are lumped together in some tasks (speech recognition), while for part-of-speech or named-entity tagging, capitalization is a useful feature and is retained.

How about inflected forms like *cats* versus *cat*? These two words have the same **lemma** *cat* but are different wordforms. A **lemma** is a set of lexical forms having the same stem, the same major part-of-speech, and the same word sense. The **word-form** is the full inflected or derived form of the word. For morphologically complex languages like Arabic, we often need to deal with lemmatization. For many tasks in English, however, wordforms are sufficient.

How many words are there in English? To answer this question we need to distinguish two ways of talking about words. **Types** are the number of distinct words in a corpus; if the set of words in the vocabulary is V , the number of types is the vocabulary size $|V|$. **Tokens** are the total number N of running words. If we ignore punctuation, the following Brown sentence has 16 tokens and 14 types:

(2.3) They picnicked by the pool, then lay back on the grass and looked at the stars.

Corpus	Tokens = N	Types = $ V $
Shakespeare	884 thousand	31 thousand
Brown corpus	1 million	38 thousand
Switchboard telephone conversations	2.4 million	20 thousand
COCA	440 million	2 million
Google N-grams	1 trillion	13 million

Figure 2.10 Rough numbers of types and tokens for some corpora. The largest, the Google N-grams corpus, contains 13 million types, but this count only includes types appearing 40 or more times, so the true number would be much larger.

When we speak about the number of words in the language, we are generally referring to word types. Fig. 2.10 shows the rough numbers of types and tokens computed from some popular English corpora. The larger the corpora we look at, the more word types we find, and in fact this relationship between the number of types

Herdan's Law
Heaps' Law

$|V|$ and number of tokens N is called **Herdan's Law** (Herdan, 1960) or **Heaps' Law** (Heaps, 1978) after its discoverers (in linguistics and information retrieval respectively). It is shown in Eq. 2.4, where k and β are positive constants, and $0 < \beta < 1$.

$$|V| = kN^\beta \quad (2.4)$$

The value of β depends on the corpus size and the genre, but at least for the large corpora in Fig. 2.10, β ranges from .67 to .75. Roughly then we can say that the vocabulary size for a text goes up significantly faster than the square root of its length in words.

Another measure of the number of words in the language is the number of lemmas instead of wordform types. Dictionaries can help in giving lemma counts; dictionary **entries** or **boldface forms** are a very rough upper bound on the number of lemmas (since some lemmas have multiple boldface forms). The 1989 edition of the Oxford English Dictionary had 615,000 entries.

2.3 Text Normalization

Before almost any natural language processing of a text, the text has to be normalized. At least three tasks are commonly applied as part of any normalization process:

1. Segmenting/tokenizing words from running text
2. Normalizing word formats
3. Segmenting sentences in running text.

In the next sections we walk through each of these tasks.

2.3.1 Unix tools for crude tokenization and normalization

Let's begin with an easy, if somewhat naive version of word tokenization and normalization (and frequency computation) that can be accomplished solely in a single UNIX command-line, inspired by Church (1994). We'll make use of some Unix commands: `tr`, used to systematically change particular characters in the input; `sort`, which sorts input lines in alphabetical order; and `uniq`, which collapses and counts adjacent identical lines.

For example let's begin with the complete words of Shakespeare in one textfile, `sh.txt`. We can use `tr` to tokenize the words by changing every sequence of non-alphabetic characters to a newline ('A-Za-z' means alphabetic, the `-c` option complements to non-alphabet, and the `-s` option squeezes all sequences into a single character):

```
tr -sc 'A-Za-z' '\n' < sh.txt
```

The output of this command will be:

```
THE
SONNETS
by
William
Shakespeare
From
fairest
```

```

creatures
We
...

```

Now that there is one word per line, we can sort the lines, and pass them to `uniq -c` which will collapse and count them:

```
tr -sc 'A-Za-z' '\n' < sh.txt | sort | uniq -c
```

with the following output:

```

1945 A
72 AARON
19 ABBESS
25 Aaron
6 Abate
1 Abates
5 Abbess
6 Abbey
3 Abbot
...

```

Alternatively, we can collapse all the uppercase to lowercase:

```
tr -sc 'A-Za-z' '\n' < sh.txt | tr A-Z a-z | sort | uniq -c
```

whose output is

```

14725 a
97 aaron
1 abaissiez
10 abandon
2 abandoned
2 abase
1 abash
14 abate
3 abated
3 abatement
...

```

Now we can sort again to find the frequent words. The `-n` option to `sort` means to sort numerically rather than alphabetically, and the `-r` option means to sort in reverse order (highest-to-lowest):

```
tr -sc 'A-Za-z' '\n' < sh.txt | tr A-Z a-z | sort | uniq -c | sort -n -r
```

The results show that the most frequent words in Shakespeare, as in any other corpus, are the short **function words** like articles, pronouns, prepositions:

```

27378 the
26084 and
22538 i
19771 to
17481 of
14725 a
13826 you
12489 my
11318 that
11112 in
...

```

Unix tools of this sort can be very handy in building quick word count statistics for any corpus.

2.3.2 Word Tokenization and Normalization

tokenization
normalization

The simple UNIX tools above were fine for getting rough word statistics but more sophisticated algorithms are generally necessary for **tokenization**, the task of segmenting running text into words, and **normalization**, the task of putting words/tokens in a standard format.

While the Unix command sequence just removed all the numbers and punctuation, for most NLP applications we'll need to keep these in our tokenization. We often want to break off punctuation as a separate token; commas are a useful piece of information for parsers, periods help indicate sentence boundaries. But we'll often want to keep the punctuation that occurs word internally, in examples like *m.p.h.*, *Ph.D.*, *AT&T*, *cap'n*. Special characters and numbers will need to be kept in prices (\$45.55) and dates (01/02/06); we don't want to segment that price into separate tokens of "45" and "55". And there are URLs (<http://www.stanford.edu>), Twitter hashtags (#nlproc), or email addresses (someone@cs.colorado.edu).

Number expressions introduce other complications as well; while commas normally appear at word boundaries, commas are used inside numbers in English, every three digits: 555,500.50. Languages, and hence tokenization requirements, differ on this; many continental European languages like Spanish, French, and German, by contrast, use a comma to mark the decimal point, and spaces (or sometimes periods) where English puts commas, for example, 555 500,50.

A tokenizer can also be used to expand clitic contractions that are marked by apostrophes, for example, converting *what're* to the two tokens *what are*, and *we're* to *we are*. Some such contractions occur in other alphabetic languages, including articles and pronouns in French (*j'ai*, *l'homme*).

Depending on the application, tokenization algorithms may also tokenize multiword expressions like *New York* or *rock 'n' roll* as a single token, which requires a multiword expression dictionary of some sort. This makes tokenization intimately tied up with **named entity detection** the task of detecting names, dates, and organizations Chapter 18.

Penn Treebank
tokenization

One commonly used tokenization standard is known as the **Penn Treebank tokenization** standard, used for the parsed corpora (treebanks) released by the Linguistic Data Consortium (LDC), the source of many useful datasets. This standard separates out clitics (*doesn't* becomes *does* plus *n't*), keeps hyphenated words together, and separates out all punctuation:

Input: "The San Francisco-based restaurant," they said, "doesn't charge \$10".

Output:

"	The	San	Francisco-based	restaurant	,	"	they		
said	,	"	does	n't	charge	\$	10	"	.

Tokens can also be **normalized**, in which a single normalized form is chosen for words with multiple forms like *USA* and *US* or *uh-huh* and *uhhuh*. This standardization may be valuable, despite the spelling information that is lost in the normalization process. For information retrieval, we might want a query for *US* to match a document that has *USA*; for information extraction we might want to extract coherent information that is consistent across differently-spelled instances.

case folding

Case folding is another kind of normalization. For tasks like speech recognition and information retrieval, everything is mapped to lower case. For sentiment anal-

ysis and other text classification tasks, information extraction, and machine translation, by contrast, case is quite helpful and case folding is generally not done (losing the difference, for example, between *US* the country and *us* the pronoun can outweigh the advantage in generality that case folding provides).

In practice, since tokenization needs to be run before any other language processing, it is important for it to be very fast. The standard method for tokenization/normalization is therefore to use deterministic algorithms based on regular expressions compiled into very efficient finite state automata. Carefully designed deterministic algorithms can deal with the ambiguities that arise, such as the fact that the apostrophe needs to be tokenized differently when used as a genitive marker (as in *the book's cover*), a quotative as in *'The other class', she said*, or in clitics like *they're*. We'll discuss this use of automata in Chapter 3.

2.3.3 Word Segmentation in Chinese: the MaxMatch algorithm

hanzi

maximum
matching

Some languages, including Chinese, Japanese, and Thai, do not use spaces to mark potential word-boundaries, and so require alternative segmentation methods. In Chinese, for example, words are composed of characters known as **hanzi**. Each character generally represents a single morpheme and is pronounceable as a single syllable. Words are about 2.4 characters long on average. A simple algorithm that does remarkably well for segmenting Chinese, and often used as a baseline comparison for more advanced methods, is a version of greedy search called **maximum matching** or sometimes **MaxMatch**. The algorithm requires a dictionary (wordlist) of the language.

The maximum matching algorithm starts by pointing at the beginning of a string. It chooses the longest word in the dictionary that matches the input at the current position. The pointer is then advanced to the end of that word in the string. If no word matches, the pointer is instead advanced one character (creating a one-character word). The algorithm is then iteratively applied again starting from the new pointer position. Fig. 2.11 shows a version of the algorithm.

```
function MAXMATCH(sentence, dictionary D) returns word sequence W

  if sentence is empty
    return empty list
  for i ← length(sentence) downto 1
    firstword = first i chars of sentence
    remainder = rest of sentence
    if InDictionary(firstword, D)
      return list(firstword, MaxMatch(remainder, dictionary))

  # no word was found, so make a one-character word
  firstword = first char of sentence
  remainder = rest of sentence
  return list(firstword, MaxMatch(remainder, dictionary))
```

Figure 2.11 The MaxMatch algorithm for word segmentation.

MaxMatch works very well on Chinese; the following example shows an application to a simple Chinese sentence using a simple Chinese lexicon available from the Linguistic Data Consortium:

Input: 他特别喜欢北京烤鸭 “He especially likes Peking duck”
Output: 他 特别 喜欢 北京烤鸭
 He especially likes Peking duck

MaxMatch doesn’t work as well on English. To make the intuition clear, we’ll create an example by removing the spaces from the beginning of Turing’s famous quote “We can only see a short distance ahead”, producing “wecanonlyseeashortdistanceahead”. The MaxMatch results are shown below.

Input: wecanonlyseeashortdistanceahead
Output: we canon l y see ash ort distance ahead

On English the algorithm incorrectly chose *canon* instead of stopping at *can*, which left the algorithm confused and having to create single-character words *l* and *y* and use the very rare word *ort*.

The algorithm work better in Chinese than English, because Chinese has much shorter words than English. We can quantify how well a segmenter works using a metric called **Word Error Rate**. We compare our output segmentation with a perfect hand-segmented (‘gold’) sentence, seeing how many words differ. The metric we use, **word error rate**, is just the normalized minimum edit distance in words: the number of word insertions, deletions, and substitutions divided by the length of the gold sentence in words; we’ll see in Section 2.4 how to compute the edit distance. Even in Chinese, however, MaxMatch has problems, for example dealing with **unknown words** (words not in the dictionary) or genres that differ a lot from the assumptions made by the dictionary builder.

The most accurate Chinese segmentation algorithm generally use statistical **sequence models** trained via supervised machine learning on hand-segmented training sets; we’ll introduce sequence models in Chapter 8.

2.3.4 Lemmatization and Stemming

Lemmatization is the task of determining that two words have the same root, despite their surface differences. The words *am*, *are*, and *is* have the shared lemma *be*; the words *dinner* and *dinners* both have the lemma *dinner*. Representing a word by its lemma is important for web search, since we want to find pages mentioned *woodchucks* if we search for *woodchuck*. This is especially important in morphologically complex languages like Russian, where for example the word *Moscow* has different endings in the phrases *Moscow*, *of Moscow*, *from Moscow*, and so on. Lemmatizing each of these forms to the same lemma will let us find all mentions of Moscow. The lemmatized form of a sentence like *He is reading detective stories* would thus be *He be read detective story*.

How is lemmatization done? The most sophisticated methods for lemmatization involve complete **morphological parsing** of the word. **Morphology** is the study of the way words are built up from smaller meaning-bearing units called **morphemes**. Two broad classes of morphemes can be distinguished: **stems**—the central morpheme of the word, supplying the main meaning— and **affixes**—adding “additional” meanings of various kinds. So, for example, the word *fox* consists of one morpheme (the morpheme *fox*) and the word *cats* consists of two: the morpheme *cat* and the morpheme *-s*. A morphological parser takes a word like *cat* and parses it into the two morphemes *cat* and *s*, or a Spanish word like *amaren* (‘if in the future they would love’) into the morphemes *amar* ‘to love’, *3PL*, and *future subjunctive*. We’ll introduce morphological parsing in Chapter 3.

Word Error
Rate

word error rate

morpheme
stem
affix

The Porter Stemmer

stemming
Porter stemmer

While using finite-state transducers to build a full morphological parser is the most general way to deal with morphological variation in word forms, we sometimes make use of simpler but cruder chopping off of affixes. This naive version of morphological analysis is called **stemming**, and one of the most widely used stemming algorithms is the simple and efficient [Porter \(1980\)](#) algorithm. The Porter stemmer applied to the following paragraph:

This was not the map we found in Billy Bones's chest, but
an accurate copy, complete in all things-names and heights
and soundings-with the single exception of the red crosses
and the written notes.

produces the following stemmed output:

Thi wa not the map we found in Billi Bone s chest but an
accur copi complet in all thing name and height and sound
with the singl except of the red cross and the written note

cascade

The algorithm is based on series of rewrite rules run in series, as a **cascade**, in which the output of each pass is fed as input to the next pass; here is a sampling of the rules:

ATIONAL → ATE (e.g., relational → relate)
ING → ε if stem contains vowel (e.g., motoring → motor)
SSES → SS (e.g., grasses → grass)

Detailed rule lists for the Porter stemmer, as well as code (in Java, Python, etc.) can be found on Martin Porter's homepage; see also the original paper ([Porter, 1980](#)).

Simple stemmers can be useful in cases where we need to collapse across different variants of the same lemma. Nonetheless they do tend to commit errors of both over- and under-generalizing, as shown in the table below ([Krovetz, 1993](#)):

Errors of Commission		Errors of Omission	
organization	organ	European	Europe
doing	doe	analysis	analyzes
numerical	numerous	noise	noisy
policy	police	sparse	sparsity

2.3.5 Sentence Segmentation

Sentence
segmentation

Sentence segmentation is another important step in text processing. The most useful cues for segmenting a text into sentences are punctuation like periods, question marks, exclamation points. Question marks and exclamation points are relatively unambiguous markers of sentence boundaries. Periods, on the other hand, are more ambiguous. The period character “.” is ambiguous between a sentence boundary marker and a marker of abbreviations like *Mr.* or *Inc.* The previous sentence that you just read showed an even more complex case of this ambiguity, in which the final period of *Inc.* marked both an abbreviation and the sentence boundary marker. For this reason, sentence tokenization and word tokenization may be addressed jointly.

In general, sentence tokenization methods work by building a binary classifier (based on a sequence of rules or on machine learning) that decides if a period is part

of the word or is a sentence-boundary marker. In making this decision, it helps to know if the period is attached to a commonly used abbreviation; thus, an abbreviation dictionary is useful.

State-of-the-art methods for sentence tokenization are based on machine learning and are introduced in later chapters.

2.4 Minimum Edit Distance

Much of natural language processing is concerned with measuring how similar two strings are. For example in spelling correction, the user typed some errorful string—let’s say *graffe*—and we want to know what the user meant. The user probably intended a word that is similar to *graffe*. Among candidate similar words, the word *giraffe*, which differs by only one letter from *graffe*, seems intuitively to be more similar than, say *grail* or *graf*, which differ in more letters. Another example comes from **coreference**, the task of deciding whether two strings such as the following refer to the same entity:

Stanford President John Hennessy
Stanford University President John Hennessy

Again, the fact that these two strings are very similar (differing by only one word) seems like useful evidence to making a decision that that they might be coreferent.

minimum edit
distance

Minimum edit distance gives us a way to quantify both of these intuitions about string similarity. More formally, the **minimum edit distance** between two strings is defined as the minimum number of editing operations (operations like insertion, deletion, substitution) needed to transform one string into another.

alignment

The gap between *intention* and *execution*, for example, is 5 (delete an *i*, substitute *e* for *n* and *x* for *t*, insert *c*, substitute *u* for *n*). It’s much easier to see this by looking at the most important visualization for string distances, an **alignment** between the two strings, shown in Fig. 2.12. Given two sequences, an **alignment** is a correspondence between substrings of the two sequences. Thus, we say *i* **aligns** with the empty string, *N* with *E*, and so on. Beneath the aligned strings is another representation; a series of symbols expressing an **operation list** for converting the top string into the bottom string: **d** for deletion, **s** for substitution, **i** for insertion.




Figure 2.12 Representing the minimum edit distance between two strings as an **alignment**. The final row gives the operation list for converting the top string into the bottom string: **d** for deletion, **s** for substitution, **i** for insertion.

We can also assign a particular cost or weight to each of these operations. The **Levenshtein** distance between two sequences is the simplest weighting factor in which each of the three operations has a cost of 1 (Levenshtein, 1966)—we assume that the substitution of a letter for itself, for example, *t* for *t*, has zero cost. The Levenshtein distance between *intention* and *execution* is 5. Levenshtein also proposed

an alternative version of his metric in which each insertion or deletion has a cost of 1 and substitutions are not allowed. (This is equivalent to allowing substitution, but giving each substitution a cost of 2 since any substitution can be represented by one insertion and one deletion). Using this version, the Levenshtein distance between *intention* and *execution* is 8.

2.4.1 The Minimum Edit Distance Algorithm

How do we find the minimum edit distance? We can think of this as a search task, in which we are searching for the shortest path—a sequence of edits—from one string to another.




Figure 2.13 Finding the edit distance viewed as a search problem

The space of all possible edits is enormous, so we can't search naively. However, lots of distinct edit paths will end up in the same state (string), so rather than recomputing all those paths, we could just remember the shortest path to a state each time we saw it. We can do this by using **dynamic programming**. Dynamic programming is the name for a class of algorithms, first introduced by [Bellman \(1957\)](#), that apply a table-driven method to solve problems by combining solutions to sub-problems. Some of the most commonly used algorithms in natural language processing make use of dynamic programming, such as the **Viterbi** and **forward** algorithms (Chapter 7) and the **CKY** algorithm for parsing (Chapter 12).

The intuition of a dynamic programming problem is that a large problem can be solved by properly combining the solutions to various sub-problems. Consider the shortest path of transformed words that represents the minimum edit distance between the strings *intention* and *execution* shown in Fig. 2.14.

i n t e n t i o n	← delete i
n t e n t i o n	← substitute n by e
e t e n t i o n	← substitute t by x
e x e n t i o n	← insert u
e x e n u t i o n	← substitute n by c
e x e c u t i o n	

Figure 2.14 Path from *intention* to *execution*.

Imagine some string (perhaps it is *exention*) that is in this optimal path (whatever it is). The intuition of dynamic programming is that if *exention* is in the optimal operation list, then the optimal sequence must also include the optimal path from *intention* to *exention*. Why? If there were a shorter path from *intention* to *exention*, then we could use it instead, resulting in a shorter overall path, and the optimal sequence wouldn't be optimal, thus leading to a contradiction.

The **minimum edit distance** algorithm was named by [Wagner and Fischer \(1974\)](#)

dynamic
programming

minimum edit
distance

but independently discovered by many people (summarized later, in the Historical Notes section of Chapter 7).

Let's first define the minimum edit distance between two strings. Given two strings, the source string X of length n , and target string Y of length m , we'll define $D(i, j)$ as the edit distance between $X[1..i]$ and $Y[1..j]$, i.e., the first i characters of X and the first j characters of Y . The edit distance between X and Y is thus $D(n, m)$.

We'll use dynamic programming to compute $D(n, m)$ bottom up, combining solutions to subproblems. In the base case, with a source substring of length i but an empty target string, going from i characters to 0 requires i deletes. With a target substring of length j but an empty source going from 0 characters to j characters requires j inserts. Having computed $D(i, j)$ for small i, j we then compute larger $D(i, j)$ based on previously computed smaller values. The value of $D(i, j)$ is computed by taking the minimum of the three possible paths through the matrix which arrive there:

$$D[i, j] = \min \begin{cases} D[i-1, j] + \text{del-cost}(\text{source}[i]) \\ D[i, j-1] + \text{ins-cost}(\text{target}[j]) \\ D[i-1, j-1] + \text{sub-cost}(\text{source}[i], \text{target}[j]) \end{cases}$$

If we assume the version of Levenshtein distance in which the insertions and deletions each have a cost of 1 ($\text{ins-cost}(\cdot) = \text{del-cost}(\cdot) = 1$), and substitutions have a cost of 2 (except substitution of identical letters have zero cost), the computation for $D(i, j)$ becomes:

$$D[i, j] = \min \begin{cases} D[i-1, j] + 1 \\ D[i, j-1] + 1 \\ D[i-1, j-1] + \begin{cases} 2; & \text{if } \text{source}[i] \neq \text{target}[j] \\ 0; & \text{if } \text{source}[i] = \text{target}[j] \end{cases} \end{cases}$$

The algorithm itself is summarized in Fig. 2.15 and Fig. 2.16 shows the results of applying the algorithm to the distance between *intention* and *execution* with the version of Levenshtein in Eq. 2.5.

Knowing the minimum edit distance is useful for algorithms like finding potential spelling error corrections. But the edit distance algorithm is important in another way; with a small change, it can also provide the minimum cost **alignment** between two strings. Aligning two strings is useful throughout speech and language processing. In speech recognition, minimum edit distance alignment is used to compute word error rate in speech recognition (Chapter 25). Alignment plays a role in machine translation, in which sentences in a parallel corpus (a corpus with a text in two languages) need to be matched to each other.

To extend the edit distance algorithm to produce an alignment, we can start by visualizing an alignment as a path through the edit distance matrix. Figure 2.17 shows this path with the boldfaced cell. Each boldfaced cell represents an alignment of a pair of letters in the two strings. If two boldfaced cells occur in the same row, there will be an insertion in going from the source to the target; two boldfaced cells in the same column indicates a deletion.

Figure 2.17 also shows the intuition of how to compute this alignment path. The computation proceeds in two steps. In the first step, we augment the minimum edit distance algorithm to store backpointers in each cell. The backpointer from a cell points to the previous cell (or cells) that we came from in entering the current cell.

```

function MIN-EDIT-DISTANCE(source, target) returns min-distance

   $n \leftarrow \text{LENGTH}(\text{source})$ 
   $m \leftarrow \text{LENGTH}(\text{target})$ 
  Create a distance matrix distance[ $n+1, m+1$ ]

  # Initialization: the zeroth row and column is the distance from the empty string
   $D[0,0] = 0$ 
  for each row  $i$  from 1 to  $n$  do
     $D[i,0] \leftarrow D[i-1,0] + \text{del-cost}(\text{source}[i])$ 
  for each column  $j$  from 1 to  $m$  do
     $D[0,j] \leftarrow D[0,j-1] + \text{ins-cost}(\text{target}[j])$ 

  # Recurrence relation:
  for each row  $i$  from 1 to  $n$  do
    for each column  $j$  from 1 to  $m$  do
       $D[i,j] \leftarrow \text{MIN}( D[i-1,j] + \text{del-cost}(\text{source}[i]),$ 
                           $D[i-1,j-1] + \text{sub-cost}(\text{source}[i], \text{target}[j]),$ 
                           $D[i,j-1] + \text{ins-cost}(\text{target}[j]))$ 

  # Termination
  return  $D[n,m]$ 

```

Figure 2.15 The minimum edit distance algorithm, an example of the class of dynamic programming algorithms. The various costs can either be fixed (e.g., $\forall x, \text{ins-cost}(x) = 1$) or can be specific to the letter (to model the fact that some letters are more likely to be inserted than others). We assume that there is no cost for substituting a letter for itself (i.e., $\text{sub-cost}(x, x) = 0$).

Src\Tar	#	e	x	e	c	u	t	i	o	n
#	0	1	2	3	4	5	6	7	8	9
i	1	2	3	4	5	6	7	6	7	8
n	2	3	4	5	6	7	8	7	8	7
t	3	4	5	6	7	8	7	8	9	8
e	4	3	4	5	6	7	8	9	10	9
n	5	4	5	6	7	8	9	10	11	10
t	6	5	6	7	8	9	8	9	10	11
i	7	6	7	8	9	10	9	8	9	10
o	8	7	8	9	10	11	10	9	8	9
n	9	8	9	10	11	12	11	10	9	8

Figure 2.16 Computation of minimum edit distance between *intention* and *execution* with the algorithm of Fig. 2.15, using Levenshtein distance with cost of 1 for insertions or deletions, 2 for substitutions. In italics are the initial values representing the distance from the empty string.

backtrace

We've shown a schematic of these backpointers in Fig. 2.17, after a similar diagram in Gusfield (1997). Some cells have multiple backpointers because the minimum extension could have come from multiple previous cells. In the second step, we perform a **backtrace**. In a backtrace, we start from the last cell (at the final row and column), and follow the pointers back through the dynamic programming matrix. Each complete path between the final cell and the initial cell is a minimum distance alignment. Exercise 2.7 asks you to modify the minimum edit distance algorithm to store the pointers and compute the backtrace to output an alignment.

	#	e	x	e	c	u	t	i	o	n
#	0	1	2	3	4	5	6	7	8	9
i	1	↖↖↖ 2	↖↖↖ 3	↖↖↖ 4	↖↖↖ 5	↖↖↖ 6	↖↖↖ 7	↖ 6	↖ 7	↖ 8
n	2	↖↖↖ 3	↖↖↖ 4	↖↖↖ 5	↖↖↖ 6	↖↖↖ 7	↖↖↖ 8	↖ 7	↖↖↖ 8	↖ 7
t	3	↖↖↖ 4	↖↖↖ 5	↖↖↖ 6	↖↖↖ 7	↖↖↖ 8	↖ 7	↖↖↖ 8	↖↖↖ 9	↖ 8
e	4	↖ 3	↖ 4	↖↖↖ 5	↖↖↖ 6	↖↖↖ 7	↖↖↖ 8	↖↖↖ 9	↖↖↖ 10	↖ 9
n	5	↖ 4	↖↖↖ 5	↖↖↖ 6	↖↖↖ 7	↖↖↖ 8	↖↖↖ 9	↖↖↖ 10	↖↖↖ 11	↖↖↖ 10
t	6	↖ 5	↖↖↖ 6	↖↖↖ 7	↖↖↖ 8	↖↖↖ 9	↖ 8	↖ 9	↖↖↖ 10	↖↖↖ 11
i	7	↖ 6	↖↖↖ 7	↖↖↖ 8	↖↖↖ 9	↖↖↖ 10	↖ 9	↖ 8	↖ 9	↖↖↖ 10
o	8	↖ 7	↖↖↖ 8	↖↖↖ 9	↖↖↖ 10	↖↖↖ 11	↖ 10	↖ 9	↖ 8	↖ 9
n	9	↖ 8	↖↖↖ 9	↖↖↖ 10	↖↖↖ 11	↖↖↖ 12	↖ 11	↖ 10	↖ 9	↖ 8

Figure 2.17 When entering a value in each cell, we mark which of the three neighboring cells we came from with up to three arrows. After the table is full we compute an **alignment** (minimum edit path) by using a **backtrace**, starting at the **8** in the lower-right corner and following the arrows back. The sequence of bold cells represents one possible minimum cost alignment between the two strings.

While we worked our example with simple Levenshtein distance, the algorithm in Fig. 2.15 allows arbitrary weights on the operations. For spelling correction, for example, substitutions are more likely to happen between letters that are next to each other on the keyboard. We'll discuss how these weights can be estimated in Ch. 5. The Viterbi algorithm, for example, is an extension of minimum edit distance that uses probabilistic definitions of the operations. Instead of computing the “minimum edit distance” between two strings, Viterbi computes the “maximum probability alignment” of one string with another. We'll discuss this more in Chapter 7.

2.5 Summary

This chapter introduced a fundamental tool in language processing, the **regular expression**, and showed how to perform basic **text normalization** tasks including **word segmentation** and **normalization**, **sentence segmentation**, and **stemming**. We also introduce the important **minimum edit distance** algorithm for comparing strings. Here's a summary of the main points we covered about these ideas:

- The **regular expression** language is a powerful tool for pattern-matching.
- Basic operations in regular expressions include **concatenation** of symbols, **disjunction** of symbols (`[]`, `|`, and `.`), **counters** (`*`, `+`, and `{n,m}`), **anchors** (`^`, `$`) and precedence operators (`(,)`).
- **Word tokenization and normalization** are generally done by cascades of simple regular expressions substitutions or finite automata.
- The **Porter algorithm** is a simple and efficient way to do **stemming**, stripping off affixes. It does not have high accuracy but may be useful for some tasks.
- The **minimum edit distance** between two strings is the minimum number of operations it takes to edit one into the other. Minimum edit distance can be computed by **dynamic programming**, which also results in an **alignment** of the two strings.

Bibliographical and Historical Notes

Kleene (1951) and (1956) first defined regular expressions and the finite automaton, based on the McCulloch-Pitts neuron. Ken Thompson was one of the first to build regular expressions compilers into editors for text searching (Thompson, 1968). His editor *ed* included a command “g/regular expression/p”, or Global Regular Expression Print, which later became the Unix *grep* utility.

Text normalization algorithms has been applied since the beginning of the field. One of the earliest widely-used stemmers was Lovins (1968). Stemming was also applied early to the digital humanities, by Packard (1973), who built an affix-stripping morphological parser for Ancient Greek. Currently a wide variety of code for tokenization and normalization is available, such as the Stanford Tokenizer (<http://nlp.stanford.edu/software/tokenizer.shtml>) or specialized tokenizers for Twitter (O’Connor et al., 2010), or for sentiment (<http://sentiment.christopherpotts.net/tokenizing.html>). See Palmer (2012) for a survey of text preprocessing. While the max-match algorithm we describe is commonly used as a segmentation baseline in languages like Chinese, higher accuracy algorithms like the Stanford CRF segmenter, are based on sequence models; see Tseng et al. (2005) and Chang et al. (2008). NLTK is an essential tool that offers both useful Python libraries (<http://www.nltk.org>) and textbook descriptions (Bird et al., 2009). of many algorithms including text normalization and corpus interfaces.

For more on Herdan’s law and Heaps’ Law, see Herdan (1960, p. 28), Heaps (1978), Egghe (2007) and Baayen (2001); Yasseri et al. (2012) discuss the relationship with other measures of linguistic complexity. For more on edit distance, see the excellent Gusfield (1997). Our example measuring the edit distance from ‘intention’ to ‘execution’ was adapted from Kruskal (1983). There are various publicly available packages to compute edit distance, including Unix *diff* and the NIST *sclite* program (NIST, 2005).

In his autobiography Bellman (1984) explains how he originally came up with the term *dynamic programming*:

“...The 1950s were not good years for mathematical research. [the] Secretary of Defense ...had a pathological fear and hatred of the word, research... I decided therefore to use the word, “programming”. I wanted to get across the idea that this was dynamic, this was multi-stage... I thought, let’s ... take a word that has an absolutely precise meaning, namely dynamic... it’s impossible to use the word, dynamic, in a pejorative sense. Try thinking of some combination that will possibly give it a pejorative meaning. It’s impossible. Thus, I thought dynamic programming was a good name. It was something not even a Congressman could object to.”

Exercises

2.1 Write regular expressions for the following languages.

1. the set of all alphabetic strings;
2. the set of all lower case alphabetic strings ending in a *b*;

3. the set of all strings from the alphabet a, b such that each a is immediately preceded by and immediately followed by a b ;
- 2.2** Write regular expressions for the following languages. By “word”, we mean an alphabetic string separated from other words by whitespace, any relevant punctuation, line breaks, and so forth.
1. the set of all strings with two consecutive repeated words (e.g., “Humbert Humbert” and “the the” but not “the bug” or “the big bug”);
 2. all strings that start at the beginning of the line with an integer and that end at the end of the line with a word;
 3. all strings that have both the word *grotto* and the word *raven* in them (but not, e.g., words like *grottos* that merely *contain* the word *grotto*);
 4. write a pattern that places the first word of an English sentence in a register. Deal with punctuation.
- 2.3** Implement an ELIZA-like program, using substitutions such as those described on page 9. You may choose a different domain than a Rogerian psychologist, if you wish, although keep in mind that you would need a domain in which your program can legitimately engage in a lot of simple repetition.
- 2.4** Compute the edit distance (using insertion cost 1, deletion cost 1, substitution cost 1) of “leda” to “deal”. Show your work (using the edit distance grid).
- 2.5** Figure out whether *drive* is closer to *brief* or to *divers* and what the edit distance is to each. You may use any version of *distance* that you like.
- 2.6** Now implement a minimum edit distance algorithm and use your hand-computed results to check your code.
- 2.7** Augment the minimum edit distance algorithm to output an alignment; you will need to store pointers and add a stage to compute the backtrace.
- 2.8** Implement the MaxMatch algorithm.
- 2.9** To test how well your MaxMatch algorithm works, create a test set by removing spaces from a set of sentences. Implement the Word Error Rate metric (the number of word insertions + deletions + substitutions, divided by the length in words of the correct string) and compute the WER for your test set.

- Baayen, R. H. (2001). *Word frequency distributions*. Springer.
- Bellman, R. (1957). *Dynamic Programming*. Princeton University Press.
- Bellman, R. (1984). *Eye of the Hurricane: an autobiography*. World Scientific Singapore.
- Bird, S., Klein, E., and Loper, E. (2009). *Natural Language Processing with Python*. O'Reilly.
- Chang, P.-C., Galley, M., and Manning, C. D. (2008). Optimizing Chinese word segmentation for machine translation performance. In *Proceedings of ACL Statistical MT Workshop*, pp. 224–232.
- Church, K. W. (1994). Unix for Poets. Slides from 2nd EL-SNET Summer School and unpublished paper ms.
- Clark, H. H. and Fox Tree, J. E. (2002). Using uh and um in spontaneous speaking. *Cognition*, 84, 73–111.
- Egghe, L. (2007). Untangling Herdan's law and Heaps' law: Mathematical and informetric arguments. *JASIST*, 58(5), 702–709.
- Godfrey, J., Holliman, E., and McDaniel, J. (1992). SWITCHBOARD: Telephone speech corpus for research and development. In *ICASSP-92*, San Francisco, pp. 517–520.
- Gusfield, D. (1997). *Algorithms on Strings, Trees, and Sequences: Computer Science and Computational Biology*. Cambridge University Press.
- Heaps, H. S. (1978). *Information retrieval. Computational and theoretical aspects*. Academic Press.
- Herdan, G. (1960). *Type-token mathematics*. The Hague, Mouton.
- Kleene, S. C. (1951). Representation of events in nerve nets and finite automata. Tech. rep. RM-704, RAND Corporation. RAND Research Memorandum.
- Kleene, S. C. (1956). Representation of events in nerve nets and finite automata. In Shannon, C. and McCarthy, J. (Eds.), *Automata Studies*, pp. 3–41. Princeton University Press.
- Krovetz, R. (1993). Viewing morphology as an inference process. In *SIGIR-93*, pp. 191–202.
- Kruskal, J. B. (1983). An overview of sequence comparison. In Sankoff, D. and Kruskal, J. B. (Eds.), *Time Warps, String Edits, and Macromolecules: The Theory and Practice of Sequence Comparison*, pp. 1–44. Addison-Wesley.
- Kučera, H. and Francis, W. N. (1967). *Computational Analysis of Present-Day American English*. Brown University Press, Providence, RI.
- Levenshtein, V. I. (1966). Binary codes capable of correcting deletions, insertions, and reversals. *Cybernetics and Control Theory*, 10(8), 707–710. Original in *Doklady Akademii Nauk SSSR* 163(4): 845–848 (1965).
- Lovins, J. B. (1968). Development of a stemming algorithm. *Mechanical Translation and Computational Linguistics*, 11(1–2), 9–13.
- NIST (2005). Speech recognition scoring toolkit (sctk) version 2.1. <http://www.nist.gov/speech/tools/>.
- O'Connor, B., Krieger, M., and Ahn, D. (2010). Tweetmotif: Exploratory search and topic summarization for twitter. In *ICWSM*.
- Packard, D. W. (1973). Computer-assisted morphological analysis of ancient Greek. In Zampolli, A. and Calzolari, N. (Eds.), *Computational and Mathematical Linguistics: Proceedings of the International Conference on Computational Linguistics*, Pisa, pp. 343–355. Leo S. Olschki.
- Palmer, D. (2012). Text preprocessing. In Indurkha, N. and Damerau, F. J. (Eds.), *Handbook of Natural Language Processing*, pp. 9–30. CRC Press.
- Porter, M. F. (1980). An algorithm for suffix stripping. *Program*, 14(3), 130–127.
- Thompson, K. (1968). Regular expression search algorithm. *Communications of the ACM*, 11(6), 419–422.
- Tseng, H., Chang, P., Andrew, G., Jurafsky, D., and Manning, C. D. (2005). Conditional random field word segmenter. In *Proceedings of the Fourth SIGHAN Workshop on Chinese Language Processing*.
- Wagner, R. A. and Fischer, M. J. (1974). The string-to-string correction problem. *Journal of the Association for Computing Machinery*, 21, 168–173.
- Weizenbaum, J. (1966). ELIZA – A computer program for the study of natural language communication between man and machine. *Communications of the ACM*, 9(1), 36–45.
- Weizenbaum, J. (1976). *Computer Power and Human Reason: From Judgement to Calculation*. W.H. Freeman and Company.
- Yasseri, T., Kornai, A., and Kertész, J. (2012). A practical approach to language complexity: a wikipedia case study. *PloS one*, 7(11).