



北京大学

PEKING UNIVERSITY

JUDGE ONLINE FOR ACM/ICPC



Online Judge Web Board Home Page F.A.Qs Statistical Charts	Problem Set Problems Submit Problem Online Status Prob.ID: <input type="text"/> <input type="button" value="Go"/>	Authors Register Update your info Authors ranklist <input type="text"/> <input type="button" value="Search"/>	Online Contests Current Contest Past Contests Scheduled Contests Award Contest	User User ID: <input type="text"/> Password: <input type="text"/> <input type="button" value="login"/> Register
---	---	---	---	---

Binary Search Heap Construction

Language: ▼

Time Limit: 2000MS

Memory Limit: 30000K

Total Submissions: 11854

Accepted: 3247

Description

Read the statement of problem G for the definitions concerning trees. In the following we define the basic terminology of heaps. A heap is a tree whose internal nodes have each assigned a priority (a number) such that the priority of each internal node is less than the priority of its parent. As a consequence, the root has the greatest priority in the tree, which is one of the reasons why heaps can be used for the implementation of priority queues and for sorting.

A binary tree in which each internal node has both a label and a priority, and which is both a binary search tree with respect to the labels and a heap with respect to the priorities, is called a treap. Your task is, given a set of label-priority-pairs, with unique labels and unique priorities, to construct a treap containing this data.

Input

The input contains several test cases. Every test case starts with an integer n . You may assume that $1 \leq n \leq 50000$. Then follow n pairs of strings and numbers $l_1/p_1, \dots, l_n/p_n$ denoting the label and priority of each node. The strings are non-empty and composed of lower-case letters, and the numbers are non-negative integers. The last test case is followed by a zero.

Output

For each test case output on a single line a treap that contains the specified nodes. A treap is printed as ($<$ left sub-treap $>$ label $>$ priority $>$ right sub-treap $>$). The sub-treaps are printed recursively, and omitted if leafs.

Sample Input

```
7 a/7 b/6 c/5 d/4 e/3 f/2 g/1
7 a/1 b/2 c/3 d/4 e/5 f/6 g/7
7 a/3 b/6 c/4 d/7 e/2 f/5 g/1
0
```

Sample Output

```
(a/7(b/6(c/5(d/4(e/3(f/2(g/1))))))  
(((((a/1)b/2)c/3)d/4)e/5)f/6)g/7)  
(((a/3)b/6(c/4))d/7((e/2)f/5(g/1)))
```

Source

Ulm Local 2004

[\[Submit\]](#) [\[Go Back\]](#) [\[Status\]](#) [\[Discuss\]](#)



[Home Page](#)



[Go Back](#)



[To top](#)

All Rights Reserved 2003-2013 Ying Fuchen,Xu Pengcheng,Xie Di
Any problem, Please [Contact Administrator](#)