

Equivariant Graph Neural Networks

Kfir Eliyahu Ben Eliav Jonathan Kouchly

December 11, 2024

Outline

- 1 Motivation
- 2 Mathematical Background
- 3 Invariant and Equivariant Construction

1 Motivation

2 Mathematical Background

3 Invariant and Equivariant Construction

Motivation

- Our neural networks can operate on data of many types.

Motivation


- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.

Motivation

- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.
- These data types have different structures and qualities, and we would like to build architectures that best suit them.


Motivation

- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.
- These data types have different structures and qualities, and we would like to build architectures that best suit them.




Motivation

- A cat is a cat no matter how you look at it.



Motivation


- A cat is a cat no matter how you look at it.



- It is acceptable to assume that being invariant to the rotation of the cat is a good property for a classification network.


Motivation

- Our focus today is on sets and graph data.



Simple graph

	A	B	C	D
A	0	1	1	1
B	1	0	0	0
C	1	0	0	1
D	1	0	1	0



1 Motivation

2 Mathematical Background

3 Invariant and Equivariant Construction

The Permutation Group S_n

- The permutation group S_n is the group of all permutations of n elements.
- It has $n!$ elements, representing the $n!$ ways to order n elements.
- Given a set $X = \{x_1, x_2, \dots, x_n\}$, a permutation $\pi \in S_n$ is a bijection $\pi : X \rightarrow X$
- e.g. $x = (x_1, x_2, x_3)$, and $\pi = (1, 2, 3) \in S_3$ is the permutation that maps $1 \rightarrow 2$, $2 \rightarrow 3$ and $3 \rightarrow 1$.
- We denote the **action** of π on x as $\pi x = (x_3, x_1, x_2)$.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is *permutation invariant* if $f(x) = f(\pi x)$ for all $\pi \in H$.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is *permutation invariant* if $f(x) = f(\pi x)$ for all $\pi \in H$.

$$f[\text{😊😊😬😞}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

$$f[\text{😊😊😞😬}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is *permutation equivariant* if $\pi f(x) = f(\pi x)$ for all $\pi \in H$.

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is *permutation equivariant* if $\pi f(x) = f(\pi x)$ for all $\pi \in H$.

$$f[\text{😊😊😬😞}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

$$f[\text{😊😊😞😬}] = [0.15 \ 0.1 \ \mathbf{0.8} \ 0.05]$$

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $\pi \in S_n$ can be represented as a permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$,

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $\pi \in S_n$ can be represented as a permutation matrix $P \in \mathbb{R}^{n \times n}$,
- The action of π on X is then PX .

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $\pi \in S_n$ can be represented as a permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$,
- The action of π on X is then $\mathbf{P}X$.
- An invariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{d'}$ such that $f(X) = f(\mathbf{P}X)$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $\pi \in S_n$ can be represented as a permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$,
- The action of π on X is then $\mathbf{P}X$.
- An invariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{d'}$ such that $f(X) = f(\mathbf{P}X)$.
- An equivariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{n \times d'}$ such that $\mathbf{P}f(X) = f(\mathbf{P}X)$.

Permutation of a Set

- Our data is now a graph signal $(A, X) \in \mathbb{R}^{n \times n} \times \mathbb{R}^{n \times d}$.

Permutation of a Set

- Our data is now a graph signal $(A, X) \in \mathbb{R}^{n \times n} \times \mathbb{R}^{n \times d}$.
- A permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$ acts on the adjacency matrix A and the feature matrix X .

Permutation of a Set

- Our data is now a graph signal $(A, X) \in \mathbb{R}^{n \times n} \times \mathbb{R}^{n \times d}$.
- A permutation matrix $\mathbf{P} \in \mathbb{R}^{n \times n}$ acts on the adjacency matrix A and the feature matrix X .
- The action of \mathbf{P} on (A, X) is $(\mathbf{P}^T A \mathbf{P}, \mathbf{P} X)$.

- 1 Motivation
- 2 Mathematical Background
- 3 Invariant and Equivariant Construction

Conclusion

- end

Thank You!