

Equivariant Graph Neural Networks

Kfir Eliyahu Ben Eliav Jonathan Kouchly

December 22, 2024

Outline

- 1 Motivation
- 2 Mathematical Background
- 3 Deep Sets

1 Motivation

2 Mathematical Background

3 Deep Sets

Motivation

- Our neural networks can operate on data of many types.

Motivation


- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.

Motivation

- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.
- These data types have different structures and qualities, and we would like to build architectures that best suit them.


Motivation

- Our neural networks can operate on data of many types.
- We often work with images, text, audio, graphs and more.
- These data types have different structures and qualities, and we would like to build architectures that best suit them.




Motivation

- A cat is a cat no matter how you look at it.



Motivation


- A cat is a cat no matter how you look at it.



- It is acceptable to assume that being invariant to the rotation of the cat is a good property for a classification network.


Motivation

- Our focus today is on sets and graph data.



Simple graph

	A	B	C	D
A	0	1	1	1
B	1	0	0	0
C	1	0	0	1
D	1	0	1	0



Construction of an Equivariant Neural Network

- When constructing an equivariant neural network, two things should always be considered:

Construction of an Equivariant Neural Network

- When constructing an equivariant neural network, two things should always be considered:
 - ① The symmetries of the data:
What inherent structure should our model be oblivious to?

Construction of an Equivariant Neural Network

- When constructing an equivariant neural network, two things should always be considered:
 - 1 The symmetries of the data:
What inherent structure should our model be oblivious to?
 - 2 The space of functions learnable by the network:
Are we fully utilizing the space of functions that are equivariant

1 Motivation

2 Mathematical Background

3 Deep Sets

The Permutation Group S_n

- The permutation group S_n is the group of all permutations of n elements.
- It has $n!$ elements, representing the $n!$ ways to order n elements.
- Given a set $X = \{x_1, x_2, \dots, x_n\}$, a permutation $\pi \in S_n$ is a bijection $\pi : X \rightarrow X$
- e.g. $x = (x_1, x_2, x_3)$, and $\pi = (1, 2, 3) \in S_3$ is the permutation that maps $1 \rightarrow 2$, $2 \rightarrow 3$ and $3 \rightarrow 1$.
- We denote the **action** of π on x as $\pi x = (x_3, x_1, x_2)$.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}$ is permutation invariant if $f(x) = f(\pi x)$ for all $\pi \in H$.

Permutation Invariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}$ is permutation invariant if $f(x) = f(\pi x)$ for all $\pi \in H$.

$$f[\text{😊😊😏😞}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

$$f[\text{😊😊😞😏}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is permutation invariant if $\pi f(x) = f(\pi x)$ for all $\pi \in H$.

Permutation Equivariance

- Let $H \leq S_n$ be a subgroup of the symmetric group.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ is permutation invariant if $\pi f(x) = f(\pi x)$ for all $\pi \in H$.

$$f[\text{😊😊😞😞}] = [0.15 \ 0.1 \ 0.05 \ \mathbf{0.8}]$$

$$f[\text{😊😊😞😞}] = [0.15 \ 0.1 \ \mathbf{0.8} \ 0.05]$$

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $g \in S_n$ can be represented as a permutation matrix $P \in \mathbb{R}^{n \times n}$,

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $g \in S_n$ can be represented as a permutation matrix $P \in \mathbb{R}^{n \times n}$,
- The action of g on X is then PX .

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $g \in S_n$ can be represented as a permutation matrix $P \in \mathbb{R}^{n \times n}$,
- The action of g on X is then PX .
- An invariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{d'}$ such that $f(X) = f(PX)$.

Permutation of a Set

- Assume our set is $X = \{x_1, x_2, \dots, x_n\}$.
- We can represent X as a matrix $X \in \mathbb{R}^{n \times d}$.
- Any permutation $g \in S_n$ can be represented as a permutation matrix $P \in \mathbb{R}^{n \times n}$,
- The action of g on X is then PX .
- An invariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{d'}$ such that $f(X) = f(PX)$.
- An equivariant neural network is a function $f : \mathbb{R}^{n \times d} \rightarrow \mathbb{R}^{n \times d'}$ such that $Pf(X) = f(PX)$.

Permutation of a Graph

- Our data is now a graph adjacency matrix $A \in \mathbb{R}^{n \times n}$.

Permutation of a Graph

- Our data is now a graph adjacency matrix $A \in \mathbb{R}^{n \times n}$.
- A permutation matrix $P \in \mathbb{R}^{n \times n}$ acts on the adjacency matrix A and the feature matrix X .

Equivariant Network Construction

Theorem

Let L be a linear equivariant layer, and let f be a neural network constructed by stacking L and non-linearities σ . Then f is permutation equivariant.

Equivariant Network Construction

Theorem

Let L be a linear equivariant layer, and let f be a neural network constructed by stacking L and non-linearities σ . Then f is permutation equivariant.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

Equivariant Network Construction

Theorem

Let L be a linear equivariant layer, and let f be a neural network constructed by stacking L and non-linearities σ . Then f is permutation equivariant.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

$$f(gx) = L(\sigma(L(\sigma(\dots L(gx) \dots)))) = L(\sigma(L(\dots g\sigma(L(x)) \dots))) = \dots$$

Equivariant Network Construction

Theorem

Let L be a linear equivariant layer, and let f be a neural network constructed by stacking L and non-linearities σ . Then f is permutation equivariant.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

$$f(gx) = L(\sigma(L(\sigma(\dots L(gx) \dots)))) = L(\sigma(L(\dots g\sigma(L(x)) \dots))) = \dots$$

$$gL(\sigma(L(\sigma(\dots L(x) \dots)))) = gf(x)$$



Invariant Network Construction

Theorem

Let f be an equivariant neural network and let ϕ be a permutation invariant function. Then $h = \phi(f(x))$ is a permutation invariant neural network.

Invariant Network Construction

Theorem

Let f be an equivariant neural network and let ϕ be a permutation invariant function. Then $h = \phi(f(x))$ is a permutation invariant neural network.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

Invariant Network Construction

Theorem

Let f be an equivariant neural network and let ϕ be a permutation invariant function. Then $h = \phi(f(x))$ is a permutation invariant neural network.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

$$h(gx) = \phi(f(gx)) = \phi(gf(x)) = \phi(f(x)) = h(x)$$



1 Motivation

2 Mathematical Background

3 Deep Sets

- A seminal work in the field of equivariant neural networks.

- A seminal work in the field of equivariant neural networks.
- Recall the two properties we mentioned earlier (symmetries of the data and the space of functions learnable by the network).

- A seminal work in the field of equivariant neural networks.
- Recall the two properties we mentioned earlier (symmetries of the data and the space of functions learnable by the network).
- *DeepSets* is an architecture that is equivariant to set permutations and is maximally expressive in the space of permutation equivariant functions.

- A seminal work in the field of equivariant neural networks.
- Recall the two properties we mentioned earlier (symmetries of the data and the space of functions learnable by the network).
- *DeepSets* is an architecture that is equivariant to set permutations and is maximally expressive in the space of permutation equivariant functions.
- We are going to see the construction and prove it satisfies equivariance and expressiveness.

- We saw a general structure of an invariant and equivariant network.
- To fill in the details, we need to define the equivariant layer L and the invariant function ϕ .

- We saw a general structure of an invariant and equivariant network.
- To fill in the details, we need to define the equivariant layer L and the invariant function ϕ .

Definition

Consider a set $x = \{x_1, x_2, \dots, x_n\}$, where $x_i \in \mathbb{R}$.
A *DeepSets* layer is defined as

$$L(x) = \lambda Ix + \mathbf{x}1$$

Definition

Consider a set $x = \{x_1, x_2, \dots, x_n\}$, where $x_i \in \mathbb{R}$.

A *DeepSets* layer is defined as

$$L(x) = \lambda I\mathbf{x} + \mathbf{x}\mathbf{1}$$

.

DeepSets Layer

Definition

Consider a set $x = \{x_1, x_2, \dots, x_n\}$, where $x_i \in \mathbb{R}$.

A *DeepSets* layer is defined as

$$L(x) = \lambda Ix + \mathbf{x}\mathbf{1}$$

Theorem

A DeepSets layer is permutation equivariant.

DeepSets Layer

Definition

Consider a set $x = \{x_1, x_2, \dots, x_n\}$, where $x_i \in \mathbb{R}$.

A *DeepSets* layer is defined as

$$L(x) = \lambda \mathbf{I}x + \mathbf{x}\mathbf{1}$$

Theorem

A DeepSets layer is permutation equivariant.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

DeepSets Layer

Definition

Consider a set $x = \{x_1, x_2, \dots, x_n\}$, where $x_i \in \mathbb{R}$.

A *DeepSets* layer is defined as

$$L(x) = \lambda Ix + x\mathbf{1}$$

.

Theorem

A DeepSets layer is permutation equivariant.

Proof.

Let x be a set of n elements, and let $g \in S_n$ be a permutation.

$$L(gx) = \lambda I(gx) + (gx)\mathbf{1} = g(\lambda Ix) + x\mathbf{1} = gL(x)$$



- We have an initial layer L , which we proved is equivariant.

- We have an initial layer L , which we proved is equivariant.
- A deep sets invariant network is now constructed as:

$$f(x) = \phi(L\sigma(L\sigma(\dots L\sigma(L(x))\dots))) \quad \text{where} \quad \phi(x) = \sum_{i=1}^n x_i$$

- We have an initial layer L , which we proved is equivariant.
- A deep sets invariant network is now constructed as:

$$f(x) = \phi(L\sigma(L\sigma(\dots L\sigma(L(x))\dots))) \quad \text{where} \quad \phi(x) = \sum_{i=1}^n x_i$$

- It is easy to see that ϕ is permutation invariant, and thus f is permutation invariant.
- For a classification network, take some classification module ρ (e.g. an MLP), and define the final network as:

$$h(x) = \rho(f(x))$$

- Notice that the network is only defined for sets with elements in \mathbb{R} .
- We can extend this to a set $X \in \mathbb{R}^{n \times d}$ by defining L as:

$$L(x) = \mathbf{X}W_1 + \mathbf{1}\mathbf{1}^T \mathbf{X}W_2$$

- This keeps the general structure of the layer: a linear transformation of the distinct elements of the set summed with the mean of the set.

- We have shown that the *DeepSets* network is permutation invariant.
- We now want to show that it is maximally expressive in the space of permutation invariant functions.

- We have shown that the *DeepSets* network is permutation invariant.
- We now want to show that it is maximally expressive in the space of permutation invariant functions.

Theorem

A DeepSets network is maximally expressive in the space of permutation invariant functions.

- We have shown that the *DeepSets* network is permutation invariant.
- We now want to show that it is maximally expressive in the space of permutation invariant functions.

Theorem

A DeepSets network is maximally expressive in the space of permutation invariant functions.

Proof.

- We have shown that the *DeepSets* network is permutation invariant.
- We now want to show that it is maximally expressive in the space of permutation invariant functions.

Theorem

A DeepSets network is maximally expressive in the space of permutation invariant functions.

Proof.

H.W. (using standard results from approximation theory). ☐

Conclusion

- end

Thank You!