Jacobian-Velocity Bounds for Deployment Risk Under Covariate Drift

Jonathan R. Landers
Independent Researcher
New York, NY, USA
jonathan.robert.landers@gmail.com

***Abstract*—We study long-horizon deployment of a frozen predictor under dynamic covariate shift. A time-domain Poincaré inequality reduces temporal risk volatility to derivative energy, and a Jacobian-velocity theorem identifies directional tangent energy along the deployment path as the governing quantity under explicit along-path regularity and domination assumptions. Under low-rank drift, that quantity reduces to directional Jacobian energy in the drift subspace, motivating drift-aligned tangent regularization (DTR) and a matched monitoring proxy. Rather than smoothing the network isotropically, DTR penalizes sensitivity only along estimated drift directions. We validate the theorem-to-method pipeline in four experiments: a synthetic benchmark for the time-domain inequality, a controlled synthetic comparison against isotropic Jacobian regularization, and two frozen-deployment studies on the UCI Air Quality and Tetouan power-consumption datasets. DTR consistently reduces risk volatility and directional gain relative to standard training, beats isotropic smoothing in the controlled low-rank regime, and improves real-deployment stability on both Air Quality and Tetouan. Moderate drift-subspace misspecification is tolerable while orthogonal misspecification largely removes the benefit.**

***Index Terms*—covariate drift, deployment risk, Jacobian regularization, temporal robustness, distribution shift**

I. Introduction

Distribution shift is often discussed statically, either through source-target generalization gaps in domain adaptation [1] or through dataset-shift taxonomies that separate covariate, label, and concept shift [2]. Long-horizon deployment is different. A model may be frozen while the environment moves continuously, so the relevant object is not a single out-of-domain error but a risk trajectory. Temporal benchmarks and deployment studies make the same point from different angles. Even when labels and architecture are fixed, performance can move materially over time [3]–[6]. The practical question is therefore not only whether shift occurs, but how violently performance can move once deployment begins.

This paper develops a geometric answer. If the feature stream follows a path X_t and the predictor has local tangent map $J_f(X_t)$, then instability is governed not by shift magnitude alone but by the directional interaction between the data velocity $\dot{X}_t$ and the model tangent geometry. The dangerous quantity is $J_f(X_t)\dot{X}_t$. The intuition is simple. The same deployment path can be almost harmless for one model and damaging for another, because only motion through steep tangent directions accumulates into large score variation. If the stream moves through a flat direction, drift can be present without being operationally dangerous. If it moves through a steep direction, even gentle but persistent motion can compound into long-horizon degradation. The paper's central bound formalizes this. Under explicit along-path regularity and directional domination assumptions,

$$\mathrm{Var}_U(r(U)) \leq \frac{\beta^2 T}{\pi^2} \int_0^T \mathbb{E}\|J_f(X_t)\dot{X}_t\|^2 dt.$$

First, a time-domain Poincaré inequality converts temporal volatility into derivative energy. Second, a Jacobian-velocity theorem bounds that energy under explicit along-path assumptions on the deployment performance field. Third, a low-rank drift specialization naturally motivates a drift-aligned regularizer and a matched monitoring proxy. Fourth, we test the resulting story with a synthetic time-domain sanity check, a compact isotropic-versus-directional comparison, and two real frozen-deployment studies on Air Quality and Tetouan. The empirical sequence mirrors the logic of the paper: verify the temporal inequality, compare competing regularizers in the idealized low-rank regime, then move to real deployments where the drift subspace must be estimated. Concretely, the paper identifies directional tangent energy as the quantity governing frozen-model deployment volatility, uses the resulting low-rank reduction to motivate drift-aligned tangent regularization (DTR) and a matched hazard proxy, and gives empirical evidence that the same directional geometry remains visible in both controlled synthetic experiments and two real field deployments.

The paper is deliberately scoped to frozen-model deployment under covariate drift. It does not address general distribution shift or test-time adaptation, but asks specifically what local geometry governs frozen-model degradation and whether that geometry remains visible on real drifting data. Code, scripts, and supplementary materials are available in a public repository [7]. A companion project page with figures and summaries is available at [8].

II. Related Work

The paper sits closest to temporal distribution shift and dynamic deployment evaluation. Classical shift analyses study source-target error under changed input distributions [1], dataset-shift taxonomies separate covariate, label, and concept shift [2], and concept-drift work emphasizes sequential adaptation under evolving streams [3]. More recent benchmark-driven work has made temporal structure explicit, both in naturally

shifted datasets and in stylized train-deploy protocols [4]–[6]. Related theory also studies heterogeneous distribution shift without an explicit temporal deployment path [9]. Here the focus is the volatility of one frozen model along a deployment path rather than a worst-case shift gap.

The paper is also adjacent to test-time adaptation [10]–[12]. Those methods update the model online to track changing data. Here the predictor remains frozen. That restriction is deliberate. It isolates the geometric mechanism of degradation itself and yields a quantity that can be analyzed, regularized, and monitored without mixing in the dynamics of online parameter updates.

Finally, the work draws on two technical lines. The regularization side is related to Jacobian-based control of robustness [13], [14] and to empirical evidence linking sensitivity to generalization [15], but the object here is directional rather than isotropic. Only tangent energy in likely drift directions enters the bound. The monitoring side is related to shift detection, uncertainty under shift, and sequential change detection [16]–[22]. Our hazard score is not presented as a sequentially optimal detector. It is a model-aware proxy matched to the same drift geometry used in training.

III. Setup and Assumptions

Let $t \in [0, T]$ index deployment time. Let $X_t \in \mathbb{R}^d$ denote the covariate process, and let $f_\theta : \mathbb{R}^d \to \mathbb{R}$ be a frozen scalar score function. We study a scalar deployment performance field $g_\theta : \mathbb{R}^d \to \mathbb{R}$ and the associated trajectory

$$r(t) := \mathbb{E}[g_\theta(X_t)]. \tag{1}$$

For classification, a natural example is

$$g_\theta(x) = \mathbb{E}_{Y \sim P_0(\cdot|x)}[\ell(f_\theta(x), Y)],$$

but the theorem below does not rely on this representation alone. Instead, we state the regularity needed to make the risk-trajectory argument defensible. The point of this setup is to separate two roles that are often conflated in shift analyses. The model is frozen, while the covariate stream is allowed to move.

To measure temporal instability, draw $U \sim \mathrm{Unif}[0, T]$ and define

$$\mathrm{Var}_U(r(U)) = \mathbb{E}[(r(U) - \mathbb{E}r(U))^2]. \tag{2}$$

The quantity in (2) is the notion of deployment volatility studied throughout the paper.

Assumption A1 (trajectory regularity). The sample paths $t \mapsto X_t$ are almost surely absolutely continuous and

$$\mathbb{E} \int_0^T \|\dot{X}_t\|^2 dt < \infty.$$

Assumption A2 (chain rule under the expectation). The field g_θ is weakly differentiable, $t \mapsto g_\theta(X_t)$ is almost surely absolutely continuous, and

$$g_\theta(X_t) - g_\theta(X_s) = \int_s^t \nabla g_\theta(X_u)^\top \dot{X}_u \, du,$$

for all $0 \le s < t \le T$ on almost every sample path, with

$$\mathbb{E} \int_0^T |\nabla g_\theta(X_t)^\top \dot{X}_t| dt < \infty.$$

Assumption A3 (score Jacobian well posed and directional domination along deployment). There exists a measurable matrix field J_f such that $J_f(X_t)$ is well defined almost surely for almost every $t \in [0, T]$,

$$\mathbb{E} \int_0^T \|J_f(X_t)\dot{X}_t\|^2 dt < \infty,$$

and there exists $\beta > 0$ such that

$$|\nabla g_\theta(X_t)^\top \dot{X}_t| \le \beta \|J_f(X_t)\dot{X}_t\|$$

for almost every $t \in [0, T]$ on almost every sample path.

Assumption A3 is the paper's main compatibility condition. It should not be read as a consequence of dynamic covariate shift alone. Rather, it asserts that along the realized deployment path, the local change in the chosen performance field is dominated by the local change in the score, and that the score Jacobian is well posed there.

Remark 1 (What A3 means, when it holds, and when it fails)**.** *A3 is deliberately along-path rather than pointwise in every ambient direction. The proof only needs control of $\nabla g_\theta(X_t)^\top \dot{X}_t$ by $J_f(X_t)\dot{X}_t$ along the realized velocity.*

A3 holds in the natural composition case. If $g_\theta(x) = h(f_\theta(x))$, then

$$\nabla g_\theta(X_t)^\top \dot{X}_t = h'(f_\theta(X_t))\, J_f(X_t)\dot{X}_t,$$

so A3 follows with $\beta = \sup |h'|$ whenever $J_f(X_t)$ is well defined almost surely for almost every t. For Bernoulli cross-entropy against a fixed soft target, $|h'| \le 1$, giving $\beta = 1$. The theorem is therefore not ReLU-specific. Smooth predictors fit directly, and piecewise-linear predictors such as ReLU networks fit as soon as the deployment path avoids their nondifferentiability set almost surely for almost every deployment time.

A3 does not follow from pure covariate shift alone. The general risk $g_\theta(x) = \mathbb{E}_{Y \sim P_0(\cdot|x)}[\ell(f_\theta(x), Y)]$ carries an extra $\nabla \eta(x)$ term from the label conditional, which need not be dominated by the score-Jacobian term even when η is time-invariant. A3 also fails under simultaneous concept shift, and at score saturation wherever $\nabla f_\theta(x) = 0$ but $\nabla g_\theta(x) \neq 0$.

IV. Main Theorem Package

The first step is purely temporal.

Lemma 1 (Time-domain derivative-energy control)**.** *If r is absolutely continuous on $[0, T]$, then*

$$\mathrm{Var}_U(r(U)) \le \frac{T}{\pi^2} \int_0^T (r'(t))^2 dt. \tag{3}$$

Proof. Let $\bar{r} = T^{-1} \int_0^T r(t)\, dt$. The Wirtinger inequality yields

$$\int_0^T (r(t) - \bar{r})^2 dt \le \frac{T^2}{\pi^2} \int_0^T (r'(t))^2 dt. \tag{4}$$



Fig. 1. Geometric intuition for drift-aligned instability. The deployment path is the same in both panels, but the local tangent geometry is different. When the drift direction aligns with a steep tangent direction, the score changes rapidly, whereas when the model is flat along that same direction, the score remains stable. Figure 1 visualizes the directional quantity that appears in Theorem 1 and (5).

Divide by T. □

Lemma 1 says volatility is impossible without derivative energy; see (3). The next result identifies the geometric driver of that energy.

Theorem 1 (Jacobian-velocity control of risk volatility)**.** *Assume A1–A3. Then r is absolutely continuous and*

$$\mathrm{Var}_U(r(U)) \le \frac{\beta^2 T}{\pi^2} \int_0^T \mathbb{E}\|J_f(X_t)\dot{X}_t\|^2 dt. \tag{5}$$

Proof. Fix $0 \le s < t \le T$. By Assumption A2 and Fubini,

$$\begin{aligned} r(t) - r(s) &= \mathbb{E}\left[\int_s^t \nabla g_\theta(X_u)^\top \dot{X}_u \, du\right] \\ &= \int_s^t \mathbb{E}[\nabla g_\theta(X_u)^\top \dot{X}_u] \, du. \end{aligned}$$

Hence r is absolutely continuous and, for almost every t,

$$r'(t) = \mathbb{E}[\nabla g_\theta(X_t)^\top \dot{X}_t]. \tag{6}$$

Jensen's inequality and Assumption A3 then give

$$\begin{aligned} (r'(t))^2 &\le \mathbb{E}[(\nabla g_\theta(X_t)^\top \dot{X}_t)^2] \\ &\le \beta^2 \mathbb{E}\|J_f(X_t)\dot{X}_t\|^2. \end{aligned} \tag{7}$$

Apply Lemma 1 and (3). □

Theorem 1 isolates a single instability mechanism for the trajectory in (1). Deployment volatility is driven by accumulated tangent amplification along the realized motion of the data stream, as captured by (5). Figure 1 is a geometric rendering of that statement. In that sense, the theorem turns Jacobian-based sensitivity analysis and regularization [13]–[15] into a statement about temporal deployment risk rather than static local robustness. The bound also has a useful operational reading. Volatility requires two ingredients at once, data motion and tangent gain. If either one is small, long-horizon fluctuation remains small.

The low-rank regime gives the algorithmic specialization.

Corollary 1 (Drift-subspace bound)**.** *Assume the hypotheses of Theorem 1. If*

$$\dot{X}_t = V a_t + \rho_t, \qquad V \in \mathbb{R}^{d\times k},$$

with $V^\top V = I_k$ and $V^\top \rho_t = 0$, then

$$\mathrm{Var}_U(r(U)) \le \frac{2\beta^2 T}{\pi^2}(B_V + B_\rho), \tag{8}$$

where

$$\begin{aligned} B_V &:= \int_0^T \mathbb{E}[\|J_f(X_t)V\|_F^2 \|a_t\|^2] dt, \\ B_\rho &:= \int_0^T \mathbb{E}\|J_f(X_t)\rho_t\|^2 dt. \end{aligned}$$

Proof. By Theorem 1 and (5),

$$\begin{aligned} \|J_f(X_t)\dot{X}_t\|^2 &= \|J_f(X_t)Va_t + J_f(X_t)\rho_t\|^2 \\ &\le 2\|J_f(X_t)Va_t\|^2 + 2\|J_f(X_t)\rho_t\|^2. \end{aligned}$$

Since V has orthonormal columns,

$$\|J_f(X_t)Va_t\|^2 \le \|J_f(X_t)V\|_F^2 \|a_t\|^2.$$

Integrate over t. □

Corollary 1 is the paper's main reduction. When B_ρ is small, the leading stability term in (8) is governed by the directional Jacobian energy in the drift subspace rather than by isotropic smoothness. This is precisely the regime in which low-dimensional temporal drift can be a useful approximation [5] and low-rank change models become algorithmically plausible [20].

V. Method

The theorem package suggests a simple design principle. If instability is created by motion through steep directions, then regularization should flatten the model along directions deployment is expected to traverse, not everywhere at once.

A. Drift-aligned tangent regularization

Let V estimate the dominant drift subspace from unlabeled deployment covariates. Two minimal estimators are sufficient for the present paper. One is a mean-difference direction

$$\Delta\mu_t = \mu_t - \mu_{t-\Delta}, \qquad v_t = \frac{\Delta\mu_t}{\|\Delta\mu_t\|},$$

or the top-k principal directions of the difference cloud $\{X_t - X_{t-\Delta}\}$ over a rolling window.

With a fixed subspace estimate V, we train using

$$\mathcal{L}_{\mathrm{DTR}}(\theta) = \mathbb{E}_{(X,Y)}\ell(f_\theta(X), Y) \;+\; \lambda\mathbb{E}_X\|J_f(X)V\|_F^2. \quad (9)$$

The objective in (9) is not global Jacobian smoothing. It is a directional sensitivity constraint. The model is flattened only along directions expected to dominate future drift. Corollary 1 explains why this is the quantity worth shrinking, and it distinguishes DTR from isotropic Jacobian penalties that aim at broader smoothness or margin control [13], [14]. It is also conceptually adjacent to empirical sensitivity analyses that track related Jacobian quantities without imposing directional structure [15]. In other words, DTR concentrates regularization budget on directions the future trajectory is expected to traverse, rather than spreading it uniformly over directions the deployment path may never visit.

B. Monitoring score

The same geometry yields a matched deployment diagnostic, now at the level of a theorem-motivated proxy rather than the literal corollary integrand. Let

$$\begin{aligned} s_t &:= \|\Delta\mu_t\|/\Delta, \quad g_t := \mathbb{E}\|J_f(X_t)V_t\|_F^2, \\ h_t &:= s_t^2 g_t. \end{aligned} \quad (10)$$

Proposition 1 (Rank-1 bookkeeping for the hazard score)**.** *Consider the rank-1 monitoring proxy used below, so that $V_t = v_t \in \mathbb{R}^d$ is a unit vector. Suppose the block mean difference satisfies*

$$\frac{\Delta\mu_t}{\Delta} = v\bar{a}_t + \bar{\rho}_t, \qquad \|v\| = 1, \qquad v^\top\bar{\rho}_t = 0,$$

where $\bar{a}_t$ is the block-averaged aligned drift coefficient and $\bar{\rho}_t$ is the block-averaged residual drift. Write

$$v_t = \cos\theta_t\, v + \sin\theta_t\, u_t, \qquad u_t^\top v = 0, \qquad \|u_t\| = 1,$$

and define

$$\begin{aligned} G_{\|,t} &:= \mathbb{E}\|J_f(X_t)v\|^2, \\ G_{\perp,t} &:= \mathbb{E}\|J_f(X_t)u_t\|^2, \\ C_t &:= \mathbb{E}\langle J_f(X_t)v, J_f(X_t)u_t\rangle. \end{aligned}$$

Then

$$s_t^2 = |\bar{a}_t|^2 + \|\bar{\rho}_t\|^2$$

and

$$g_t = \cos^2\theta_t\, G_{\|,t} \;+\; \sin^2\theta_t\, G_{\perp,t} \;+\; 2\sin\theta_t\cos\theta_t\, C_t.$$

Consequently,

$$\begin{aligned} h_t = {} & (|\bar{a}_t|^2 + \|\bar{\rho}_t\|^2) \\ & \times \Big(\cos^2\theta_t\, G_{\|,t} \;+\; \sin^2\theta_t\, G_{\perp,t} \;+\; 2\sin\theta_t\cos\theta_t\, C_t\Big). \end{aligned}$$

Proof. The identities are immediate from orthogonal decompositions. The first uses $(\Delta\mu_t)/\Delta = v\bar{a}_t + \bar{\rho}_t$ with $v^\top\bar{\rho}_t = 0$. The second expands $J_f(X_t)v_t = \cos\theta_t\, J_f(X_t)v + \sin\theta_t\, J_f(X_t)u_t$ and takes expectations. □

Proposition 1 makes the proxy gap explicit in the rank-1 monitoring setting. The finite-window drift statistic contributes the residual term $\|\bar{\rho}_t\|^2$, while angular error mixes aligned, orthogonal, and overlap energies through θ_t, $G_{\perp,t}$, and C_t. In that precise bookkeeping sense, h_t matches the leading low-rank quantity from Corollary 1 up to block averaging, residual drift, and subspace-estimation error rather than reproducing the corollary integrand exactly. It becomes large only when the stream is moving quickly *and* the predictor is steep along that motion. Relative to dataset-shift diagnostics [16], uncertainty diagnostics under shift [17], and sequential detection procedures [18], [19], [22], the point of h_t is alignment rather than optimality. It monitors the same directional mechanism singled out by the theory without claiming to be a sequentially optimal detector. This symmetry between training and monitoring is deliberate. The same geometry used to suppress future instability is reused to measure when future instability is likely.

VI. Experiments

A. Synthetic time-domain sanity check

The synthetic study uses the smallest setup that exposes the paper's mechanism. There is one stable signal coordinate, one drifting nuisance coordinate, and a frozen classifier whose tangent geometry can either amplify or suppress that drift. The drift direction is deliberately known so the theorem-to-method link can be read cleanly [5], [6]. Labels are sampled as $Y \sim \mathrm{Bernoulli}(1/2)$ and we write $S = 2Y - 1 \in \{-1, +1\}$. Conditional on S, features are generated as

$$x_1 \sim \mathcal{N}(1.05S, 0.90^2), \qquad x_2 \sim \mathcal{N}(1.25S + \delta(t), 0.55^2).$$

The first coordinate is a stable signal. The second is a nuisance coordinate that is predictive at training time but drifts during deployment. The label mechanism is held fixed throughout. Only $\delta(t)$ changes. The benchmark is intentionally simple. Its job is to make the paper's directional mechanism observable with as little confounding structure as possible.

The drift schedule is monotone and smooth, with speed

$$\begin{aligned} &\dot{\delta}(t) = 0.55 + 1.05e^{-((t-0.33)/0.10)^2} + 0.75e^{-((t-0.76)/0.08)^2}, \\ &\delta(0) = 0, \end{aligned}$$

so the stream contains two periods of rapid motion. We train a one-hidden-layer ReLU classifier with 12 hidden units, binary cross-entropy loss, Adam with learning rate 0.02, and 140



Fig. 2. Synthetic time-domain sanity check. Each point is one trained model evaluated over the drifting deployment path. The horizontal axis is the derivative-energy quantity from Lemma 1 and (3), and the vertical axis is empirical volatility $\mathrm{Var}_U(r(U))$. DTR shifts models toward lower energy and lower volatility.

epochs. Each training set has 1024 examples drawn at $t = 0$, each deployment time uses a fresh sample of 2048 points, and we sweep $\lambda \in \{0, 0.01, 0.03, 0.08\}$ over two random seeds. DTR uses the true drift direction $V = e_2$ so that this experiment isolates the theorem-to-method link rather than subspace-estimation error.

Figure 2 plays the lemma-linked role in the paper's narrative arc. Each point is one trained model, plotted by empirical risk volatility in (2) versus the derivative-energy quantity from Lemma 1 and (3). The points sit below the diagonal, as they should, and DTR moves the cloud toward the lower-left corner. The saved summaries also respect the full Jacobian-velocity upper bound from Theorem 1, but that bound is numerically looser, so the figure emphasizes the sharper temporal step that anchors the rest of the pipeline. Across all eight models, mean volatility falls from 3.13×10^{-3} to 2.62×10^{-4}, while mean directional gain falls from 44.9 to 1.91.

B. Directional versus isotropic smoothing

The main algorithmic question is not whether Jacobian regularization helps in general, but whether directional smoothing beats isotropic smoothing when drift is concentrated in one known direction. We answer that question in the same synthetic environment by replacing the DTR penalty with an isotropic Jacobian penalty

$$\lambda \mathbb{E}\|\nabla f_\theta(X)\|^2,$$

while keeping the directional penalty

$$\lambda \mathbb{E}\|J_f(X)V\|_F^2$$

for DTR, with the same architecture, optimizer, seeds, and sweep $\lambda \in \{0.01, 0.03, 0.08\}$. Under rank-1 drift, isotropic smoothing spends budget in directions the deployment path does not substantially traverse, whereas DTR spends it only along the realized motion. Table I summarizes the mean values across the nonzero-λ sweep. DTR improves on both baselines on every metric. Figure 3 (left) shows the matched $\lambda = 0.03$ comparison.

TABLE I
DIRECTIONAL COMPARISON SHOWING THE MEAN OVER THE NONZERO-λ SWEEP. LOWER IS BETTER ON ALL METRICS.

Method	Deriv. energy	Volatility	Dir. gain	Term. risk
Standard	4.80×10^{-3}	3.13×10^{-3}	44.9	0.171
Isotropic	6.11×10^{-4}	4.46×10^{-4}	2.15	0.168
DTR	3.14×10^{-4}	2.62×10^{-4}	1.91	0.134

We then test drift-subspace misspecification by rotating the one-dimensional subspace used by DTR. Writing the estimated direction as

$$\hat{v}_\alpha = (\sin\alpha, \cos\alpha),$$

its alignment with the true drift direction e_2 is $\cos\alpha$. With the correct subspace, the directional advantage remains strongest. With a mild 20° rotation, volatility rises by a factor of 1.43 and terminal risk by a factor of 1.20 relative to aligned DTR, but both remain far below the standard model. The same cosine-sine bookkeeping used in Proposition 1 helps explain that pattern: small angular error mainly rescales the aligned contribution, whereas large misalignment transfers weight to orthogonal energy. With an orthogonal subspace, the effect largely disappears. Derivative energy rises by a factor of 31.7, volatility by 23.9, and directional gain by 19.4. Figure 3 (right) therefore sharpens the paper's claim in the intended way. DTR is more targeted than isotropic Jacobian smoothing when the drift geometry is right, and its gains depend on keeping the estimated drift subspace reasonably aligned with realized motion.

C. Real field deployments

We next ask whether the same directional story survives on real deployments where the drift subspace must be estimated from unlabeled covariates. We use two complementary regression settings: Air Quality as the direct sensor-drift case, and Tetouan as a weather-driven load-prediction task with fixed label semantics and explicit exogenous covariates.

The UCI Air Quality dataset records hourly outputs of a five-sensor gas array together with temperature and humidity in an Italian city, and the associated field-study paper explicitly discusses sensor drift and seasonal influences over long deployments [23]. We predict the reference CO concentration $\mathrm{CO(GT)}$ from the five sensor channels $\mathrm{PT08.S1}$–$\mathrm{PT08.S5}$ together with T, RH, and AH. Rows with the dataset's -200 missing-value marker are removed, leaving 1573 training points from the first 12 weeks, 580 validation points from the next 4 weeks, and 5191 deployment points grouped into 20 biweekly blocks. The predictor is frozen after training, deployment risk is blockwise mean-squared error, and a fixed two-dimensional drift subspace V is estimated from



Fig. 3. Synthetic directional comparisons. Left shows matched $\lambda = 0.03$ ratios for derivative energy, risk volatility, directional gain, and terminal risk, normalized by the standard model. DTR is lower than isotropic Jacobian regularization on all four metrics. Right shows the same metrics normalized by aligned DTR for the correct subspace, a mild 20° rotation, and a wrong subspace. Mild misspecification is tolerable, but wrong subspaces are not.

unlabeled deployment covariates using the top singular vectors of consecutive biweekly mean-shift vectors. We train a two-hidden-layer ReLU regressor with width 32, Adam with learning rate 0.01, and $\lambda \in \{0, 0.003, 0.01, 0.03, 0.08\}$ over three random seeds. Monitoring uses the same geometry in blockwise rank-1 form: if μ_t is the standardized covariate mean in block t and $\Delta = 1$ block, then

$$s_t = \|\mu_t - \mu_{t-1}\|, \qquad v_t = \frac{\mu_t - \mu_{t-1}}{\|\mu_t - \mu_{t-1}\|},$$
$$g_t = \mathbb{E}[(\nabla f_\theta(X_t)^\top v_t)^2], \qquad h_t = s_t^2 g_t.$$

The Air Quality result supports the same mechanism, even though the theorem is not claimed as an exact model of this field dataset. Across the full nonzero-λ sweep, mean deployment-risk volatility falls from 9.29×10^{-2} to 8.16×10^{-2}, while mean directional gain falls from 8.65×10^{-2} to 6.80×10^{-2}. The representative setting $\lambda = 0.03$ is stronger: mean volatility falls to 6.49×10^{-2} and mean directional gain to 6.09×10^{-2}, with lower mean terminal risk (0.149 versus 0.169). Figure 5 shows one representative seed, where DTR lowers both the risk peak (0.949 versus 1.15) and the mean hazard score (0.148 versus 0.212).

We then test a second real benchmark on the UCI Tetouan City power-consumption dataset [24]. It is a ten-minute 2017 weather-and-load series with three zone-level targets; we predict Zone 1 power consumption from temperature, humidity, wind speed, and diffuse-flow channels. Using the same frozen-model protocol, we train on January–April, validate on May–June, and deploy on July–December in six monthly blocks, yielding 17280/8784/26352 training/validation/deployment points. This benchmark gives a stronger real-data directional result. The selected DTR model ($\lambda = 3 \times 10^{-4}$) reduces deployment MSE from 1.16×10^8 for standard training and 9.31×10^7 for isotropic smoothing to 6.84×10^7, and reduces volatility from 1.09×10^{16} and 4.89×10^{15} to 1.77×10^{15}. Figure 4 shows the



Fig. 4. Tetouan frozen deployment over six monthly blocks. DTR stays below both standard and isotropic training throughout the deployment horizon, with the largest gap in the late-summer high-risk regime.

representative monthly risk trajectory: DTR stays below both baselines throughout deployment, with the largest separation in the late-summer high-risk regime. Air Quality therefore remains the more direct sensor-drift field case, while Tetouan shows that the same drift-aligned geometry can also improve frozen deployment in a cleaner weather-driven regression setting.

VII. Discussion and Limitations

The crucial caution is Assumption A3. Dynamic covariate shift by itself does not imply that the conditional-risk field is controlled by the score Jacobian along the realized path. We impose that domination explicitly because it is exactly what the theorem uses. The result is also not tied to ReLU networks in particular. ReLU models are one admissible class when deployment avoids kink sets almost surely for almost every



Fig. 5. Real field deployment on UCI Air Quality. Left shows biweekly deployment MSE for a standard CO regressor and a DTR regressor after training on the first 12 weeks and freezing the model. Right shows the matched hazard score $h_t = s_t^2 g_t$, with block drift magnitude in the background. DTR suppresses tangent gain along realized motion and therefore flattens both risk and hazard.

deployment time, but smooth models fit the same theorem just as well.

The four empirical pieces play different roles. The time-domain sanity check asks whether the Poincaré step is visible in trained models at all. The isotropic-versus-directional comparison asks whether the low-rank specialization has real design content. The Air Quality and Tetouan studies ask whether the same directional quantities still matter on real frozen deployments once the drift subspace must be estimated. That progression matches the claim: isolate the temporal bound, test the low-rank design implication, then check whether the same directional quantities remain visible on noisier field data.

The low-rank story also depends on estimating a drift subspace. The synthetic misspecification study suggests that moderate angular error is tolerable but large misalignment is not. In the real-data studies we estimate a fixed subspace from unlabeled future covariates, which is more realistic than the aligned synthetic setting but still retrospective. A real online deployment would require rolling estimation of V_t, and the quality of the monitoring score would then depend on residual drift energy and subspace-estimation error. Finally, the Jacobian-velocity bound is an upper bound: useful because it is actionable, not because it is tight in every regime.

VIII. Conclusion

Long-horizon robustness under dynamic shift is best viewed as a tangent-control problem. The data stream contributes a velocity, the model contributes a local linear map, and deployment volatility is governed by their interaction. The central message is simple. Deployment becomes unstable when environmental motion repeatedly passes through directions to which the model is locally sensitive. The theorem package makes this precise, DTR acts on it, and the four experiments test whether the same directional geometry remains operative from clean synthetic settings through to real Air Quality and Tetouan deployments — it does, which is the paper's main empirical finding.

That positioning matters. Relative to temporal-shift benchmarks and static shift analyses [1], [4]–[6], the paper contributes a theorem-backed mechanism: deployment trajectories differ across frozen models because the same environmental motion can encounter very different directional tangent gains. Relative to test-time adaptation [10]–[12], it studies the frozen-model regime in which that geometry can be analyzed directly. Relative to Jacobian smoothing and shift detection [13], [14], [16], [22], it ties training-time regularization and deployment-time monitoring to the same directional notion of drift sensitivity. If future deployment motion is concentrated in a few directions, then robustness should be enforced, measured, and monitored in those directions rather than spread uniformly over the ambient space.

References

[1] S. Ben-David, J. Blitzer, K. Crammer, A. Kulesza, F. Pereira, and J. Wortman Vaughan, "A theory of learning from different domains," *Machine Learning*, vol. 79, no. 1–2, pp. 151–175, 2010.

[2] J. G. Moreno-Torres, T. Raeder, R. Alaiz-Rodriguez, N. V. Chawla, and F. Herrera, "A unifying view on dataset shift in classification," *Pattern Recognition*, vol. 45, no. 1, pp. 521–530, 2012.

[3] J. Gama, I. Zliobaite, A. Bifet, M. Pechenizkiy, and A. Bouchachia, "A survey on concept drift adaptation," *ACM Computing Surveys*, vol. 46, no. 4, pp. 44:1–44:37, 2014.

[4] P. W. Koh, S. Sagawa, H. Marklund, S. M. Xie, M. Zhang, A. Balsubramani, W. Hu, M. Yasunaga, R. L. Phillips, I. Gao, T. Lee, E. David, I. Stavness, W. Guo, B. A. Earnshaw, I. Haque, S. Beery, J. Leskovec, A. Kundaje, E. Pierson, S. Levine, C. Finn, and P. Liang, "Wilds: A benchmark of in-the-wild distribution shifts," in *Proceedings of the 38th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 139, 2021, pp. 5637–5664.

[5] H. Yao, C. Choi, B. Cao, Y. Lee, P. W. Koh, and C. Finn, "Wild-time: A benchmark of in-the-wild distribution shift over time," in *Advances in Neural Information Processing Systems*, 2022.

[6] E. Han, C. Huang, and K. Wang, "Model assessment and selection under temporal distribution shift," in *Proceedings of the 41st International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 235, 2024, pp. 17 374–17 392.

[7] J. R. Landers, "jacobian-velocity-bounds," GitHub repository, 2026, [Online]. Available: https://github.com/jonland82/jacobian-velocity-bounds. Accessed: Apr. 15, 2026.

[8] ——, "Jacobian-velocity bounds project page," Project website, 2026, [Online]. Available: https://jonland82.github.io/jacobian-velocity-bounds/. Accessed: Apr. 15, 2026.

[9] M. Simchowitz, A. Ajay, P. Agrawal, and A. Krishnamurthy, "Statistical learning under heterogeneous distribution shift," in *Proceedings of the 40th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 202, 2023, pp. 31 800–31 851.

[10] Y. Sun, X. Wang, Z. Liu, J. Miller, A. A. Efros, and M. Hardt, "Test-time training with self-supervision for generalization under distribution shifts," in *Proceedings of the 37th International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 119, 2020, pp. 9229–9248.

[11] D. Wang, E. Shelhamer, S. Liu, B. Olshausen, and T. Darrell, "Tent: Fully test-time adaptation by entropy minimization," in *International Conference on Learning Representations*, 2021.

[12] S. Gui, X. Li, and S. Ji, "Active test-time adaptation: Theoretical analyses and an algorithm," in *International Conference on Learning Representations*, 2024.

[13] J. Sokolic, R. Giryes, G. Sapiro, and M. R. D. Rodrigues, "Robust large margin deep neural networks," *IEEE Transactions on Signal Processing*, vol. 65, no. 16, pp. 4265–4280, 2017.

[14] T. Kim and H. Yang, "An infinite-width analysis on the jacobian-regularised training of a neural network," in *Proceedings of the 41st International Conference on Machine Learning*, ser. Proceedings of Machine Learning Research, vol. 235, 2024, pp. 24 584–24 657.

[15] R. Novak, Y. Bahri, D. A. Abolafia, J. Pennington, and J. Sohl-Dickstein, "Sensitivity and generalization in neural networks: An empirical study," *International Conference on Learning Representations*, 2018.

[16] S. Rabanser, S. Günnemann, and Z. C. Lipton, "Failing loudly: An empirical study of methods for detecting dataset shift," in *Advances in Neural Information Processing Systems*, 2019.

[17] Y. Ovadia, E. Fertig, J. Ren, Z. Nado, D. Sculley, S. Nowozin, J. Dillon, B. Lakshminarayanan, and J. Snoek, "Can you trust your model's uncertainty? evaluating predictive uncertainty under dataset shift," in *Advances in Neural Information Processing Systems*, 2019.

[18] S. Wu, E. Diao, J. Ding, T. Banerjee, and V. Tarokh, "Robust quickest change detection for unnormalized models," in *Proceedings of the Thirty-Ninth Conference on Uncertainty in Artificial Intelligence*, ser. Proceedings of Machine Learning Research, vol. 216, 2023, pp. 2314–2323.

[19] Y. Cao and Y. Xie, "Multi-sensor gradual change detection," in *Proceedings of the 53rd Annual Allerton Conference on Communication, Control, and Computing*, 2015, pp. 827–834.

[20] Y. Xie and L. M. Seversky, "Sequential low-rank change detection," in *Proceedings of the 54th Annual Allerton Conference on Communication, Control, and Computing*, 2016, pp. 128–133.

[21] V. Krishnamurthy and L. Snow, "Quickest change detection using time inconsistent anticipatory and quantum decision modeling," in *Proceedings of the 58th Annual Allerton Conference on Communication, Control, and Computing*, 2022, pp. 1–8.

[22] A. Cooper and S. P. Meyn, "Quickest change detection using mismatched cusum extended abstract," in *Proceedings of the 60th Annual Allerton Conference on Communication, Control, and Computing*, 2024, pp. 1–7.

[23] S. De Vito, E. Massera, M. Piga, L. Martinotto, and G. Francia, "On field calibration of an electronic nose for benzene estimation in an urban pollution monitoring scenario," *Sensors and Actuators B: Chemical*, vol. 129, no. 2, pp. 750–757, 2008.

[24] A. Salam and A. El Hibaoui, "Power consumption of tetouan city," UCI Machine Learning Repository, 2018, [Dataset].