COMPUTERS AND INFORMATICS
2757-8259 YYYY, Volume 0 Issue 0
DOI: 10.62189/ci.X Article

When Does SHAP Outperform LIME? Model- and Configuration-Dependent Results from a Paired Tabular Benchmark

Author information is given on the separate title page (masked review).

Submitted: *DD.MM.YYYY*
Accepted: *DD.MM.YYYY*
Published: *DD.MM.YYYY*

Abstract:

~~LIME and SHAP are the most widely used model-agnostic~~Choosing between post-hoc explainers for a tabular ~~models~~model is a decision about faithfulness, stability and computational cost, yet controlled ~~paired~~ comparisons ~~of the two~~ under matched conditions remain scarce. This paper ~~extends an earlier~~reports a paired benchmark of SHAP, LIME, Anchors and DiCE in which every explainer sees the same model, the same test ~~to~~ instances and the ~~full grid of a public benchmark: 75 cells that share model,~~ same seed ~~and sample size, over~~, on one recorded host. The primary benchmark covers five model families on the ~~UCI~~ Adult census-income dataset~~, with Holm-corrected paired tests and~~; six further datasets, chosen to cross feature dimension with feature type, and a configuration sweep are reported as exploratory evidence. Cost is reported as CPU time and as the number of model evaluations, which does not depend on the hardware. [R: main result for fidelity and stability, with effect sizes ~~for five endpoints. SHAP leads on stability (d_z = 3.00), fidelity (d_z = 4.82) and faithfulness gap (d_z = 2.63), and~~.] [R: result for Anchors and DiCE.] [R: cost result, including whether the TreeExplainer ordering between XGBoost and random forests holds when both ensembles are matched in size.] [R: whether the stability ordering holds over the LIME ~~gives sparser explanations. Two results depend on conditions that are usually left implicit. First, the latency ordering depends on the model family: SHAP's TreeExplainer was faster than LIME in every XGBoost cell and slower in every random-forest cell, and LIME was faster for non-tree models (median 53.3 ms vs. 694.6 ms). Second, LIME's near-zero stability on Adult is not a fixed property of the method: it is high on two further tabular datasets and, in a single-model probe, rises with the~~ kernel width~~.~~ and the KernelSHAP budget.] The results support choosing the explainer ~~according to the~~by model architecture, configuration and ~~the~~ latency budget, and they ~~show that a ranking obtained on one dataset and one configuration does not transfer by default. All artifacts are public~~state which claims hold beyond the configurations tested.

Keywords: *Benchmarking, Computational cost, Explainable artificial intelligence, Explanation evaluation, ~~LIME, SHAP~~Feature attribution*

© YYYY Published by peer-reviewed open access scientific journal, Computers and Informatics (C&I) at DergiPark (dergipark.org.tr/ci)

Cite this paper as: Surname, N., & Surname, N., Title of the article, *Computers and Informatics*, YYYY; v(i); pp-pp, https://doi.org/10.62189/ci.0000000

1. INTRODUCTION

A team that deploys a tabular classifier and must explain its predictions faces a concrete decision: which post-hoc explainer to use, for which model, under which latency budget. The candidates differ in the kind of explanation they return. LIME [1] and SHAP [2] ~~are the two most widely used model-agnostic post-hoc explainers for tabular models. A practitioner who must choose one of them needs to know~~return feature attributions, Anchors [3] returns a rule and DiCE [4] a counterfactual. They also differ in how ~~they differ in~~faithfully the ~~properties that matter for the deployment: whether an~~ explanation tracks the model, ~~whether~~how stable it is ~~stable, how many features it uses and how long it takes. Their theoretical differences are well known, but they do~~ under small changes of the input, and how much computation it needs [5–7]. Theory does not ~~by themselves~~ settle the choice across model families~~, sampling regimes and runtime constraints [3, 4].~~

~~The~~ and configurations [8, 9], and the empirical guidance is weaker than the popularity of the ~~two~~ methods suggests~~. Evaluation of explanations is spread over several~~: evaluations use different metric families, and ~~comparisons between~~ the ranking of explainers often ~~depend~~depends as much on the metric ~~chosen~~and the configuration as on the methods ~~themselves [5–7]. Work that uses several metrics shows that fidelity, stability, sparsity and cost carry complementary signals [8, 9]. Controlled comparisons of LIME and SHAP under matched conditions, where the two explainers see the same model, the same instances and the same random seed, remain scarce. Without that pairing, a difference between the methods cannot be separated from a difference between the models or the samples they were run on.~~ [10–12].

Two gaps follow. The first is *control*. Comparisons in which all explainers see the same model, the same instances, the same seed and the same host, so that a difference can be attributed to the explainer, are scarce: published SHAP–LIME comparisons are often case studies in a single domain [13, 14]. Cost needs the same control: it transfers to another deployment only when it is measured on a stated host, as item 2c of the REFORMS checklist for machine-learning-based science recommends [15], and when it is also counted in a unit that does not depend on that host, such as the number of model calls. The second gap is *configuration*. Results are usually reported for one configuration, although the hyperparameters that build LIME's neighborhood [16] or bound KernelSHAP's sampling [7] can change the outcome. Without control and without more than one configuration, a recommendation cannot state the conditions under which it holds.

This paper addresses the two gaps with three contributions. The first closes the gap in control, the second the gap in configuration, and the third states what the results support once both are closed:

1. **A controlled, paired benchmark of four explainers** (SHAP, LIME, Anchors and DiCE) on five model families, with every run on one recorded host, and cost reported as CPU time and as the number of model evaluations, a measure that does not depend on the hardware (Sections 4.1 and 4.2).

2. ~~This paper reports such a paired comparison. It reuses the execution cohort released with an earlier study [10], which introduced the measurement protocol and compared four explainer families. That study already contains a first paired test of SHAP against LIME, on the 45 matched cells of three model families (logistic regression, random forest and XGBoost): SHAP was higher on fidelity, stability and faithfulness gap, and LIME was cheaper and sparser. It announced the analysis on the full grid of 75 cells without reporting it, and it reported averages over conditions only. The present paper completes that contrast on the 75 cells of the five model families, with confidence intervals and effect sizes, and then asks the question that an average over conditions hides: *when does the answer depend on the model and on the configuration?*~~

Configuration-aware results: a sweep over the LIME kernel width and sample size and over the KernelSHAP budget and background, and controls that test whether the stability measurement itself is valid (Sections 4.3 and 4.4).

3. **Bounded recommendations**: every claim is labelled as confirmatory or exploratory and stated with the models, datasets and configurations under which it holds (Section 5).

The paper makes ~~three contributions:~~

~~1. **Paired inferential evidence on the full grid.** The SHAP–LIME difference, tested before on a 45-cell subset, is quantified on the 75 matched cells of the UCI Adult census-income dataset, over five model families, with Holm-corrected paired tests, confidence intervals and effect sizes for five endpoints (Section 4).~~

~~2. **Two conditional results.** The latency ordering of the two methods depends on the model family, and reverses between two tree ensembles (Section 4.4). LIME's near-zero stability on Adult depends on the kernel width and on the feature space, and is high on two further datasets (Sections 4.5 and 4.6).~~

~~3. **A deployment recommendation conditioned on the model architecture**, with an explicit statement of which claims generalize and which do not (Section 5).~~

~~The paper makes~~ ranking claims under a stated protocol. It does not claim that ~~either method~~an explanation is correct for a task, and it does not test whether ~~users~~people decide better with ~~either~~any explainer.

2. BACKGROUND AND RELATED WORK

~~2.1.~~ LIME

~~LIME approximates a black-box model f locally around an instance x by training~~ fits an interpretable surrogate g to the model f on perturbed samples around an instance x, weighted by a proximity kernel π_x, as in Eq. (1):

$$\xi(x) = \operatorname{argmin}_{g \in G} \mathcal{L}(f, g, \pi_x) + \Omega(g), \tag{1}$$

where ~~$\xi(x)$ is the explanation returned for x,~~ G is the class of ~~interpretable~~ surrogates (sparse linear models here), $\mathcal{L}$ measures how poorly g reproduces f on ~~perturbed samples, each sample~~the weighted ~~by its proximity π_x to x,~~samples and $\Omega(g)$ penalizes surrogate complexity [1]. ~~LIME's behavior is shaped by the hyperparameters that build the neighborhood: the~~The kernel width, the number of ~~perturbed~~ samples and the feature budget~~. These controls yield compact explanations~~ shape the neighborhood, and ~~low latency, but they introduce~~ the sampling makes the explanation stochastic~~ variation, because local neighborhoods are sampled rather than exhaustively enumerated.~~

~~2.2~~. SHAP

~~SHAP explains a prediction through~~ assigns additive ~~feature~~ attributions $f(x) = \phi_0 + \sum_{i=1}^{M} \phi_i$~~, where ϕ_0 is the model's expected output over a background sample, M is the number of features and ϕ_i is the Shapley-value contribution of feature i. SHAP values are the unique additive attributions~~ that satisfy local accuracy, missingness and consistency~~ [2].~~, where ϕ_0 is the expected output over a background sample and M the number of features [2].~~ KernelSHAP estimates them ~~with~~by a weighted regression over sampled feature coalitions and applies to any model; ~~tree-specific implementations exploit the model~~ TreeSHAP computes them from the structure ~~for speed. Relative to local-surrogate methods, SHAP is typically denser and, outside tree models, computationally heavier, because many coalition~~

~~evaluations are required.~~of tree ensembles. Anchors searches for a rule that fixes the prediction with a target precision [3]; DiCE searches for a counterfactual instance with the opposite prediction [4].

~~2.3. Evaluating and Comparing Explainers~~

Quantitative evaluation ~~of explanations~~ relies ~~mostly~~ on proxy metrics ~~that need no human judgment: fidelity or~~: faithfulness under feature removal [~~11–13~~17, 18], robustness ~~of the explanation~~ to small input changes ~~of the input [14], and structural properties such as~~ [19] and sparsity~~. Toolkits~~, standardized in toolkits and benchmarks ~~standardize these measurements [15, 16], and systematic reviews document how unevenly they are applied [5, 6]. Several results warn against reading a proxy score as correctness: attribution methods~~ [20, 21]. Removal-based scores depend on the removal scheme [22], attributions can pass perturbation tests and fail sanity checks [~~17], removal-based scores depend on the removal scheme [18], and LIME~~ 23], LIME and SHAP can ~~both~~ be manipulated [~~19]~~.24], and Shapley~~-value~~ attributions ~~have known limitations~~are hard to read as importance ~~measures~~ when features are dependent [~~20~~25]; feature attribution has provable limits as a basis for inferring model behavior [26], and attribution methods can mark features with no relation to the target as important [27].

~~For a fair comparison of LIME and SHAP, confounders unrelated to the explainer must be controlled. This motivates the protocol of Section 3: an identical transformed feature space, shared model artifacts, a fixed class target, and cells matched on (model, seed, N). Under these controls the expected trade-offs become testable: LIME should favor sparsity and speed, and SHAP should favor stability and faithfulness.~~

Recent work compares SHAP and LIME in applied settings, among them education [13], software engineering [14] and mixed-type tabular models [28], and across tabular and image classifiers [6]; their respective strengths are reviewed in [29, 30]. Guidelines and open benchmarks for functionally grounded evaluation on tabular data are emerging [5, 31]. Estimators of Shapley values differ in accuracy and cost [7], LIME's neighborhood sampling can be redesigned to raise its fidelity [16], and counterfactual explainers can disagree on the same instance [32]. This study adds a comparison in which the four explainers are paired on the same instances, their configuration is varied, the validity of the stability measurement is tested, and cost is counted in model evaluations as well as in time.

3. MATERIALS AND METHODS

3.1. ~~Cohort~~Design and Research Questions

All results come from one experimental cohort run for this study under the protocol below (Table 1). An earlier analysis of the SHAP–LIME question used runs collected on several hosts; an audit found that in most of its cells the evaluation instances overlapped the training partition, that one model could not be recovered and that its timings mixed hosts, so no number from it is used here.

For each endpoint Y and each instance, the paired difference is $\Delta_X = Y_{\mathrm{SHAP}} - Y_X$ for $X \in \{\mathrm{LIME}, \mathrm{Anchors}, \mathrm{DiCE}\}$. Three hypotheses state an expected direction; each is tested two-sided, and a difference is read in the stated direction only when its interval excludes zero on that side. Sparsity is reported descriptively:

- **H1 (stability).** SHAP is more stable than X: $\Delta_X(S) > 0$.
- **H2 (cost).** SHAP is more expensive than X: $\Delta_X(C) > 0$, tested in CPU time; the rows passed to the model are reported alongside, without a test.
- **H3 (faithfulness).** SHAP is more faithful than X: $\Delta_X(F) > 0$ and $\Delta_X(G) > 0$.
- **Sparsity (descriptive).** With its 10-feature budget LIME's sparsity is set by the user, and Anchors returns few features by construction, so a test of sparsity would test a configuration, not a method.

Table 1. Design of the benchmark. The primary benchmark is confirmatory; the other parts are exploratory

Factor	Levels
Datasets	Adult (primary, 108 encoded features); Breast Cancer (30), German Credit (61), Diabetes (8), Spambase (57), Phishing (68), Connect-4 (126)
Models	logistic regression, random forest, XGBoost, SVM (RBF), MLP
Explainers	SHAP, LIME (full vector; 10-feature variant), Anchors, DiCE
Seeds	Adult: 5; other datasets: 3
Instances	up to 25 per stratum (TP, TN, FP, FN) of the test split, per model and seed; stability on 3 per stratum
Paired cells	Adult: 25 (model × seed); other datasets: 90
Timing subset	5 instances per stratum, 3 repetitions, one host
Sweep and controls	Section 4.3 and Section 4.4

3.2. Data and Models

Adult [33, 34] is the primary dataset. Six further binary datasets were chosen so that feature dimension crosses feature type: Breast Cancer [35] and German Credit [36] from the UCI repository [37], and Diabetes, Spambase, Phishing and Connect-4 [38–41] in a 2×2 of numeric or categorical features and lower or higher dimension. For Connect-4, a win is the positive class and the two other outcomes the negative class.

Each dataset has one fixed stratified split (80/20, seed 42), shared by preprocessing, model training and every seed. Numeric features are scaled and categorical features one-hot encoded, both fitted on the training split only. Training is capped at 20,000 rows (a stratified subsample) so that the SVM fits in reasonable time. The five models [42, 43] are trained once per dataset with fixed hyperparameters (supplementary file) and frozen; every run checks the model file against its recorded hash. A seed therefore changes the evaluation instances and the explainers' randomness, never the model. Evaluation instances are drawn from the test split only, up to 25 from each confusion-matrix stratum; smaller strata are taken whole, and the realized counts are reported. Within a cell, all explainers see the same instances. In small strata, different seeds can draw the same instance; the overlap is measured and reported [R: overlap].

3.3. ~~The runs analysed here come from the execution cohort released by Herrera-Vásquez and Herrero-Uceda [10], under the protocol and reproducibility contract defined there. The analysis is not the same: that study reports an omnibus comparison across four explainer families at the block level and a paired SHAP–~~Explainers

All explainers receive the same encoded features and explain the predicted~~LIME test restricted to 45 cells of three model families. The present analysis covers the 75 matched cells of the five families at the run level, with directional hypotheses, Holm-corrected paired tests, confidence intervals and per-endpoint effect sizes, and it examines how the differences vary with the model family, the dataset and the LIME configuration. Reusing the cohort is deliberate: a fresh execution would add environment variation to a comparison whose purpose is to isolate the explainer.~~

~~Four directional questions are addressed, each with its hypothesis, where S is stability, P sparsity, C cost and F fidelity:~~

- ~~**RQ1 (robustness).** Is SHAP more stable than LIME under input perturbation? $H_1: S_{\mathrm{SHAP}} > S_{\mathrm{LIME}}$.~~
- ~~**RQ2 (parsimony).** Is LIME sparser than SHAP? $H_2: P_{\mathrm{LIME}} < P_{\mathrm{SHAP}}$, where P is the active-feature ratio (lower is sparser).~~

- **RQ3 (efficiency).** Is LIME computationally cheaper than SHAP? H_3: $C_{\text{LIME}} < C_{\text{SHAP}}$.
- **RQ4 (faithfulness).** Does SHAP give stronger fidelity and faithfulness signals than LIME? H_4: $F_{\text{SHAP}} > F_{\text{LIME}}$.

3.2. Experimental Design and Analysis Units

The benchmark has four factors: model family $g \in \{\text{logreg}, \text{rf}, \text{xgb}, \text{svm}, \text{mlp}\}$; explainer $k \in \{\text{LIME}, \text{SHAP}\}$; seed $s \in \{42,123,456,789,999\}$; and sampling intensity $N \in \{50,100,200\}$ instances per stratum of the confusion matrix (TP, TN, FP, FN). This yields $5 \times 2 \times 5 \times 3 = 150$ planned runs, all of which are artifact-qualified (75 LIME, 75 SHAP), forming 75 matched SHAP–LIME cells on identical (g, s, N) coordinates.

To avoid pseudoreplication, the analysis is hierarchical: metric values are computed per instance, averaged per run, and the paired SHAP–LIME run means on shared (g, s, N) cells are the inferential unit.

3.3. Data, Models and Explainer Protocol

All experiments of the main cohort use the UCI Adult dataset [21, 22] with a stratified split and deterministic seeds. The preprocessing pipeline is fitted on the training partition only, with numeric scaling and one-hot encoding of categorical features, which gives 103 transformed features. A fixed set of pre-trained models is shared across all explainer runs to isolate the explainer effect: random forest [23], gradient-boosted trees [24], logistic regression, a support vector machine (SVM) and a multilayer perceptron (MLP). Evaluation instances are sampled by confusion-matrix stratum. Realized instance counts range from 27 to 800 (median 400).

Both explainers consume the same transformed feature space and target the probability of the positive class:

- **SHAP:** `TreeExplainer`TreeSHAP for tree-modelsthe random forest and `KernelExplainer`XGBoost; KernelSHAP for the other models, with a50 background sample of $n = 50$rows and a budget of 500 coalitions.
- **LIME:** tabular local surrogate1,000 samples and the library's default kernel width, $0.75\sqrt{M}$ (≈ 7.79 on Adult). The primary contrast uses the full attribution vector; a variant with a the 10-feature budget shows the effect of `num_`the budget.
- **Anchors:** precision target 0.95; the attribution vector marks the features`=10, an effective num_samples=1000` and `kernel_width=3.` of the anchor with 1 and the others with 0.

These are fixed reference settings, not the library defaults. The sensitivity of the results to the LIME kernel width is examined in Section 4.6.

- **DiCE:** one counterfactual of the opposite class (random search); the attribution of feature j is $|x_j - x'_j|$.

Anchors (a rule) and DiCE (a counterfactual) enter as reference explainers of other kinds: the research questions remain about SHAP and LIME, and the two references show whether a SHAP–LIME difference is specific to the pair or shared by explainers in general. These settings are the libraries' defaults where defaults exist, so that a practitioner's first run is what is measured. KernelSHAP's budget is set explicitly because the default ($2M + 2048$ coalitions) made the SVM the cost driver of the whole design; Section 4.3 measures the effect of the default against the explicit budget. Anchors and DiCE return explanations of different kinds, so their vectors measure which features the explanation uses, not signed contributions; the metrics below are comparable across the four methods in that sense.

3.4. Metrics

The metrics follow the protocol of the earlier study [10]. Throughout,Let $f(x)$ isbe the model's predicted probability of the positive class, and $e(x) \in \mathbb{R}^M$ is the attribution vector an explainer returns for instance x with M features, and "; masking" feature j replaces it with its value with the training set mean $\bar{x}_j$. The metrics follow common definitions [17–19]:

1. **Stability** S: robustness of the explanation to small input noise [14]. The explainer is run on $T = 15$ perturbed copies $x^{(a)} = x + \varepsilon^{(a)}$, with $\varepsilon^{(a)} \sim \mathcal{N}(0, \sigma^2 I)$ and $\sigma = 0.1$, and S is the mean cosine similarity over all $T(T-1)/2$ pairs of $T = 15$ explanations of perturbed copies $x + \varepsilon^{(a)}$, $\varepsilon^{(a)} \sim \mathcal{N}(0, \sigma^2 I)$the resulting attribution vectors $e^{(a)} = e(x^{(a)})$,, $\sigma = 0.1$, added to every encoded feature (scaled numeric and one-hot columns alike), with S computed on 3 instances per stratum, Eq. (2):

$$S = \frac{2}{T(T-1)} \sum_{1 \le a < b \le T} \cos\left(e^{(a)}, e^{(b)}\right). \tag{2}$$

- S is 1 when every perturbation yields an attribution vector with the same direction, and near 0 when directions are unrelated.

2. **Sparsity** P: active-feature ratio, the share of the M features whose absolute attribution exceeds the threshold 10^{-4}. A lower active ratio means a sparser explanation.

3. - The cosine with an all-zero vector is set to 0; such vectors are counted and S is also reported without them. Noise on one-hot columns leaves the data manifold; Section 4.4 repeats S with category-preserving perturbations and without noise.

2. **Fidelity** F: a single-feature variant of the faithfulnessthe Pearson correlation of Bhatt et al. [11]. Each feature j, across the M features, between $|e_j(x)|$ and the prediction change $|f(x) - f(\tilde{x}^{(j)})|$ when feature j alone is masked on its own, giving the masked instance $\tilde{x}^{(j)}$, and F is given by, Eq. (3):

$$F = \rho\left(\{|e_j(x)|\}_{j=1}^{M},\ \{|f(x) - f(\tilde{x}^{(j)})|\}_{j=1}^{M}\right),. \tag{3}$$

- where ρ is the Pearson correlation across the M features. F is high when the features an explanation ranks as important are those whose removal moves the prediction most.

4- Absolute values are used because the masked change is unsigned. When either vector is constant, F is undefined and set to 0; these cases are counted.

3. **Faithfulness gap** Δ_k: a deletion test in the spirit of [12, 13]. The G: the prediction change when the $k = 5$ features with the largest $|e_j(x)|$ are masked together, giving $\tilde{x}^{(\text{top-}k)}$, and Δ_k is given by Eq. (4):.

$$\Delta_k = \left|f(x) - f\left(\tilde{x}^{(\text{top-}k)}\right)\right|. \tag{4}$$

- A larger Δ_k means4. **Sparsity** P: the share of features the explanation names first carry more of the prediction.with $|e_j(x)| > 10^{-4}$ (lower is sparser).

5. **Cost** C: per-instance wall-clock explanationCPU time (ms).

LIME's active-feature count is bounded by `num_features`=10, which is a hard ceiling on the per explanation and the number of non-zero attributions. LIME's sparsity is therefore a consequence of a hyperparameter, not an emergent property of the method. The active-feature ratio measures whether LIME, *as configured*, returns fewer significant features than SHAP; it does not test whether LIME is intrinsically sparser.rows the explainer passes to the model (Section 3.6).

3.5. 3.5. Inferential Protocol

The statistical plan follows established practice for comparing learning methods [25]: a two-sided paired Wilcoxon signed-rank test on the matched cells for each metric [26]; the paired effect size d_z for magnitude [27]; and Holm–Bonferroni control of multiplicity over the five primary metrics [28]. All inferential claims are restricted to artifact-qualified runs: parseable, non-empty results with explicit matched pairing.

Statistical Analysis

Instances are nested in seeds and seeds in models, so instance-level differences are not independent. For each endpoint and contrast, the instance-level differences Δ_{gsi} of model g, seed s and instance i are fitted by a linear mixed model $\Delta_{gsi} = \mu + u_g + v_{gs} + \epsilon_{gsi}$, with random intercepts for the model and for the seed within the model [44]; μ is the effect, reported with its 95% confidence interval and two-sided Wald p-value; if the model cannot be fitted, a t-test on the cell means is used and the case is reported. Because five models are few clusters, the interval is checked by a cluster bootstrap that resamples models [45]. Only instances valid for both explainers of a contrast enter it. On the cell-mean differences, the standardized paired difference d_z [46], the Hodges–Lehmann estimate [47] and the matched-pairs rank-biserial correlation [48], the effect size of the Wilcoxon signed-rank test [49], are reported. The confirmatory family is four endpoints (S, F, G and CPU time) times three contrasts; p-values are Holm-corrected over these twelve tests [50]. The four explainers are ranked on the cell means of S, F and G by the Friedman test with the Nemenyi critical difference [51]. The sweep, the controls and the six further datasets are exploratory and are reported without tests.

3.6. ~~Reproducibility~~Cost Measurement and Computing ~~Infrastructure~~Environment

~~The protocol is configuration-driven (YAML files with seeded execution). Each run writes a `results.json` artifact; malformed or empty runs are excluded explicitly and nothing is imputed. All experiments ran on CPU. The reference software environment is Python 3.11 with scikit-learn 1.7.1, XGBoost 3.1.2, SHAP 0.50.0, LIME 0.2.0.1, NumPy 2.2.6, pandas 2.3.3 and SciPy 1.16.3, pinned in the repository. Runs were executed on several commodity workstations under macOS, Windows and Linux, distributed by a work queue. Each run artifact records its configuration, seed, timestamps and duration; processor and memory specifications were not recorded. The consequence for the cost endpoint is discussed in Section 5.3.~~

All runs used one laptop (AMD Ryzen 5 4600H, 6 cores, 31.4 GB RAM, Windows 11), Python 3.11 with scikit-learn 1.7.1, XGBoost 3.1.2, SHAP 0.50.0, LIME 0.2.0.1, alibi 0.9.6 (Anchors) and dice-ml 0.12. Quality was computed in parallel worker processes; quality does not depend on speed. Cost was measured in a separate pass on a subset (Table 1): one process with one thread, pinned to one core, on mains power; the explainers interleaved per instance, after one warm-up explanation each; three repetitions, of which the median is used; and measurements paused while any other process used more than 10% of a core or the machine was in use. A wrapper counts every row the explainer passes to the model. Rows evaluated, unlike time, transfer to other hardware: multiplied by the cost of one model evaluation they give the explainer's cost on any host. For logistic regression and the MLP, whose cost per row is known, this is also given in floating-point operations.

4. RESULTS

~~The analysis covers 150 runs (75 LIME, 75 SHAP) forming 75 paired cells with identical $(\text{model}, \text{seed}, N)$. Matched coverage spans the five model families ($\text{xgb} = 15$, $\text{logreg} = 15$, $\text{rf} = 15$, $\text{mlp} = 15$, $\text{svm} = 15$) and the three sampling intensities.~~

4.1. ~~Context: Earlier Results on This Cohort~~

~~The omnibus comparison over this cohort—SHAP, LIME, Anchors [29] and DiCE [30], tested over $n = 15$ blocks per method—is reported in the earlier study [10] and is not reproduced here. It establishes that the four methods are not exchangeable on fidelity or stability, that SHAP leads both endpoints, and that the SHAP–LIME fidelity separation falls marginally below the Nemenyi critical difference. Block aggregation was necessary there because Anchors and DiCE are not complete across the grid (57/75 and 68/75 artifact-qualified runs, respectively, against 75/75 for SHAP and LIME). The same study reports~~

~~a paired Wilcoxon test of SHAP against LIME on 45 matched cells (logistic regression, random forest and XGBoost), significant on the five metrics in the directions found below. The analysis that follows extends that test to the 75 cells of the five model families. The 45 cells are a subset of the 75, so the two analyses are not independent. The earlier material is context, not evidence, for any claim made in this paper.~~

~~4.2.~~ Primary ~~Paired Inference~~Benchmark on Adult

Table 2 reports the effects on the 25 Adult cells. [R: per contrast, the direction and size of the stability and faithfulness effects, and in how many cells the sign holds.] [R: Friedman ranking of the four explainers per endpoint.] [R: share of all-zero vectors and of undefined fidelity per explainer, and whether excluding them changes any effect.] The distribution of the instance-level differences is shown in the supplementary file.

Table 2. ~~Table 1 summarizes the paired run-level outcomes on the 75 matched cells. The five primary endpoints are significant under Holm-adjusted testing~~Primary benchmark (Adult, 25 cells). Per-method mean levels and paired effects $\Delta_X = SHAP - X$; mixed-model estimate with 95% CI, Holm-adjusted p, standardized paired difference d_z, Hodges–Lehmann estimate (HL) and matched rank-biserial correlation r_{rb}. Cost: CPU ms per explanation

~~*Table 1. Matched SHAP versus LIME paired results ($n = 75$ cells). For all metrics, Δ = SHAP − LIME, with a 95% confidence interval on the mean paired difference. Sparsity is measured as active-feature ratio, so a positive Δ means SHAP produces denser explanations. Per-method mean levels for this cohort are reported in [10] and are not restated here*~~

~~Metric~~Endpoint	~~ΔX~~	SHAP	X	~~95%~~Δ_X [95% CI]	p_{Holm}	d_z	HL	r_{rb}
Stability	~~+0.718~~LIME	~~[+0.663, +0.773]~~[R]	~~2.6×10^{-13}~~[R]	~~3.00~~[R]	[R]	[R]	[R]	[R]
~~Sparsity (active ratio)~~	~~+0.142~~Anchors	~~[+0.103, +0.181]~~	~~2.6×10^{-13}~~[R]	~~0.84~~[R]	[R]	[R]	[R]	[R]
	DiCE		[R]	[R]	[R]	[R]	[R]	[R]
Fidelity	~~+0.248~~LIME	~~[+0.236, +0.260]~~[R]	~~2.6×10^{-13}~~[R]	~~4.82~~[R]	[R]	[R]	[R]	[R]
~~Faithfulness Gap~~	~~+0.045~~Anchors	~~[+0.041, +0.049]~~	~~2.6×10^{-13}~~[R]	~~2.63~~[R]	[R]	[R]	[R]	[R]
	DiCE		[R]	[R]	[R]	[R]	[R]	[R]
Faithf. gap	LIME	[R]	[R]	[R]	[R]	[R]	[R]	[R]
	Anchors		[R]	[R]	[R]	[R]	[R]	[R]
	DiCE		[R]	[R]	[R]	[R]	[R]	[R]
Cost ~~(ms)~~	~~+8047.6~~LIME	~~[+3939.2, +12155.9]~~[R]	~~1.2×10^{-10}~~[R]	~~0.45~~[R]	[R]	[R]	[R]	[R]
	Anchors		[R]	[R]	[R]	[R]	[R]	[R]
	DiCE		[R]	[R]	[R]	[R]	[R]	[R]
Sparsity	all	[R]	[R]	descriptive				

4.2. Cost

Table 3 gives the cost per explanation by model family. [R: CPU-time ordering by model family; the share of model time in the explainer's time.] [R: rows evaluated per explanation: LIME 1,000; KernelSHAP about 25,000 (500 coalitions × 50 background rows); Anchors and DiCE as measured.] Earlier runs suggested that TreeSHAP was faster than LIME on XGBoost but slower on the random forest, two ensembles of different size. Here both have 100 trees, and the comparison is repeated with matched depth and with cost plotted against the total number of leaves [R: whether the reversal holds, and whether it follows the size of the forest or the implementation].

Table 3. The stability effect is the largest separation in the study. The median paired stability difference is +0.866 in favor of SHAP, and the direction is the same in all 75 matched cells. Under the reference configuration, LIME's attribution vectors change direction under small input noise, whereas SHAP's are comparatively invariant.

For sparsity the sign is also the same in all 75 matched cells. The metric is the active-feature ratio, so SHAP's larger value means denser explanations: LIME is systematically sparser, within the limit stated in Section 3.4.

Cost per explanation on Adult (one host, one core): median CPU time and rows evaluated by the model; theoretical complexity per explanation (T trees, L leaves, D depth; n_s samples or coalitions; n_b background rows). FLOPs for logistic regression and the MLP in the text

Fidelity favors SHAP in all 75 matched cells, with a mean paired difference of +0.248 and a very large effect size ($d_z = 4.82$). The faithfulness gap favors SHAP in 74 of 75 matched cells, with a mean paired difference of +0.045 and a large effect size ($d_z = 2.63$). Figure 1 shows the paired mean differences for the four quality-oriented endpoints.




Figure 1. Mean paired difference (SHAP − LIME) with its 95% confidence interval for the quality-oriented primary endpoints ($n = 75$ matched cells), as in Table 1. For the active ratio, a positive difference means SHAP is denser, that is, LIME is sparser

4.3. Reproducibility across Seeds

To characterize how much the readings vary with the seed, the coefficient of variation (CV = SD/mean) was computed across the five seeds of the random-forest stratum at $N = 100$ (Table 2); the medians over all fifteen (N, model) strata are similar (0.9, 1.4, 2.3 and 88.2% in the table's row order). SHAP yields highly reproducible fidelity and stability readings (CV < 1%). LIME fidelity is acceptable (CV = 2.6%), whereas LIME stability has CV = 86.2%. That figure mostly reflects the denominator: when the mean cosine similarity is near zero, any nonzero variation produces an extreme relative deviation. In absolute terms the spread is small (seed SD 0.015): the informative result is the level itself, which is near zero under the reference configuration

~~*Table 2. Coefficient of variation (CV = SD/mean) across the five seeds of the random-forest, N = 100 stratum for the two primary quality endpoints. The CV is uninformative for LIME stability, whose mean is near zero*~~

~~Method – Metric~~Explainer	~~CV~~Model	~~Reproducible?~~Complexity	CPU (ms)	Rows evaluated
SHAP ~~– Fidelity~~(Tree)	~~0.8%~~RF, XGB	~~Yes~~$O(TLD^2)$, no model calls	[R]	0
SHAP ~~–~~ (Kernel)~~Stability~~	logreg, SVM, MLP~~0.7%~~	~~Yes~~$O(n_s n_b)$ rows	[R]	[R]
LIME~~ – Fidelity~~	~~2.6%~~all	~~Yes~~$O(n_s)$ rows + fit $O(n_s M^2)$	[R]	[R]
~~LIME –~~ ~~Stability~~Anchors	~~86.2%~~all	~~CV not meaningful~~adaptive (precision target)	[R]	[R]
DiCE	all	iterative search	[R]	[R]

4.3. Configuration Sensitivity

The sweep varied, on Adult for every model and three seeds, LIME's kernel width and number of samples, and KernelSHAP's budget and background size; KernelSHAP was also run on the two tree ensembles, to separate the method from the TreeSHAP implementation. The grid crosses LIME kernel widths of 0.75, 1.5, 3, 5, 10 and 15 and the default $0.75\sqrt{M}$ with 250 to 5,000 samples, KernelSHAP budgets of 100 to 1,000 coalitions and the default with 10 to 100 background rows, and TreeSHAP with 10 to 100 background rows; each cell has one instance per stratum, with stability on each. [R: Figure 1 placeholder: Pareto fronts of stability, fidelity and cost per model, one panel per model, computed on the instances valid under every configuration.] [R: whether the sign of each SHAP–LIME difference holds over the grid; the share of degenerate explanations at small kernel widths; the effect of the library default against the 500-coalition budget.]

4.4. Validity of the Measurements

Five controls test whether the stability and fidelity measurements measure the explainer: (a) explanations of the unperturbed instance repeated T times, which isolates each explainer's own sampling variance; (b) noise that keeps one-hot features valid (a category is resampled instead of adding Gaussian noise to its indicators); (c) rank correlation and top-k overlap on the full vectors, besides the cosine; (d) the effect of excluding all-zero vectors; and (e) the fidelity ordering under four masking schemes (zero, mean, marginal and grouped replacement, where associated features such as education and its numeric code are masked together) on every model. [R: for each control, whether the SHAP–LIME stability and fidelity orderings hold, and how much of LIME's instability is its own sampling variance.]

4.5. Other Datasets

Table 4 reports the four explainers on the six further datasets, now including SHAP stability. [R: whether the Adult orderings hold across the 2×2 of dimension and feature type; where they change.]

Table 4. ~~4.4. Runtime: the Ordering Depends on the~~ Other datasets (exploratory): mean ± SD over 3 seeds, averaged over the five models (per model in the supplementary file)

~~**Model Family**~~

~~The cost difference is significant but strongly heterogeneous. SHAP is slower in 59 of 75 matched cells. The matched-cell median cost is 684.1 ms for SHAP against 65.7 ms for LIME, and the median per-cell~~

SHAP/LIME cost ratio is approximately 5.3 ×. The SHAP distribution is heavy-tailed, so its mean lies far above its median (the per-method means are reported in [10]): the 90th and 95th percentile latencies are approximately 51,456 ms and 67,066 ms, respectively, compared with 12,825 ms and 13,192 ms for LIME. This tail is concentrated in KernelSHAP contexts, especially the SVM.

The quality ordering (stability, sparsity direction, fidelity, faithfulness gap) is the same in every model family. The cost ordering is not. SHAP is faster in all 15 XGBoost matched cells and in one SVM cell, whereas the logistic regression, random forest and MLP cells are uniformly SHAP-slower (Figure 2, Table 3). The two tree ensembles behave in opposite ways. For XGBoost, `TreeExplainer` was faster than LIME in all 15 matched cells (median 18.1 ms vs. 61.8 ms). For random forests it was slower in all 15 cells (median 1,262.4 ms vs. 335.6 ms). A candidate explanation, not tested here, is that the cost of `TreeExplainer` grows with the number and depth of the trees. For the non-tree models, where SHAP runs in kernel mode, LIME has the lower median runtime (53.3 ms vs. 694.6 ms). "LIME is faster" is therefore a majority statement in this cohort, not a property of the two methods, and "SHAP is fast on tree models" does not hold for tree models in general.

Table 3. Median per-instance cost by model group on the matched cells, and the number of cells in which SHAP was the faster method. SHAP uses `TreeExplainer` for the two tree ensembles and `KernelExplainer` for the non-tree models

		Stability	Fidelity						
Model groupDataset	Cells	SHAP median (ms)	LIME median (ms)	Anch.	DiCE	SHAP faster	LIME	Anch.	DiCE
XGBoostBreast Cancer		15[R]	18.1[R]	61.8[R]	15 of 15[R]	[R]	[R]	[R]	[R]
Random forestGerman Credit		15[R]	1,262.4[R]	335.6[R]	0 of 15[R]	[R]	[R]	[R]	[R]
Non-tree (DiabetesLogreg, SVM, MLP)		45[R]	694.6[R]	53.3[R]	1 of 45[R]	[R]	[R]	[R]	[R]
Spambase		[R]	[R]	[R]	[R]	[R]	[R]	[R]	[R]
Phishing		[R]	[R]	[R]	[R]	[R]	[R]	[R]	[R]
Connect-4		[R]	[R]	[R]	[R]	[R]	[R]	[R]	[R]




Figure 2. Runtime behavior under matched-cell pairing (n = 75). (A) Overall cost distribution by method (log scale). (B) Model-level median cost (log scale), showing the XGBoost exception where SHAP is faster while other families are SHAP-slower

4.5. Cross-Dataset Extension

To probe external validity within tabular classification, a cross-dataset study (EXP3) compared SHAP, LIME and Anchors [29] on two further binary classification datasets: Breast Cancer Wisconsin [31, 32]

(n = 569, 30 continuous features) and German Credit [31, 33] (n = 1,000, 20 mixed features). Both used random forest and XGBoost models across three random seeds each, yielding 12 paired dataset–model–seed comparisons per method pair.

Fidelity ordering (SHAP vs. Anchors). SHAP exceeds Anchors in fidelity in all 12 paired combinations (Table 4), with mean gaps ranging from +0.26 (German Credit, XGB) to +0.51 (Breast Cancer, RF).

Table 4. Cross-dataset extension: mean Anchors fidelity (3-seed average) and the paired SHAP−Anchors fidelity gap. The gap is positive in all 12 paired combinations. SHAP fidelity levels for this cohort are reported in [10]; the Anchors levels and the gaps are contributed here

Dataset	Model	Anchors	Gap (SHAP − Anchors)
Breast Cancer	RF	0.265	+0.514
Breast Cancer	XGB	0.208	+0.409
German Credit	RF	0.351	+0.363
German Credit	XGB	0.451	+0.260

LIME on the further datasets. Table 5 reports LIME fidelity and stability on the same datasets, with the paired SHAP−LIME fidelity gap. Two findings follow. First, SHAP > LIME fidelity holds on German Credit (mean gaps +0.23 for RF and +0.24 for XGB, positive for every seed), in the direction found on Adult. On Breast Cancer the fidelity gap narrows substantially: SHAP leads LIME by only +0.07 (RF) and +0.07 (XGB), compared to +0.27 (RF) and +0.21 (XGB) in the corresponding model strata on Adult. Second, LIME *stability* on these datasets (0.75–0.93) is an order of magnitude higher than on Adult, where it is near zero, at the same reference kernel width. The near-zero stability observed on Adult is therefore not a fixed property of LIME.

Table 5. Cross-dataset extension: mean fidelity and stability (3-seed average) for LIME, and the paired SHAP−LIME fidelity gap. Stability is the mean pairwise cosine similarity under T = 15 Gaussian perturbations (σ = 0.1), the protocol of the main cohort. For comparison, LIME on Adult in the matched model strata: fidelity 0.457 (RF) and 0.553 (XGB); stability ≈ 0.01–0.02 across all model families

Dataset	Model	Fidelity	Gap (SHAP − LIME)	Stability	Sparsity	Cost (ms)
Breast Cancer	RF	0.713	+0.07	0.922	0.331	12.3
Breast Cancer	XGB	0.543	+0.07	0.927	0.331	7.5
German Credit	RF	0.483	+0.23	0.854	0.163	21.1
German Credit	XGB	0.468	+0.24	0.748	0.163	10.2

SHAP stability was not instrumented in the cross-dataset study, so a direct SHAP–LIME stability comparison on Breast Cancer and German Credit is not available.

4.6. LIME Stability Depends on the Kernel Width

A probe on Adult varied the LIME kernel width with everything else fixed (random forest, seed 42, N = 100, `num_samples=1000`, `num_features=10`). Table 6 reports the result. Fidelity and stability are computed over the instances that have at least one non-zero weight. The probe covers one model and one seed, so it shows that the dependence exists; it does not measure its size across models.

Table 6. LIME sensitivity to `kernel_width` on Adult (random forest, seed 42, $N = 100$). Reference condition: `kernel_width=3.0`

`kernel_width`	Valid instances	Fidelity	Stability	Sparsity	Cost (ms)
0.25	0/100 (degenerate)	—	—	0.000	30
0.75	0/100 (degenerate)	—	—	0.000	30
3.0 *(ref.)*	96/100	0.518	0.000	0.087	30
10.0	100/100	0.441	0.664	0.093	32

Kernel widths of 0.25 and 0.75 produce zero-weight explanations for all 100 instances, because the exponential neighborhood collapses in the 103-dimensional one-hot-encoded space. The reference width of 3.0 is the smallest of the tested settings that yields usable explanations. Widening the kernel to 10.0 raises stability to 0.664 at a cost in fidelity (0.518 → 0.441). Together with the cross-dataset result, where LIME reaches 0.75–0.93 at the reference width, the probe supports a bounded conclusion: under the reference kernel width, LIME's stability on Adult is near zero; it rises with the kernel width and is high on two lower-dimensional datasets, so it is modulated by the configuration and by the feature space. Adult's one-hot encoding is a candidate cause, and the stability protocol itself may contribute: the Gaussian noise is added to every transformed feature, including the one-hot indicator columns, which then take values that no real instance has. Breast Cancer has no categorical feature. No experiment here separates the encoding from the perturbation scheme, and the two further datasets also differ from Adult in size, class balance and the mix of continuous and categorical features, so this design does not isolate either cause. The near-zero reading should not be taken as a configuration-independent property of LIME.

4.7. Sensitivity of the Fidelity Ordering to the Masking Scheme

The fidelity and faithfulness-gap metrics mask features independently. Adult contains associated features, so a masked instance may fall outside the training distribution, where model outputs are less reliable. To assess whether this changes the method ordering, a probe reused the stored top-10 explanations of the five Adult random-forest runs at $N = 50$, one per seed, and recomputed the prediction-drop metrics under four masking schemes: independent zero masking, mean replacement, marginal empirical replacement, and grouped mean replacement, which masks associated feature sets together (for example `education` and `education_num`). Table 7 reports the result.

Table 7. SHAP–LIME top-k prediction-drop advantage and drop-correlation advantage under four masking schemes (Adult random-forest stratum, five runs at $N = 50$, one per seed). The SHAP direction is positive in all five paired seed cells under every scheme

Masking scheme	Mean SHAP–LIME gap	Mean drop-correlation delta
Independent zero masking	+0.098	+0.515
Mean replacement	+0.098	+0.512
Marginal empirical replacement	+0.081	+0.625
Grouped mean replacement	+0.053	+0.494

SHAP's advantage is positive in all five paired cells under every scheme. Its magnitude, measured as the prediction-drop gap, does not increase, and falls overall, as the masking takes more of the feature dependence into account (+0.098 → +0.098 → +0.081 → +0.053). The drop-correlation delta does not follow this ordering: it is highest under marginal empirical replacement (+0.625) and lowest under

~~grouped mean replacement (+0.494). With five pairs, the exact Wilcoxon test cannot reach $\alpha = 0.05$ under any scheme, so this agreement is descriptive. The probe uses stored top-10 explanations, not full attribution vectors, and is a stress test of the construct, not a replacement for the primary analysis: the direction holds in every pair, and the magnitude depends in part on the masking protocol.~~

5. DISCUSSION

5.1. What Holds, and Where

Table 5 states each claim with its evidence and its scope. Confirmatory claims rest on the ~~Paired Analysis Adds~~primary benchmark and its corrected tests; exploratory claims rest on the sweep, the controls and the further datasets, and are reported as patterns, not as tested effects. [R: two or three sentences on the main pattern, including the conditions under which an ordering changes.]

Table 5. ~~The four hypotheses are supported on Adult: SHAP is more stable (RQ1) and scores higher on fidelity and faithfulness gap (RQ4); LIME is sparser as configured (RQ2) and cheaper in most cells (RQ3). The analysis on the full grid confirms the direction that the earlier 45-cell test found, extends it to the SVM and the MLP, and attaches an interval and an effect size to each endpoint; the fidelity and stability differences have the same sign in every cell. SHAP delivers higher stability and fidelity at a substantially higher expected runtime; LIME delivers lower latency and more compact explanations at the cost of robustness.~~

~~Two of these results come with conditions, and the conditions are the part most likely to matter in practice. The runtime result (RQ3) reverses between XGBoost and random forests, two models that a guideline would group together as "tree-based". The stability result (RQ1) is measured at one LIME kernel width on one feature space; a wider kernel or a lower-dimensional dataset raises LIME's stability from near zero to between 0.664 and 0.927. A comparison run on one dataset with one configuration would report either of these as a property of the methods.~~

~~One candidate reason for SHAP's fidelity advantage is that SHAP ties attribution mass to the model's response to feature removal: local accuracy means the attributions sum to the prediction change relative to the background distribution [2], and removal-based fidelity asks a related question. This mechanism was not tested and carries no guarantee: the masking used here replaces features with reference values and not with SHAP's background expectation, KernelSHAP is itself a sampled estimate, and the advantage is small on Breast Cancer.~~

What holds, where, and under which configuration

~~5.2. Recommendation Conditioned on the Model Architecture~~

~~Table 8 states the recommendation in two tiers. The first-tier criterion is not a preference for a method. It is a function of the model architecture: where a model-aware explainer is also fast, as `TreeExplainer` was for XGBoost, the trade-off between fidelity and latency disappears and SHAP is the better choice in both tiers; where it is not, as for the random forests here, the trade-off remains and has to be measured for the deployed model.~~

Table 8. Recommendation by deployment tier, conditioned on the model architecture

Tier Claim	Recommendation Status	Evidence and condition Scope
SHAP more stable than *X*	confirmatory	[R]
Tier 1: real-time, end-user facing SHAP more faithful than *X*	**SHAP** (`TreeExplainer`) for XGBoost; **LIME** for models without a fast model-aware explainer; for other tree ensembles, measure latency before choosing. confirmatory	For XGBoost, SHAP was faster in all 15 matched cells and more faithful. For random forests it was slower in all 15 cells. For non-tree models LIME has the lower median runtime (Section 4.4). Applies when sub-second latency and compact explanations matter more than maximum fidelity. [R]
Tier 2: auditing, model analysis SHAP more expensive than *X*	**SHAP.** confirmatory	Consistent paired advantages in stability, fidelity and faithfulness gap (d_z = 3.00, 4.82, 2.63). Applies to offline or analyst-mediated work that tolerates latencies of seconds to minutes; the sample budget depends on whether SHAP runs in tree-specific or kernel mode. [R]
Orderings over the configuration grid	exploratory	[R]
Orderings on other datasets	exploratory	[R]
TreeSHAP vs LIME cost by ensemble	exploratory	[R]
Usefulness for people	not tested	no participant study

The recommendations are restricted to what was tested. [R: where SHAP is preferable on faithfulness and stability and at what cost; where a cheaper explainer suffices; which configuration choices a practitioner should check before relying on either rule.]

5.2. 5.3. Validity and Limitations

Ranking claims, not validity claims. The differences reported here are comparative performance within a benchmark **Relation to Earlier Work**

Earlier comparisons of SHAP and LIME, including a multi-metric benchmark on Adult [52], reported SHAP ahead on fidelity and stability and LIME ahead on cost, for one configuration and with timings from unrecorded hardware. This study differs in four respects: all four explainers are paired on the same instances; every run uses one recorded host and cost is also counted in model evaluations; the configuration is varied and the measurement is tested; and the results extend to six further datasets. [R: which earlier statements are confirmed, qualified or reversed.]

5.3. Limitations

The endpoints compare explainers under a protocol. A claim; they do not establish that an explanation is correct for a task would need stronger evidence:, which needs ground truth from synthetic or transparent models, perturbation protocols that respect feature dependence, or human-centered validation [34, 35]. Formal analyses show that several evaluation [53], and attribution families assign high importance to methods can mark suppressor variables as important when features are dependent [36, 37], and faithfulness-style evaluations are informative but do not settle correctness on their own [18, 38].

Configuration. Both methods were run with one fixed reference configuration. The cost gap reflects the method family and the concrete implementation pathway (tree-specific or kernel SHAP).27]. Anchors and DiCE vectors encode which features an explanation uses, not signed contributions. Cost was measured on one host; times scale with the hardware, rows evaluated do not. The kernel-width probestudy covers one model and one seed. Sensitivity to the SHAP background sample and to the kernel width in other models was not examined.

Execution hosts and the cost endpoint. Cost is per-instance wall-clock time, and the runs were executed on several workstations whose processor and memory specifications were not recorded (Section 3.6). The two members of a paired cell are matched on model, seed and N, but did not necessarily run on the same host. Absolute latencies, and the medians reported here, include between-host variance and are indicative of this environment; they are not hardware-normalized measurements. The quality endpoints do not depend on the host.

Generalization. Table 9 states the boundary of each claim. The comparison is limited to tabular binary classification; image, text, graph with five model families and time-series explanations need different masking schemes and endpoints and were seven datasetsnot tested. The endpoints measure how well an explanation tracks the model it explains. They say nothing about whether that model is accurate or fair, and nothing about whether a person decides better with the explanation.

Table 9. Generalizability boundary of the empirical claims

Claim	Evidence	Generalization status
SHAP > LIME stability	Adult matched cells, one LIME kernel width	Holds for the Adult protocol only; LIME stability is high on two further datasets, where SHAP stability was not measured
SHAP > LIME fidelity	Adult, plus German Credit and Breast Cancer	Supported within tabular classification, with a small gap on Breast Cancer; not established for other data types
LIME lower runtime	Adult, model-dependent	Bounded by the model architecture and the SHAP implementation; `TreeExplainer` reverses the ordering for XGBoost but not for random forests
SHAP > Anchors fidelity	Breast Cancer and German Credit	Fidelity ordering only; not a stability or runtime result
Usefulness for people	No participant study	Not established

6. CONCLUSIONS

On 75 matched cells of the Adult dataset, SHAP shows consistent paired advantages over LIME in stability ($d_z = 3.00$), fidelity ($d_z = 4.82$) and faithfulness gap ($d_z = 2.63$), and LIME produces sparser explanations and runs faster in most model contexts. A cross-dataset extension supports the fidelity direction on two further tabular datasets.

The choice between the two methods is a matter of fit for purpose, and two of the usual rules of thumb need a condition. SHAP is not fast on tree models in general: it was faster than LIME for XGBoost and slower for random forests. LIME is not unstable in general: its near-zero stability on Adult is specific to the reference kernel width and to that feature space. The practical recommendation is to prefer SHAP where stability and fidelity dominate, to prefer LIME where latency dominates and no fast model-aware explainer exists, and to measure latency for the deployed model before relying on either rule.

Future work should instrument SHAP stability on further datasets, vary the SHAP background sample and the LIME kernel width across models, and extend the comparison beyond tabular classification. Whether either method[R: two to three sentences that restate only results of Table 2 and Table 5: the

confirmatory orderings with effect sizes, the cost in rows evaluated, and the conditions under which an ordering changes.] The choice of explainer depends on the model architecture, the configuration and the latency budget, and a ranking obtained under one configuration should not be transferred to another without measuring it. Whether any of these explainers helps people decide is a separate question that needs a study with participants.

Competing Interests

No competing financial interests or personal relationships that could have appeared to influence the work reported in this paper are declared. No external funding was received for this study.

Data and Code Availability

The ~~experimental~~ code, the ~~run artifacts~~frozen models with their hashes, every result row and the analysis ~~exports~~scripts are available in a public repository and ~~in~~ a versioned archive with a DOI, ~~both released~~ under the MIT License; their addresses are withheld for masked review and are given on the title page. ~~The artifacts needed to reproduce this study are the main-cohort results (), the inferential exports (), the cross-dataset results (and), the kernel-width probe () and the masking-sensitivity exports (). Every reported value is re-derived from these files by a verification script that runs in continuous integration~~A supplementary file lists the design, the hyperparameters, the per-dataset and per-model results and the commands that regenerate every table from the result rows.

REFERENCES

[1] Ribeiro MT, Singh S, Guestrin C. "Why should I trust you?": Explaining the predictions of any classifier. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining; 2016. p. 1135–1144. https://doi.org/10.1145/2939672.2939778

[2] Lundberg SM, Lee SI. A unified approach to interpreting model predictions. In: Advances in Neural Information Processing Systems 30; 2017. p. 4765–4774.

~~[3]~~[3] Ribeiro MT, Singh S, Guestrin C. Anchors: High-precision model-agnostic explanations. In: Proceedings of the 32nd AAAI Conference on Artificial Intelligence; 2018. p. 1527–1535. https://doi.org/10.1609/aaai.v32i1.11491

[4] Mothilal RK, Sharma A, Tan C. Explaining machine learning classifiers through diverse counterfactual explanations. In: Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency; 2020. p. 607–617. https://doi.org/10.1145/3351095.3372850

[5] Velmurugan M, Ouyang C, Xu Y, Sindhgatta R, Wickramanayake B, Moreira C. Developing guidelines for functionally-grounded evaluation of explainable artificial intelligence using tabular data. Engineering Applications of Artificial Intelligence. 2025;141:109772. https://doi.org/10.1016/j.engappai.2024.109772

[6] Ababneh M, Aljarrah A. Faithfulness and stability of black box explanations for tabular and image classifiers. Big Data and Cognitive Computing. 2026;10(11):362. https://doi.org/10.3390/bdcc10110362

[7] Olsen LHB, Glad IK, Jullum M, Aas K. A comparative study of methods for estimating model-agnostic Shapley value explanations. Data Mining and Knowledge Discovery. 2024;38(4):1782–1829. https://doi.org/10.1007/s10618-024-01016-z

[8] Retzlaff CO, Angerschmid A, Saranti A, Schneeberger D, Röttger R, Müller H, et al. Post-hoc vs ante-hoc explanations: xAI design guidelines for data scientists. Cognitive Systems Research. 2024;86:101243. https://doi.org/10.1016/j.cogsys.2024.101243

~~[4] Ali S, Abuhmed T, El-Sappagh S, Muhammad K, Alonso-Moral JM, Confalonieri R, et al. Explainable Artificial Intelligence (XAI): What we know and what is left to attain Trustworthy Artificial Intelligence~~[9]~~. Information Fusion. 2023;99:101805. https://doi.org/10.1016/j.inffus.2023.101805~~

~~[5]~~] Longo L, Brcic M, Cabitza F, Choi J, Confalonieri R, Del Ser J, et al. Explainable artificial intelligence (XAI) 2.0: A manifesto of open challenges and interdisciplinary research directions. Information Fusion. 2024;106:102301. https://doi.org/10.1016/j.inffus.2024.102301

[10] Nauta M, Trienes J, Pathak S, Nguyen E, Peters M, Schmitt Y, et al. From anecdotal evidence to quantitative evaluation methods: A systematic review on evaluating explainability. ACM Computing Surveys. 2023;55(13s):1–42. https://doi.org/10.1145/3583558

[~~6~~11] Canha D, Kubler S, Främling K, Fagherazzi G. A functionally-grounded benchmark framework for XAI methods: Insights and foundations from a systematic literature review. ACM Computing Surveys. 2025;57(12):1–40. https://doi.org/10.1145/3737445

~~[7][12] Longo L, Brcic M, Cabitza F, Choi J, Confalonieri R, Del Ser J, et al. Explainable artificial intelligence (XAI) 2.0: A manifesto of open challenges and interdisciplinary research directions. Information Fusion. 2024;106:102301. https://doi.org/10.1016/j.inffus.2024.102301~~

~~[8]~~ Pawlicki M, Pawlicka A, Uccello F, Szelest S, D'Antonio S, Kozik R, et al. Evaluating the necessity of the multiple metrics for assessing explainable AI: A critical examination. Neurocomputing. 2024;602:128282. https://doi.org/10.1016/j.neucom.2024.128282

~~[9]~~[13] Hooshyar D, Yang Y. Problems with SHAP and LIME in interpretable AI for education: A comparative study of post-hoc explanations and neural-symbolic rule extraction. IEEE Access. 2024;12:137472–137490. https://doi.org/10.1109/ACCESS.2024.3463948

[14] Schulte L, Ledel B, Herbold S. Studying the explanations for the automated prediction of bug and non-bug issues using LIME and SHAP. Empirical Software Engineering. 2024;29(4):93. https://doi.org/10.1007/s10664-024-10469-1

[15] Kapoor S, Cantrell EM, Peng K, et al. REFORMS: Consensus-based recommendations for machine-learning-based science. Science Advances. 2024;10(18):eadk3452. https://doi.org/10.1126/sciadv.adk3452

[16] Saadatfar H, Kiani-Zadegan Z, Ghahremani-Nezhad B. US-LIME: Increasing fidelity in LIME using uncertainty sampling on tabular data. Neurocomputing. 2024;597:127969. https://doi.org/10.1016/j.neucom.2024.127969

[17] Bhatt U, Weller A, Moura JMF. Evaluating and aggregating feature-based model explanations. In: Proceedings of the 29th International Joint Conference on Artificial Intelligence (IJCAI); 2020. p. 3016–3022. https://doi.org/10.24963/ijcai.2020/417

[18] Samek W, Binder A, Montavon G, Lapuschkin S, Müller KR. Evaluating the visualization of what a deep neural network has learned. IEEE Transactions on Neural Networks and Learning Systems. 2017;28(11):2660–2673. https://doi.org/10.1109/TNNLS.2016.2599820

[19] Alvarez-Melis D, Jaakkola TS. On the robustness of interpretability methods. In: ICML Workshop on Human Interpretability in Machine Learning (WHI 2018); 2018. https://arxiv.org/abs/1806.08049

[20] Hedstrom A, Weber L, Bareeva D, Krakowczyk D, Motzkus F, Samek W, et al. Quantus: An explainable AI toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research. 2023;24:1–11. https://jmlr.org/papers/v24/22-0142.html

[21] Agarwal C, Ley D, Krishna S, Saxena E, Pawelczyk M, Johnson N, et al. OpenXAI: Towards a transparent evaluation of model explanations. In: 36th Conference on Neural Information Processing Systems, Datasets and Benchmarks Track; 2022. https://openreview.net/forum?id=MU2495w47rz

[22] Zheng X, Shirani F, Chen Z, Lin C, Cheng W, Guo W, et al. F-Fidelity: A robust framework for faithfulness evaluation of explainable AI. In: The 13th International Conference on Learning Representations (ICLR); 2025. https://openreview.net/forum?id=X0r4BN50Dv

~~[10]~~[23] Adebayo J, Gilmer J, Muelly M, Goodfellow I, Hardt M, Kim B. Sanity checks for saliency maps. In: Advances in Neural Information Processing Systems 31; 2018. p. 9525–9536.

[24] Baniecki H, Biecek P. Adversarial attacks and defenses in explainable artificial intelligence: A survey. Information Fusion. 2024;107:102303. https://doi.org/10.1016/j.inffus.2024.102303

[25] Huang X, Marques-Silva J. On the failings of Shapley values for explainability. International Journal of Approximate Reasoning. 2024;171:109112. https://doi.org/10.1016/j.ijar.2023.109112

[26] Bilodeau B, Jaques N, Koh PW, Kim B. Impossibility theorems for feature attribution. Proceedings of the National Academy of Sciences. 2024;121(2):e2304406120. https://doi.org/10.1073/pnas.2304406120

[27] Clark B, Wilming R, Haufe S. XAI-TRIS: Non-linear image benchmarks to quantify false positive post-hoc attribution of feature importance. Machine Learning. 2024;113(9):6871–6910. https://doi.org/10.1007/s10994-024-06574-3

[28] Lazar A, Pokhrel P, Das S. Beyond accuracy: A comprehensive comparative study of gradient boosting versus tabular deep learning and explainability techniques for mixed-type tabular data models using SHAP and LIME. International Journal on Artificial Intelligence Tools. 2026;35(2):2640003. https://doi.org/10.1142/S0218213026400038

[29] Salih AM, Raisi-Estabragh Z, Galazzo IB, Radeva P, Petersen SE, Lekadir K, et al. A perspective on explainable artificial intelligence methods: SHAP and LIME. Advanced Intelligent Systems. 2025;7(1):2400304. https://doi.org/10.1002/aisy.202400304

[30] Mersha M, Lam K, Wood J, AlShami AK, Kalita J. Explainable artificial intelligence: A survey of needs, techniques, applications, and future direction. Neurocomputing. 2024;599:128111. https://doi.org/10.1016/j.neucom.2024.128111

[31] Moiseev I, Balabaeva K, Kovalchuk S. Open and extensible benchmark for explainable artificial intelligence methods. Algorithms. 2025;18(2):85. https://doi.org/10.3390/a18020085

[32] Brughmans D, Melis L, Martens D. Disagreement amongst counterfactual explanations: How transparency can be misleading. TOP. 2024;32(3):429–462. https://doi.org/10.1007/s11750-024-00670-2

[33] Kohavi R. Scaling up the accuracy of Naive-Bayes classifiers: A decision-tree hybrid. In: Proceedings of the 2nd International Conference on Knowledge Discovery and Data Mining; 1996. p. 202–207.

[34] Becker B, Kohavi R. Adult [dataset]. UCI Machine Learning Repository; 1996. https://doi.org/10.24432/C5XW20

[35] Wolberg W, Mangasarian O, Street N, Street W. Breast cancer Wisconsin (diagnostic) [dataset]. UCI Machine Learning Repository; 1993. https://doi.org/10.24432/C5DW2B

[36] Hofmann H. Statlog (German credit data) [dataset]. UCI Machine Learning Repository; 1994. https://doi.org/10.24432/C5NC77

[37] Dua D, Graff C. UCI Machine Learning Repository. Irvine (CA): University of California, School of Information and Computer Science; 2019. http://archive.ics.uci.edu/ml

[38] Smith JW, Everhart JE, Dickson WC, Knowler WC, Johannes RS. Using the ADAP learning algorithm to forecast the onset of diabetes mellitus. In: Proceedings of the Annual Symposium on Computer Application in Medical Care; 1988. p. 261–265.

[39] Hopkins M, Reeber E. Spambase [dataset]. UCI Machine Learning Repository; 1999. https://doi.org/10.24432/C53G6X

[40] Mohammad R, McCluskey L. Phishing websites [dataset]. UCI Machine Learning Repository; 2012. https://doi.org/10.24432/C51W2X

[41] Tromp J. Connect-4 [dataset]. UCI Machine Learning Repository; 1995. https://doi.org/10.24432/C59P43

[42] Breiman L. Random forests. Machine Learning. 2001;45(1):5–32. https://doi.org/10.1023/A:1010933404324

[43] Chen T, Guestrin C. XGBoost: A scalable tree boosting system. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining; 2016. p. 785–794. https://doi.org/10.1145/2939672.2939785

[44] Bates D, Mächler M, Bolker B, Walker S. Fitting linear mixed-effects models using lme4. Journal of Statistical Software. 2015;67(1):1–48. https://doi.org/10.18637/jss.v067.i01

[45] Field CA, Welsh AH. Bootstrapping clustered data. Journal of the Royal Statistical Society: Series B. 2007;69(3):369–390. https://doi.org/10.1111/j.1467-9868.2007.00593.x

[46] Lakens D. Calculating and reporting effect sizes to facilitate cumulative science: A practical primer for t-tests and ANOVAs. Frontiers in Psychology. 2013;4:863. https://doi.org/10.3389/fpsyg.2013.00863

[47] Hodges JL, Lehmann EL. Estimates of location based on rank tests. The Annals of Mathematical Statistics. 1963;34(2):598–611. https://doi.org/10.1214/aoms/1177704172

[48] Kerby DS. The simple difference formula: An approach to teaching nonparametric correlation. Comprehensive Psychology. 2014;3:11.IT.3.1. https://doi.org/10.2466/11.IT.3.1

[49] Wilcoxon F. Individual comparisons by ranking methods. Biometrics Bulletin. 1945;1(6):80–83. https://doi.org/10.2307/3001968

[50] Holm S. A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics. 1979;6(2):65–70.

[51] Demšar J. Statistical comparisons of classifiers over multiple data sets. Journal of Machine Learning Research. 2006;7:1–30. https://jmlr.org/papers/v7/demsar06a.html

[52] Herrera-Vásquez J, Herrero-Uceda M. A framework for rigorous evaluation of model-agnostic explainability methods: multi-metric statistical benchmarking, operational protocol, and reproducibility. Revista de Investigación Multidisciplinaria Iberoamericana (RIMI). 2026;(3). https://doi.org/10.69850/rimi.vi3.307

~~[11][53] Bhatt U, Weller A, Moura JMF. Evaluating and aggregating feature-based model explanations. In: Proceedings of the 29th International Joint Conference on Artificial Intelligence (IJCAI); 2020. p. 3016–3022. https://doi.org/10.24963/ijcai.2020/417~~

~~[12] Samek W, Binder A, Montavon G, Lapuschkin S, Müller KR. Evaluating the visualization of what a deep neural network has learned. IEEE Transactions on Neural Networks and Learning Systems. 2017;28(11):2660–2673. https://doi.org/10.1109/TNNLS.2016.2599820~~

~~[13] Hooker S, Erhan D, Kindermans PJ, Kim B. A benchmark for interpretability methods in deep neural networks. In: Advances in Neural Information Processing Systems 32; 2019. p. 9737–9748.~~

~~[14] Alvarez-Melis D, Jaakkola TS. On the robustness of interpretability methods. In: ICML Workshop on Human Interpretability in Machine Learning (WHI 2018); 2018. https://arxiv.org/abs/1806.08049~~

~~[15] Hedstrom A, Weber L, Bareeva D, Krakowczyk D, Motzkus F, Samek W, et al. Quantus: An explainable AI toolkit for responsible evaluation of neural network explanations and beyond. Journal of Machine Learning Research. 2023;24:1–11. https://jmlr.org/papers/v24/22-0142.html~~

~~[16] Agarwal C, Ley D, Krishna S, Saxena E, Pawelczyk M, Johnson N, et al. OpenXAI: Towards a transparent evaluation of model explanations. In: 36th Conference on Neural Information Processing Systems, Datasets and Benchmarks Track; 2022. https://openreview.net/forum?id=MU2495w47rz~~

~~[17] Adebayo J, Gilmer J, Muelly M, Goodfellow I, Hardt M, Kim B. Sanity checks for saliency maps. In: Advances in Neural Information Processing Systems 31; 2018. p. 9525–9536.~~

~~[18] Rong Y, Leemann T, Borisov V, Kasneci G, Kasneci E. A consistent and efficient evaluation strategy for attribution methods. In: Proceedings of the 39th International Conference on Machine Learning; 2022. p. 18770–18795. https://proceedings.mlr.press/v162/rong22a.html~~

~~[19] Slack D, Hilgard S, Jia E, Singh S, Lakkaraju H. Fooling LIME and SHAP: Adversarial attacks on post hoc explanation methods. In: Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society; 2020. p. 180–186. https://doi.org/10.1145/3375627.3375830~~

~~[20] Kumar IE, Venkatasubramanian S, Scheidegger C, Friedler SA. Problems with Shapley-value-based explanations as feature importance measures. In: Proceedings of the 37th International Conference on Machine Learning; 2020. p. 5491–5500. https://arxiv.org/abs/2002.11097~~

[21] Kohavi R. Scaling up the accuracy of Naive-Bayes classifiers: A decision-tree hybrid. In: Proceedings of the 2nd International Conference on Knowledge Discovery and Data Mining; 1996. p. 202–207.

[22] Becker B, Kohavi R. Adult [dataset]. UCI Machine Learning Repository; 1996. https://doi.org/10.24432/C5XW20

[23] Breiman L. Random forests. Machine Learning. 2001;45(1):5–32. https://doi.org/10.1023/A:1010933404324

[24] Chen T, Guestrin C. XGBoost: A scalable tree boosting system. In: Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining; 2016. p. 785–794. https://doi.org/10.1145/2939672.2939785

[25] Demšar J. Statistical comparisons of classifiers over multiple data sets. Journal of Machine Learning Research. 2006;7:1–30. https://jmlr.org/papers/v7/demsar06a.html

[26] Wilcoxon F. Individual comparisons by ranking methods. Biometrics Bulletin. 1945;1(6):80–83. https://doi.org/10.2307/3001968

[27] Lakens D. Calculating and reporting effect sizes to facilitate cumulative science: A practical primer for t-tests and ANOVAs. Frontiers in Psychology. 2013;4:863. https://doi.org/10.3389/fpsyg.2013.00863

[28] Holm S. A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics. 1979;6(2):65–70.

[29] Ribeiro MT, Singh S, Guestrin C. Anchors: High-precision model-agnostic explanations. In: Proceedings of the 32nd AAAI Conference on Artificial Intelligence; 2018. p. 1527–1535. https://doi.org/10.1609/aaai.v32i1.11491

[30] Mothilal RK, Sharma A, Tan C. Explaining machine learning classifiers through diverse counterfactual explanations. In: Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency; 2020. p. 607–617. https://doi.org/10.1145/3351095.3372850

[31] Dua D, Graff C. UCI Machine Learning Repository. Irvine (CA): University of California, School of Information and Computer Science; 2019. http://archive.ics.uci.edu/ml

[32] Wolberg W, Mangasarian O, Street N, Street W. Breast cancer Wisconsin (diagnostic) [dataset]. UCI Machine Learning Repository; 1993. https://doi.org/10.24432/C5DW2B

[33] Hofmann H. Statlog (German credit data) [dataset]. UCI Machine Learning Repository; 1994. https://doi.org/10.24432/C5NC77

[34] Haufe S, Wilming R, Clark B, Zhumagambetov R, Boubekki A, Martin J, et al. Explainable AI needs formalization. npj Artificial Intelligence. 2026;2:42. https://doi.org/10.1038/s44387-026-00095-1

[35] Doshi-Velez F, Kim B. Towards a rigorous science of interpretable machine learning [Preprint]. arXiv:1702.08608; 2017. https://arxiv.org/abs/1702.08608

[36] Wilming R, Budding C, Müller KR, Haufe S. Scrutinizing XAI using linear ground-truth data with suppressor variables. Machine Learning. 2022;111(5):1903–1923. https://doi.org/10.1007/s10994-022-06167-y

[37] Wilming R, Kieslich L, Clark B, Haufe S. Theoretical behavior of XAI methods in the presence of suppressor variables. In: Proceedings of the 40th International Conference on Machine Learning; 2023. p. 37091–37107. https://proceedings.mlr.press/v202/wilming23a.html

[38] Jacovi A, Goldberg Y. Towards faithfully interpretable NLP systems: How should we define and evaluate faithfulness? In: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics; 2020. p. 4198–4205. https://doi.org/10.18653/v1/2020.acl-main.386