

VR5-KET Image Data ANOVA

Jonathan Ramos

2024-03-12

```
library(ggplot2)
library(ggpubr)
library(car) # For levene.test() function
```

```
## Loading required package: carData
library(emmeans)
```

Stats in Python were weird

Yesterday I did all the ANOVAs and post hoc tests for the standard stain types (normalized intensity, mean cell counts). I spot checked a few in prism and found that all the main effect F values were slightly different. The interaction effects all agree. Looking into this issue a little deeper, it seems that R agrees with SPSS which agrees with Prism and so I will just have to repeat these in R.

EDA and ANOVA function

This function performs the same type of ANOVA as performed in graphpad prism. In addition, performs some exploratory data analysis to assess normality and homogeneity of variances (both quantitatively and qualitatively)

```
Sidak <- function(pvals)
  # takes a vector of p-values and corrects p-values according to
  # Sidaks method for multiple comparisons (1967)
  #
  # Jonathan Ramos 3/12/2024
  {
    adjusted <- c()
    j <- length(pvals)

    for (i in 1:j){
      adj_p <- 1-(1-pvals[i])^j
      adjusted <- c(adjusted, adj_p)
    }
    return(adjusted)
  }

eda_anova <- function(fname)
  # takes a filename, loads data from csv; data 4 columns:
  # react_treat, react, treat, and norm_int (response var)
  # react_treat is just react and treat in one string separated by "_"
```

```

# builds factor cols for categorical cols (norm_int is numeric, all others are categorical)
# then performs the following tasks:
# checks assumptions of normality with qqplot and shapiro wilk tests
# checks assumptions of equal variances with box plot and levene test
# performs 2way ANOVA (2 by 2, react by treat)
# performs post hoc pairwise comparisons (emmeans of levels of react by treat
# and emmeans of levels of treat by react)
# prints out all statistical test results and returns plot objects
# for the two plots: the qqplots and the box plots
#
# Jonathan Ramos 3/12/2024

{
df <- read.csv(fname, header=TRUE, sep=",")
df$react_treat_factor <- as.factor(df$react_treat)
df$react_factor <- as.factor(df$react)
df$treat_factor <- as.factor(df$treat)

### check assumption of normality
# quantitative assessment
# print(tapply(df$norm_int, df$react_treat_factor, shapiro.test))

# qualitative assessment
g <- ggqqplot(df, x="norm_int", facet.by=c("treat_factor", "react_factor"))

### check assumption of equal variances
# quantitative assessment
# print(leveneTest(y = df$norm_int, group=df$react_treat_factor, center='mean'))

# qualitative assessment
f <- ggplot(df, aes(x=treat_factor, y=norm_int)) + geom_boxplot(aes(fill=treat_factor), alpha=0.5) +
  #geom_dotplot(binaxis = "y", stackdir = "center", dotsize=0.5) +
  facet_wrap(~react_factor) +
  theme(axis.text.x = element_text(angle = 45, vjust = 1, hjust=1))

# run the ANOVA, display summary
df.lm <- lm(norm_int ~ treat_factor + react_factor + treat_factor*react_factor, contrasts=list(treat_
df.III.aov <- car::Anova(df.lm, type = 3)
print(df.III.aov)

# post hoc pairwise comparisons
emm <- emmeans(df.lm, ~ treat_factor * react_factor)
p1 <- pairs(emm, simple="treat_factor", adjust="tukey")
p2 <- pairs(emm, simple="react_factor", adjust="tukey")

# add col to summary dataframe containing sidak adjusted p-values
adjusted_p.value1 <- Sidak(summary(p1, adjust="tukey")$p.value)
s1 <- summary(p1)
s1['adjusted_p.value'] <- adjusted_p.value1

adjusted_p.value2 <- Sidak(summary(p2, adjust="tukey")$p.value)
s2 <- summary(p2)
s2['adjusted_p.value'] <- adjusted_p.value2

```

```
# display results
print(s1)
print(s2)

return(list(g, f))
}
```

pulling out filenames

```
singles = list.files(pattern="KET-VR5_single")
quads = list.files(pattern="KET-VR5_quad")
pv = list.files(pattern="PV_coloc")
cfos = list.files(pattern="cFos_coloc")
npas4 = list.files(pattern="Npas4_coloc")
wfa = list.files(pattern="WFA_coloc")
```

Single cFos

```
fname = singles[1]

print(fname)

## [1] "KET-VR5_single_cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq   Df   F value    Pr(>F)
## (Intercept)    8420.2    1 15088.1755 < 2.2e-16 ***
## treat_factor      3.2    1   5.7738  0.01629 *
## react_factor      0.6    1   1.0990  0.29451
## treat_factor:react_factor 15.3    1   27.3998 1.697e-07 ***
## Residuals      4461.7 7995
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL   0.0476 0.0230 7995   2.071  0.0384      7.52e-02
##
## react_factor = VR5:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL  -0.1284 0.0245 7995  -5.231 <.0001      3.40e-07
##
## treat_factor = KET:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0704 0.0247 7995   2.846  0.0044      8.86e-03
##
## treat_factor = SAL:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.1056 0.0228 7995  -4.637 <.0001      7.20e-06

print(fname)

## [1] "KET-VR5_single_cFos_NORM_Rsubset.csv"
```

Single Npas4

```
fname = singles[2]

print(fname)

## [1] "KET-VR5_single_Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq   Df  F value    Pr(>F)
## (Intercept)    6049.4    1 33334.848 < 2.2e-16 ***
## treat_factor      37.3    1   205.787 < 2.2e-16 ***
## react_factor       6.0    1    33.249 8.392e-09 ***
## treat_factor:react_factor  17.7    1    97.598 < 2.2e-16 ***
## Residuals      1535.3 8460
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL   -0.228 0.0132 8460 -17.269  <.0001      0.00000
##
## react_factor = VR5:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL   -0.042 0.0134 8460  -3.133  0.0017      0.00347
##
## treat_factor = KET:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.0387 0.0144 8460  -2.697  0.0070      0.014
##
## treat_factor = SAL:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.1472 0.0122 8460  12.093  <.0001      0.000

print(fname)

## [1] "KET-VR5_single_Npas4_NORM_Rsubset.csv"
```

Single PV

```
fname = singles[3]

print(fname)

## [1] "KET-VR5_single_PV_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq   Df   F value Pr(>F)
## (Intercept)    1439.86    1 2560.0767 <2e-16 ***
## treat_factor      0.61    1   1.0888 0.2969
## react_factor      1.50    1   2.6751 0.1022
## treat_factor:react_factor 0.68    1   1.2069 0.2722
## Residuals      709.79 1262
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL  0.09150 0.0620 1262   1.475  0.1404          0.261
##
## react_factor = VR5:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL -0.00235 0.0587 1262  -0.040  0.9680          0.999
##
## treat_factor = KET:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.0229 0.0649 1262  -0.354  0.7237          0.9236
##
## treat_factor = SAL:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.1168 0.0556 1262  -2.101  0.0359          0.0705

print(fname)

## [1] "KET-VR5_single_PV_NORM_Rsubset.csv"
```

Single WFA

```
fname = singles[4]

print(fname)

## [1] "KET-VR5_single_WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df    F value    Pr(>F)
## (Intercept)      594.90  1 1075.7751 < 2.2e-16 ***
## treat_factor         6.84  1  12.3617 0.0004601 ***
## react_factor        11.21  1  20.2770 7.582e-06 ***
## treat_factor:react_factor  0.64  1   1.1627 0.2811975
## Residuals        497.14 899
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.123 0.0725 899  -1.692  0.0909          0.17362
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.231 0.0698 899  -3.311  0.0010          0.00193
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.281 0.0771 899   3.645  0.0003          0.000566
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.172 0.0647 899   2.662  0.0079          0.015751

print(fname)

## [1] "KET-VR5_single_WFA_NORM_Rsubset.csv"
```

PV coloc w cFos

```
fname = pv[1]

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df    F value Pr(>F)
## (Intercept)    667.64  1 1315.7840 <2e-16 ***
## treat_factor      0.00  1   0.0096 0.9219
## react_factor     1.27  1   2.5028 0.1142
## treat_factor:react_factor 1.17  1   2.3023 0.1297
## Residuals      288.21 568
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   0.0853 0.0852 568   1.001  0.3173           0.534
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0971 0.0848 568  -1.145  0.2525           0.441
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5 -0.00389 0.0903 568  -0.043  0.9657           0.999
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5 -0.18630 0.0793 568  -2.349  0.0192           0.038

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos_NORM_Rsubset.csv"
```


PV coloc w cFos, Npas4

```
fname = pv[2]

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos,Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value  Pr(>F)
## (Intercept)    399.86  1 801.8523 < 2e-16 ***
## treat_factor      0.03  1  0.0591 0.80806
## react_factor      0.05  1  0.0958 0.75709
## treat_factor:react_factor  2.38  1  4.7762 0.02952 *
## Residuals      174.04 349
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL      0.185 0.104 349   1.775  0.0768         0.148
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL     -0.148 0.111 349  -1.332  0.1839         0.334
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.190 0.114 349   1.668  0.0962         0.183
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.143 0.101 349  -1.413  0.1585         0.292

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos,Npas4_NORM_Rsubset.csv"
```

PV coloc w cFos, WFA

```
fname = pv[3]

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value    Pr(>F)
## (Intercept)    311.346  1 993.0975 < 2.2e-16 ***
## treat_factor      0.018  1  0.0579  0.810089
## react_factor      2.113  1  6.7392  0.009956 **
## treat_factor:react_factor  0.000  1  0.0014  0.970414
## Residuals      83.394 266
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0190 0.0942 266  -0.202  0.8401          0.974
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0139 0.0995 266  -0.140  0.8887          0.988
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.180 0.101 266  -1.793  0.0741          0.143
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.175 0.093 266  -1.885  0.0605          0.117

print(fname)

## [1] "KET-VR5_PV_coloc_w_cFos,WFA_NORM_Rsubset.csv"
```

PV coloc w Npas4

```
fname = pv[4]

print(fname)

## [1] "KET-VR5_PV_coloc_w_Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value  Pr(>F)
## (Intercept)    587.59  1 1191.6395 < 2e-16 ***
## treat_factor      0.23  1   0.4717  0.49252
## react_factor      0.05  1   0.0942  0.75908
## treat_factor:react_factor  2.43  1   4.9271  0.02687 *
## Residuals      254.43 516
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL      0.182 0.0874 516   2.083  0.0377          0.074
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL     -0.096 0.0898 516  -1.070  0.2853          0.489
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.158 0.0960 516   1.649  0.0998          0.190
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.120 0.0805 516  -1.488  0.1373          0.256

print(fname)

## [1] "KET-VR5_PV_coloc_w_Npas4_NORM_Rsubset.csv"
```

PV coloc w Npas4, WFA

```
fname = pv[5]

print(fname)

## [1] "KET-VR5_PV_coloc_w_Npas4,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value  Pr(>F)
## (Intercept)    283.152  1 1072.9078 < 2e-16 ***
## treat_factor      0.133  1   0.5057 0.47767
## react_factor      0.651  1   2.4667 0.11756
## treat_factor:react_factor 0.772  1   2.9257 0.08843 .
## Residuals      65.450 248
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   0.0662 0.0862 248   0.768  0.4432          0.690
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.1604 0.1006 248  -1.594  0.1121          0.212
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.00927 0.0995 248   0.093  0.9258          0.9945
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.21739 0.0875 248  -2.483  0.0137          0.0272

print(fname)

## [1] "KET-VR5_PV_coloc_w_Npas4,WFA_NORM_Rsubset.csv"
```

PV coloc w WFA

```
fname = pv[6]

print(fname)

## [1] "KET-VR5_PV_coloc_w_WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value    Pr(>F)
## (Intercept)    532.65  1 1645.8078 < 2.2e-16 ***
## treat_factor      0.01  1   0.0379  0.845679
## react_factor      2.33  1   7.1933  0.007591 **
## treat_factor:react_factor  0.23  1   0.7166  0.397733
## Residuals      143.70 444
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   0.0565 0.0767 444   0.737  0.4614           0.710
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0354 0.0769 444  -0.460  0.6456           0.874
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.0996 0.0814 444  -1.224  0.2215           0.3939
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.1915 0.0719 444  -2.665  0.0080           0.0159

print(fname)

## [1] "KET-VR5_PV_coloc_w_WFA_NORM_Rsubset.csv"
```

cFos coloc w Npas4

```
fname = cfos[1]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq   Df  F value    Pr(>F)
## (Intercept)    4420.2    1 8145.4834 < 2.2e-16 ***
## treat_factor      1.2    1   2.2220   0.1361
## react_factor      0.1    1   0.1328   0.7156
## treat_factor:react_factor  18.8    1   34.6292  4.33e-09 ***
## Residuals      2082.7 3838
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL      0.179 0.0337 3838   5.307  <.0001      2.35e-07
##
## react_factor = VR5:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## KET - SAL     -0.107 0.0349 3838  -3.055  0.0023      4.53e-03
##
## treat_factor = KET:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.134 0.0371 3838   3.611  0.0003      6.17e-04
##
## treat_factor = SAL:
##   contrast estimate      SE    df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.151 0.0313 3838  -4.845  <.0001      2.63e-06

print(fname)

## [1] "KET-VR5_cFos_coloc_w_Npas4_NORM_Rsubset.csv"
```

cFos coloc w Npas4, WFA

```
fname = cfos[2]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_Npas4,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value Pr(>F)
## (Intercept)    218.715  1 515.1406 <2e-16 ***
## treat_factor      0.168  1  0.3958 0.5299
## react_factor      0.034  1  0.0812 0.7760
## treat_factor:react_factor  0.792  1  1.8658 0.1734
## Residuals      93.406 220
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL      0.068 0.112 220   0.607  0.5442          0.792
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL     -0.184 0.147 220  -1.255  0.2109          0.377
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.0997 0.135 220   0.739  0.4607          0.709
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.1523 0.126 220  -1.210  0.2274          0.403

print(fname)

## [1] "KET-VR5_cFos_coloc_w_Npas4,WFA_NORM_Rsubset.csv"
```

cFos coloc w PV

```
fname = cfos[3]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df   F value Pr(>F)
## (Intercept)    645.92  1 1188.8512 <2e-16 ***
## treat_factor      0.00  1   0.0038 0.9509
## react_factor      0.72  1   1.3329 0.2488
## treat_factor:react_factor 0.67  1   1.2309 0.2677
## Residuals      308.60 568
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    0.0728 0.0882 568   0.826  0.4093          0.651
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.0652 0.0877 568  -0.743  0.4578          0.706
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.0028 0.0935 568  -0.030  0.9761          0.999
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.1408 0.0821 568  -1.716  0.0867          0.166

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV_NORM_Rsubset.csv"
```


cFos coloc w PV, Npas4

```
fname = cfos[4]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV,Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq  Df  F value Pr(>F)
## (Intercept)      409.80   1 739.7976 <2e-16 ***
## treat_factor         0.00   1   0.0072  0.9326
## react_factor         0.41   1   0.7462  0.3883
## treat_factor:react_factor  1.35   1   2.4443  0.1189
## Residuals       193.33 349
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL      0.119 0.110 349   1.081  0.2805          0.482
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL     -0.133 0.117 349  -1.130  0.2593          0.451
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.0563 0.120 349   0.468  0.6403          0.871
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.1953 0.107 349  -1.828  0.0683          0.132

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV,Npas4_NORM_Rsubset.csv"
```

cFos coloc w PV, WFA

```
fname = cfos[5]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq  Df  F value Pr(>F)
## (Intercept)      326.41   1 614.1396 <2e-16 ***
## treat_factor         0.29   1   0.5521 0.4581
## react_factor         0.05   1   0.0849 0.7710
## treat_factor:react_factor 0.93   1   1.7546 0.1864
## Residuals       141.37 266
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   0.1844 0.123 266   1.504  0.1337          0.250
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0519 0.130 266  -0.400  0.6892          0.903
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0922 0.131 266   0.704  0.4823          0.732
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.1441 0.121 266  -1.190  0.2350          0.415

print(fname)

## [1] "KET-VR5_cFos_coloc_w_PV,WFA_NORM_Rsubset.csv"
```

cFos coloc w WFA

```
fname = cfos[6]

print(fname)

## [1] "KET-VR5_cFos_coloc_w_WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value Pr(>F)
## (Intercept)    400.64  1  921.0911 <2e-16 ***
## treat_factor      0.25  1   0.5814  0.4462
## react_factor      0.03  1   0.0610  0.8051
## treat_factor:react_factor 0.15  1   0.3459  0.5568
## Residuals      177.90 409
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0115 0.0891 409  -0.129  0.8972           0.989
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0892 0.0975 409  -0.915  0.3609           0.592
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0225 0.0986 409   0.229  0.8193           0.967
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.0552 0.0879 409  -0.627  0.5309           0.780

print(fname)

## [1] "KET-VR5_cFos_coloc_w_WFA_NORM_Rsubset.csv"
```

Npas4 coloc w cFos

```
fname = npas4[1]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq   Df   F value    Pr(>F)
## (Intercept)    2972.88    1 12856.5226 < 2.2e-16 ***
## treat_factor      15.05    1   65.1041 9.413e-16 ***
## react_factor       0.00    1    0.0001  0.9913
## treat_factor:react_factor  5.63    1   24.3642 8.313e-07 ***
## Residuals      887.48 3838
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE   df t.ratio p.value adjusted_p.value
## KET - SAL  -0.2058 0.0220 3838  -9.358  <.0001      0.0000
##
## react_factor = VR5:
##   contrast estimate      SE   df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0496 0.0228 3838  -2.178  0.0295      0.0581
##
## treat_factor = KET:
##   contrast estimate      SE   df t.ratio p.value adjusted_p.value
## FR1 - VR5  -0.0779 0.0242 3838  -3.222  0.0013      0.002565
##
## treat_factor = SAL:
##   contrast estimate      SE   df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0783 0.0204 3838   3.836  0.0001      0.000255

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_cFos_NORM_Rsubset.csv"
```

Npas4 coloc w cFos, WFA

```
fname = npas4[2]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_cFos,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df  F value    Pr(>F)
## (Intercept)    138.558  1 1503.1874 < 2.2e-16 ***
## treat_factor      0.787  1   8.5427  0.003831 **
## react_factor      0.665  1   7.2098  0.007803 **
## treat_factor:react_factor 0.422  1   4.5784  0.033479 *
## Residuals      20.279 220
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.2177 0.0522 220  -4.173  <.0001      8.64e-05
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0337 0.0684 220  -0.492  0.6229      8.58e-01
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0234 0.0629 220   0.373  0.7096      0.915679
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.2074 0.0586 220   3.537  0.0005      0.000985

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_cFos,WFA_NORM_Rsubset.csv"
```

Npas4 coloc w PV

```
fname = npas4[3]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value    Pr(>F)
## (Intercept)    331.04  1 1412.5563 < 2.2e-16 ***
## treat_factor      6.78  1   28.9210 1.145e-07 ***
## react_factor      0.07  1    0.2972 0.585909
## treat_factor:react_factor  1.83  1    7.8101 0.005389 **
## Residuals      120.93 516
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.353 0.0603 516  -5.858  <.0001      2.00e-08
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.112 0.0619 516  -1.802  0.0721      1.39e-01
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.0972 0.0662 516  -1.468  0.1427      0.2650
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.1443 0.0555 516   2.598  0.0096      0.0192

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV_NORM_Rsubset.csv"
```

Npas4 coloc w PV, cFos

```
fname = npas4[4]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV,cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value    Pr(>F)
```

```

## (Intercept)                226.485    1 898.4550 < 2.2e-16 ***
## treat_factor                5.871    1 23.2890 2.087e-06 ***
## react_factor                0.027    1  0.1090  0.74146
## treat_factor:react_factor   1.424    1  5.6504  0.01799 *
## Residuals                   87.977 349
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.391 0.0743 349 -5.264 <.0001      4.90e-07
##
## react_factor = VR5:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.133 0.0792 349 -1.679  0.0941      1.79e-01
##
## treat_factor = KET:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.147 0.0812 349 -1.810  0.0712      0.137
##
## treat_factor = SAL:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.111 0.0721 349  1.542  0.1240      0.233
print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV,cFos_NORM_Rsubset.csv"

```

Npas4 coloc w PV, WFA

```
fname = npas4[5]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV,WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df  F value    Pr(>F)
## (Intercept)    169.802  1 1641.5781 < 2.2e-16 ***
## treat_factor      0.850  1   8.2155  0.004510 **
## react_factor      0.912  1   8.8148  0.003281 **
## treat_factor:react_factor 0.359  1   3.4728  0.063566 .
## Residuals      25.653 248
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.1962 0.054 248  -3.635  0.0003      0.000675
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0416 0.063 248  -0.660  0.5098      0.759672
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0459 0.0623 248   0.736  0.4623      0.710857
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.2005 0.0548 248   3.658  0.0003      0.000622

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_PV,WFA_NORM_Rsubset.csv"
```


Npas4 coloc w WFA

```
fname = npas4[6]

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value    Pr(>F)
## (Intercept)    220.716  1 2244.1567 < 2.2e-16 ***
## treat_factor      0.951  1   9.6676 0.0020413 **
## react_factor      1.140  1  11.5925 0.0007452 ***
## treat_factor:react_factor  0.440  1   4.4721 0.0352131 *
## Residuals      31.964 325
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.1866 0.0457 325  -4.081  0.0001      0.000113
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0355 0.0549 325  -0.647  0.5179      0.767627
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.0461 0.0535 325   0.861  0.3899      6.28e-01
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   0.1971 0.0473 325   4.167 <.0001      7.93e-05

print(fname)

## [1] "KET-VR5_Npas4_coloc_w_WFA_NORM_Rsubset.csv"
```

WFA coloc w cFos

```
fname = wfa[1]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value    Pr(>F)
## (Intercept)    238.082  1 469.7587 < 2.2e-16 ***
## treat_factor     10.343  1  20.4085 8.197e-06 ***
## react_factor      3.784  1   7.4658 0.006561 **
## treat_factor:react_factor  0.388  1   0.7663 0.381888
## Residuals      207.288 409
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.260 0.0962 409  -2.700  0.0072      0.014387
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.385 0.1053 409  -3.652  0.0003      0.000587
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.257 0.1064 409   2.417  0.0161      0.0319
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.132 0.0949 409   1.395  0.1638      0.3008

print(fname)

## [1] "KET-VR5_WFA_coloc_w_cFos_NORM_Rsubset.csv"
```

WFA coloc w cFos, Npas4

```
fname = wfa[2]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_cFos,Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value    Pr(>F)
## (Intercept)    113.549  1 184.1764 < 2.2e-16 ***
## treat_factor      4.385  1   7.1118  0.008227 **
## react_factor      2.472  1   4.0100  0.046459 *
## treat_factor:react_factor  0.040  1   0.0642  0.800221
## Residuals      135.635 220
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    -0.268 0.135 220  -1.990  0.0479          0.0935
##
## react_factor = VR5:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    -0.325 0.177 220  -1.836  0.0676          0.1307
##
## treat_factor = KET:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.251 0.163 220   1.542  0.1245          0.233
##
## treat_factor = SAL:
## contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.194 0.152 220   1.282  0.2010          0.362

print(fname)

## [1] "KET-VR5_WFA_coloc_w_cFos,Npas4_NORM_Rsubset.csv"
```

WFA coloc w Npas4

```
fname = wfa[3]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value    Pr(>F)
## (Intercept)    175.155  1 342.8635 < 2.2e-16 ***
## treat_factor      4.164  1   8.1504  0.004582 **
## react_factor      4.822  1   9.4386  0.002304 **
## treat_factor:react_factor  0.008  1   0.0164  0.898133
## Residuals      166.030 325
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.243 0.104 325  -2.330  0.0204          0.0404
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.222 0.125 325  -1.774  0.0769          0.1479
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.24 0.122 325   1.965  0.0503          0.0980
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.26 0.108 325   2.416  0.0162          0.0322

print(fname)

## [1] "KET-VR5_WFA_coloc_w_Npas4_NORM_Rsubset.csv"
```

WFA coloc w PV

```
fname = wfa[4]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value    Pr(>F)
## (Intercept)    294.116  1 760.6333 < 2.2e-16 ***
## treat_factor      5.393  1  13.9466 0.0002126 ***
## react_factor      2.483  1   6.4207 0.0116226 *
## treat_factor:react_factor  0.007  1   0.0194 0.8893554
## Residuals      171.682 444
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    -0.213 0.0838 444  -2.546  0.0112          0.0224
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    -0.230 0.0840 444  -2.736  0.0065          0.0129
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.159 0.0889 444   1.783  0.0753          0.145
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.142 0.0785 444   1.809  0.0711          0.137

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV_NORM_Rsubset.csv"
```

WFA coloc w PV, cFos

```
fname = wfa[5]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV,cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value    Pr(>F)
## (Intercept)    169.097  1 403.8585 < 2.2e-16 ***
## treat_factor      6.783  1  16.2002 7.436e-05 ***
## react_factor      1.716  1   4.0982 0.04393 *
## treat_factor:react_factor  0.326  1   0.7791 0.37820
## Residuals      111.375 266
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.249 0.109 266  -2.286  0.0230          0.04555
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.389 0.115 266  -3.378  0.0008          0.00168
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.2301 0.116 266   1.979  0.0488          0.0952
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.0904 0.107 266   0.841  0.4011          0.6413

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV,cFos_NORM_Rsubset.csv"
```

WFA coloc w PV, Npas4

```
fname = wfa[6]

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV,Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value    Pr(>F)
## (Intercept)    138.565  1 401.7973 < 2.2e-16 ***
## treat_factor      3.586  1  10.3986  0.001431 **
## react_factor      2.524  1   7.3203  0.007291 **
## treat_factor:react_factor  0.064  1   0.1856  0.666997
## Residuals      85.526 248
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.277 0.0985 248  -2.809  0.0054          0.0107
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.212 0.1150 248  -1.839  0.0671          0.1296
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.172 0.114 248   1.515  0.1310          0.2449
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.238 0.100 248   2.374  0.0184          0.0364

print(fname)

## [1] "KET-VR5_WFA_coloc_w_PV,Npas4_NORM_Rsubset.csv"
```

quad cFos

```
fname = quads[1]

print(fname)

## [1] "KET-VR5_quad_cFos_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value    Pr(>F)
## (Intercept)    203.883  1 419.9202 < 2e-16 ***
## treat_factor      0.031  1   0.0634  0.80156
## react_factor      0.002  1   0.0047  0.94539
## treat_factor:react_factor  1.707  1   3.5153  0.06253 .
## Residuals      82.054 169
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL      0.232 0.137 169   1.698  0.0914      0.174
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL     -0.177 0.170 169  -1.041  0.2993      0.509
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5      0.197 0.161 169   1.225  0.2221      0.395
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     -0.212 0.148 169  -1.438  0.1523      0.281

print(fname)

## [1] "KET-VR5_quad_cFos_NORM_Rsubset.csv"
```


quad Npas4

```
fname = quads[2]

print(fname)

## [1] "KET-VR5_quad_Npas4_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df  F value    Pr(>F)
## (Intercept)    105.731  1 1198.6533 < 2.2e-16 ***
## treat_factor      0.848  1   9.6178  0.002259 **
## react_factor      0.673  1   7.6339  0.006363 **
## treat_factor:react_factor 0.526  1   5.9578  0.015684 *
## Residuals      14.907 169
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.2582 0.0584 169  -4.424  <.0001      3.46e-05
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL  -0.0308 0.0726 169  -0.424  0.6724      8.93e-01
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.015 0.0687 169   0.218  0.8273      0.970177
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5    0.242 0.0630 169   3.850  0.0002      0.000335

print(fname)

## [1] "KET-VR5_quad_Npas4_NORM_Rsubset.csv"
```

quad PV

```
fname = quads[3]

print(fname)

## [1] "KET-VR5_quad_PV_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##              Sum Sq Df F value Pr(>F)
## (Intercept)    186.804  1 717.5646 <2e-16 ***
## treat_factor      0.008  1   0.0301  0.8625
## react_factor      0.445  1   1.7098  0.1928
## treat_factor:react_factor  0.116  1   0.4437  0.5063
## Residuals      43.996 169
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL    0.0394 0.100 169   0.393  0.6947          0.907
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.0672 0.125 169  -0.539  0.5909          0.833
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.0513 0.118 169  -0.435  0.6640          0.887
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5   -0.1580 0.108 169  -1.460  0.1461          0.271

print(fname)

## [1] "KET-VR5_quad_PV_NORM_Rsubset.csv"
```

quad WFA

```
fname = quads[4]

print(fname)

## [1] "KET-VR5_quad_WFA_NORM_Rsubset.csv"

figs = eda_anova(fname)

## Anova Table (Type III tests)
##
## Response: norm_int
##
##               Sum Sq Df F value    Pr(>F)
## (Intercept)    91.702  1 224.9661 < 2.2e-16 ***
## treat_factor     3.415  1   8.3767  0.004302 **
## react_factor     1.541  1   3.7806  0.053512 .
## treat_factor:react_factor  0.007  1   0.0172  0.895798
## Residuals      68.889 169
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
## react_factor = FR1:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.303 0.125 169  -2.415  0.0168          0.0333
##
## react_factor = VR5:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## KET - SAL   -0.277 0.156 169  -1.772  0.0782          0.1502
##
## treat_factor = KET:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.182 0.148 169   1.230  0.2204          0.392
##
## treat_factor = SAL:
##   contrast estimate      SE df t.ratio p.value adjusted_p.value
## FR1 - VR5     0.208 0.135 169   1.535  0.1265          0.237

print(fname)

## [1] "KET-VR5_quad_WFA_NORM_Rsubset.csv"
```