

Royal Enfield - Bullet350_Twinspark_Owner_Manual

1 RELOADED

Get ready for the adventure of a lifetime. Reengineered. Redesigned. Revitalized.

The all-new Bullet Electra 350 UCE features a modern Unit Construction engine with 5 gears on the left. Easier to ride, more torque and no maintenance trouble. It's the Bullet Reloaded.

This manual is designed to give you complete control over your motorcycle. It contains important information on efficient operation and maintenance. We've also included tips on riding safely, as well as suggestions to enhance your motorcycling experience.

Your safety is of prime concern to us and we urge you to be a responsible rider. Please select your riding gear carefully in accordance with your terrain, style and weather conditions. And ensure the same for your pillion rider as well. Respect the law of the land and ride safe.

Finally, we welcome you to the Royal Enfield community. You can locate your nearest club or sign up for the next big ride at www.royalenfield.com

The legend rides on.

2 All information in this manual is based on the latest product information available at the time of publication. Due to continuous improvements or other changes, there may be discrepancies between information in this manual and your vehicle. Royal Enfield reserves the right to make production changes at any time without prior notice and without incurring any obligation to make same or similar changes to vehicles previously built or sold.

All images shown are for reference to explain and need not to be exactly the same on the model you own. Technical specifications are subject to change without prior notice.

© Copyright 2014 Royal Enfield (A unit of Eicher Motors Ltd.). All Rights Reserved. No part of this manual shall be copied, distributed or otherwise dealt without the express permission in writing of Royal Enfield. **N O T I C E**

Part No. 592579/B / Qty. 1000 / Apr. 14

3 Personal and vehicle information	4
Free service record	5
Specifications	6
Safety Definitions	9
Safe and happy riding	10
Vehicle identification numbers	11
Location of key parts	12
Operation of controls	15
Pre-Operational Checks	21
Running in Period	22
Starting	23
Gear Shifting, Riding & Stopping	25
Parking	26
Tools & First Aid kit	27
Periodical maintenance chart	28
Recommended lubricants	31
Do it yourself.....	32
Washing procedure	46
Storage precautions	47
Long trip precautions	49

BL Motorcycles Ltd

Professional Workshop Manual - English Translation

Caring for Mileage	50
Complete Wiring diagram	53
Trouble shooting	54
Warranty terms & conditions.....	61
Emission Warranty	63
All India Road Signs	67
Log Book	68
Free Service coupons	70
Paid Service & Maintenance Record	79
Notes.....	87

Annexures

Vehicle Installation Form

Pre-Delivery Inspection Report

Bike Installation Confirmation By Customer

Form 22 C O N T E N T S

4 P E R S O N A L & V E H I C L E I N F O R M A T I O N

Vehicle Installation Form (VIF) No.

Name

Door No./Street

Locality

City State Pin

Contact Nos. Res: Off: Mobile : Email :

Engine No. Battery No.

Frame No. Battery make

Reg. No. Licence No.

Date of Sale Valid till dt.

Model Key No. :

Tyre make Colour

Sold by Dealer Code

5

F R E E S E R V I C E R E C O R D

It is our endeavour to provide excellent service to your Bullet Electra 350 UCE at all times. Towards this we provide four free services at specific intervals.

Please avail these services at the specified time, in any of the Royal Enfield Authorised Dealer / Service Point nearest to you and as a token of satisfactory services, kindly return the free service coupon duly filled in and signed, to the service outlet.

Availing the free services in the specified time is a prerequisite for warranty consideration.

The cost of fuel, oil, oil filter element, grease etc. used for all free services are chargeable to the customer.

Note : Please ensure that the free service details are recorded in this sheet immediately after the service is carried out.

Date of Service

Kms Covered

Servicing Dealers Name

BL Motorcycles Ltd

Professional Workshop Manual - English Translation

Address

1st Service

4th Service

2nd Service

3rd Service

Dealer / ASP

Rubber Stamp

Dealer / ASP

Rubber Stamp

Dealer / ASP

Rubber Stamp

Dealer / ASP

Rubber Stamp

6

SPECIFICATIONS

ENGINE AND ENGINE SYSTEMS

Engine Type Single Cylinder

..... 4 Stroke, OHV,

..... Dual Spark Ignition

..... air cooled

Bore 70mm

Stroke 90mm

Swept volume 346cc

Compression ratio 8.5:1

Max. Power BHP @ RPM 19.8@5250

Max. Torque in NM@ RPM 28@4000

Idle RPM 1050+

200

Starting Kick Start/E-Start

Air filter element Paper element

Lubrication Wet sump, Forced

..... lubrication

Engine oil capacity 2.75 Litres

Carburetor UCAL, BS29

Engine oil grade Royal Enfield

..... 15 W 50 API SL

..... Engine Oil (JASOMA)

Cooling Natural air flow

TRANSMISSION

Clutch Wet multiplate

Primary drive Duplex chain drive

Primary ratio 2.15 : 1

Gear box Constant Mesh

..... 5 Speed

Gear Ratio 1st 3.06:1

BL Motorcycles Ltd

Professional Workshop Manual - English Translation

..... 2nd 2.01:1
..... 3rd 1.52:1
..... 4th 1.21:1
..... 5th 1:1
7Final drive 15 Teeth (Sprocket)
Final Ratio 2.533:1

CHASSIS

Frame Tubular
Suspension :Front Telescopic, hydraulic
..... damping,
..... Stroke 130 mm
Rear Swing arm with
..... gas shock absorbers
..... stroke 80mm
Fr. Fork oil capacity 195 ml per leg
Front fork oil 1F (Endurance fork oil)
Front Brake : Disc Brake . Hydraulic 280mm
..... ventilated disc.
Rear Foot operated 153 mm
..... single lead, internal
..... expanding
Brake oil Capacity 60 ml
Brake oil grade DOT 3 or DOT 4
Tyre size : Front 3.25x19 4/6 PR
Rear 3.25x19 4/6 PR

TYRE PRESSURE

Solo Front 20 psi/1.41 kg/cm²
Rear 30 psi/2.11 kg/cm²
With Pillion Front 22 psi/1.55 kg/cm²
Rear 32 psi/2.20 kg/cm²
Steering lock..... In built
Fuel tank capacity 13.5 Litres
Reserve 2 Litres approx.

ELECTRICALS

Generation..... Alternator
System : E-Start 12V-DC (III Phase)
Kick Start 12V-AC/DC (I Phase) S P E C I F I C A T I O N S

8Values / Dimensions given above are for your guidance only.

In view of continuous improvements being done on our products, the specifications are likely to change without prior notice.

Ignition Digital Dual Spark
..... Ignition, TCI System
Battery : E-Start 12V-14 AH MF (III Phase)
Kick Start 12V-5 AH (I Phase)
Head lamp MFR 12V, 35/35W

BL Motorcycles Ltd

Professional Workshop Manual - English Translation

Tail lamp 12V, 5W
Brake lamp 12V, 21W
Parking lamp 12V, 2W (2 Nos.)
Speedometer lamp 12V, 3.4W
Hi beam indicator 12V, 2W
Turn Signal Tell Tale 12V, 2W
Turn signal 12V, 10W
Horn 12V, 2.5 Amp(Max.)
Starter Motor (for E-Start) 12V, 0.7KW

SPECIFICATIONS WARNING

Using bulbs / other electrical gadgets other than specified rating may lead to over loading / erratic behaviour / premature failure of electrical system.

Modifications on the bike which are not approved by Royal Enfield may not only disqualify for warranty, but also affects performance of the bike.

WEIGHTS

Kerb weight (90% fuel & Oil)

E-Start 187 Kgs

Kick Start 183 Kgs

Max pay load 163 Kgs.

DIMENSIONS

Length 2140 mm

Width..... 810 mm