## **Specifications**

Output level ...... During audio output

Number of channels ......2

Jack ......RCA jacks

200 mVrms (1 kHz, -20 dB)

General	Digital Audio Characteristics
System	Frequency response 4 Hz to 44 kHz
Power requirements AC 120 V, 50/60 Hz	(DVD fs: 96 kHz)
Power consumption11 W	S/N ratio
Power consumption (standby) 0.7 W	Dynamic range
Weight 2.5 kg / 5 lb 8 oz	Total harmonic distortion 0.0025 %
Dimensions 420 (W) x 55 (H) x 283 (D) mm	Wow and flutter Limit of measurement (±0.001 % W. PEAK) or lower
(16.5 (W) x 2.2 (H) x 11.1 (D) in.) Operating temperature +5 °C to +35 °C	(±0.001 % W. FEAR) OF lower
(+41 °F to +95 °F)	Other Terminals
Operating humidity 5 % to 85 %	Coaxial digital output RCA jack
(no condensation)	RS-232C D-sub 9-pin, male
(no condendation)	RS-232C and extended D-sub 15-pin, female
Component Video Output	110 2020 and extended D dab to pin, ternale
Y (luminance) - Output level 1 Vp-p (75 Ω)	Accessories
PB (color) - Output level 0.65 Vp-p (75 Ω)	Audio/video cable1
PR (color) - Output level 0.65 Vp-p (75 Ω)	Power cable1
Jack RCA jacks	Remote control1
,	AA/R6P dry cell batteries2
S-Video Output	Operating Instructions1
Y (luminance) - Output level 1 Vp-p (75 Ω)	Warranty card1
C (color) - Output level 265 mVp-p (75 Ω)	
Jack S-video jack	
0.60	Note
Video Output	The specifications and design of this
Output level 1 Vp-p (75 Ω)	product are subject to change without
JackRCA jack	notice, due to improvement.
ues es sous es un accompación de la differir su entre de managementa de carbación entre a la destinación de Participa ( 3 № 30°) ( 14°) de Carbación de Carbació	
Audio Output (1 Stereo Pair)	
그 무슨 마음이 어머니는 이 이렇지 않아 아이를 보고 있다면 하는데 이렇게 아니는데 그래요.	