AERONAUTICAL DATA TABULATION

INSTRUMENT APPROACH CHART FOR FASZ RWY 17														
Serial Number	Path Descriptor	Waypoint Identifier	LATITUDE	LONGITUDE	Flyover	Fix	Course °M(°T)	Distance (NM)	Turn Direction	Altitude (FT)	Speed (KT IAS)	VPA/TCH	Magnetic Variation (°W)	Navigation Specification
10	IF	UTREX	24°58'20.000"S	031°15'18.100"E	-	IAF	-	-	-	FL105	180	-	19.97	RNP APCH
20	TF	SZ1N1	24°53'30.588"S	031°28'01.427"E	-	-	087 (066.73)	12.50	-	+4900	180	-	19.97	RNP APCH
30	TF	SZ1T1	24°51'50.201"S	031°32'25.289"E	-	IF	087 (066.73)	4.70	R	+3320	160	-	19.97	RNP APCH
40	TF	SZ1F1	24°54'37.391"S	031°33'48.469"E	-	FAF	176 (155.58)	3.00	-	@2250	140	-	19.97	RNP APCH
50	TF	RW17	24°57'19.089"S	031°35'08.978"E	Υ	MAPT	176 (155.58)	3.00	-	@1084	180	3.72/50	19.97	RNP APCH
60	FA	-	-	-	-	-	176 (°M)	-	-	+1820	-	2 (3.5%)	19.97	RNP APCH
70	DF	SZ1M1	25°00'55.440"S	031°25'40.540"E	-	MATF	-	-	-	-	180	2 (3.5%)	19.97	RNP APCH
80	FA	-	-	-	-	-	304 (283.73)	-	-	+4800	-	2 (3.5%)	19.97	RNP APCH