

150MSALLSEAM - 1-1/2” MECHANICAL SEAM

METAL	MAX. WIDTH	SUBSTRATE	FPA	HZVZ	TDI	UL LISTING	CLIP SPACING	NOTES	UPLIFT PRESSURE
.032” Alum	16”	15/32” plywood	✓	✓	✓	✓	8”	E	213.5
.032” Alum	16”	15/32” plywood	✓		✓	✓	8”	E	206
.032” Alum	16”	15/32” plywood	✓	✓	✓	✓	16”	E	138.5
.032” Alum	16”	15/32” plywood	✓		✓	✓	16”	E	101
.032” Alum	20”	15/32” plywood	✓		✓	✓	8”	E	159.25
.032” Alum	20”	15/32” plywood	✓	✓	✓	✓	10.5”	E	198.5
.032” Alum	20”	15/32” plywood	✓	✓	✓	✓	13”	E	178
.032” Alum	20”	15/32” plywood	✓	✓	✓	✓	13”	E	156
.032” Alum	20”	15/32” plywood	✓		✓	✓	16”	B, E	118
.032” Alum	20”	15/32” plywood	✓	✓	✓	✓	19”	E	76
16oz Cu	16”	15/32” plywood	✓	✓	✓	✓	12”	E	198.5
16oz Cu	16”	15/32” plywood	✓	✓	✓	✓	16”	E	149
16oz Cu	16”	.5/32” plywood	✓		✓	✓	16”	F	159.25
16oz Cu	16”	15/32” plywood	✓		✓	✓	16”	F	82.25
24ga Steel	16”	15/32” plywood	✓	✓	✓	✓	6”	E	176
24ga Steel	16”	15/32” plywood	✓	✓	✓	✓	8”	E	198.5
24ga Steel	16”	15/32” plywood	✓		✓	✓	8”	E	198.5
24ga Steel	16”	.5/32” plywood	✓	✓	✓	✓	16”	E	166
24ga Steel	16”	15/32” plywood	✓		✓	✓	16”	E	168.5
24ga Steel	16”	15/32” plywood	✓	✓	✓	✓	24”	E	86
24ga Steel	20”	15/32” plywood	✓		✓	✓	8”	E	121.75
24ga Steel	20”	15/32” plywood	✓		✓	✓	8”	F	189.25
24ga Steel	20”	15/32” plywood	✓		✓	✓	16”	E	91.75
26ga Steel	16”	15/32” plywood	✓	✓	✓	✓	12”	E	218.8

Notes: B - WITH sealant, E - 90° seam, F - 180°seam

This list represents Metal Alliance's best effort to summarize current FL Product Approvals and TDI listings and is subject to change without notice. For the most up to date information, visit the [Florida Building Commission](#) and [Texas Department of Insurance](#) websites.