

# Continuous Representations of Words

a.k.a. word vectors  
a.k.a. word embeddings  
a.k.a. projection layers

Jon Dehdari

November 30, 2015

Good Morning!

## Words as Integers

- Our previous representations of words (and word classes) have been fairly flat
- For example, the word '*monkey*' can be represented as an integer, such as '7'

## Words as Integers

- Our previous representations of words (and word classes) have been fairly flat
- For example, the word '*monkey*' can be represented as an integer, such as '7'
- **One-hot encoding** represents that as:

0	0	0	0	0	0	1	0	0	0	...	0
---	---	---	---	---	---	---	---	---	---	-----	---

## Words as Integers

- Our previous representations of words (and word classes) have been fairly flat
- For example, the word '*monkey*' can be represented as an integer, such as '7'
- **One-hot encoding** represents that as:

0	0	0	0	0	0	1	0	0	0	...	0
---	---	---	---	---	---	---	---	---	---	-----	---

- and the word class (eg. 2) containing '*monkey*':

0	1	0	0
---	---	---	---

## Words as Integers

- Our previous representations of words (and word classes) have been fairly flat
- For example, the word '*monkey*' can be represented as an integer, such as '7'
- **One-hot encoding** represents that as:

0	0	0	0	0	0	1	0	0	0	...	0
---	---	---	---	---	---	---	---	---	---	-----	---

- and the word class (eg. 2) containing '*monkey*':

0	1	0	0
---	---	---	---

- Both of these are sparse vectors of booleans, with just one entry having a 'true' value

## Words as Integers

- Our previous representations of words (and word classes) have been fairly flat
- For example, the word '*monkey*' can be represented as an integer, such as '7'
- **One-hot encoding** represents that as:

0	0	0	0	0	0	1	0	0	0	...	0
---	---	---	---	---	---	---	---	---	---	-----	---

- and the word class (eg. 2) containing '*monkey*':

0	1	0	0
---	---	---	---

- Both of these are sparse vectors of booleans, with just one entry having a 'true' value
- Either way, we're working with integers ( $\dots, -2, -1, 0, 1, 2, \dots$ )



## Words as $\mathbb{R}$ Real Numbers

- We can do more with real numbers (eg. -1.5, 0.23, 55.01)





## Words as $\mathbb{R}$ Real Numbers

- We can do more with real numbers (eg. -1.5, 0.23, 55.01)
- We can represent the word '*monkey*' as a dense vector of real numbers:

0.38	-1.27	-0.55	1.44
------	-------	-------	------



## Words as $\mathbb{R}$ Real Numbers

- We can do more with real numbers (eg. -1.5, 0.23, 55.01)
- We can represent the word '*monkey*' as a dense vector of real numbers:

0.38	-1.27	-0.55	1.44
------	-------	-------	------

- We can have the plural form, '*monkeys*' be close in that vector space:

<b>0.31</b>	-1.27	<b>-0.61</b>	1.44
-------------	-------	--------------	------



## Words as $\mathbb{R}$ Real Numbers

- We can do more with real numbers (eg. -1.5, 0.23, 55.01)
- We can represent the word '*monkey*' as a dense vector of real numbers:

0.38	-1.27	-0.55	1.44
------	-------	-------	------

- We can have the plural form, '*monkeys*' be close in that vector space:

<b>0.31</b>	-1.27	<b>-0.61</b>	1.44
-------------	-------	--------------	------

- We can also have a related word, like '*ape*' be close in that vector space, *but in different dimensions*:

0.38	<b>-1.33</b>	-0.55	<b>1.49</b>
------	--------------	-------	-------------

## Applications of Word Vectors

- **Word distances.** For example, closest words to '*Sweden*':

Word	Cosine Distance
Norway	0.75
Denmark	0.72
Finland	0.62
Switzerland	0.59
...	


# Applications of Word Vectors

- **Word distances.** For example, closest words to 'Sweden':

Word	Cosine Distance
Norway	0.75
Denmark	0.72
Finland	0.62
Switzerland	0.59

...

- **Analogy.** E.g., *Japan* is to *Tokyo* as *Germany* is to *Berlin*




# Applications of Word Vectors

- **Word distances.** For example, closest words to 'Sweden':

Word	Cosine Distance
Norway	0.75
Denmark	0.72
Finland	0.62
Switzerland	0.59

...

- **Analogy.** E.g., *Japan is to Tokyo as Germany is to Berlin*



$$\text{Japan} - \text{Tokyo} \approx \text{Germany} - \text{Berlin}$$

## Applications of Word Vectors

- **Sentence Completion** (actually just restricted language modeling):
- “All red-headed men who are above the age of [ 800 | seven | twenty-one | 1,200 | 60,000 ] years , are eligible.”
- “That is his [ generous | mother’s | successful | favorite | main ] fault , but on the whole he’s a good worker.”


## Applications of Word Vectors

- **Sentence Completion** (actually just restricted language modeling):
- “All red-headed men who are above the age of [ 800 | seven | twenty-one | 1,200 | 60,000 ] years , are eligible.”
- “That is his [ generous | mother’s | successful | favorite | main ] fault , but on the whole he’s a good worker.”
- Mikolov et al (2013b) selected the test word that best predicted the context



# Projection Layer in Neural Language Models

- **Neural Language Modeling** – this was actually one of the earliest uses of word vectors. We'll talk more about these later this semester



## word2vec

- Tomáš Mikolov and colleagues found that you don't need the full neural-net language model to get useful word vectors


## word2vec

- Tomáš Mikolov and colleagues found that you don't need the full neural-net language model to get useful word vectors
- In fact, you don't need a neural network at all. He removed the hidden layer, giving a traditional logistic regression model


## word2vec

- Tomáš Mikolov and colleagues found that you don't need the full neural-net language model to get useful word vectors
- In fact, you don't need a neural network at all. He removed the hidden layer, giving a traditional logistic regression model
- He developed a simplified form of training called negative sampling (derived from earlier NCE). It's a little like a binary MaxEnt classifier

## word2vec: CBOW & Skip-gram



**CBOW**




**Skip-gram**

# Hyperparameters

- Window size: how much surrounding context to use
- Normalization: softmax (traditional) vs. hierarchical softmax vs. negative sampling
- Vector dimensions: 100–500 common
- Number of negative samples: 3–10 common
- Number of training epochs, initial learning rate, negative sample distribution ( $\alpha = 0.75$ ), model, ...

# Matrix Factorization of Count Co-Occurrences

- Glove and Latent Semantic Analysis (LSA) count the co-occurrences of word pairs, then use matrix factorization techniques like singular value decomposition (SVD) for dimensionality reduction of this original matrix



## Unifying these Approaches

- Word2vec, Glove, and LSA all do matrix factorization (Levy & Goldberg, 2014), but the successful ones are weighted for word frequency
- Pointwise Mutual Information (PMI) is (implicitly) used by these:

$$\text{PMI}(x, y) = \log \frac{P(x, y)}{P(x) P(y)}$$



## Try Them Out!

- Original word2vec code:  
<https://code.google.com/p/word2vec/> – includes nice illustrations
- Python version: Gensim
- Java version in DL4J
- Glove