# PCAP1

HOLOGY7{4n_E4sy_1CmP_Ch4ll3ngE}

```python
import pyshark
# Define the pcap file and the IP address to filter by
pcap_file = 'chall/chall.pcapng'
source_ip = '192.168.216.129'
cap = pyshark.FileCapture(pcap_file, display_filter='icmp')
# Loop through each packet and filter by source IP and ICMP type (echo request)
for packet in cap:
    try:
        if packet.ip.src == source_ip and packet.icmp.type == '8':
            data_hex = packet.icmp.data.replace(':', '')[:32]
            print(data_hex) ## decode hex 2x
    except AttributeError:
        # Skip packets that do not have the expected fields
        continue
# Close the capture
cap.close()
```



# PCAP 2







Use Extract File -> SMB to dump


(rickroll)

Extract level_500.zip sampai level_1.zip ditemukan folder berisi profile mozillla firefox

```
import os
import zipfile
import shutil

def extract_until_target(zip_file_path, target_file, output_folder):
    # Create the output folder if it doesn't exist
    os.makedirs(output_folder, exist_ok=True)

    # Initialize the list of files to extract
    files_to_extract = [zip_file_path]

    while files_to_extract:
        current_zip = files_to_extract.pop()

        # Extract the current ZIP file
        with zipfile.ZipFile(current_zip, 'r') as zip_ref:
            zip_ref.extractall(output_folder)
            extracted_files = zip_ref.namelist()

        # Check if the target file is extracted
        if target_file in extracted_files:
            print(f"Found {target_file} in {current_zip}.")
            # Copy the target file to the output folder
            shutil.copy(os.path.join(output_folder, target_file),
output_folder)
            print(f"Copied {target_file} to {output_folder}.")
            break

              for file in extracted_files:
            if file.endswith('.zip'):
```

```
                files_to_extract.append(os.path.join(output_folder, file))

initial_zip_file = 'level_500.zip'  # Path to your initial zip file
target_zip_file = 'level_1.zip'       # The target zip file you want to
find
reachable_folder = 'aaa'  # The folder to copy the target zip file into
extract_until_target(initial_zip_file, target_zip_file, reachable_folder)
```




Terdapat file menarik yaitu logins.json dengan data login instagram terenkripsi


Gunakan ini untuk dekripsi
https://github.com/unode/firefox_decrypt