

# The `jmsdelim` package

Jonathan Sterling

September 14, 2019

## 1 Overview

Sizing delimiters using `\left` and `\right` should be outlawed! The results are nearly always unaesthetic, primarily because the correct size of a mathematical delimiter is a typesetting consideration which does *not* emanate from the physical size of the interior.

Correctly sizing delimiters is very difficult, particularly in well-architected documents: a correctly engineered mathematical document will include macros for all operations, and these macros necessarily will include delimiters (such as parentheses). However, the correct size for the delimiter cannot be chosen ahead of time, because it will depend on the arguments; two options are available:

1. Provide optional arguments to each notation macro for choosing delimiter sizes. This is nearly intractable to do in practice.
2. Ignore delimiter sizes.

With `jmsdelim` we offer an alternative: the correct delimiter sizes can be set at the *leaf nodes* of a mathematical expression, and magically bubble upward through the delimiters.

## 2 Document interface

---

`\DelimMin` `\DelimMin{⟨intexprmin⟩}`

---

This sets the minimum delimiter size to `⟨intexprmin⟩` outside the current location; delimiter sizes are represented as natural numbers, with `0` the smallest size.

`\DelimMin` is the work-horse of `jmsdelim`; let us consider an example of what one might do prior to adopting `jmsdelim`. Suppose we have defined a macro `\Psh` for the free co-completion, following the notation of the French school, and we wish to parenthesize an instance of it:

$\mathrm{Hom}_{\mathbf{Cat}}(1, \widehat{\mathbb{C}})$

```
\NewDocumentCommand\Cat{}{\mathbf{Cat}}
\NewDocumentCommand\Psh{m}{\widehat{#1}}
\NewDocumentCommand\Hom{mmm}{
  \operatorname{Hom}_{#1}(#2,#3)
}
\[\Hom{\Cat}{1}{\Psh{\mathbb{C}}}\]
```

One might have tried to get a better result by using `\left` and `\right`:

$\mathrm{Hom}_{\mathbf{Cat}}(1, \widehat{\mathbb{C}})$	<pre>\NewDocumentCommand\Cat{}{\mathbf{Cat}} \NewDocumentCommand\Psh{m}{\widehat{#1}} \NewDocumentCommand\HomX{mmm}{   \operatorname{Hom}_{#1}\left(#2,#3\right) }</pre>
$\mathrm{Hom}_{\mathbf{Cat}}(1, \widehat{\mathbb{C}})$	<pre>\NewDocumentCommand\Hom{mmm}{   \operatorname{Hom}_{#1}\mleft(#2,#3\mright) } \[\Hom{\Cat}{1}{\Psh{\mathbb{C}}}\] \[\HomX{\Cat}{1}{\Psh{\mathbb{C}}}\]</pre>

The above is appallingly worse: the height of the hat does not in any way determine the correct size for the delimiter! The solution using `jmsdelim` is quite simple, however: first, we change `\Hom` to call `\DelimPrn`, and then we use `\DelimMin` within the `\Psh` notation.

$\mathrm{Hom}_{\mathbf{Cat}}(1, \widehat{\mathbb{C}})$	<pre>\NewDocumentCommand\Cat{}{\mathbf{Cat}} \NewDocumentCommand\Psh{m}{\DelimMin{1}\widehat{#1}} \NewDocumentCommand\Hom{mmm}{   \operatorname{Hom}_{#1}\DelimPrn{#2,#3} } \[\Hom{\Cat}{1}{\Psh{\mathbb{C}}}\]</pre>
--	---

## 2.1 Basic Delimiter commands

Like `mleftright` [Obe16], `jmsdelim` ensures the correct amount of space on the outside of the delimiters using `\mathopen` and `\mathclose`.

<hr/> <hr/>	<code>\DelimSurround{&lt;left&gt;}{&lt;right&gt;}{&lt;body&gt;}</code>
	Surrounds <code>&lt;body&gt;</code> with appropriately sized <code>&lt;left&gt;</code> and <code>&lt;right&gt;</code> delimiters respectively.

$ \sum_i b_i $	<pre>\NewDocumentCommand\Sum{mm}{%   \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \[\DelimSurround{\vert}{\vert}{\Sum{i}{b_i}}\]</pre>
----------------	--

<hr/> <hr/>	<code>\DelimSurround{&lt;sep&gt;}{&lt;lbody&gt;}{&lt;rbody&gt;}</code>
	Places an appropriately sized <code>&lt;sep&gt;</code> between <code>&lt;lbody&gt;</code> and <code>&lt;rbody&gt;</code> .

$a \parallel \sum_i b_i$	<pre>\NewDocumentCommand\Sum{mm}{%   \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \[\DelimBetween{\Vert}{a}{\Sum{i}{b_i}}\]</pre>
--------------------------	---

<hr/> <hr/>	<code>\DelimSurround{⟨left⟩}{⟨sep⟩}{⟨right⟩}{⟨lbody⟩}{⟨rbody⟩}</code>
	Places an appropriately sized <code>⟨sep⟩</code> between <code>⟨lbody⟩</code> and <code>⟨rbody⟩</code> , surrounding the result by <code>⟨left⟩</code> and <code>⟨right⟩</code> respectively.
$\{\sum_i a \cdot b_i \mid a \in A\}$	<pre> \NewDocumentCommand\Sum{mm}{%   \DelimMin{1}{\textstyle\sum}_{#1}{#2}% } \[   \DelimBetweenSurround{\lbrace}{\vert}{\rbrace}{     \Sum{i}{a\cdot b_i}   }{a\in A} \]</pre>

## 2.2 Derived delimiter commands

<hr/>	<code>\DelimPrn{⟨body⟩}</code>
	Surrounds <code>⟨body⟩</code> in parentheses.
<hr/>	<code>\DelimBrk{⟨body⟩}</code>
	Surrounds <code>⟨body⟩</code> in square brackets.
<hr/>	<code>\DelimBrc{⟨body⟩}</code>
	Surrounds <code>⟨body⟩</code> in curly braces.
<hr/>	<code>\DelimGl{⟨body⟩}</code>
	Surrounds <code>⟨body⟩</code> in angle brackets.
<hr/>	<code>\DelimBbrk{⟨body⟩}</code>
	Surrounds <code>⟨body⟩</code> in Scott brackets (requires <code>\llbracket</code> , <code>\rrbracket</code> to be defined).

## 2.3 Configuration and options

<hr/>	<code>\jmsdelimsetup{⟨options⟩}</code>
	<code>jmsdelim</code> can be customized along a few axes.
<hr/>	<code>size_commands</code>
	The option <code>size_commands</code> is a comma-separated list which contains a list of sizing commands for delimiters, from smallest to largest.

### 3 Interface for macro authors

The internals of `jmsdelim` are implemented in `expl3`.

<hr/> <hr/> <code>jmsdelim_scope:nn</code>	<code>jmsdelim_scope:nn {⟨pre⟩} {⟨post⟩}</code>  This is the fundamental control structure for authors of custom delimiting commands; <code>⟨pre⟩</code> is a block of code that renders things to temporary boxes, and <code>{⟨post⟩}</code> is code that <i>uses</i> these boxes, placing them relative to some delimiters. The function of <code>\jmsdelim_scope:nn</code> is to watch for the delimiter size updates induced by <code>⟨pre⟩</code> , and set the delimiter size commands correctly before executing <code>⟨post⟩</code> . Both <code>⟨pre⟩</code> and <code>⟨post⟩</code> are to be executed in the same block level.
<hr/> <hr/> <code>jmsdelim_hbox_set:Nn</code>	<code>jmsdelim_hbox_set:Nn {⟨box⟩} {⟨contents⟩}</code>  This command is meant to be used inside the <code>⟨pre⟩</code> block of <code>\jmsdelim_scope:nn</code> ; it typesets <code>⟨contents⟩</code> in the box named by <code>⟨box⟩</code> , correctly propagating the math style.
<hr/> <hr/> <code>jmsdelim_size_cmd:</code>	<code>jmsdelim_size_cmd:</code>  This command is meant to be used inside the <code>⟨post⟩</code> block of <code>\jmsdelim_scope:nn</code> to set the size of a given delimiter; it behaves like <code>\big</code> , etc.
<hr/> <hr/> <code>jmsdelim_surround:nnn</code>	<code>jmsdelim_surround:nnn {⟨left⟩} {⟨right⟩} {⟨body⟩}</code>  This routine surrounds <code>⟨body⟩</code> with the delimiters <code>⟨left⟩</code> and <code>⟨right⟩</code> of the appropriate size respectively.
<hr/> <hr/> <code>jmsdelim_between:nnn</code>	<code>jmsdelim_between:nnn {⟨sep⟩} {⟨lbody⟩} {⟨rbody⟩}</code>  This routine separates <code>⟨lbody⟩</code> and <code>⟨rbody⟩</code> with a separator <code>⟨sep⟩</code> of the appropriate size.
<hr/> <hr/> <code>jmsdelim_between:nnnnn</code>	<code>jmsdelim_between:nnnnn {⟨left⟩} {⟨sep⟩} {⟨right⟩} {⟨lbody⟩} {⟨rbody⟩}</code>  This routine separates <code>⟨lbody⟩</code> and <code>⟨rbody⟩</code> with a separator <code>⟨sep⟩</code> of the appropriate size, and surrounds the result by <code>⟨left⟩</code> and <code>⟨right⟩</code> respectively of the same size.

### 4 `jmsdelim` implementation

```

1 ⟨*package⟩
2 \RequirePackage{expl3}
3 \RequirePackage{l3keys2e}
4 \RequirePackage{xparse}
5 \RequirePackage{ifluatex}
6 \RequirePackage{scalarel}
7 \ProvidesExplPackage {jmsdelim} {2020/11/02} {0.2.0}
8   {Compositional delimiter sizing}
9 ⟨@=jmsdelim⟩

```

We first declare the options for the `jmsdelim` module, together with their default values.

```

10 \keys_define:nn { jmsdelim } {
11   size~commands .clist_set:N = \l__jmsdelim_size_cmds,
12 }
13 \keys_set:nn { jmsdelim } {
14   size~commands = {relax,big,Big,bigg,Bigg},
15 }

```

Then, we set up the internal state that will be used by jmsdelim.

```

16 \int_new:N \g__jmsdelim_size
17 \int_new:N \g__jmsdelim_size_up
18 \int_gset:Nn \g__jmsdelim_size {0}
19 \int_gset:Nn \g__jmsdelim_size_up {0}

```

## 4.1 Internals

`\__jmsdelim_clist_item:Nn` A version of `\clist_item:Nn` that takes the last item when the index is out of bounds.

```

20 \cs_new:Npn \__jmsdelim_clist_item:Nn #1 #2 {
21   \clist_item:Nn #1 {
22     \int_min:nn { #2 } {\clist_count:N #1}
23   }
24 }

```

(End definition for `\__jmsdelim_clist_item:Nn`.)

`__jmsdelim_setup_sizes:`

```

25 \cs_new:Npn \__jmsdelim_setup_sizes: {
26   \int_gset:Nn \g__jmsdelim_size {
27     \int_max:nn \g__jmsdelim_size \g__jmsdelim_size_up
28   }
29
30   \cs_set_eq:Nc \jmsdelim_size_cmd: {
31     \__jmsdelim_clist_item:Nn \l__jmsdelim_size_cmds {
32       \g__jmsdelim_size + 1
33     }
34   }
35 }

```

(End definition for `__jmsdelim_setup_sizes:`.)

### 4.1.1 Preservation of math styles

It is fairly complicated and inefficient to preserve math styles across boxes. There is an appropriate way to do so in Lua<sup>A</sup>T<sub>E</sub>X, which we use conditionally if available; otherwise, we make use of `\ThisStyle` and `\SavedStyle` from `scalerel` [Seg16], which are more inefficient. In fact, it becomes impossible to use jmsdelim in PDF<sup>A</sup>L<sup>A</sup>T<sub>E</sub>X when the nesting is sufficiently deep, whereas there is no corresponding blowup in Lua<sup>A</sup>T<sub>E</sub>X. The `\ignoremathstyle` and `\discernmathstyle` macros from `scalerel` can be used to turn off the inefficient preservation of math styles locally, such as in the case where no subscripts are used.

\_\_jmsdelim luatex save mathstyle:N

```
36 \cs_new:Npn \__jmsdelim_luatex_save_mathstyle:N #1 {
37   \ifcase \mathstyle
38     \cs_set_eq:NN #1 \displaystyle
39   \or
40     \cs_set_eq:NN #1 \crampeddisplaystyle
41   \or
42     \cs_set_eq:NN #1 \textstyle
43   \or
44     \cs_set_eq:NN #1 \crampedtextstyle
45   \or
46     \cs_set_eq:NN #1 \scriptstyle
47   \or
48     \cs_set_eq:NN #1 \crampedscriptstyle
49   \or
50     \cs_set_eq:NN #1 \scriptscriptstyle
51   \or
52     \cs_set_eq:NN #1 \crampedscriptscriptstyle
53   \fi
54 }
```

(End definition for \_\_jmsdelim\_luatex\_save\_mathstyle:N.)

\_\_jmsdelim\_restore\_mathstyle:n

```
55 \cs_new:Npn \__jmsdelim_restore_mathstyle: {
56   \SavedStyle
57 }
```

(End definition for \_\_jmsdelim\_restore\_mathstyle:n.)

\_\_jmsdelim\_save\_mathstyle:n

```
58 \cs_new:Npn \__jmsdelim_save_mathstyle:n #1 {
59   \ifluatex
60     \__jmsdelim_luatex_save_mathstyle:N \__jmsdelim_restore_mathstyle:
61     #1
62   \else
63     \ThisStyle{#1}
64   \fi
65 }
```

(End definition for \_\_jmsdelim\_save\_mathstyle:n.)

## 4.2 Public interface for macro authors

jmsdelim\_scope:nn

```
66 \cs_new:Npn \jmsdelim_scope:nn #1 #2 {
67   \group_begin:
68     \int_set:Nn \l_tmpa_int \g__jmsdelim_size_up
69     \int_gset:Nn \g__jmsdelim_size_up 0
```

```

70 \int_gset:Nn \g__jmsdelim_size 0
71 \group_begin:
72 \__jmsdelim_save_mathstyle:n {
73   #1
74   \__jmsdelim_setup_sizes:
75   #2
76 }
77 \group_end:
78 \int_gset:Nn \g__jmsdelim_size_up {\int_max:nn \g__jmsdelim_size_up \l_tmpa_int}
79 \group_end:
80 }

```

(End definition for jmsdelim\_scope:nn. This function is documented on page 4.)

jmsdelim\_hbox\_set:Nn

```

81 \cs_new:Npn \jmsdelim_hbox_set:Nn #1 #2 {
82   \mode_if_math:TF
83     { \hbox_set:Nn #1 {\m@th\__jmsdelim_restore_mathstyle: #2$} }
84     { \hbox_set:Nn #1 { #2 } }
85 }

```

(End definition for jmsdelim\_hbox\_set:Nn. This function is documented on page 4.)

jmsdelim\_surround:nnn

```

86 \cs_new:Npn \jmsdelim_surround:nnn #1 #2 #3 {
87   \jmsdelim_scope:nn {
88     \jmsdelim_hbox_set:Nn \l_tmpa_box {#3}
89   }{
90     \mathopen\jmsdelim_size_cmd: {#1}
91     \box_use:N \l_tmpa_box
92     \mathclose\jmsdelim_size_cmd: {#2}
93   }
94 }

```

(End definition for jmsdelim\_surround:nnn. This function is documented on page 4.)

jmsdelim\_between:nnn

```

95 \cs_new:Npn \jmsdelim_between:nnn #1 #2 #3 {
96   \jmsdelim_scope:nn {
97     \jmsdelim_hbox_set:Nn \l_tmpa_box {#2}
98     \jmsdelim_hbox_set:Nn \l_tmpb_box {#3}
99   }{
100     \box_use:N \l_tmpa_box
101     \mathrel{\jmsdelim_size_cmd: {#1}}
102     \box_use:N \l_tmpb_box
103   }
104 }

```

(End definition for jmsdelim\_between:nnn. This function is documented on page 4.)

jmsdelim\_between:nnnnn

```
105 \cs_new:Npn \jmsdelim_between:nnnnn #1 #2 #3 #4 #5 {  
106   \jmsdelim_scope:nn {  
107     \jmsdelim_hbox_set:Nn \l_tmpa_box {#4}  
108     \jmsdelim_hbox_set:Nn \l_tmpb_box {#5}  
109   }{  
110     \mathopen\jmsdelim_size_cmd: {#1}  
111     \box_use:N \l_tmpa_box  
112     \mathrel{\jmsdelim_size_cmd: {#2}}  
113     \box_use:N \l_tmpb_box  
114     \mathclose\jmsdelim_size_cmd: {#3}  
115   }  
116 }
```

(End definition for jmsdelim\_between:nnnnn. This function is documented on page 4.)

### 4.3 Document interace

DelimMin

```
117 \NewDocumentCommand\DelimMin{m}{  
118   \int_gset:Nn \g__jmsdelim_size_up {#1}  
119 }
```

(End definition for DelimMin. This function is documented on page 1.)

DelimSurround

```
120 \NewDocumentCommand\DelimSurround{mmm}{  
121   \jmsdelim_surround:nnn {#1} {#2} {#3}  
122 }
```

(End definition for DelimSurround. This function is documented on page 2.)

DelimBetween

```
123 \NewDocumentCommand\DelimBetween{mmm}{  
124   \jmsdelim_between:nnn {#1} {#2} {#3}  
125 }
```

(End definition for DelimBetween. This function is documented on page 2.)

DelimBetweenSurround

```
126 \NewDocumentCommand\DelimBetweenSurround{mmmmm}{  
127   \jmsdelim_between:nnnnn {#1} {#2} {#3} {#4} {#5}  
128 }
```

(End definition for DelimBetweenSurround. This function is documented on page 3.)

DelimPrn



```

129 \NewDocumentCommand\DelimPrn{m}{
130   \jmsdelim_surround:nnn {(} {)} {#1}
131 }

```

(End definition for DelimPrn. This function is documented on page 3.)

### DelimBrk

```

132 \NewDocumentCommand\DelimBrk{m}{
133   \jmsdelim_surround:nnn {[} {]} {#1}
134 }

```

(End definition for DelimBrk. This function is documented on page 3.)

### DelimBrc

```

135 \NewDocumentCommand\DelimBrc{m}{
136   \jmsdelim_surround:nnn {\lbrace} {\rbrace} {#1}
137 }

```

(End definition for DelimBrc. This function is documented on page 3.)

### DelimBbrk

```

138 \NewDocumentCommand\DelimBbrk{m}{
139   \jmsdelim_surround:nnn {\llbracket} {\rrbracket} {#1}
140 }

```

(End definition for DelimBbrk. This function is documented on page 3.)

### DelimGl

```

141 \NewDocumentCommand\DelimGl{m}{
142   \jmsdelim_surround:nnn {\langle} {\rangle} {#1}
143 }

```

(End definition for DelimGl. This function is documented on page 3.)

```

144 \ProcessKeysPackageOptions {jmsdelim}

```

## References

- [Obe16] Heiko Oberdick. *The mlefttright package*. May 16, 2016. URL: <https://ctan.org/pkg/mlefttright> (cit. on p. 2).
- [Seg16] Steven B. Segletes. *scalerel – Constrained scaling and stretching of objects*. Dec. 29, 2016. URL: <https://ctan.org/pkg/scalerel> (cit. on p. 5).