

# CS2102

## Database Systems

AY2022/23 Semester 2

Notes by Jonathan Tay

Last updated on January 9, 2023

---

### Contents

#### I Relational Model

1

---

## Part I

# Relational Model

Data in **relational databases** are stored in **relations** (tables). Column headers are **attributes**, and rows are **tuples**.

The **degree** is the number of columns, and the **cardinality** is the number of rows.

The **domain** of an attribute  $A_i$ , denoted as  $\text{dom}(A_i)$ , is the set of all possible *atomic* values for  $A_i$ . NULL is an additional special value for unknown or invalid values.

### keys

A **superkey** is a subset of attributes that uniquely identifies a tuple. A **key** is a *minimal* superkey.

The **candidate keys** is the set of all keys for a relation, of which one is selected as a **primary key**.

Primary key values must be non-NULL.

### foreign keys

A **foreign key** is a subset of attributes of a *referencing relation* that refers to the primary key of a *referenced relation*:

(referencing attributes)  $\rightsquigarrow$  (referenced attributes)

Because the names of the attributes are not necessarily unique, each attribute is prefixed with the name of the relation, like so:

(<relation name> · <attribute name>, ...)  $\rightsquigarrow$  ...

Foreign keys must appear as a primary key in the referenced table, NULL, or a tuple containing NULL.