

## Oscilloscope Overview




Copyright (C) 2006, Jonathan Weaver	Title		
- 55p)g.n. (5) 2555, 55a.n.a.n. 175a.rs.	PPM Scope 1MHz Version 1.02		
	Author		
Permission is granted for use, modification, and redistribution	Jonathan Weaver		
This notice and copyright shall remain intact. The author	jonw0224@netscape.net		
grants no warantee of usability or fitness for a particular purpose. The author assumes no liability related to use. See terms and conditions for more details.	File   Docum		Document
	Z:\PIC_DE\	/\WORK\OSC\PPM1MHz.dsn 100	
	Revision	Date	Sheets
	1.02	5/9/2006	1 of 4

#### Control and Sampling - Oscilloscope Core



Copyright (C) 2006, Jonathan Weaver	Title PPM Scope 1MHz Version 1.02		
	Author		
Permission is granted for use, modification, and redistribution	Jonathan Weaver		
This notice and copyright shall remain intact. The author	jonw0224@netscape.net		
grants no warantee of usability or fitness for a particular purpose. The author assumes no liability related to use. See terms and conditions for more details.	File Document		Document
	Z:\PIC_DE\	\WORK\OSC\PPM1MHz.dsn 100	
	Revision	Date	Sheets
	1.02	5/9/2006	2 of 4


### **Analog Signal Conditioning**



Copyright (C) 2006, Jonathan Weaver	Title		
Copyrigin (C) 2000, Containan Trouter	PPM Scope 1MHz Version 1.02		
	Author		
Permission is granted for use, modification, and redistribution	Jonathan Weaver		
This notice and copyright shall remain intact. The author	jonw0224@netscape.net		
grants no warantee of usability or fitness for a particular	File   Docum		Document
purpose. The author assumes no liability related to use. See terms and conditions for more details.	Z:\PIC_DE\	/\WORK\OSC\PPM1MHz.dsn	100
	Revision	Date	Sheets
	1.02	5/9/2006	3 of 4

# Computer Interface - Logic Level Circuits

### **Trigger Level Selector**



Note: The computer interface port is a DB9 connector on the back of the box. It is intended to be connected to either a serial port and a parallel port. The pinouts for the connector for the computer interface port, and the cooresponding connections from the computer interface port to a parallel or serial port are below

DB9 - Computer Interface Port	DB9 - Serial Port	DB25 - Parallel Port
SER/PAR (Sheet 2) - Pin 1	SER/PAR - NC	SER/PAR - Pin 18
I2CDATA (Sheet 2) - Pin 2	I2CDATA - NC	I2CDATA - Pin 1
I2CCLK (Sheet 2) - Pin 3	I2CCLK - NC	I2CCLK - Pin 4
I2CDATAIN (Sheet 2) - Pin 4	I2CDATAIN - NC	I2CDATAIN - Pin 11
TX (Sheet 4) - Pin 5	TX - Pin 2	TX - NC
RX (Sheet 4) - Pin 6	RX - Pin 3	RX - Pin 19
GND - Pin 7, 8, 9	GND - Pin 5	GND - Pins 20 thru 25
	Connect Bins 1, 4, and 6	

together on serial port

Connect Pins 7 and 8 together on serial port

TriggerIn +5	+12 LM311 U7 + V+	+5 10k R44
10k 3 R43 TriggerLevel	- V- G	7 Trigger

Copyright (C) 2006, Jonathan Weaver	Title		
	PPM Scope 1MHz Version 1.02		
	Author		
Permission is granted for use, modification, and redistribution	Jonathan Weaver		
This notice and copyright shall remain intact. The author	jonw0224@netscape.net		
grants no warantee of usability or fitness for a particular	File		
purpose. The author assumes no liability related to use.  See terms and conditions for more details.	Z:\PIC_DE\	/\WORK\OSC\PPM1MHz.dsn	
	Revision	Date	
	1.02	5/9/2006	

Title

Document

100

Sheets

4 of 4