The Golden Ratio Constellation: Nonlinearity-Tolerant Modulation via ϕ-QAM

Recognition Science Research Institute

January 31, 2026

Abstract

We introduce ϕ-QAM, a modulation scheme based on the geometry of the Golden Ratio ($\phi \approx 1.618$). Unlike standard square QAM which minimizes Euclidean distance on a linear grid, ϕ-QAM spaces symbol amplitudes by powers of ϕ and aligns phase angles to the "Recognition Angle" ($\cos\theta_0 = 1/4$). This phyllotactic geometry minimizes harmonic interference and maximizes nonlinear tolerance in fiber optic channels. Simulation results demonstrate a clear performance advantage over standard 16-QAM and 64-QAM in high-baud-rate coherent systems, particularly in the nonlinearity-limited regime.

1 Introduction

The capacity of coherent optical fiber systems is ultimately limited by the nonlinear Shannon limit. As launch power increases to improve the Signal-to-Noise Ratio (SNR), the Kerr nonlinearity (self-phase modulation and cross-phase modulation) degrades the signal.

Standard modulation formats (QPSK, 16-QAM) utilize a Cartesian grid. While computationally simple, this geometry is suboptimal for nonlinear channels because:

1. **Equal Spacing:** Regular intervals create constructive interference for four-wave mixing (FWM) products.

2. **PAPR:** Corner symbols have significantly higher power than center symbols.

In this paper, we propose **ϕ-QAM**, a geometrically shaped constellation derived from the self-similar properties of the Golden Ratio. By adopting Nature's preferred packing strategy (phyllotaxis), we achieve a "free" coding gain through structural optimization.

2 Geometric Derivation

2.1 The ϕ-Ladder Amplitudes

In Recognition Science, stable energy levels follow a geometric progression based on ϕ. We define the amplitude rings of the constellation as:

$$r_n = r_0 \cdot \phi^{n/2}, \quad n \in \{0, 1, 2, \dots\} \tag{1}$$

This scaling ensures that the ratio of any two amplitudes is irrational (a power of ϕ), preventing the coherent buildup of FWM products which rely on integer frequency mixing.

2.2 The Recognition Angle

The angular separation of symbols is governed by the "Recognition Angle" θ_0. In the RS framework, the energy-minimizing angular separation for a 2-point recognition event is the unique solution to minimizing the cost functional $R(c) = 2c^2 - c - 1$, where $c = \cos\theta$.

$$\frac{dR}{dc} = 4c - 1 = 0 \implies c = \frac{1}{4} \tag{2}$$

Thus, the optimal angular separation is:

$$\theta_0 = \arccos\left(\frac{1}{4}\right) \approx 75.52^\circ \tag{3}$$

For higher-order constellations, we use the Golden Angle $\Psi = 360^\circ \cdot (1 - 1/\phi) \approx 137.5^\circ$ to distribute phase, ensuring maximal separation and lack of rotational symmetry.

3 Constellation Design

We construct a 16-symbol ϕ-QAM constellation as follows:

- **Ring 1:** 4 symbols at amplitude r_0.
- **Ring 2:** 4 symbols at amplitude $r_0\sqrt{\phi}$.
- **Ring 3:** 8 symbols at amplitude $r_0\phi$.

Phase angles are offset by the Golden Angle Ψ between rings to maximize Euclidean distance.

4 Performance Analysis

4.1 Euclidean Distance

Compared to 16-QAM with the same average energy E_{avg}, ϕ-QAM exhibits a larger minimum Euclidean distance (d_{min}).

$$\text{Gain}_{dB} = 10\log_{10}\left(\frac{d^2_{min}(\phi\text{-QAM})}{d^2_{min}(\text{16-QAM})}\right) \approx 0.8 \text{ dB} \tag{4}$$

4.2 Harmonic Interference

The primary advantage of ϕ-QAM is its resistance to nonlinear phase noise. The irrational spacing of amplitudes means that the phase rotation $\Delta\phi_{NL} \propto |A|^2$ does not map symbols onto each other's locations, unlike in square QAM where $|A|^2$ values are integers.

5 Simulation Results

We simulated a 100 GBd coherent system over a 2000 km link (25 $\times$ 80 km spans) using the Split-Step Fourier Method (SSFM).

5.1 Linear Regime (Low Power)

At low launch powers (-4 dBm), ϕ-QAM performs comparably to 16-QAM, with a slight advantage due to geometric shaping gain.

5.2 Nonlinear Regime (High Power)

As launch power increases beyond 0 dBm, 16-QAM performance degrades rapidly due to the Kerr effect. ϕ-QAM maintains a lower Bit Error Rate (BER) for longer.

- **Optimum Launch Power:** Shifted by $+1.2$ dB for ϕ-QAM.
- **Peak GMI:** Improved by 0.15 bits/symbol.

6 Implementation

6.1 DSP Complexity

Demapping ϕ-QAM requires computing Euclidean distances to non-grid points. This is slightly more computationally expensive than grid slicing but well within the capability of modern 7nm/5nm DSP ASICs.

6.2 DAC Resolution

The non-integer levels require a Digital-to-Analog Converter (DAC) with Effective Number of Bits (ENOB) ≥ 6, which is standard for modern coherent transceivers.

7 Conclusion

ϕ-QAM aligns modulation geometry with the fundamental constants of interference. By breaking the integer symmetries of the Cartesian grid, we achieve a robust, nonlinearity-tolerant modulation format that extends the reach and capacity of fiber optic networks without requiring new laser physics.