# Toward a Zero-Junk Genome: Recognition Science Predictions for DNA as Z-Invariant Storage

Jonathan Washburn
Recognition Science Research Institute, Austin, Texas
washburn.jonathan@gmail.com

March 17, 2026 (Third-Pass Revision)

**Abstract**

The genetic code maps $64 = 8^2$ codons to 20 amino acids, wobble degeneracy dominates 14 of 16 codon family boxes, and the 4 bp half-octave helical rotation lies within $1^\circ$ of the small golden angle $360^\circ/\varphi^2$. Recognition Science (RS) derives these facts from a single algebraic primitive, the Recognition Composition Law, whose unique cost function forces the golden ratio $\varphi$, spatial dimension $D$=3, and an 8-tick discrete clock. We formalize a 6-bit codon encoding into a qualia space $Q_6$ and prove that synonymous wobble substitutions need not preserve Z-parity (the topological invariant of the encoding), establishing a hierarchy: amino-acid identity is conserved more strongly than parity at the wobble position. We show that the abstract $(8, 1, 8)$ repetition code saturates the Singleton bound and uniquely maximizes minimum distance among length-8 codes. We present five falsifiable predictions—including mod-8 non-uniformity in intron lengths and a minimal-intron window near $8\varphi^5 \approx 89$ bp—and propose a five-layer decomposition of non-coding DNA (error correction, phase alignment, ledger balance, modular control, temporal coordination) as a structured research program. Since the first draft, the Lean surface has expanded substantially: 49 modules, 8,246 lines, zero axioms, zero unproved assertions. A major new computation-assisted result—the standard genetic code is optimal over a 363,004-element classwise degeneracy-preserving search under a position-weighted mutation cost—has been added and is described in §3. Throughout, we separate formal theorems (machine-checked in Lean 4) from model-level interpretations and empirical hypotheses.

## Contents

**1 Introduction** **2**

**2 Recognition Science Background** **2**

**3 Formal Results** **3**
3.1 Codon Combinatorics . . . 3
3.2 Wobble Symmetry . . . 3
3.3 The $(8, 1, 8)$ Repetition Code . . . 3
3.4 Helix Geometry and Intron Structure . . . 4
3.5 Global Optimality of the Codon-to-Amino-Acid Assignment . . . 4
3.6 Bio-Clocking and the FOLD Operator . . . 4
3.7 Position-Specific Mutation Vulnerability . . . 5

**4 A Five-Layer Decomposition of Non-Coding DNA** **5**

**5 Falsifiable Predictions** **6**

**6 Open Problems** **7**

**7 Conclusion** **8**

# 1 Introduction

Approximately 98% of the human genome does not encode proteins. What this non-coding majority *does* is the subject of a debate that has run for half a century. Ohno's original "junk DNA" proposal [1] treated most non-coding sequence as evolutionary debris. The ENCODE project reported biochemical activity across roughly 80% of the genome [2], but critics argued that detectable activity is not the same as selected function [3, 4]. Comparative-genomics estimates of the fraction under purifying selection range from 5–15% [5, 6, 7], leaving the status of the remaining non-coding sequence genuinely open.

Recognition Science (RS) enters this debate with an unusual structural claim: the genome is not primarily a protein recipe book but a storage format for topological invariants. In this view, the 8-fold structure of the double helix (4 nucleotides $\times$ 2 strands), the $64 = 8^2$ codon space, the degeneracy pattern, and the non-coding architecture are all reflections of a single algebraic backbone—the Recognition Composition Law (RCL)—from which the golden ratio $\varphi$, spatial dimension $D = 3$, and an 8-tick discrete clock are forced consequences [14].

This paper has three goals:

1. Present the strongest DNA-related results that are currently machine-checked in Lean 4.
2. Propose a five-layer research decomposition of non-coding DNA and state it as a falsifiable program rather than a closed theorem.
3. Identify the concrete empirical and mechanistic steps that separate the present formal scaffold from a complete theory.

We adopt a three-level claim discipline throughout. A **theorem** is a statement proved in the current Lean development. A **model** is a structured interpretation implemented as definitions and consistency lemmas. A **hypothesis** is an empirical or mechanistic claim not yet derived from the formal surface.

# 2 Recognition Science Background

The core primitive of RS is the Recognition Composition Law:

$$J(xy) + J(x/y) = 2\,J(x)\,J(y) + 2\,J(x) + 2\,J(y). \tag{1}$$

This is a calibrated multiplicative form of the d'Alembert functional equation. Under normalization $J(1) = 0$ and the calibration $J''(1) = 1$, the unique continuous solution is the canonical cost

$$J(x) = \tfrac{1}{2}(x + x^{-1}) - 1. \tag{2}$$

The function $J$ is non-negative, vanishes only at $x = 1$, and satisfies the symmetry $J(x) = J(1/x)$.

From this single primitive, a forcing chain (labeled T0–T8 in the Lean codebase) derives a sequence of structural consequences. The steps most relevant to DNA are:

- **T6** ($\varphi$ forcing): Self-similarity in the discrete ledger forces $x^2 = x + 1$, so $\varphi = (1 + \sqrt{5})/2$ appears as the unique positive fixed point. This is the origin of every golden-ratio signature in the theory.
- **T7** (8-tick): The minimal ledger-compatible walk in $D = 3$ has period $2^3 = 8$, creating an 8-phase discrete clock.

- **T8** ($D = 3$): Linking requirements and gap-45 synchronization ($\mathrm{lcm}(8, 45) = 360$) force exactly three spatial dimensions.

For the biology papers, the practical upshot is that $\varphi$, the number 8, and three-dimensionality are not free parameters but derived constants. The DNA question becomes: given this algebraic vocabulary, what can be said about the structure of genomes?

# 3 Formal Results

This section presents the DNA-related statements that are currently machine-checked in Lean 4 within the `IndisputableMonolith.Genetics` namespace, drawing on the RS constants and combinatorics from the `RecognitionScience` namespace.

## 3.1 Codon Combinatorics

The double helix provides $4 \times 2 = 8$ recognition slots per position (four nucleotide types on two complementary strands), matching the 8-tick period. The codon space has $4^3 = 64 = 8^2$ entries. Both equalities are proved by computation in Lean.

The standard genetic code maps these 64 codons to 20 amino acids plus 3 stop signals, with degeneracies summing to 61 sense codons. In the RS formalization, 20 "WTokens" (semantic atoms derived from the 8-tick DFT basis) are placed in bijection with the 20 canonical amino acids [14]. The cardinality match $20 = 20$ is proved; the specific biochemical assignment (which token maps to which amino acid) is a model-level correspondence, not a derived theorem.

## 3.2 Wobble Symmetry

Third-position degeneracy dominates the code.

**Theorem 3.1** (14 of 16 Family Boxes)**.** *Of the* 16 *family boxes defined by the first two codon positions, exactly* 14 *preserve clean wobble symmetry (all four third-position variants synonymous, or a clean pyrimidine/purine* 2+2 *split). Only the Ile/Met box (*3+1*) and the Cys/Trp/Stop box (*2+1+1*) break this pattern. Of the* 14 *clean boxes, exactly* 8 *are fully four-fold degenerate.*

The proof enumerates all 16 boxes, evaluates the genetic-code mapping at each, and checks the wobble condition by `native_decide`.

**Theorem 3.2** (Wobble Does Not Preserve Z-Parity)**.** *In the* 6*-bit codon encoding (3 nucleotides* $\times$ *2 bits each, mapped into* $Q_6$*), synonymous wobble substitutions need not preserve the Z-parity (bit-count mod* 2*). Concretely, GTT and GTC both encode valine, but* $\mathrm{parity}(\texttt{GTT}) = 1$ *while* $\mathrm{parity}(\texttt{GTC}) = 0$.

This result is interesting because it reveals a hierarchy of conservation in the genetic code. The code prioritizes preserving amino-acid identity over preserving Z-parity at the wobble position. If parity-like invariants play a biological role—as the RS framework proposes—they must operate at a level coarser than single-codon wobble, perhaps across reading frames, exon boundaries, or gene-level sums.

## 3.3 The $(8, 1, 8)$ Repetition Code

**Proposition 3.3.** *The abstract* $(8, 1, 8)$ *repetition code achieves:*

1. *Maximum possible minimum distance:* $d = n = 8$.
2. *Tight Singleton bound:* $d = n - k + 1$.
3. *Error correction of up to* $\lfloor (d-1)/2 \rfloor = 3$ *errors.*

*Moreover, any* $(8, k, d)$ *code with* $k \geq 2$ *has* $d \leq 7$*, so the repetition code uniquely maximizes distance among length-*8 *codes.*

This is a coding-theoretic template motivated by the RS 8-tick structure. It establishes that if a biological system uses an 8-phase encoding, the repetition code is the unique distance-optimal architecture. Whether the genetic code literally instantiates this template is an empirical question; the standard code's average degeneracy of $61/20 \approx 3.05$ is consistent with substantial but not maximal redundancy [11, 12].

### 3.4 Helix Geometry and Intron Structure

**Theorem 3.4** (Golden-Angle Proximity). *B-form DNA has approximately* 10.5 *bp per helical turn. The rotation subtended by* 4 *bp (the "half-octave") is* $4 \times 360°/10.5 \approx 137.1°$. *The small golden angle is* $360°/\varphi^2 \approx 137.5°$. *These differ by less than* $1°$*:*

$$\left| 4 \times \frac{360}{10.5} - \frac{360}{\varphi^2} \right| < 1°.$$

*The proof uses rigorous rational squeezes on* $\varphi$ *(via* $\sqrt{5}$ *bounds) and is machine-checked.*

**Theorem 3.5** (Minimal-Intron Estimate). *Using the algebraic identity* $\varphi^5 = 5\varphi + 3$, *the product* $8\varphi^5$ *satisfies* $|8\varphi^5 - 89| < 1$. *The observed minimum functional intron size in mammals is* 85–90 *bp.*

Together, these results support the hypothesis that introns function as helical phase-alignment spacers whose lengths are constrained by the 8-tick clock. The golden-angle proximity explains *why* a 4 bp unit would be structurally preferred, and the $8\varphi^5$ estimate identifies a natural minimal length scale.

### 3.5 Global Optimality of the Codon-to-Amino-Acid Assignment

**Proposition 3.6** (Computation-Assisted Position-Weighted Classwise Optimality). *Under a position-dependent mutation cost with eight components (hydrophobicity*$^2$ *at positions 1–3, charge*$^2$ *at position 3, side-chain volume*$^2$ *at positions 1–2, and biosynthetic pathway distance at positions 1–2), the standard genetic code is the unique cost minimizer over the 363,004 non-identity permutations obtained by enumerating each degeneracy class separately:* $(2!-1) + (9!-1) + (1!-1) + (5!-1) + (3!-1) = 363{,}004$. *The integer-weighted worst-case margin on this classwise search is* $+37{,}136$. *Lean proves the exact classwise search size and contains 52* `native_decide` *certificates covering every pairwise swap and every non-identity 6-fold permutation; the full classwise optimality statement is confirmed by exhaustive external computation.*

This result partially resolves Prediction 5.6 from the first draft: the code *is* locally optimal within every degeneracy class and is exhaustively optimal over the currently enumerated classwise search under a biologically motivated position-weighted metric. The key insight is that mutations at different codon positions have very different chemical consequences: position 2 changes almost always alter the amino acid's chemical class, while position 3 (wobble) changes are frequently synonymous. A companion paper [16] provides the full derivation, sensitivity analysis, and the exact separation between Lean-certified and externally enumerated parts of the argument.

### 3.6 Bio-Clocking and the FOLD Operator

**Proposition 3.7** (Bio-Clock Recurrence). *The bio-clocking function* $\tau_{\text{bio}}(N) = \tau_0 \cdot \varphi^N$ *satisfies* $\tau_{\text{bio}}(N+1) = \varphi \cdot \tau_{\text{bio}}(N)$, *and the sequence is strictly monotone increasing.*

**Proposition 3.8** (FOLD Idempotence). *The FOLD operator on the 8-tick register,* $\text{FOLD}(v)_k = (v_k + v_{(8-k) \bmod 8})/2$, *is idempotent:* $\text{FOLD}(\text{FOLD}(v)) = \text{FOLD}(v)$ *for all* $k \in \{0, \ldots, 7\}$. *The proof proceeds by exhaustive case analysis over all 8 values.*

The RS interpretation is that sexual reproduction physically instantiates FOLD: meiotic recombination averages complementary parental phase registers, annihilating accumulated phase drift. The following two results give this interpretation formal teeth.

**Theorem 3.9** (FOLD Annihilates Antisymmetric Phase Debt)**.** *Decompose any phase profile $v \in \mathbb{R}^8$ into symmetric and antisymmetric parts:*

$$v_k^{\text{sym}} = \frac{v_k + v_{8-k}}{2}, \qquad v_k^{\text{anti}} = \frac{v_k - v_{8-k}}{2}.$$

*Then* $\text{FOLD}(v) = v^{\text{sym}}$ *and the antisymmetric part of* $\text{FOLD}(v)$ *is identically zero for all* $k \in \{0, \ldots, 7\}$*. The proof proceeds by exhaustive* `fin_cases` *and* `ring`*.*

**Corollary 3.10** (Sexual Advantage)**.** *A lineage applying FOLD each generation has bounded (zero) antisymmetric phase debt. An asexual lineage preserves its antisymmetric component unchanged; if mutations inject positive debt $\delta$ per generation, the debt grows as $n\delta$ (Muller's ratchet in phase-profile language).*

### 3.7 Position-Specific Mutation Vulnerability

**Theorem 3.11** (Wobble is Safest; Position 2 is Most Dangerous)**.** *For each of the* 64 *codons, compute the total chemical-distance cost of all single-nucleotide mutations at positions* 1*,* 2*, and* 3 *separately, weighted by a transition/transversion ratio $\kappa = 2$. Summing over all codons:*

$$\textit{Position 3 (wobble)} \;\leq\; \textit{Position 1} \;\leq\; \textit{Position 2}.$$

*Both inequalities are strict and are verified by* `native_decide` *over the full* $64 \times 9$ *mutation table.*

Position 2 largely determines the chemical class of the amino acid (hydrophobic, polar, charged), so mutations there are the most costly. The wobble position carries the least information and the most degeneracy—it is the "least significant bit" of the codon. This ordering is a consequence of how the standard code arranges amino acids in the $8 \times 8$ codon grid, and it is one of the properties that any candidate "J-cost metric" must reproduce.

## 4 A Five-Layer Decomposition of Non-Coding DNA

The RS genetics framework suggests a five-layer account of non-coding sequence. We present it here as a *research decomposition*—a structured way to organize existing and future empirical work—rather than as a completed derivation.

| Layer | RS interpretation | Current evidence |
|---|---|---|
| Error correction | Codon degeneracy ($61/20 \approx 3\times$) and the $20/7$ token-to-dimension ratio provide noise immunity. | Degeneracy counts formalized; code near-optimality supported by Haig–Hurst and Freeland–Hurst analyses [11, 12]. |
| Phase alignment | Introns act as helical spacers, keeping exon junctions at golden-angle offsets. | Golden-angle theorem (theorem 3.4) and minimal-intron estimate (theorem 3.5) are proved; mod-8 enrichment is empirical and dataset-sensitive. |
| Ledger balance | Repetitive elements (SINEs, LINEs, LTR retrotransposons) serve as complementary entries in the $\sigma$=0 double-entry ledger. | Hypothesis: conceptually grounded in RS, but not yet tested by targeted knockout or comparative-genomics studies. |
| Modular control | Regulatory DNA is interface architecture, selected by MDL-style fitness $r(g) \propto \exp(-\beta L_g)$. | Model: abstract MDL inequalities proved; genome fractions not derived from annotation data. |
| Temporal coordination | Methylation, replication timing, and FOLD-mediated recombination implement clocks and phasing. | FOLD idempotence and bio-clock recurrence proved; molecular mechanism open. |

How does this compare with existing accounts of non-coding DNA? The selfish-DNA hypothesis [8] treats transposable elements as genomic parasites; RS reinterprets them as ledger-balancing substrate. The ENCODE "80% functional" claim [2] counts biochemical activity; RS would require structural necessity under the cost function. The comparative-genomics constraint estimates of 5–15% under purifying selection [5, 6] measure evolutionary conservation; RS predicts additional *phase-sensitive* constraint that standard alignment-based methods may not detect because it depends on helical position rather than linear sequence identity.

**Hypothesis 4.1** (Zero-Junk Program)**.** *As functional assays, comparative genomics, and phase-sensitive analyses improve, the fraction of sequence assignable to one or more of the five layers will grow substantially beyond current constraint estimates.*

This is not the same as asserting that every base pair has a strong organismal phenotype. A structurally constrained architecture can still contain redundancy, buffering, and context-dependent function [7].

## 5 Falsifiable Predictions

**Prediction 5.1** (Mod-8 Intron Non-Uniformity)**.** *Preregistered analyses of intron-length distributions should show statistically significant non-uniformity mod* 8*, even though the dominant residue class may depend on transcript weighting or gene set.* Falsifier*: uniform distribution of intron lengths mod* 8 *across well-powered datasets.*

**Prediction 5.2** (Minimal-Intron Window)**.** *The interval* 85–92 *bp (centered on* $8\varphi^5 \approx 88.7$*) should be enriched among minimal functional introns in curated mammalian datasets.* Falsifier*: minimal functional introns consistently* $\gg 100$ *or* $\ll 70$ *bp.*

**Prediction 5.3** (Topology-Aware Mutation Metrics)**.** *The* $Q_6$ *adjacency structure should predict mutational tolerance better than a coarse synonymous/non-synonymous dichotomy, especially for near-neighbor substitutions at the third codon position.* Falsifier*: no improvement in pathogenicity prediction from* $Q_6$ *distance over existing metrics (BLOSUM, Grantham).*

**Prediction 5.4** (Bio-Clocking Clusters)**.** *Biological timing constants involved in folding, transcription, and neural signaling should cluster near $\varphi$-spaced rungs on a logarithmic timescale.* Falsifier*: timing constants uniformly or randomly distributed on a log scale.*

**Prediction 5.5** (Phase-Sensitive Constraint Beyond Sequence Conservation)**.** *Regions of non-coding DNA that are not conserved by standard alignment-based methods should nonetheless show measurable constraint when assayed against helical position, chromatin timing, or coordinated expression phasing.* Falsifier*: no detectable phase-sensitive signal in non-conserved non-coding sequence.*

**Prediction 5.6** (The Code Optimizes More Than Chemical Similarity — **CONFIRMED**)**.** ***Original prediction (first draft):*** *RS predicts the code is locally optimal under a composite J metric that includes biosynthetic-pathway cost and position-dependent weighting, not just simple chemical distance.*

***Status:*** Substantially confirmed. *Proposition 3.6 shows that under a position-weighted cost with 8 components (hydrophobicity, charge, volume, and biosynthetic gap, each weighted by codon position), the standard code is the unique optimum over the 363,004 classwise non-identity permutations currently enumerated. The simple chemistry-only metric fails (42 improving swaps exist [15]); the position-weighted metric succeeds on the enumerated classwise search with margin* +37,136 *[16].*

# 6 Open Problems

**The codon-assignment problem (now partially resolved).** At the first draft, the formalism explained why there are 64 codons and 20 amino acids but not why *this* codon maps to *that* amino acid. As of this revision, Proposition 3.6 establishes that the standard code is the unique optimum on a 363,004-element classwise degeneracy-preserving search under a position-weighted cost [16]. The remaining open questions are (i) extending this from the classwise search to the full coupled degeneracy-preserving product space, and (ii) the WToken-to-amino-acid structural bridge: the cardinality match ($20 = 20$) and the fine-class constraint (WToken mode families partition the 20 amino acids into 8 classes of size 2–4) are formalized, but the mechanistic route from DFT-derived semantic classes to amino-acid side-chain chemistry is open.

**The chemistry bridge.** The WToken/amino-acid bijection is a theorem about cardinalities and mode families. The WToken fine-class partition constrains the 20! assignment space to 36,864 alternatives, and the position-weighted cost strongly favors the standard code on the formally and computationally explored neighborhoods [16]. What remains open is the *physical mechanism* linking DFT mode structure to tRNA recognition, aminoacyl-tRNA synthetase specificity, and biosynthetic pathway organization.

**From definitions to derivations.** The current genome-budget fractions (1.5/35/25/25/10/3.5) are explicit definitions in the Lean files, not outputs of a comparative-genomics pipeline or a first-principles optimization. To become a testable theory, they must be replaced by derived quantities.

**The intron evidence base.** The golden-angle theorem and minimal-intron estimate are clean formal results. The mod-8 enrichment claims are explicitly dataset-scoped in the current Lean files; different gene sets yield different peak residues. A publishable biology paper will need preregistered pipelines, raw counts, and sensitivity analyses across multiple annotation releases.

**Physical FOLD.** FOLD is a mathematically clean operator on an 8-register. Whether meiotic recombination, homologous pairing, and chromatin remodeling actually implement it at the molecular level is an open experimental question.

**Engagement with transposable-element biology.** The ledger-balance interpretation of repetitive DNA is the most speculative of the five layers. It must be tested against the mature body of work on selfish DNA [8], constructive neutral evolution [9], and the documented regulatory co-option of transposable elements [10].

# 7 Conclusion

This paper has presented eight machine-checked results and one computation-assisted codon-assignment result that connect the RS algebraic backbone to concrete features of DNA: the codon-space combinatorics ($64 = 8^2$, 14/16 family-box wobble symmetry, 8 four-fold degenerate boxes), the wobble-parity non-preservation theorem, the $(8, 1, 8)$ code optimality, the golden-angle/intron geometry, the bio-clock recurrence, FOLD idempotence with antisymmetric-phase cancellation, the position-specific mutation-vulnerability ordering (wobble safest, position 2 most dangerous), and the position-weighted classwise codon-assignment optimum (Proposition 3.6). It has also proposed a five-layer decomposition of non-coding DNA as a structured research program and stated six falsifiable predictions, one of which (Prediction 5.6) is now substantially confirmed.

The honest current status is that RS provides a nontrivial formal scaffold—not yet a finished theory of the genome. The exact budget fractions are modeling choices, and the strongest biological interpretations (ledger balance, physical FOLD, phase-sensitive constraint) remain hypotheses. What distinguishes the RS approach from prior accounts of non-coding DNA is not a claim of completeness but a specific algebraic language ($J$, $\varphi$, 8-tick) that generates falsifiable quantitative predictions rather than post-hoc narrative.

The immediate next steps are clear: preregistered intron-length analyses, a $Q_6$-based mutation-tolerance benchmark, and a comparative study of repeat-element phasing across mammalian clades. Each of these can be conducted independently of the broader RS theory and evaluated on its own empirical merits.

**Lean formalization.** All theorem-level structural results in this paper are machine-checked in Lean 4 (v4.27.0) with Mathlib, within the `Genetics` namespace of the `IndisputableMonolith` codebase. The namespace now contains **49 modules totaling 8,246 lines** with zero `sorry`, zero `axiom`, and zero placeholder proofs. The one exception is Proposition 3.6, whose exact classwise search size is formalized in Lean and whose 52 local/classwise certificates are formalized in Lean, while the full 363,004-case optimum statement is confirmed by exhaustive external computation. Key module groups include:

- **Codon objective and optimization**: `CodonNeighborCost`, `MutationModel`, `CompositeJCost`, `CodonAssignmentObjective`, `CodonAssignmentOptimality`, `CodonAssignmentGlobalOptimality`, `DegeneracySearchSpace`, `ComputableAssignmentCost`, `CertifiedResults`, `PositionWeightedCost`
- **Wobble, parity, and conservation**: `AminoAcidZClassification`, `ZInvariantPipeline`, `ZParityDegeneracyTable`, `WobbleZParity`, `ConservationHierarchy`
- **Helix geometry and intron placement**: `IntronStructure`, `PhaseAlignmentLayer`, `HelicalPhaseModel`, `IntronPlacementOptimality`
- **Bio-clocking and FOLD**: `TemporalCoordinationLayer`, `ChromosomePhaseProfile`, `HydrationGearbox` `GearboxSelectivity`
- **Five-layer genome decomposition**: `ErrorCorrectionLayer`, `PhaseAlignmentLayer`, `LedgerBalancingLayer`, `ModularArchitectureLayer`, `TemporalCoordinationLayer`, `GenomeBudget`, `DNAFramework`

- **WToken bridge and search**: `WTokenAssignmentBridge`, `BiosyntheticPathways`, `TranslationKinetic`
  `SearchSpaceCounting`, `DominanceLemmas`, `NearUniqueness`

**Acknowledgments.** The Lean 4 formalization builds on Mathlib. Empirical intron data referenced by the current genetics files are from Ensembl (GRCh38).

## References

[1] S. Ohno, *So much "junk" DNA in our genome*, Brookhaven Symp. Biol. **23**, 366–370 (1972).

[2] The ENCODE Project Consortium, *An integrated encyclopedia of DNA elements in the human genome*, Nature **489**, 57–74 (2012).

[3] D. Graur *et al.*, *On the immortality of television sets: "function" in the human genome according to the evolution-free gospel of ENCODE*, Genome Biol. Evol. **5**, 578–590 (2013).

[4] W.F. Doolittle, *Is junk DNA bunk? A critique of ENCODE*, Proc. Natl. Acad. Sci. USA **110**, 5294–5300 (2013).

[5] C.P. Ponting and R.C. Hardison, *What fraction of the human genome is functional?*, Genome Res. **21**, 1769–1776 (2011).

[6] C.M. Rands *et al.*, *8.2% of the human genome is constrained: variation in rates of turnover across functional element classes in the human lineage*, PLoS Genet. **10**, e1004525 (2014).

[7] M. Kellis *et al.*, *Defining functional DNA elements in the human genome*, Proc. Natl. Acad. Sci. USA **111**, 6131–6138 (2014).

[8] L.E. Orgel and F.H.C. Crick, *Selfish DNA: the ultimate parasite*, Nature **284**, 604–607 (1980).

[9] A. Stoltzfus, *On the possibility of constructive neutral evolution*, J. Mol. Evol. **49**, 169–181 (1999).

[10] E.B. Chuong, N.C. Elde, and C. Feschotte, *Regulatory activities of transposable elements: from conflicts to benefits*, Nat. Rev. Genet. **18**, 71–86 (2017).

[11] D. Haig and L.D. Hurst, *A quantitative measure of error minimization in the genetic code*, J. Mol. Evol. **33**, 412–417 (1991).

[12] S.J. Freeland and L.D. Hurst, *The genetic code is one in a million*, J. Mol. Evol. **47**, 238–248 (1998).

[13] S. Horvath, *DNA methylation age of human tissues and cell types*, Genome Biol. **14**, R115 (2013).

[14] J. Washburn, *The Algebra of Reality: A Recognition Science Derivation of Physical Law*, Axioms **15**(2), 90 (2025).

[15] J. Washburn, *The Standard Genetic Code Is Not Locally Optimal Under Simple Chemical Distance*, in preparation (2026).

[16] J. Washburn, *The Standard Genetic Code Is Globally Optimal Under Position-Weighted Mutation Cost*, in preparation (2026).