

```
1: #include <stdio.h>
2:
3: #define SIZE 5
4:
5: struct Student {
6:     char name[100];
7:     int age;
8:     int id;
9:     float avg;
10: };
11:
12: struct Node {
13:     struct Student data;
14:     struct Node* next;
15: };
16:
17: void inputStudent(struct Student* s);
18: void printStudent(struct Student* s);
19: int printTop(struct Student* s);
20:
21: int main() {
22:     struct Student student[SIZE];
23:
24:     inputStudent(student);
25:
26:     printf("-----\n");
27:     printf("[í\225\231ì\203\235 ì \225ë³´ ì¶\234ë ¥]\n");
28:     printf("-----\n");
29:
30:     int top = printTop(student);
31:
32:     for (int i = 0; i < SIZE; i++) {
33:         if (i == top) { continue; }
34:         printStudent(&student[i]);
35:     }
36:
37:     return 0;
38: }
39: void inputStudent(struct Student* s) {
40:     for (int i = 0; i < SIZE; i++) {
41:         printf("[%dë²\210ì$, í\225\231ì\203\235 ì\236\205ë ¥]\n", i + 1);
42:         printf("í\225\231ì\203\235 ì\235´ë!\204 ì\236\205ë ¥: ");
43:         scanf("%s", s[i].name);
44:         printf("í\225\231ì\203\235 ë\202\230ì\235´ ì\236\205ë ¥: ");
45:         scanf("%d", &s[i].age);
46:         printf("í\225\231ì\203\235 ì\225\231ë²\210 ì\236\205ë ¥: ");
47:         scanf("%d", &s[i].id);
48:         printf("í\225\231ì\203\235 ì\217\211ë• ì \220ì\210\230 ì\236\205ë ¥: ");
49:         scanf("%f", &s[i].avg);
50:         printf("\n");
51:     }
52:
53: }
54: void printStudent(struct Student* s) {
55:
56:     printf("ì\235´ë!\204: %s\n", s->name);
57:     printf("ë\202\230ì\235´: %d\n", s->age);
58:     printf("í\225\231ë²\210: %d\n", s->id);
59:     printf("í\217\211ë• ì \220ì\210\230: %.1f\n", s->avg);
60:     printf("\n");
61:
62: }
63:
64: int printTop(struct Student* s) {
65:     int top = 0;
66:     int temp = 0;
67:     for (int i = 1; i < SIZE; i++) {
```

```
68:         if (s[i].avg > s[temp].avg) {
69:             temp = i;
70:         }
71:     }
72:     top = temp;
73:     printStudent(&s[top]);
74:     return top;
75: }
```

```

1: #include <stdio.h>
2: #include <stdlib.h>
3: #include <string.h>
4:
5: struct Student {
6:     char* name;
7:     int age;
8:     int id;
9:     float avg;
10: };
11:
12: struct Node {
13:     struct Student data;
14:     struct Node* next;
15: };
16:
17: // í\225\231i\203\235 í\225ë³' í\236\205ë ¥
18: struct Student inputStudent() {
19:     struct Student s;
20:     char array[100]; //í\225\231i\203\235 í\235'ë; \204 í \200i\236¥í\225
ë°°i\227'
21:
22:     printf("\ní\225\231i\203\235 í\235'ë; \204 í\236\205ë ¥
(ë\235\204i\226'í\223°ë,° í\217-í\225"): ");
23:     getchar(); // í\236\205ë ¥ ë²\204í\215¥ ë¹\204i\232°ë,°
24:     if (fgets(array, sizeof(array), stdin) != NULL) {
25:         array[strcspn(array, "\n")] = '\0';
26:     }
27:     s.name = (char*)malloc(strlen(array) + 1);
28:     strcpy(s.name, array); //í\227-ë,°i\204\234 ë°\234í\226\211ë¬,í\236\220
ë\223mi\226'ë°\220
29:
30:     printf("í\225\231i\203\235 ë\202\230i\235' í\236\205ë ¥: ");
31:     scanf("%d", &s.age);
32:
33:     printf("í\225\231i\203\235 í\225\231ë²\210 í\236\205ë ¥: ");
34:     scanf("%d", &s.id);
35:
36:     printf("í\225\231i\203\235 í\217\211ë• í \220i\210\230 í\236\205ë ¥: ");
37:     scanf("%f", &s.avg);
38:
39:     return s;
40: }
41:
42: // í \204i²' í\225\231i\203\235 í¥\234ë ¥
43: void printAll(struct Node* head) {
44:     int i = 0;
45:     while (head != NULL) {
46:         printf("\n[%dë²\210i$, í\225\231i\203\235]\n", i + 1);
47:         printf("í\235'ë; \204: %s\n", head->data.name);
48:         printf("ë\202\230i\235': %d\n", head->data.age);
49:         printf("í\225\231ë²\210: %d\n", head->data.id);
50:         printf("í\217\211ë• í \220i\210\230: %.1f\n", head->data.avg);
51:         head = head->next;
52:     }
53: }
54:
55: // í\234ë³ í \220i\210\230 í\225\231i\203\235 í¥\234ë ¥
56: void printTop(struct Node* head) {
57:     if (head == NULL) return;
58:     struct Node* topStu = head;
59:     while (head != NULL) {
60:         if (head->data.avg > topStu->data.avg) {
61:             topStu = head;
62:         }
63:         head = head->next;
64:     }

```

```

65:     printf("\ní\234ë³ í\217\211ë• í \220i\210\230 í\225\231i\203\235]\n");
66:     printf("í\235'ë; \204: %s\n", topStu->data.name);
67:     printf("ë\202\230i\235': %d\n", topStu->data.age);
68:     printf("í\225\231ë²\210: %d\n", topStu->data.id);
69:     printf("í\217\211ë• í \220i\210\230: %.1f\n", topStu->data.avg);
70: }
71:
72: // í\235'ë; \204 ë\230\220ë\212\224 í\225\231ë²\210i\234¥ë; \234 ë²\200i\203\211
73: struct Node* searchStudent(struct Node* head) {
74:     int choice;
75:     char array[100];
76:     int id;
77:
78:     printf("ë²\200i\203\211 ë,°í\200 í\204 í\203\235 (1. í\235'ë; \204, 2.
í\225\231ë²\210): ");
79:     scanf("%d", &choice);
80:
81:     if (choice == 1) {
82:         getchar();
83:         printf("í\235'ë; \204 í\236\205ë ¥: ");
84:         if (fgets(array, sizeof(array), stdin) != NULL) {
85:             array[strcspn(array, "\n")] = '\0';
86:         }
87:         while (head != NULL) {
88:             if (strcmp(head->data.name, array) == 0) //ë¬,í\236\220i\227'
ë¹\204ëµ\220
89:                 return head;
90:             head = head->next;
91:         }
92:     }
93:     else if (choice == 2) {
94:         printf("í\225\231ë²\210 í\236\205ë ¥: ");
95:         scanf("%d", &id);
96:         while (head != NULL) {
97:             if (head->data.id == id)
98:                 return head;
99:             head = head->next;
100:         }
101:     }
102:     return NULL;
103: }
104:
105: // í\225\231i\203\235 í\202-í \234
106: struct Node* deleteStudent(struct Node* head) {
107:     int choice, id;
108:     char array[100];
109:     struct Node* prev = NULL;
110:     struct Node* cur = head;
111:
112:     printf("í\202-í \234 ë,°í\200 í\204 í\203\235 (1. í\235'ë; \204, 2.
í\225\231ë²\210): ");
113:     scanf("%d", &choice);
114:
115:     if (choice == 1) {
116:         printf("í\235'ë; \204 í\236\205ë ¥: ");
117:         if (fgets(array, sizeof(array), stdin) != NULL) {
118:             array[strcspn(array, "\n")] = '\0';
119:         }
120:         while (cur != NULL) {
121:             if (strcmp(cur->data.name, array) == 0) break;
122:             prev = cur;
123:             cur = cur->next;
124:         }
125:     }
126:     else if (choice == 2) {
127:         printf("í\225\231ë²\210 í\236\205ë ¥: ");
128:         scanf("%d", &id);

```

```
129:         while (cur != NULL) {
130:             if (cur->data.id == id) break;
131:             prev = cur;
132:             cur = cur->next;
133:         }
134:     }
135:
136:     if (cur == NULL) {
137:         printf("ì\202-ì \234ì\225 í\225\231ì\203\235ì\235\204 ì°%ì\235\204
ì\210\230 ì\227\206ì\212pë\213\210ë\213p. \n");
138:         return head;
139:     }
140:
141:     if (prev == NULL) head = cur->next;
142:     else prev->next = cur->next;
143:
144:     printf("\n%s í\225\231ì\203\235 í \225ë³´ê°\200
ì\202-ì \234ë\220\230ì\227\210ì\212pë\213\210ë\213p. \n", cur->data.name);
145:     free(cur);
146:     free(prev);
147:     return head;
148: }
149:
150: // í\225\231ì\203\235 í \225ë³´ í\210\230ì \225
151: void modifyStudent(struct Node* head) {
152:     struct Node* target = searchStudent(head);
153:     if (target == NULL) {
154:         printf("í\225\231ì\203\235ì\235\204 ì°%ì\235\204 ì\210\230
ì\227\206ì\212pë\213\210ë\213p. \n");
155:         return;
156:     }
157:     printf("\n[ê,òì´ í \225ë³´]\nì\235´ë; \204: %s\në\202\230ì\235´:
%d\ní\225\231ë²\210: %d\ní\217\211ë• í \220ì\210\230: %.1f\n", target->data.name,
target->data.age, target->data.id, target->data.avg);
158:
159:     char array[100];
160:     getchar();
161:     printf("\nì\203\210ë; \234ì\232´ ë\202\230ì\235´ í\236\205ë ¥: ");
162:     fgets(array, sizeof(array), stdin);
163:     array[strcspn(array, "\n")] = '\0';
164:     free(target->data.name);
165:     target->data.name = (char*)malloc(strlen(array) + 1);
166:     strcpy(target->data.name, array);
167:
168:     printf("ì\203\210ë; \234ì\232´ ë\202\230ì\235´ í\236\205ë ¥: ");
169:     scanf("%d", &target->data.age);
170:     printf("ì\203\210ë; \234ì\232´ í\225\231ë²\210 í\236\205ë ¥: ");
171:     scanf("%d", &target->data.id);
172:     printf("ì\203\210 í\217\211ë• í \220ì\210\230 í\236\205ë ¥: ");
173:     scanf("%f", &target->data.avg);
174:
175:     printf("\nì\225\231ì\203\235 í \225ë³´ê°\200
ì\210\230ì \225ë\220\230ì\227\210ì\212pë\213\210ë\213p. \n");
176: }
177:
178: // ë@ \224ë³´ë;¬ í\225´ì \234
179: void freeAll(struct Node* head) {
180:     struct Node* temp;
181:     while (head != NULL) {
182:         temp = head;
183:         head = head->next;
184:         free(temp->data.name);
185:         free(temp);
186:     }
187:     printf("í\224\204ë; \234ë•,ë\236´ì\235\204 íç\205ë£\214í\225ë@ë\213\210ë\213p.
ë@ \224ë³´ë;¬ë¥% í\225´ì \234ì\225ë@ë\213\210ë\213p. ... \n");
188: }
```

```
189:
190: int main() {
191:     struct Node* head = NULL, * tail = NULL;
192:     int menu;
193:
194:     while (1) {
195:         printf("\n\n===== ë@ \224ë\211´ =====\n");
196:         printf("1. í\225\231ì\203\235 í \225ë³´ í\236\205ë ¥\n2. ì \204ì²´
ì\225\231ì\203\235 íç\234ë ¥\n3. ìp\234ë³ í \220ì\210\230 í\225\231ì\203\235
ìç\234ë ¥\n4. í\225\231ì\203\235 ë²\200ì\203\211 (ì\235´ë; \204 ë\230\220ë\212\224
ì\225\231ë²\210) \n");
197:         printf("5. í\225\231ì\203\235 í\202-ì \234 (ì\235´ë; \204
ë\230\220ë\212\224 í\225\231ë²\210) \n6. í\225\231ì\203\235 í\210\230ì \225 (ì\235´ë; \204
ë\230\220ë\212\224 í\225\231ë²\210) \n0. íç\205ë£\214 \n===== \n");
198:         printf("\në@ \224ë\211´ í\204 í\203\235: ");
199:         scanf("%d", &menu);
200:
201:         if (menu == 1) {
202:             struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
203:             newNode->data = inputStudent();
204:             newNode->next = NULL;
205:             if (head == NULL) head = tail = newNode;
206:             else {
207:                 tail->next = newNode;
208:                 tail = newNode;
209:             }
210:
211:             else if (menu == 2) printAll(head);
212:             else if (menu == 3) printTop(head);
213:             else if (menu == 4) {
214:                 struct Node* found = searchStudent(head);
215:                 if (found)
216:                     printf("\n[ë²\200ì\203\211 ë²°ë³¼]\nì\235´ë; \204:
%s\në\202\230ì\235´: %d\ní\225\231ë²\210: %d\ní\217\211ë• í \220ì\210\230: %.1f\n",
found->data.name, found->data.age, found->data.id, found->data.avg);
217:                 else
218:                     printf("í\225\231ì\203\235ì\235\204 ì°%ì\235\204 ì\210\230
ì\227\206ì\212pë\213\210ë\213p. \n");
219:             }
220:             else if (menu == 5) head = deleteStudent(head);
221:             else if (menu == 6) modifyStudent(head);
222:             else if (menu == 0) {
223:                 freeAll(head);
224:                 break;
225:             }
226:             else {
227:                 printf("ì\236\230ë³»ë\220\234 í\236\205ë ¥ì\236\205ë\213\210ë\213p.
\n");
228:             }
229:         }
230:         return 0;
231:     }
232: }
```