### Inheritance

Jonathan Windle

University of East Anglia

J.Windle@uea.ac.uk

May 30, 2017

## Overview I

Intro

- 2 Inheritance
  - Base class
  - Sub Class

3 Polymorphic pointers and references

#### Intro

- Advantages:
  - Encourages code use
  - Encourages modularity, data hiding and encapsulation
  - Makes programs maintainable and easily extendable
- Disadvantages:
  - Can lead to overly complicated implementations.
  - Introduces computational overheads.

#### Inheritance

Abstract Base class:

```
class Speaker
private:
// Inherited, but not visible in sub-class
        string utterance;
public:
// Can be overridden, inherited and visible in sub-class
        virtual string getUtterance() {
                return utterance;
  Pure virtual, must be overridden before instantiation
        virtual void speak() = 0;
        Speaker(string utterance) {
                this->utterance = utterance;
```

### Sub Class

#### Concrete Sub Class:

```
class Philosopher: public Speaker
public:
// Override pure virtual method, can now instantiate
        void speak() {
                cout << "My philosophy is..." << getUtterance() << endl;</pre>
  Add new methods to inherited behaviour
        inline void philosophosise() {
                cout << "But what do I mean..." << getUtterance() << endl;
   Over-ride inherited virtual method, these cannot be inline
        string getUtterance() {
                return "Woof-woof";
   Call super-class constructor
        Philosopher(string philosophy): Speaker(philosophy)
```

## Polymorphic pointers and references

- Superclass pointers can point to sub-class objects.
- Superclass references can reference sub-class objects.
- Can only access methods present in the super-class.

```
int main(int argc, char* argv[]) {
        Philosopher descartes ("I think, therefore I am");
        Dog rover;
        Speaker* speaker = &descartes;
   Uses speak in Philosopher class
        speaker -> speak();
        speaker = &rover;
   Uses speak in Dog class
        speaker -> speak();
        Speaker &orater = descartes;
   Pointers and references can be polymorphic
        orater.speak();
        return 0;
```

# The End