THEME: VIS + AI · INFORMATION VISUALIZATION TERM PROJECT PROPOSAL

LagLens: What Does a Robot Do While Its Policy Is Still Thinking?

A visual analytics tool for robot policies that plan in chunks and need time to think


How such a robot works

1. **Plan.** A robot **policy** (a neural network) looks at the camera once and plans its next 16 moves: an **action chunk**.
2. **Act.** The robot performs the first *h* moves of the chunk without looking again, then needs a new chunk.
3. **Think.** Computing a chunk takes time *d* (**inference latency**, here 0–600 ms). What should the robot do meanwhile? (right)
   • **Sync**: **wait**. Safe, but the robot stands idle.
   • **Async**: **keep moving** on the old chunk. No waiting, but the scene changes while the policy thinks, so the new chunk is made for a scene that no longer exists (an **outdated plan**) and may not continue the current motion: the robot **jumps** when it switches (a **chunk-boundary discontinuity**). **Naive async** just swaps the chunks; **inpaint async** computes the new chunk so that it continues the old one.

The problem. Engineers choose the strategy, *d* and *h* from one success rate per setting, e.g. “naive async, d = 4: 62 % vs. sync, d = 0: 72 %”. That number cannot show **which** situations broke, **when**, or **why** (idling, outdated plans or jumps). We found no visualization tool for this.

Our idea: same start, different schedule. We run one pretrained policy from the **same 50 start states** under **46 schedules** (strategy × *d* × *h*) and record every planned chunk. Any two schedules can then be compared start by start and replayed move by move.

The three strategies over time (d = 2, h = 4)




think = policy computing a chunk · act = robot moving (tint changes per chunk) · hatched = idle · lollipop = jump at a switch

A real case from our data: same start (#1035), d = 4 (400 ms), h = 4

Task: push the grey T-block onto the dashed T-goal (top view). Only the strategy differs.



Inpaint async ✓ success



Naive async ✗ failure: a 259 px jump at a switch knocks the block away

Our own recorded runs of a pretrained robot policy

Task (PushT, simulated, top view): a round pusher (the *agent*) must push a T-shaped block onto a fixed T-shaped goal. **Policy**: a pretrained Diffusion Policy (`lerobot/diffusion_pusht`) that turns the last 2 camera frames and pusher positions into a chunk of 16 moves (target positions of the pusher). It builds every chunk from random noise, so running the same schedule again can change an outcome; one *noise replicate* measures how often. Same 50 start states × (46 schedules + 1 noise replicate) = **2,350 episodes** (recorded runs, also called rollouts); every planned chunk and every executed move is logged.

Attribute (episode table, 2,350 items × 21 attributes)	Type	Order / range / levels	Meaning
strategy KEY	nominal	sync · naive · inpaint	what the robot does while a chunk is computed
latency d KEY	ordinal (ratio, steps)	0 < 1 < 2 < 4 < 6 steps (0–600 ms)	inference delay; d = 0 only for sync
horizon h KEY	ordinal (ratio, steps)	2 < 4 < 6 < 8	moves executed from each chunk before switching
replicate KEY	nominal (binary)	0 · 1	1 = sync d0 h8 run again with new random noise (chance level)
seed KEY	nominal (ID)	1000–1049 (50 levels)	start state of block & pusher, same in every schedule
success	nominal (binary)	0 = fail, 1 = success	coverage > 95 % within 300 steps
coverage_final	quant. ratio, ↑	0.00–0.99	overlap of T-block with goal
steps_to_success	quant. ratio, ↓	68–300 (empty if failed)	time to finish
seam_gap_mean / max	quant. ratio (px), ↓	2.3–222.2 / 6–305	chunk-boundary discontinuity: jump between old and new plan at a hand-over
think_motion_mean / max	quant. ratio (px), ↓	0.0–106.5 / 0–317	how far the robot moved while the policy was thinking (change the new chunk did not see)
staleness_mean	quant. ratio (steps)	0.5–9.5	age of the camera picture behind each move (≈ d + (h−1)/2, equal for all strategies)
idle_frac	quant. ratio, ↓	0.00–0.75	share of steps with nothing to execute
jerk_mean · path_len · n_inferences	quant. ratio	1.2–221.3 · 205–12828 px · 8–150	smoothness (jerk = 2nd difference of actions) · distance travelled · # chunks computed

Dataset type: multidimensional **table** of episodes, each linked to two **temporal** tables and to a **spatial** field (512 × 512 px workspace).

- **Step table** (598,117 items) · keys: schedule, seed, t (ordinal, 10 Hz) · values: agent x, y; block x, y (interval, px); block θ (cyclic, rad); action x, y (interval, px); chunk id (ordinal); index j 0–15 (ordinal); age (ratio, steps since its camera picture); held (binary, 1 = idle step); coverage (ratio 0–1, block–goal overlap).
- **Chunk table** (119,373 items) · keys: schedule, seed, chunk id · values: t_obs (time of the camera picture), t_avail (time the chunk was ready), executed window, 16 predicted (x, y) actions.
- **Size**: 240 KB episode CSV + 112 MB step/chunk JSON (lazy-loaded per schedule).

Keys vs. values: keys = (strategy, latency, horizon, replicate) → *schedule*; × seed → episode; × t → step; × chunk id → chunk. Everything else is a value.

Novel data: no public dataset logs per-inference chunks (survey, Oct 2026). Generated by us; scripts in `scripts/`. 1 step = 100 ms.

Two people who must decide how a policy is executed




PRIMARY PERSONA

Mara Jensen

28 · 4th-year PhD student, robot learning lab · Copenhagen, Denmark

- **Context**: trains diffusion / flow-matching policies (generative models that output action chunks); deploys them on a real arm while the GPU server sits across the building (60–250 ms Wi-Fi latency).
- **Goals**: pick an execution strategy and horizon that keep success high at the latency she actually has; explain *why* in a paper.
- **Needs**: per-episode evidence of what failed, aligned with what the policy planned at that moment.
- **Pain points**: only success-rate tables and video; cannot tell whether a failure came from waiting, an outdated plan or a jump; re-running real robot trials is costly; matplotlib debug plots show one episode at a time.



SECONDARY PERSONA

Arjun Mehta

37 · ML platform engineer, warehouse-robotics start-up · Seoul (Pangyo), Korea

- **Context**: owns the policy-serving software (the robot sends camera frames to a GPU server, which returns action chunks); does not train models.
- **Goals**: set a latency budget (the largest inference delay a robot may tolerate) per robot and a safe default strategy; know when to fall back to sync.
- **Needs**: an overview of how success degrades with latency for each strategy, with confidence that it is not a few lucky seeds.
- **Pain points**: research papers report curves on other robots; no shared vocabulary with researchers about “why it jitters”.

Difference	Mara (primary)	Arjun (secondary)
Expertise	Policy internals (diffusion, chunking)	Systems, networking, latency
Granularity of questions	Single episodes, single chunk hand-overs	Schedules and aggregate trends
Main view used	Workspace replay + execution timeline, seed shifts (T3, T4)	Latency-response curves + paired seed table (T1, T2)
Decision made	Which strategy / horizon to propose and why	Latency budget and fallback rule

Portraits: StyleGAN-generated, public domain (Wikimedia Commons “Woman 1.jpg”, “Man 2.jpg”); the people do not exist. Personas are fictional.

Four tasks, from all schedules down to a single chunk switch

#	Action + target	Concrete question (Mara)	Why	Expected outcome
T1	**Compare → trends** of success and of each strategy's cost (idle time, outdated plans, jumps) across schedules	"How fast does success fall with latency for each strategy, and which horizon is most robust?"	Choose a candidate schedule for the latency the lab actually has.	A shortlist of robust schedules and a latency budget per strategy.
T2	**Locate → outliers**: initial states whose outcome **flips** between a reference and a candidate schedule	"Going from sync d=0 to naive async d=4, *which* seeds start failing, and which are rescued?"	Aggregate rates hide which situations break; paired seeds isolate the schedule's effect.	A small set of fragile seeds to inspect (and to add to a regression test set).
T3	**Identify → features** in time & space: where idling, outdated plans and jumps occur in a flipped episode	"At which step does the candidate diverge from the reference, and did the robot wait, act on an outdated plan, or jump?"	Diagnose the mechanism of failure, not just its rate.	A causal hypothesis, e.g. "a 30 px discontinuity right at block contact makes the push slip."
T4	**Discover → correlation** between jumps at chunk switches (boundary discontinuities) and task outcome (coverage) over paired episodes	"When a seed moves from R to C, do larger discontinuities go with lower coverage? Does inpainting shrink the discontinuities?"	If jumps are what breaks episodes, a strategy that shrinks them should rescue seeds; check it on our policy.	Evidence for or against a strategy (direction and size of shift per seed).

Arjun mainly needs **T1** (latency budget) and **T2** (is the drop driven by a few seeds?). **Mara** chains T1 → T2 → T3 → T4 in one session: overview first, then drill down to a single chunk hand-over (details on demand).

Each view answers one task with the most effective idiom

View	Task	Idiom & why (VIS literature)	Interaction
A · Latency Response	T1	*"How fast does each strategy get worse as the policy gets slower?"* **Line chart small multiples**: one panel per horizon h, x = latency d on its true scale, y = metric, strategies **superposed** (hue + shape). Position on a common scale beats the luminance of a heatmap [Cleveland & McGill 84; Heer & Bostock 10]; superposition for direct sync-vs-async comparison, juxtaposition across h [Gleicher 11]. **95 % interval** lines instead of bars [Correll & Gleicher 14]; hover = paired difference to R.	Click mark = C (compare), shift-click = R (baseline); **one question bar**: Success · Idle (cost of sync) · Outdated (cost of async) · Discontinuity (cost of naive async), drives A *and* B; recomputes on seeds selected in B.
B · Paired Seed Table	T2, T4	*"Which start states flip between R and C, and is that more than chance?"* **Composite Table-Lens view** [Rao & Card 94; Javed & Elmqvist 12]: one row per seed shared by (left) an outcome matrix — filled = success, R column black, C column orange — and (right) **dumbbells** R → C of the attribute that belongs to A's question. Rows are **grouped by R→C change** (spatial region), so flips break their band's pattern; a **re-run** column shows chance flips (11/50).	No controls of its own. Click column header = C; click cell = open episode; **brush** dumbbells or click a band → **cross-filter** A [Weaver 10].
C · Workspace Replay	T3	*"Watch both runs side by side: what was planned, what was done, where it jumped."* Juxtaposed R | C maps at identical scale (spatial data on true geometry). Four overlays: executed part of the current chunk (solid), its thrown-away part (dashed), the chunk still being computed (dotted) and the latest **discontinuity** (magenta). Status line in strategy terms ("idle: waiting for inference").	Play / scrub / ← → (**navigate** t); hover a planned point → when planned / executed; click → jump.
D · Execution Timeline	T3	*"When was the policy thinking, which plan did each move come from, where were the jumps?"* **Gantt lanes** on a shared linear time axis [Plaisant 96; Brehmer 17]: per run a **think** track (inference) and an **act** track (chunk spans, hatched = idle), discontinuities as **lollipops** (length), coverage lines below. Sync shows think/act *alternating*, async *overlapping*.	**Brush** a time window → highlighted path in C; hover chunk → its plan in C; click → cursor.

Why this is not a generic dashboard: C and D trace every executed move back to the plan (chunk) and the camera frame it came from, which no chart tool offers; A and B compare two schedules *start state by start state* against a chance baseline (re-run), not just averages. **Less is more**: the first draft had 5 views and ~10 hues; following the rules of parsimony and consistency [Wang Baldonado 00] we merged the two seed-level views, gave every hue one meaning, and cut ten technical controls to **one question bar** named after who pays each cost.

The most important attribute gets the most effective channel

Attribute (type)	View	Mark	Channel	Justification
success rate, idle share, motion while thinking, boundary discontinuity (ratio)	A	point + line	position y (common scale)	best magnitude channel; slope = degradation
latency d (ratio)	A	—	position x (true spacing)	100 ms steps, not ordinal bins
horizon h (ordinal)	A	panel	spatial region (small multiples)	juxtaposed, shared y
strategy (nominal, 3)	A, B	line, point	hue + shape (●■◆)	redundant: never hue alone
uncertainty (95 % interval)	A	thin line	position (extent)	avoids within-the-bar bias
success per seed (binary)	B	cell	luminance (filled / empty)	2 levels → 1 luminance step
R→C change (nominal, 4)	B	row band	spatial region	top categorical channel
attribute under R and C (ratio)	B	dumbbell	position x (symlog if long-tailed)	aligned shift, no crossing
agent / block / plan (interval, px)	C	line, point, polygon	position (x, y)	spatial data, true geometry
executed / discarded / computing	C	line, point	line style + fill	separable, keeps hue for identity
think, act intervals (time)	D	bar	position + length on time axis	alternation vs overlap visible
boundary discontinuity (ratio, px)	C, D	lollipop, segment	length + magenta hue	magnitude → length
coverage (ratio)	D	line	position y	R vs C on a common scale

Hue budget — one meaning per hue

■ Reference R ■ Candidate C

● Sync ■ Naive async ◆ Inpaint

■ Discontinuity (C, D) grey: everything else

Okabe–Ito hues. CVD-checked with Machado et al. (VIS 2009) in OKLab: R vs C ΔE ≥ 48; strategy hues ≥ 9 plus redundant shape.

Ranking used (Munzner, Ch. 5):
magnitude: position on common scale > length > angle/area > luminance
identity: spatial region > hue > shape

Scalability: A 47 points · B 2,350 cells + 50 dumbbells · C/D one episode (≤ 300 steps, ≤ 150 chunks) — SVG at interactive rates.

Cleveland & McGill (1984) · Heer & Bostock (CHI 2010) · Gleicher et al. (2011) · Correll & Gleicher (VIS 2014) · Full list: docs/design_rationale.md


LagLens

pick / swap R and C anywhere

● R baseline Sync · d=4 · h=4 ▾ ⇄ ● C compare Inpaint · d=4 · h=4 ▾ ? ↺

A · Latency Response (T1)


[**Success** | Idle | Outdated | Discontinuity] ● Sync ■ Naive ◆ Inpaint



question bar sets A and B · click mark = C · shift-click = R · hover = value & Δ vs R

B · Paired Seed Table (T2, T4)

right part: attribute of the question chosen in A (no own controls)




click cell = open episode (column → C) · click header = C · click band = select its seeds

C · Workspace Replay (T3)

hover planned point = when planned / executed · click = jump · ← → space

R · Sync d4 h4 ✗ · idle: waiting for inference

C · Inpaint d4 h4 ✓ · acting · picture 4 steps old




— executed part of chunk ┄ thrown away ⋯ next chunk computing ━ boundary discontinuity

▶ play

D · Execution Timeline (T3)

think = inference · **act** = chunk executed (hatched = idle) · lollipop = boundary discontinuity



drag = time window (→ path highlighted in C) · hover chunk = its plan in C · click = cursor

Flow: A (pick R and C on the latency curves) → B (find flipped seeds, check the R→C shift, select seeds → A recomputes) → C + D (where and when it went wrong). d3.js v7 only.