# Recommender Systems

Universitat Pompeu Fabra Barcelona

**Mining Massive Datasets**

Materials provided by Prof. Carlos Castillo — https://chato.cl/teach

Instructor: Dr. Teodora Sandra Buda — https://tbuda.github.io/

# Sources

- Data Mining, The Textbook (2015) by Charu Aggarwal (Section 18.5) – slides by Lijun Zhang
- Mining of Massive Datasets 2nd edition (2014) by Leskovec et al. (Chapter 9) - slides A, B




Pioneer

# Recommender systems

- Product recommendation is perhaps one of the best known use cases:
  - Given data from user buying behaviors, profiles, interests, browsing behavior, buying behavior, and ratings about various items
  - Leverage such data to make recommendations to customers about possible buying interests

# Recommender systems (general)

- In general, the idea is:
  - Given data from user interests, including profiles, browsing behavior, item interaction behavior, ratings about various items
  - Leverage such data to make recommendations to users about further interesting items

NETFLIX

Spotify®

amazon

YouTube







Large scale engines for recommendation:

- are composed of **multiple layers**,
- use **online** and **offline** (batch) models,
- include complex **data pipelines** to move **behavioral** and **content** signals around.

Source: _March 2021

# Utility matrix

- Matrix D of size n (users) x d (items)
  - The utility value for a user-item pair ($D_{ij}$) describe some relationship between user i and item j
  - Typically, a small subset of the utility values are known

# Example utility matrices

| | Dune | Soul | Nomadland | Avengers | RRR | Encanto |
|---|---|---|---|---|---|---|
| $U_1$ | 1 | | | 5 | | 2 |
| $U_2$ | | 5 | | | 4 | |
| $U_3$ | 5 | 3 | | 1 | | |
| $U_4$ | | | 3 | | | 4 |
| $U_5$ | | | | 3 | 5 | |
| $U_6$ | 5 | | 4 | | | |

(a) **Ratings-based**

| | Dune | Soul | Nomadland | Avengers | RRR | Encanto |
|---|---|---|---|---|---|---|
| $U_1$ | 1 | | | 1 | | 1 |
| $U_2$ | | 1 | | | 1 | |
| $U_3$ | 1 | 1 | | 1 | | |
| $U_4$ | | | 1 | | | 1 |
| $U_5$ | | | | 1 | 1 | |
| $U_6$ | 1 | | 1 | | | |

(b) **Positive preference, e.g., “like”**

# Types of utility

- **Explicit**: we ask users to rate items





- **Implicit**: we take watching/consuming/buying behavior as a positive signal, skip/hide as negative

# Sources for a recommendation

- Content-based recommendation
  - Users and items are associated with features
  - Features are matched to infer interest
- Interaction-based recommendations
  - Leverage user preferences in the form of ratings or other behavior
  - Recommend through similarity or latent factors

**New items have no ratings**

and

**New users have no history**

Photo: Torque News

# Solution 1. “Side information”

Login with Facebook

Use info from close people






# Solution 2. "On-boarding" users



# Content-based recommendations

# General idea of content-based recommendations

- Movies: recommend other movies with same director, actor, genre, as viewed ones
- Products: recommend other products in same category, brand, color, as purchased ones

# Creating a recommendation

- User is associated with some documents that describe his/her interests
  - Specified demographic profile
  - Specified interests at registration time
  - Descriptions of the items bought
- Items are also associated with semi-structured descriptions


JBL GO lleva el sonido de calidad JBL a todas partes. GO es su solución de altavoz todo en uno y reproduce música en tiempo real vía Bluetooth desde smartphones y tabletas, gracias a su batería recargable. También cuenta con un práctico manos libres.

| | |
|---|---|
| Potencia | **3 W** |
| Respuesta de Frecuencia | **180Hz – 20 kHz** |
| Tipo de altavoz | **Portátil** |
| Amplificador de sonido | **Integrado** |

# Creating a recommendation (cont.)



# Possible recommendation methods

- **If no utility matrix is available**
  - k-nearest neighbor approach
    - Find the top-k items that are closest to the user (when items and users can be represented in the same space, e.g., dating apps)
  - The cosine similarity with tf-idf can be used
- **If a utility matrix is available**
  - Classification-based approach: training documents are those for which the user has specified utility, labels are utility values
  - Regression-based approach in the case of ratings
- Limitations: depends on the quality of the features

# Example: regression-based approach for content-based recommendation

| Movie | Adventure | Action | Science-Fiction | Drama | Crime | Thiller | | User 1 | User 2 |
|---|---|---|---|---|---|---|---|---|---|
| Star Wars IV | 1 | 1 | 1 | 0 | 0 | 0 | | 1 | -1 |
| Saving Private Ryan | 0 | 0 | 0 | 1 | 0 | 0 | | | |
| American Beauty | 0 | 0 | 0 | 1 | 0 | 0 | | | |
| City of Gold | 0 | 0 | 0 | 1 | 1 | 0 | | -1 | 1 |
| Interstellar | 0 | 0 | 1 | 1 | 0 | 0 | | 1 | |
| The Matrix | 1 | 1 | 1 | 0 | 0 | 1 | | | 1 |

...

We would do two regressions: one for the ratings of user 1 and another for user 2.
(We can also do this for groups of users, e.g., by city and age)

**How many rated movies would we need, as a minimum, to be able to do this?**

# Exercise Content-based recommender based on regression

- Database of ~100 electric scooters, of which 12 have been rated on a scale 1-5
- We have done linear regression on:
  - price [$], battery capacity [Wh], range [km]
- Which would be your top-3 recommended scooter among the remaining ones?

Spreadsheet link:
https://upfbarcelona.padlet.org/sandrabuda1/theory-exercises-tdmvfhddcnvfj5b8

# Pros and Cons of content-based recommendations

- Pros:
  - No cold-start problem if no utility needed
  - Able to recommend to users with very particular tastes
  - Able to recommend new and obscure items
  - Able to provide explanations that are easily understandable

# Pros and Cons of content-based recommendations

- Cons:
  - Finding the correct features might be hard
  - Recommending for new users still challenging if user features are different from item features
  - Overspecialization/”bubble”: might reinforce user interests
  - Does not exploit ratings of other users!

# Summary

# Things to remember

- Content-based recommendations
- Regression-based method

# Exercises for TT16-TT18

- Mining of Massive Datasets 2nd edition (2014) by Leskovec et al. Note that some exercises cover advanced concepts:
  - Exercises 9.2.8
  - Exercises 9.3.4
  - Exercises 9.4.6