

Module Interface Specification: SE 4G06, TRON 4TB6

Team 26, STRONE

Jordan Bierbrier

Azriel Gingoyon

Taranjit Lotey

Udeep Shah

Abraham Taha

April 5, 2023

Revision History

Date	Version	Notes
1/18/2023	1.0	Added Content
4/5/2023	1.1	Updated for feedback and consistency

Contents

1	Introduction	1
2	Notation	1
3	Module Decomposition	2
4	MIS of Login Module Design Decision - Removed	3
4.1	Module	3
4.2	Uses	3
4.3	Syntax	3
4.3.1	Exported Constants	3
4.3.2	Exported Access Programs	3
4.4	Semantics	3
4.4.1	State Variables	3
4.4.2	Environment Variables	3
4.4.3	Assumptions	3
4.4.4	Access Routine Semantics	3
5	MIS of Bluetooth Connection Module (M2)	5
5.1	Module	5
5.2	Uses	5
5.3	Syntax	5
5.3.1	Exported Constants	5
5.3.2	Exported Access Programs	5
5.4	Semantics	5
5.4.1	State Variables	5
5.4.2	Environment Variables	5
5.4.3	Assumptions	5
5.4.4	Access Routine Semantics	6
6	MIS of Keyword Selection Module (M3)	7
6.1	Module	7
6.2	Uses	7
6.3	Syntax	7
6.3.1	Exported Constants	7
6.3.2	Exported Access Programs	7
6.4	Semantics	7
6.4.1	State Variables	7
6.4.2	Environment Variables	7
6.4.3	Assumptions	7
6.4.4	Access Routine Semantics	8

7	MIS of Output Signal Module (M4)	9
7.1	Module	9
7.2	Uses	9
7.3	Syntax	9
7.3.1	Exported Constants	9
7.3.2	Exported Access Programs	9
7.4	Semantics	9
7.4.1	State Variables	9
7.4.2	Environment Variables	9
7.4.3	Assumptions	9
7.4.4	Access Routine Semantics	9
8	MIS of Profile Module Design Decision - Removed	10
8.1	Module	10
8.2	Uses	10
8.3	Syntax	10
8.3.1	Exported Constants	10
8.3.2	Exported Access Programs	10
8.4	Semantics	10
8.4.1	State Variables	10
8.4.2	Environment Variables	10
8.4.3	Assumptions	11
8.4.4	Access Routine Semantics	11
9	MIS of Battery Status Out of Scope	13
9.1	Module	13
9.2	Uses	13
9.3	Syntax	13
9.3.1	Exported Constants	13
9.3.2	Exported Access Programs	13
9.4	Semantics	13
9.4.1	State Variables	13
9.4.2	Environment Variables	13
9.4.3	Assumptions	13
9.4.4	Access Routine Semantics	13
9.4.5	Local Functions	14
10	MIS of Battery Status Sound Classification (M5)	15
10.1	Module	15
10.2	Uses	15
10.3	Syntax	15
10.3.1	Exported Constants	15
10.3.2	Exported Access Programs	15

10.4	Semantics	15
10.4.1	State Variables	15
10.4.2	Environment Variables	15
10.4.3	Assumptions	15
10.4.4	Access Routine Semantics	16
10.4.5	Local Functions	16
11	MIS of Bluetooth Communication Module (M6)	17
11.1	Module	17
11.2	Uses	17
11.3	Syntax	17
11.3.1	Exported Constants	17
11.3.2	Exported Access Programs	17
11.4	Semantics	17
11.4.1	State Variables	17
11.4.2	Environment Variables	17
11.4.3	Assumptions	17
11.4.4	Access Routine Semantics	17
12	MIS of Microphone Module (M7)	19
13	MIS of Profile Module	19
13.1	Module	19
13.2	Uses	19
13.3	Syntax	19
13.3.1	Exported Constants	19
13.3.2	Exported Access Programs	19
13.4	Semantics	19
13.4.1	State Variables	19
13.4.2	Environment Variables	19
13.4.3	Assumptions	19
13.4.4	Access Routine Semantics	19
14	Appendix	21

List of Figures

List of Tables

1	Data Notations	1
2	Module Hierarchy	2

Symbols, Abbreviations and Acronyms

See SRS Documentation at [*SRS.pdf Document Link*](#).

1 Introduction

The following document details the Module Interface Specifications for Synesthesia Wear, a wearable ~~product~~ **device** that assists users by using signal processing on gathered sounds to provide appropriate feedback (via vibrations) to the user according to inputted sound configuration settings. As a result, this gives the users peace of mind knowing that if their attention is needed (doorbell, ring, name call, etc.), Synesthesia Wear will be able to alert them.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at [Team 26 Capstone GitHub Repository](#).

2 Notation

The structure of the MIS for modules comes from [Hoffman and Strooper \(1995\)](#), with the addition that template modules have been adapted from [Ghezzi et al. \(2003\)](#). The mathematical notation comes from Chapter 3 of [Hoffman and Strooper \(1995\)](#). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by ~~SE-4G06, TRON-4TB6~~ **STRONE**.

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

Table 1: **Data Notations**

The specification of ~~SE-4G06, TRON-4TB6~~ **STRONE** uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, ~~SE-4G06, TRON-4TB6~~ **STRONE** uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

3 Module Decomposition

The following table is taken directly from the *Module Guide Document* for this project.

Level 1	Level 2
Hardware-Hiding Module (M1)	
	Login Module (Design Decision was made to remove authentication/login aspects of the project)
	Bluetooth connection Module (M2)
Behaviour-Hiding Module	Keyword Selection Module (M3)
	Output Signal Module (M4)
	Profile Module
	Battery Status Module Out of Scope
	Sound Classification Module (M5)
Software Decision Module	Bluetooth Communication Module (M6)
	Microphone Module (M7)

Table 2: Module Hierarchy

4 ~~MIS of Login Module~~ Design Decision - Removed

4.1 Module

Login Type

4.2 Uses

N/A

4.3 Syntax

4.3.1 Exported Constants

N/A

4.3.2 Exported Access Programs

Name	In	Out	Exceptions
authorize	keyInput	Authorized	
login	keyInput		Not_A_Character
switchCue	keyInput		Not_Cueable

4.4 Semantics

4.4.1 State Variables

Authorized: Authorized is a boolean that is true when the correct credentials are entered and false otherwise.

4.4.2 Environment Variables

keyInput: {key.Enter, key.AlphabetCharacters, key.LeftClick}

4.4.3 Assumptions

The Synesthesia Wear application is successfully installed on the user's device and the login page has loaded onto the screen.

4.4.4 Access Routine Semantics

switchCue(key.LeftClick):

- transition: mouseLocation.navigate()

- output: None
- exception: Not_Cueable

login(key.AlphabetCharacters):

- transition: username.addCharacter() or password.addCharacter()
- output: None
- exception: Not_A_Character

authorize(key.Enter):

- transition: login.submit()
- output: Authorized
- exception: None

5 MIS of Bluetooth Connection Module (M2)

5.1 Module

Bluetooth Connection Module (M2)

5.2 Uses

N/A

5.3 Syntax

5.3.1 Exported Constants

N/A

5.3.2 Exported Access Programs

Name	In	Out	Exceptions
Find_Device	Boolean onClick	Device_ID Array	device_NotFound
Connect_Device	(Boolean, onClick Device_ID)		

5.4 Semantics

5.4.1 State Variables

- known_Device: Device_ID \mathbb{N}
- Paired_Device

5.4.2 Environment Variables

N/A

5.4.3 Assumptions

We assume that the mobile device that the user has the application on has a bluetooth module.

5.4.4 Access Routine Semantics

Find_Device(Boolean onClick):

- transition: $(\text{OnClick} \equiv \text{True}) \implies \text{Found_Devices} = \implies \text{Found_Devices.Add}(\text{known_Devices}) \implies \text{Found_Devices.Add}(\text{device_id1})$
- output: $\text{Found_Devices}(\text{known_Device}, \text{device_id1}, \text{device_id2} \dots \text{device_idN})$
- exception: Device_NotFound

Connect_Device(Boolean onClick):

- transition: $(\text{OnClick} \equiv \text{True}) \implies \text{Paired_Device} = \text{device_id2}$
- output: None
- exception: None

6 MIS of Keyword Selection Module (M3)

6.1 Module

Keyword Selection Type (M3)

6.2 Uses

- Profile Module (Design Decision - Removed)
- Bluetooth Communication Module (M6)

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
save	keyInput	Saved	Mouse_Not_On_Save_Button
keyword	keyInput		Not_A_Character
switchCue	keyInput		Not_Cueable

6.4 Semantics

6.4.1 State Variables

Saved: Saved is a boolean that is true when the “Save” button has been pressed and false otherwise.

6.4.2 Environment Variables

keyInput: {key.AlphabetCharacters, key.LeftClick}

6.4.3 Assumptions

The Synesthesia Wear application is successfully installed on the user’s device, ~~the user was able to log into the app,~~ and the sound configuration settings page is loaded onto the screen.

6.4.4 Access Routine Semantics

switchCue(key.LeftClick):

- transition: mouseLocation.navigate()
- output: None
- exception: Not_Cueable

keyword(key.AlphabetCharacters)char:

- transition: keyword.addCharacter()
- output: None
- exception: Not_A_Character

save(key.LeftClick):

- transition: keyword.save()
- output: Saved
- exception: Mouse_Not_On_Save_Button

7 MIS of Output Signal Module (M4)

7.1 Module

Output Signal Module (M4)

7.2 Uses

- Sound Classification Module (M5)

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
onVolt	(Boolean, Class_Id)		Null_class

7.4 Semantics

7.4.1 State Variables

current_Volt: Integer of the current voltage being supplied to the motor

7.4.2 Environment Variables

N/A

7.4.3 Assumptions

We are assuming that when this module is called that the battery has sufficient charge to power the motor for the called upon number of requests

7.4.4 Access Routine Semantics

onVolt(Boolean onOFF, Class_id Current):

- transition: $\text{Count} = \text{Current} \mid \text{While count} \neq 0 \implies (\text{current_volt} \equiv 0 \wedge \text{onOFF}) \implies \text{current_Volt} = 5 \mid \text{count} - = \text{count} \mid \text{current_Volt} = 0$
- output: None
- exception: $\text{Class_id} \equiv \text{Null}$

8 ~~MIS of Profile Module~~ Design Decision - Removed

8.1 Module

Profile Module

8.2 Uses

Login Module

8.3 Syntax

8.3.1 Exported Constants

N/A

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
Set_First_Name	String		Type_Error
Set_Last_Name	String		Type_Error
Get_First_Name		String	Null_Exception
Get_Last_Name		String	Null_Exception
change_Password	String		Type_Error
Change_Username	String		Type_Error
Get_Username		String	Null_Exception

8.4 Semantics

8.4.1 State Variables

- first_name
- last_name
- password
- username

8.4.2 Environment Variables

key_input(keyboard)

8.4.3 Assumptions

We are assuming that the user has either a touchscreen keyboard or an external keyboard.

8.4.4 Access Routine Semantics

Set_first_name(String Name):

- transition: first_name = Name
- output: None
- exception: Type_Error

Set_last_name(String Name):

- transition: last_name = Name
- output: None
- exception: Type_Error

Get_first_name():

- transition: None
- output: First_name
- exception: Null_Exception

Get_last_name():

- transition: None
- output: last_name
- exception: Null_Exception

Change_password(String Name):

- transition: password = Name
- output: None
- exception: Type_Error

Change_username(String Name):

- transition: username = Name
- output: None

- exception: `Type_Error`

`Get_username()`:

- transition: `None`
- output: `username`
- exception: `Null_Exception`

9 ~~MIS of Battery Status~~ Out of Scope

9.1 Module

Battery Status

9.2 Uses

Indicator ~~N/A~~

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
Low Bat- tery	N/A	Low Status	Low Bat- tery
Battery Level	N/A	Percentage	Battery Status

9.4 Semantics

9.4.1 State Variables

N/A

9.4.2 Environment Variables

keyOutput : key.Low Battery, key.Battery Status

9.4.3 Assumptions

Battery will always have some charge on it.

9.4.4 Access Routine Semantics

- transition: N/A
- output: Battery level
- exception: N/A

9.4.5 Local Functions

- `get level(int level)`
- `battery condition(int cond)`

10 MIS of ~~Battery Status~~ Sound Classification (M5)

10.1 Module

Sound Classification (M5)

10.2 Uses

~~Categorize detected sounds~~

- Keyword Selection (M3)
- Bluetooth Communication (M6)
- Microphone (M7)

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
Sound level	Microphone	decibels	High/Low Level

10.4 Semantics

10.4.1 State Variables

N/A

10.4.2 Environment Variables

keyOutput : key.microphone **N**

keyOutput : key.decibels **N**

10.4.3 Assumptions

Surrounding sound levels are null compared to required input level.

10.4.4 Access Routine Semantics

- transition: N/A
- output: decibels
- exception: N/A

10.4.5 Local Functions

- sound level(float volume)
- sorting volume()

11 MIS of Bluetooth Communication Module (M6)

11.1 Module

BTCommModule Bluetooth Communication (M6)

11.2 Uses

None

11.3 Syntax

11.3.1 Exported Constants

DataTx:{ BT.send() }

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
RecvNewClass	DataRx	-	Class_Full
RmClass	DataRx	-	Class_Empty
UpdatePref	DataRx	-	-
SendBattV	BattV	DataTx	-

11.4 Semantics

11.4.1 State Variables

None

11.4.2 Environment Variables

BattV: {AnalogRead(BatteryVolt)}

DataRx: {BT.recieve(T1),BT.recieve(T2),BT.recieve(T3)}N

11.4.3 Assumptions

Connection with the application is already establised. Bluetooth tries to automatically reconnect if the application is disconnected.

11.4.4 Access Routine Semantics

RecvNewClass():

- transition: if(DataRx == T1) then addclass(dataRx)

- output: None
- exception: Class_Full

RmClass():

- transition: if(DataRx == T2) then rmclass(dataRx)
- output: None
- exception: Class_Empty

UpdatePref():

- transition: if(DataRx == T3) then prefchange(DataRx.class,DataRx.pref)
- output: None
- exception: None

~~SendBattV(BattV):~~

- transition: None
- output: DataTx == BattV
- exception:

12 MIS of Microphone Module (M7)

13 MIS of Profile Module

13.1 Module

MicroMod Microphone (M7)
Bluetooth Communication (M6)

13.2 Uses

None

13.3 Syntax

13.3.1 Exported Constants

None

13.3.2 Exported Access Programs

Name	In	Out	Exceptions
updateData	SoundIN,CLKINT	SoundData	-

13.4 Semantics

13.4.1 State Variables

SoundData - Array of sound inputs recorded at every sample interval

13.4.2 Environment Variables

SoundIN: { Digital.Read(Digital_Microphone) }
CLKINT: {clk.interupt(sample time)}

13.4.3 Assumptions

Clock interrupt is already set up to issue interrupts every $1/(\text{sample frequency})$

13.4.4 Access Routine Semantics

- transition: N/A
- output: decibels

- exception: N/A

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. Fundamentals of Software Engineering. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. Software Design, Automated Testing, and Maintenance: A Practical Approach. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

14 Appendix