

Module Interface Specification for SE 4G06, TRON 4TB6

Team 26, STRONE

Jordan Bierbrier

Azriel Gingoyon

Taranjit Lotey

Udeep Shah

Abraham Taha

April 5, 2023

Revision History

Date	Version	Notes
18-01-23	1.0	Added Content

Symbols, Abbreviations and Acronyms

See SRS Documentation at [*SRS.pdf Document Link*](#).

Contents

1	Introduction	1
2	Notation	1
3	Module Decomposition	1
4	MIS of Battery Status	3
4.1	Module	3
4.2	Uses	3
4.3	Syntax	3
4.3.1	Exported Constants	3
4.3.2	Exported Access Programs	3
4.4	Semantics	3
4.4.1	State Variables	3
4.4.2	Environment Variables	3
4.4.3	Assumptions	3
4.4.4	Access Routine Semantics	3
4.4.5	Local Functions	4
5	MIS of Battery Status	4
5.1	Module	4
5.2	Uses	4
5.3	Syntax	4
5.3.1	Exported Constants	4
5.3.2	Exported Access Programs	4
5.4	Semantics	4
5.4.1	State Variables	4
5.4.2	Environment Variables	4
5.4.3	Assumptions	4
5.4.4	Access Routine Semantics	5
5.4.5	Local Functions	5
6	MIS of Login Module	5
6.1	Module	5
6.2	Uses	5
6.3	Syntax	5
6.3.1	Exported Constants	5
6.3.2	Exported Access Programs	5
6.4	Semantics	5
6.4.1	State Variables	5
6.4.2	Environment Variables	6
6.4.3	Assumptions	6

6.4.4	Access Routine Semantics	6
7	MIS of Keyword Selection Module	7
7.1	Module	7
7.2	Uses	7
7.3	Syntax	7
7.3.1	Exported Constants	7
7.3.2	Exported Access Programs	7
7.4	Semantics	7
7.4.1	State Variables	7
7.4.2	Environment Variables	7
7.4.3	Assumptions	7
7.4.4	Access Routine Semantics	8
8	MIS of Bluetooth Communication Module	9
8.1	Module	9
8.2	Uses	9
8.3	Syntax	9
8.3.1	Exported Constants	9
8.3.2	Exported Access Programs	9
8.4	Semantics	9
8.4.1	State Variables	9
8.4.2	Environment Variables	9
8.4.3	Assumptions	9
8.4.4	Access Routine Semantics	9
9	MIS of Microphone Module	11
9.1	Module	11
9.2	Uses	11
9.3	Syntax	11
9.3.1	Exported Constants	11
9.3.2	Exported Access Programs	11
9.4	Semantics	11
9.4.1	State Variables	11
9.4.2	Environment Variables	11
9.4.3	Assumptions	11
9.4.4	Access Routine Semantics	11
10	MIS of Output Signal Module	12
10.1	Module	12
10.2	Uses	12
10.3	Syntax	12
10.3.1	Exported Constants	12

10.3.2	Exported Access Programs	12
10.4	Semantics	12
10.4.1	State Variables	12
10.4.2	Environment Variables	12
10.4.3	Assumptions	12
10.4.4	Access Routine Semantics	12
11	MIS of Bluetooth Connection Module	13
11.1	Module	13
11.2	Uses	13
11.3	Syntax	13
11.3.1	Exported Constants	13
11.3.2	Exported Access Programs	13
11.4	Semantics	13
11.4.1	State Variables	13
11.4.2	Environment Variables	13
11.4.3	Assumptions	13
11.4.4	Access Routine Semantics	14
12	MIS of Profile Module	15
12.1	Module	15
12.2	Uses	15
12.3	Syntax	15
12.3.1	Exported Constants	15
12.3.2	Exported Access Programs	15
12.4	Semantics	15
12.4.1	State Variables	15
12.4.2	Environment Variables	15
12.4.3	Assumptions	16
12.4.4	Access Routine Semantics	16
13	Appendix	18

1 Introduction

The following document details the Module Interface Specifications for Synesthesia Wear, a wearable product that assists users by using signal processing on gathered sounds to provide appropriate feedback (via vibrations) to the user according to inputted sound configuration settings. As a result, this gives the users peace of mind knowing that if their attention is needed (doorbell, ring, name call, etc.), Synesthesia Wear will be able to alert them.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at [Team 26 Capstone GitHub Repository](#).

2 Notation

The structure of the MIS for modules comes from ?, with the addition that template modules have been adapted from ?. The mathematical notation comes from Chapter 3 of ?. For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$.

The following table summarizes the primitive data types used by SE 4G06, TRON 4TB6.

Table 1: Notations

Data Type	Notation	Description
character	char	a single symbol or digit
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$
natural number	\mathbb{N}	a number without a fractional component in $[1, \infty)$
real	\mathbb{R}	any number in $(-\infty, \infty)$

The specification of SE 4G06, TRON 4TB6 uses some derived data types: sequences, strings, and tuples. Sequences are lists filled with elements of the same data type. Strings are sequences of characters. Tuples contain a list of values, potentially of different types. In addition, SE 4G06, TRON 4TB6 uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

3 Module Decomposition

The following table is taken directly from the [Module Guide Document](#) for this project.

Level 1	Level 2
Hardware-Hiding Module	
	Login Module
	Bluetooth connection ModuleM2
	Keyword Selection ModuleM3
Behaviour-Hiding Module	Output Signal ModuleM4
	Profile ModuleM5
	Battery Status ModuleM6
Software Decision Module	Sound Classification ModuleM7
	Bluetooth Communication ModuleM8
	Microphone ModuleM9

Table 2: Module Hierarchy

4 MIS of Battery Status

4.1 Module

~~Battery Status~~

4.2 Uses

Indicator

4.3 Syntax

4.3.1 Exported Constants

N/A

4.3.2 Exported Access Programs

Name	In	Out	Exceptions
Low Bat- tery	N/A	Low Status	Low Bat- tery
Battery Level	N/A	Percentage	Battery Status

4.4 Semantics

4.4.1 State Variables

N/A

4.4.2 Environment Variables

keyOutput : key.Low Battery, key.Battery Status

4.4.3 Assumptions

Battery will always have some charge on it.

4.4.4 Access Routine Semantics

- transition: N/A
- output: Battery level
- exception: N/A

4.4.5 Local Functions

- get level(int level)
- battery condition(int cond)

5 MIS of Battery Status

5.1 Module

Sound Classification M7

Bluetooth communication M8

5.2 Uses

Categorize detected sounds

5.3 Syntax

5.3.1 Exported Constants

N/A

5.3.2 Exported Access Programs

Name	In	Out	Exceptions
Sound level	Microphone	decibels	High/Low Level

5.4 Semantics

5.4.1 State Variables

N/A

5.4.2 Environment Variables

keyOutput : key.microphone N

keyOutput : key.decibels N

5.4.3 Assumptions

Surrounding sound levels are null compared to required input level.

5.4.4 Access Routine Semantics

- transition: N/A
- output: decibels
- exception: N/A

5.4.5 Local Functions

- sound level(float volume)
- sorting volume()

6 MIS of Login Module

6.1 Module

~~Login Type~~

6.2 Uses

N/A

6.3 Syntax

6.3.1 Exported Constants

N/A

6.3.2 Exported Access Programs

Name	In	Out	Exceptions
authorize	keyInput	Authorized	
login	keyInput		Not_A_Character
switchCue	keyInput		Not_Cueable

6.4 Semantics

6.4.1 State Variables

Authorized: Authorized is a boolean that is true when the correct credentials are entered and false otherwise.

6.4.2 Environment Variables

keyInput: {key.Enter, key.AlphabetCharacters, key.LeftClick}

6.4.3 Assumptions

The Synesthesia Wear application is successfully installed on the user's device and the login page has loaded onto the screen.

6.4.4 Access Routine Semantics

switchCue(key.LeftClick):

- transition: mouseLocation.navigate()
- output: None
- exception: Not_Cueable

login(key.AlphabetCharacters):

- transition: username.addCharacter() or password.addCharacter()
- output: None
- exception: Not_A_Character

authorize(key.Enter):

- transition: login.submit()
- output: Authorized
- exception: None

7 MIS of Keyword Selection Module

7.1 Module

Keyword Selection Type

7.2 Uses

- Profile Module **M5**
- Bluetooth Communication Module **M8**

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Access Programs

Name	In	Out	Exceptions
save	keyInput	Saved	Mouse_Not_On_Save_Button
keyword	keyInput		Not_A_Character
switchCue	keyInput		Not_Cueable

7.4 Semantics

7.4.1 State Variables

Saved: Saved is a boolean that is true when the “Save” button has been pressed and false otherwise.

7.4.2 Environment Variables

keyInput: {key.AlphabetCharacters, key.LeftClick}

7.4.3 Assumptions

The Synesthesia Wear application is successfully installed on the user’s device, the user was able to log into the app, and the sound configuration settings page is loaded onto the screen.

7.4.4 Access Routine Semantics

switchCue(key.LeftClick):

- transition: mouseLocation.navigate()
- output: None
- exception: Not_Cueable

keyword(key.AlphabetCharacters)char:

- transition: keyword.addCharacter()
- output: None
- exception: Not_A_Character

save(key.LeftClick):

- transition: keyword.save()
- output: Saved
- exception: Mouse_Not_On_Save_Button

8 MIS of Bluetooth Communication Module

8.1 Module

BTComuModule

8.2 Uses

None

8.3 Syntax

8.3.1 Exported Constants

DataTx:{ BT.send() }

8.3.2 Exported Access Programs

Name	In	Out	Exceptions
RecvNewClass	DataRx	-	Class_Full
RmClass	DataRx	-	Class_Empty
UpdatePref	DataRx	-	-
SendBattV	BattV	DataTx	-

8.4 Semantics

8.4.1 State Variables

None

8.4.2 Environment Variables

BattV: {AnalogRead(BatteryVolt)}

DataRx: {BT.recieve(T1),BT.recieve(T2),BT.recieve(T3)}N

8.4.3 Assumptions

Connection with the application is already establised. Bluetooth tries to automatically reconnect if the application is disconnected.

8.4.4 Access Routine Semantics

RecvNewClass():

- transition: if(DataRx == T1) then addclass(dataRx)

- output: None
- exception: Class_Full

RmClass():

- transition: if(DataRx == T2) then rmclass(dataRx)
- output: None
- exception: Class_Empty

UpdatePref():

- transition: if(DataRx == T3) then prefchange(DataRx.class,DataRx.pref)
- output: None
- exception: None

~~SendBattV(BattV):~~

- transition: None
- output: DataTx == BattV
- exception:

9 MIS of Microphone Module

9.1 Module

MicroMod

Bluetooth Communication M9

9.2 Uses

None

9.3 Syntax

9.3.1 Exported Constants

None

9.3.2 Exported Access Programs

Name	In	Out	Exceptions
updateData	SoundIN,CLKINT	SoundData	-

9.4 Semantics

9.4.1 State Variables

SoundData - Array of sound inputs recorded at every sample interval

9.4.2 Environment Variables

SoundIN: { Digital.Read(Digital_Microphone) } \mathbb{R}

CLKINT: {clk.interupt(sample time)}

9.4.3 Assumptions

Clock interrupt is already set up to issue interrupts every $1/(\text{sample frequency})$

9.4.4 Access Routine Semantics

- transition: N/A
- output: decibels
- exception: N/A

10 MIS of Output Signal Module

10.1 Module

Output Signal Module

10.2 Uses

- Sound Classification Module **M7**

10.3 Syntax

10.3.1 Exported Constants

N/A

10.3.2 Exported Access Programs

Name	In	Out	Exceptions
onVolt	(Boolean, Class_Id)		Null_class

10.4 Semantics

10.4.1 State Variables

current_Volt: Integer of the current voltage being supplied to the motor

10.4.2 Environment Variables

N/A

10.4.3 Assumptions

We are assuming that when this module is called that the battery has sufficient charge to power the motor for the called upon number of requests

10.4.4 Access Routine Semantics

onVolt(Boolean onOFF, Class_id Current):

- transition: $\text{Count} = \text{Current} \mid \text{While count} \neq 0 \implies (\text{current_volt} \equiv 0 \wedge \text{onOFF}) \implies \text{current_Volt} = 5 \mid \text{count} - = \text{count} \mid \text{current_Volt} = 0$
- output: None
- exception: $\text{Class_id} \equiv \text{Null}$

11 MIS of Bluetooth Connection Module

11.1 Module

Bluetooth Connection Module

11.2 Uses

N/A

11.3 Syntax

11.3.1 Exported Constants

N/A

11.3.2 Exported Access Programs

Name	In	Out	Exceptions
Find_Device	Boolean onClick	Device_ID Array	device_NotFound
Connect_Device	(Boolean, onClick Device_ID)		

11.4 Semantics

11.4.1 State Variables

- known_Device: Device_ID \mathbb{N}
- Paired_Device

11.4.2 Environment Variables

N/A

11.4.3 Assumptions

We assume that the mobile device that the user has the application on has a bluetooth module.

11.4.4 Access Routine Semantics

Find_Device(Boolean onClick):

- transition: $(\text{OnClick} \equiv \text{True}) \implies \text{Found_Devices} = \implies \text{Found_Devices.Add}(\text{known_Devices}) \implies \text{Found_Devices.Add}(\text{device_id1})$
- output: $\text{Found_Devices}(\text{known_Device}, \text{device_id1}, \text{device_id2} \dots \text{device_idN})$
- exception: Device_NotFound

Connect_Device(Boolean onClick):

- transition: $(\text{OnClick} \equiv \text{True}) \implies \text{Paired_Device} = \text{device_id2}$
- output: None
- exception: None

12 MIS of Profile Module

12.1 Module

Profile Module

12.2 Uses

Login Module

12.3 Syntax

12.3.1 Exported Constants

N/A

12.3.2 Exported Access Programs

Name	In	Out	Exceptions
Set_First_Name	String		Type_Error
Set_Last_Name	String		Type_Error
Get_First_Name		String	Null_Exception
Get_Last_Name		String	Null_Exception
change_Password	String		Type_Error
Change_Username	String		Type_Error
Get_Username		String	Null_Exception

12.4 Semantics

12.4.1 State Variables

- first_name
- last_name
- password
- username

12.4.2 Environment Variables

key_input(keyboard)

12.4.3 Assumptions

We are assuming that the user has either a touchscreen keyboard or an external keyboard.

12.4.4 Access Routine Semantics

Set_first_name(String Name):

- transition: first_name = Name
- output: None
- exception: Type_Error

Set_last_name(String Name):

- transition: last_name = Name
- output: None
- exception: Type_Error

Get_first_name():

- transition: None
- output: First_name
- exception: Null_Exception

Get_last_name():

- transition: None
- output: last_name
- exception: Null_Exception

Change_password(String Name):

- transition: password = Name
- output: None
- exception: Type_Error

Change_username(String Name):

- transition: username = Name
- output: None

- exception: `Type_Error`

`Get_username()`:

- transition: `None`
- output: `username`
- exception: `Null_Exception`

13 Appendix