

SET-UP SHEET

X4'26 SET-UP SHEET VER.1 ©XRAY

XRAY X4'26

RACE					
TRACK					
NAME				DATE	
QUAL POSITION	FINAL POSITION	BEST LAP TIME	LAPS	TIME	
		/sec	/		

TRACK					
TRACK SURFACE	☐ CARPET		☐ ASPHALT		
TRACK LAYOUT	☐ TECHNICAL	☐ MIXED	☐ FAST		
TRACTION	☐ LOW	☐ MEDIUM	☐ HIGH		

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	☐ FRONT SOLID AXLE	GEAR DIFF OIL
UP ☐ DOWN ☐	SOLID & DIFF POSITION	UP ☐ DOWN ☐

PINION	/T	SPUR GEAR	/T	F. DRIVE RATIO
--------	----	-----------	----	----------------

FRONT	SHOCKS	REAR
XRAY SPRINGS		
OIL /Cst		
REBOUND %		
☐ 4 HOLES ☐ PSS	1.1mm 1.2mm	1.1mm 1.2mm ☐ PSS
SHOCK LENGTH	/mm	SHOCK LENGTH
THICKNESS/mm		

TIRES	
ADDITIONAL	
ADDITIONAL TIMING	
WIPE OFF TIME	
TIRE WARMERS	
Timing:	Temp.:

SIDE WALL GLUE	FRONT TIRES
DIA. /mm	ADDITIVE AREA /mm

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT	%	REAR	%
MOTOR		TIMING				
ESC		BATTERIES				
BODY		WING				

Dimension from body post to window bottom line BODY POSITION	
Dimension from body post to upper holder WING SIDE PLATE YES ☐ NO ☐	
Dimension from edge to surface CUTTING	
WAVE BRACE	GF ☐ 1.6 ☐ 2.0 ☐ 2.0 ☐ 1.6 ☐ GF
TOP DECK	SCREWS ☐ SHIMS ☐
BULKHEADS	Rear used in front ☐ 2.0 ☐ 1.6
NONE	#301092 NONE ☐ BEARING ☐

COMMENTS	
----------	--

FRONT CASTER	Upper links CASTER	FRONT & REAR SUSPENSION	Upper links CASTER
5° 4° 3° Adjust with eccentric bushings	BUMP STEER /mm	SHIM /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5° Adjust with eccentric bushings
HEIGHT /mm	SHIM /mm	TOE GAIN /mm	SHIM /mm
FF /mm	FR /mm	RF /mm	RR /mm
RIDE HEIGHT	SERVO SAVER	RIDE HEIGHT	SERVO HORN

FRONT	FRONT HUB
CAMBER /deg. Left = Right BODY STOP YES ☐ NO ☐ SHIM /mm #107712 DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐	FF /mm SHIMS /mm MEDIUM ☐ GRAPH. ☐ HARD ☐ ALU ☐ #107730 Droop Gauge DRIVE SHAFT 58mm 59mm SHIM /mm UPSTOP /mm DROOP /mm Set with shocks ☐ Set without shocks ☐

REAR	REAR HUB
CAMBER /deg. Left = Right BODY POST VERTICAL ☐ HORIZONTAL ☐ SHIM /mm #107712 DOWNSTOP /mm Set with shocks ☐ Set without shocks ☐	RF /mm SHIMS /mm MEDIUM ☐ GRAPH. ☐ HARD ☐ ALU ☐ DRIVE SHAFT 52mm 54mm SHIM /mm UPSTOP /mm DROOP /mm Set with shocks ☐ Set without shocks ☐

FRONT TOP VIEW	REAR TOP VIEW
TOE OUT Left = Right ACKERMANN /mm SHORT LiPo BRASS WEIGHT YES ☐ NO ☐ BRASS WEIGHT FOR MOTOR MOUNT 40g UPPER CLAMP KIT ☐ -1mm UPPER CLAMP FLEX FRONT UPPER CFF™ ARM - S LINKS SHORT LINKS LONG STEERING BRIDGE YES ☐ NO ☐ SHIM SIZE HUB OFFSET SHIM /mm	TOE IN Left = Right UPPER CLAMP KIT ☐ -1mm UPPER CLAMP FLEX REAR UPPER CFF™ ARM - S LINKS SHORT LINKS LONG HUB OFFSET SHIM /mm

FRONT BOTTOM VIEW	REAR BOTTOM VIEW
BUMPER 3D - KIT FOAM STEER. LOCK /deg. MOTOR MOUNT SERVO HOLDER CHASSIS GRAPHITE ☐ ALU ☐ ALU 1.5mm	T-BRACE ALU BRASS CHASSIS T-BRACE REAR ARMS MEDIUM ☐ HARD ☐ SHORT ☐