Assignment on Functions

GE 1502
Cornerstone of Engineering 2
CRN: 35280
Monday, Wednesday, Thursday from 10:30 AM - 11:35 AM
308 Hurtig Hall
Thursday, February 1, 2018
Jordan Lian

Table of Contents

That’s Deep

Pseudocode/Flowchart

//library files, iostream, fstream, cstdlib
//constants, MAX
//two sub-functions, deepest point and two by two functions
//input file, output file syntax
//nested for loop, read in arrays
//call back deepest point from sub-function (using if statement logic)
//two by two functions, use if statement logic to get largest average (largest 2x2 area)

Test by hand calculation

Sample Calc: Rows 2,3
Columns 5,6
(546.6 + 547.2 + 548.7 + 547.8) / 4 = 547.575 meters squared -- largest 2x2 area

Program source code .cpp file

```
/* Jordan Lian, GE 1502, HW 3 - That's Deep!

This program will read a text file containing many ocean depth measurements in a 6 meter x 6 meter area.
The program will call two functions using call by reference to find the deepest
point in the ocean, and the deepest two by two area.
//read in array, use nested for loop

*/

#include <iostream>
#include <fstream>
#include <cstdlib>
using namespace std;

#define MAX 6

double deepest_point(double ocean[MAX][MAX]);
double two_by_two(double ocean[MAX][MAX], int& f, int& g);
```

```
int main(void)
{
	//declare variables
	string filename = "depth.txt";
	double ocean_depth[MAX][MAX];
	int i=0, j=0, f, g; //initialized variable for matrix array
	int row, column;
	double start, big;

	//read file
	cout << "The file depth.txt will read a 6x6 matrix of ocean depth values in a 6x6 area
(meters squared). Please enter depth.txt to import --> ";
	cin >> filename;

	ifstream infile;
	infile.open(filename.c_str());

	ofstream outfile;
	outfile.open("ocean_depth.txt");

	if(!infile)
	{
		cout << "You selected the wrong file. The program will terminate." << endl;
		return 0;
	}

	//reading txt file
	cout << endl;
	for(i=0; i < MAX; i++)
	{
		for(j=0; j < MAX; j++)
		{
			infile >> ocean_depth[i][j];
			cout << ocean_depth[i][j] << " ";
			outfile << ocean_depth[i][j] << " ";
		}
		cout << endl;
		outfile << endl;
	}

	//deepest point
	start =  deepest_point(ocean_depth);
	cout << "\nThe deepest point is " << start << " meters" << endl;
```

```
	outfile << "The deepest point is " << start << " meters" << endl;

	big = two_by_two(ocean_depth, f, g); //sub-function
	cout << "The deepest 2x2 area in meters squared is " << big << " bounded by rows " <<
f+1 << " and " << f+2 << " with columns "
	<< g+1 << " and " << g+2 << endl << endl;

	outfile << "The deepest 2x2 area in meters squared is " << big << " bounded by rows "
<< f+1 << " and " << f+2 << " with columns "
	<< g+1 << " and " << g+2 << endl << endl;

	system("pause");
	return 0;
}

double deepest_point(double ocean[MAX][MAX])
{
	double start=0;
	int a, b;

	for(a=0; a < MAX; a++)
	{
		for(b=0; b < MAX; b++)
		{
			if(ocean[a][b] > start)
				start = ocean[a][b];
		}
	}
	return start;
}

double two_by_two(double ocean[MAX][MAX], int& f, int& g)
{
	int d, e;
	double big = 0;
	double sum, avg;
	for(d=0; d < (MAX-1); d++)
	{
		for(e=0; e < (MAX-1); e++)
		{
			sum = ocean[d][e] + ocean[d+1][e] + ocean[d][e+1] + ocean[d+1][e+1];
			avg = sum / 4.0;
			if (avg > big)
```

```
                {
                        big = avg;
                        f = d;
                        g = e;
                }
        }
        return big;
}
```

Screenshot of Outputs



What's the Watts

Pseudocode/Flowchart

//library files, iostream, cstdlib, fstream
//constants, NROWS, NCOLS, MAX
//subfunction for calculating average
//input file, output file syntax
//read in array using nested for loops
//call back subfunction

//calculate total sum and average for the entire 10 week span, initialize total_sum = 0, sum up weekly averages, then divide by 10
//smallest output, initialize a variable to a large number, then use if statement to keep narrowing down to the smallest output, then print
//get user to choose to print out all weekly averages or just the desired weekly average (if statement)

Test by hand calculation

Sample Calculation: Week 1
(207 + 301 + 222 +302 + 22 + 167 + 125) / 7 = 192.286 → average

Total Average: Sum up each averages
(192.286 + 270.286 + 219.429 + 280.429 + 294.857 + 277.714 + 307.714 + 230.714 + 238.857 + 274.429) / 10 = 258.671

Smallest Output: 21, Week 3, Day 5 (not really a calculation)

Program source code .cpp file

```
/* Jordan Lian, GE 1502, HW 3 - What's the Watts

This program will read in a txt file containing power output values each week and each corresponding day.
The program will print the average power output over the 10 week period.
The program will also print out the average for each week.
The program will also print out the week and day where the smallest power output occurred.

*/

#include <iostream>
#include <fstream>
#include <cstdlib>
using namespace std;

#define NROWS 10
#define NCOLS 7

double week_average(double test_array[NROWS][NCOLS], int a, double& total_sum);
//power[][], average, test_row

int main(void)
```

```
{
	//declare variables
	string filename = "POWER1.txt";
	double power[NROWS][NCOLS];
	int i=0, j=0, a=0; //initialized variables for counter loops
	double average, total_sum, smallest = 500;
	int x, y; //smallest power output variables
	int user_input; //user input

	//getting the txt file
	cout << "The file POWER1.txt will read a matrix of power plant output values. Please
enter POWER1.txt to import --> ";
	cin >> filename;
	cout << endl;

	ifstream infile;
	infile.open(filename.c_str());

	ofstream outfile;
	outfile.open("Watts_Results.txt");

	if(!infile)
	{
		cout << "You selected the wrong file. The program will terminate";
		cout << "You selected the wrong file. The program will terminate";
		return 0;
	}

	//reading txt file
	for(i=0; i < NROWS; i++)
	{
		for(j=0; j < NCOLS; j++)
		{
			infile >> power[i][j];
			cout << power[i][j] << " ";

			if(power[i][j] < smallest)
			{
				smallest = power[i][j];
				x = i;
				y = j;
			}
		}
```

```
            cout << endl; //endline after the entire array is printed
        }

        //calculating total sum and average
        total_sum = 0;
        for(a=0; a < NROWS; a++)
        {
            double average = week_average(power, a, total_sum);
        }

        cout << "\nThe smallest power output in Megawatts is " << smallest << " on week " <<
x+1 << " on day "<< y+1 << endl;
        outfile << "The smallest power output in Megawatts is " << smallest << " on week " <<
x+1 << " on day "<< y+1 <<endl;
        cout << "The total average is "<< total_sum / 10 << " Megawatts" << endl;
        outfile << "The total average is "<< total_sum / 10 << " Megawatts" << endl;

        //week average
        cout << "\nPlease enter 0 if you want averages of every week or just put in the week you
want the average of --> ";
        cin >> user_input;

        if(user_input == 0)
        {
            for(a=0; a < NROWS; a++) //print out all weeks
            {
                double average = week_average(power, a, total_sum);
                cout << endl << "Week " << a+1 << ": Average Power Output in
Megawatts: " << average;
                outfile << endl << "Week " << a+1 << ": Average Power Output in
Megawatts: " << average;
            }
        }
        else if ( (user_input > 0) && (user_input <= 10) ) //user_input is in the restricted domain,
print out desired week
        {
            double average = week_average(power, user_input - 1, total_sum); //replace
second variable with user_input-1
            cout << endl << "Week " << user_input << ": Average Power Output in
Megawatts: " << average;
            outfile << endl << "Week " << user_input << ": Average Power Output in
Megawatts: " << average;
        }
```

```
	else
	{
		cout << "\nYou entered a week not within the domain. This program will
terminate..." << endl;
		outfile << "\nYou entered a week not within the domain. This program will
terminate..." << endl;
		return 0;
	}

	cout << endl << endl;
	system("pause");
	return 0;
} //end main

double week_average(double test_array[NROWS][NCOLS], int a, double& total_sum) //print out
weekly averages
{
	double sum, avg;
	//print out weekly averages
	//sum and average

		sum = test_array[a][0] + test_array[a][1] + test_array[a][2] + test_array[a][3] +
test_array[a][4] + test_array[a][5] + test_array[a][6];
		avg = sum / 7.0;

		total_sum = total_sum + avg;
		return(avg);
}
```

Screenshot of Outputs